

Package ‘betaDelta’

December 18, 2022

Title Confidence Intervals for Standardized Regression Coefficients

Version 0.0.0.9000

Description Generates confidence intervals for standardized regression coefficients using delta method standard errors for models fitted by `lm()` as described in Yuan and Chan (2011) <[doi:10.1007/s11336-011-9224-6](https://doi.org/10.1007/s11336-011-9224-6)> and Jones and Waller (2015) <[doi:10.1007/s11336-013-9380-y](https://doi.org/10.1007/s11336-013-9380-y)>.

URL <https://github.com/jeksterslab/betaDelta>,
<https://jeksterslab.github.io/betaDelta/>

BugReports <https://github.com/jeksterslab/betaDelta/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

Depends R (>= 3.5.0)

Imports methods

Suggests knitr, rmarkdown, testthat

RoxygenNote 7.2.3

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<<https://orcid.org/0000-0003-4818-8420>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

R topics documented:

BetaDelta	2
coef.betadelta	3
confint.betadelta	4
nas1982	4
print.betadelta	5
summary.betadelta	6
vcov.betadelta	7

Index

8

BetaDelta	<i>Estimate Standardized Regression Coefficients and Sampling Covariance Matrix</i>
-----------	---

Description

Estimate Standardized Regression Coefficients and Sampling Covariance Matrix

Usage

```
BetaDelta(object, type = "mvn")
```

Arguments

object	Object of class <code>lm</code> .
type	Character string. If <code>type = "mvn"</code> , use the multivariate normal-theory approach. If <code>type = "adf"</code> , use the asymptotic distribution-free approach.

Value

Returns an object of class `betaDelta` which is a list with the following elements:

call Function call.

type Standard error type.

beta Vector of standardized slopes.

vcov Sampling covariance matrix of the standardized slopes.

n Sample size.

p Number of regressors.

df $n - p - 1$ degrees of freedom

Author(s)

Ivan Jacob Agaloos Pesigan

References

- Jones, J. A., & Waller, N. G. (2015). The normal-theory and asymptotic distribution-free (ADF) covariance matrix of standardized regression coefficients: Theoretical extensions and finite sample behavior. *Psychometrika*, 80(2), 365–378. doi:10.1007/s113360139380y
- Yuan, K.-H., & Chan, W. (2011). Biases and standard errors of standardized regression coefficients. *Psychometrika*, 76(4), 670–690. doi:10.1007/s1133601192246

Examples

```

object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaDelta(object)
# Methods -----
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)

```

coef.betadelta	<i>Standardized Regression Slopes</i>
----------------	---------------------------------------

Description

Standardized Regression Slopes

Usage

```

## S3 method for class 'betadelta'
coef(object, ...)

```

Arguments

object	Object of class betadelta.
...	additional arguments.

Value

Returns a vector of standardized regression slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```

object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaDelta(object)
coef(std)

```

confint.betadelta	<i>Confidence Intervals for Standardized Regression Slopes</i>
-------------------	--

Description

Confidence Intervals for Standardized Regression Slopes

Usage

```
## S3 method for class 'betadelta'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object	Object of class betadelta.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaDelta(object)
confint(std, level = 0.95)
```

nas1982	<i>1982 National Academy of Sciences Doctoral Programs Data</i>
---------	---

Description

1982 National Academy of Sciences Doctoral Programs Data

Usage

```
nas1982
```

Format

Ratings of 46 doctoral programs in psychology in the USA with the following variables:

QUALITY Program quality ratings.

NFACUL Number of faculty members in the program.

NGRADS Number of program graduates.

PCTSUPP Percentage of program graduates who received support.

PCTGRT Percent of faculty members holding research grants.

NARTIC Number of published articles attributed to program faculty member.

PCTPUB Percent of faculty with one or more published article.

References

National Research Council. (1982). *An assessment of research-doctorate programs in the United States: Social and behavioral sciences*. doi:10.17226/9781. Reproduced with permission from the National Academy of Sciences, Courtesy of the National Academies Press, Washington, D.C.

print.betadelta	<i>Print Method for an Object of Class betaDelta</i>
-----------------	--

Description

Print Method for an Object of Class betaDelta

Usage

```
## S3 method for class 'betadelta'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

x	Object of class betadelta.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaDelta(object)
print(std)
```

summary.betadelta	<i>Summary Method for an Object of Class betaDelta</i>
-------------------	--

Description

Summary Method for an Object of Class betaDelta

Usage

```
## S3 method for class 'betadelta'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

object	Object of class betadelta.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaDelta(object)
summary(std)
```

vcov.betadelta	<i>Sampling Covariance Matrix of the Standardized Regression Slopes</i>
----------------	---

Description

Sampling Covariance Matrix of the Standardized Regression Slopes

Usage

```
## S3 method for class 'betadelta'  
vcov(object, ...)
```

Arguments

object	Object of class betadelta.
...	additional arguments.

Value

Returns a matrix of the variance-covariance matrix of standardized slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)  
std <- BetaDelta(object)  
vcov(std)
```

Index

- * **Beta Delta Functions**

- BetaDelta, [2](#)

- * **betaDelta**

- BetaDelta, [2](#)

- * **data**

- nas1982, [4](#)

- * **methods**

- coef.betadelta, [3](#)

- confint.betadelta, [4](#)

- print.betadelta, [5](#)

- summary.betadelta, [6](#)

- vcov.betadelta, [7](#)

BetaDelta, [2](#)

coef.betadelta, [3](#)

confint.betadelta, [4](#)

nas1982, [4](#)

print.betadelta, [5](#)

summary.betadelta, [6](#)

vcov.betadelta, [7](#)