

Package ‘betaMC’

February 15, 2023

Title Monte Carlo Confidence Intervals for Standardized Regression Coefficients

Version 1.0.0.9000

Description Generates Monte Carlo confidence intervals for standardized regression coefficients for models fitted by `lm()`.
'betaMC' combines ideas from Monte Carlo confidence intervals for the indirect effect (Preacher and Selig, 2012 <[doi:10.1080/19312458.2012.679848](https://doi.org/10.1080/19312458.2012.679848)>) and the sampling covariance matrix of regression coefficients (Dudgeon, 2017 <[doi:10.1007/s11336-017-9563-z](https://doi.org/10.1007/s11336-017-9563-z)>) to generate confidence intervals for standardized regression coefficients.

URL <https://github.com/jeksterslab/betaMC>,
<https://jeksterslab.github.io/betaMC/>

BugReports <https://github.com/jeksterslab/betaMC/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

Depends R (>= 3.5.0)

Imports stats, methods

Suggests knitr, rmarkdown, testthat

RoxygenNote 7.2.3

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<<https://orcid.org/0000-0003-4818-8420>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

R topics documented:

BetaMC	2
coef.betamc	4

coef.diffbetamc	5
coef.pcorbetamc	6
coef.rsqbetamc	6
confint.betamc	7
confint.diffbetamc	8
confint.pcorbetamc	9
confint.rsqbetamc	10
DiffBetaMC	11
nas1982	12
PCorBetaMC	12
print.betamc	13
print.diffbetamc	14
print.pcorbetamc	15
print.rsqbetamc	16
RSqBetaMC	17
summary.betamc	18
summary.diffbetamc	18
summary.pcorbetamc	19
summary.rsqbetamc	20
vcov.betamc	21
vcov.diffbetamc	21
vcov.pcorbetamc	22
vcov.rsqbetamc	23

Index 24

BetaMC	<i>Estimate Standardized Regression Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method</i>
--------	--

Description

Estimate Standardized Regression Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
BetaMC(
  object,
  R = 20000L,
  type = "hc3",
  g1 = 1,
  g2 = 1.5,
  k = 0.7,
  decomposition = "eigen",
  pd = TRUE,
  tol = 1e-06
)
```

Arguments

object	Object of class <code>lm</code> .
R	Positive integer. Number of Monte Carlo replications.
type	Character string. Sampling covariance matrix type. Possible values are "mvn", "adf", "hc0", "hc1", "hc2", "hc3", "hc4", "hc4m", and "hc5". <code>type = "mvn"</code> uses the normal-theory sampling covariance matrix. <code>type = "adf"</code> uses the asymptotic distribution-free sampling covariance matrix. <code>type = "hc0"</code> through "hc5" uses different versions of heteroskedasticity-consistent sampling covariance matrix.
g1	Numeric. g1 value for <code>type = "hc4m"</code> or <code>type = "hc5"</code> .
g2	Numeric. g2 value for <code>type = "hc4m"</code> .
k	Numeric. Constant for <code>type = "hc5"</code>
decomposition	Character string. Matrix decomposition of the sampling variance-covariance matrix for the data generation. If <code>decomposition = "chol"</code> , use Cholesky decomposition. If <code>decomposition = "eigen"</code> , use eigenvalue decomposition. If <code>decomposition = "svd"</code> , use singular value decomposition.
pd	Logical. If <code>pd = TRUE</code> , check if the sampling variance-covariance matrix is positive definite using <code>tol</code> .
tol	Numeric. Tolerance used for <code>pd</code> .

Details

The empirical sampling distribution of parameter estimates for the unstandardized regression model is generated using the Monte Carlo method, that is, random values of parameter estimates are sampled from the multivariate normal distribution using the estimated parameter vector as the mean vector and the specified sampling covariance matrix using the `type` argument as the covariance matrix. The standardized regression coefficients are derived from each randomly generated vector of parameters to generate the empirical sampling distribution of estimates of standardized slopes. Confidence intervals are generated by obtaining percentiles corresponding to $100(1 - \alpha)\%$ from the generated sampling distribution of standardized slopes, where α is the significance level.

Value

Returns an object of class `betamc` which is a list with the following elements:

call Function call.

lm Object of class `lm`.

lm_process Pre-processed object of class `lm`.

type Standard error type.

thetahatstar List of parameters.

thetahatstar_std Sampling distribution of standardized slopes.

vcov Sampling distribution of standardized slopes.

est Vector of standardized slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

References

- Dudgeon, P. (2017). Some improvements in confidence intervals for standardized regression coefficients. *Psychometrika*, 82(4), 928–951. doi:10.1007/s113360179563z
- Preacher, K. J., & Selig, J. P. (2012). Advantages of Monte Carlo confidence intervals for indirect effects. *Communication Methods and Measures*, 6(2), 77-98. doi:10.1080/19312458.2012.679848

See Also

Other Beta Monte Carlo Functions: [DiffBetaMC\(\)](#), [PCorBetaMC\(\)](#), [RSqBetaMC\(\)](#)

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
# Methods -----
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)
```

coef.betamc

Standardized Regression Slopes

Description

Standardized Regression Slopes

Usage

```
## S3 method for class 'betamc'
coef(object, ...)
```

Arguments

object Object of class betamc.
... additional arguments.

Value

Returns a vector of standardized regression slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
coef(std)
```

coef.diffbetamc

Differences of Standardized Regression Slopes

Description

Differences of Standardized Regression Slopes

Usage

```
## S3 method for class 'diffbetamc'
coef(object, ...)
```

Arguments

```
object      Object of class diffbetamc.
...         additional arguments.
```

Value

Returns a vector of differences of standardized regression slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
diff <- DiffBetaMC(std)
coef(diff)
```

coef.pcorbetamc	<i>Partial and Semipartial Correlation Coefficients</i>
-----------------	---

Description

Partial and Semipartial Correlation Coefficients

Usage

```
## S3 method for class 'pcorbetamc'
coef(object, ...)
```

Arguments

object	Object of class pcorbetamc.
...	additional arguments.

Value

Returns a vector of partial and semipartial correlation coefficients

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
pcor <- PCorBetaMC(std)
coef(pcor)
```

coef.rsqbetamc	<i>Multiple Correlation Coefficients</i>
----------------	--

Description

Multiple Correlation Coefficients

Usage

```
## S3 method for class 'rsqbetamc'
coef(object, ...)
```

Arguments

object Object of class rsqbetamc.
 ... additional arguments.

Value

Returns a vector of multiple correlation coefficients.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
rsq <- RSqBetaMC(std)
coef(rsq)
```

confint.betamc

Confidence Intervals for Standardized Regression Slopes

Description

Confidence Intervals for Standardized Regression Slopes

Usage

```
## S3 method for class 'betamc'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object Object of class betamc.
 parm a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
 level the confidence level required.
 ... additional arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
confint(std, level = 0.95)
```

confint.diffbetamc	<i>Confidence Intervals for Differences of Standardized Regression Slopes</i>
--------------------	---

Description

Confidence Intervals for Differences of Standardized Regression Slopes

Usage

```
## S3 method for class 'diffbetamc'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object	Object of class diffbetamc.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
diff <- DiffBetaMC(std)
confint(diff, level = 0.95)
```

confint.pcorbetamc	<i>Confidence Intervals for Partial and Semipartial Correlation Coefficients</i>
--------------------	--

Description

Confidence Intervals for Partial and Semipartial Correlation Coefficients

Usage

```
## S3 method for class 'pcorbetamc'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object	Object of class pcorbetamc.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
pcor <- PCorBetaMC(std)
confint(pcor, level = 0.95)
```

confint.rsqbetamc	<i>Confidence Intervals for Multiple Correlation Coefficients</i>
-------------------	---

Description

Confidence Intervals for Multiple Correlation Coefficients

Usage

```
## S3 method for class 'rsqbetamc'  
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object	Object of class rsqbetamc.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)  
std <- BetaMC(object, R = 100)  
# use a large R, for example, R = 20000 for actual research  
rsq <- RSqBetaMC(std)  
confint(rsq, level = 0.95)
```

DiffBetaMC

Estimate Differences of Standardized Slopes and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Description

Estimate Differences of Standardized Slopes and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
DiffBetaMC(object)
```

Arguments

object Object of class `betamc`, that is, the output of the `BetaMC()` function.

Value

Returns an object of class `diffbetamc` which is a list with the following elements:

fit The argument object.

thetahatstar Sampling distribution of differences of standardized slopes.

vcov Sampling covariance matrix of differences of standardized slopes.

est Vector of differences of standardized slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Monte Carlo Functions: [BetaMC\(\)](#), [PCorBetaMC\(\)](#), [RSqBetaMC\(\)](#)

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
diff <- DiffBetaMC(std)
# Methods -----
print(diff)
summary(diff)
coef(diff)
vcov(diff)
confint(diff, level = 0.95)
```

nas1982

*1982 National Academy of Sciences Doctoral Programs Data***Description**

1982 National Academy of Sciences Doctoral Programs Data

Usage

nas1982

Format

Ratings of 46 doctoral programs in psychology in the USA with the following variables:

QUALITY Program quality ratings.**NFACUL** Number of faculty members in the program.**NGRADS** Number of program graduates.**PCTSUPP** Percentage of program graduates who received support.**PCTGRT** Percent of faculty members holding research grants.**NARTIC** Number of published articles attributed to program faculty member.**PCTPUB** Percent of faculty with one or more published article.**References**

National Research Council. (1982). *An assessment of research-doctorate programs in the United States: Social and behavioral sciences*. doi:10.17226/9781. Reproduced with permission from the National Academy of Sciences, Courtesy of the National Academies Press, Washington, D.C.

PCorBetaMC

*Estimate Partial and Semipartial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method***Description**

Estimate Partial and Semipartial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

PCorBetaMC(object)

Arguments

object Object of class betamc, that is, the output of the BetaMC() function.

Value

Returns an object of class pcorbetamc which is a list with the following elements:

fit The argument object.

thetahatstar Sampling distribution of partial and semipartial correlation coefficients.

vcov Sampling covariance matrix of partial and semipartial correlation coefficients.

est Vector of partial and semipartial correlation coefficients.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Monte Carlo Functions: [BetaMC\(\)](#), [DiffBetaMC\(\)](#), [RSqBetaMC\(\)](#)

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
pcor <- PCorBetaMC(std)
# Methods -----
print(pcor)
summary(pcor)
coef(pcor)
vcov(pcor)
confint(pcor, level = 0.95)
```

print.betamc	<i>Print Method for an Object of Class betamc</i>
--------------	---

Description

Print Method for an Object of Class betamc

Usage

```
## S3 method for class 'betamc'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

x	Object of Class betamc.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of standardized regression slopes, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
print(std)
```

print.diffbetamc	<i>Print Method for an Object of Class diffbetamc</i>
------------------	---

Description

Print Method for an Object of Class diffbetamc

Usage

```
## S3 method for class 'diffbetamc'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

x	Object of class diffbetamc.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of differences of standardized regression slopes, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
diff <- DiffBetaMC(std)
print(diff)
```

print.pcorbetamc	<i>Print Method for an Object of Class pcorbetamc</i>
------------------	---

Description

Print Method for an Object of Class pcorbetamc

Usage

```
## S3 method for class 'pcorbetamc'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

x	Object of class pcorbetamc.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of partial and semipartial correlation coefficients, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
pcor <- PCorBetaMC(std)
print(pcor)
```

print.rsqbetamc	<i>Print Method for an Object of Class rsqbetamc</i>
-----------------	--

Description

Print Method for an Object of Class rsqbetamc

Usage

```
## S3 method for class 'rsqbetamc'  
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

x	Object of class rsqbetamc.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of multiple correlation coefficients (R-squared and adjusted R-squared), standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)  
std <- BetaMC(object, R = 100)  
# use a large R, for example, R = 20000 for actual research  
rsq <- RSqBetaMC(std)  
print(rsq)
```

RSqBetaMC	<i>Estimate Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared) and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method</i>
-----------	--

Description

Estimate Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared) and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
RSqBetaMC(object)
```

Arguments

object Object of class `betamc`, that is, the output of the `BetaMC()` function.

Value

Returns an object of class `rsqbetamc` which is a list with the following elements:

fit The argument object.

thetahatstar Sampling distribution of multiple correlation coefficients (R-squared and adjusted R-squared).

vcov Sampling covariance matrix of multiple correlation coefficients (R-squared and adjusted R-squared).

est Vector of multiple correlation coefficients (R-squared and adjusted R-squared).

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Monte Carlo Functions: [BetaMC\(\)](#), [DiffBetaMC\(\)](#), [PCorBetaMC\(\)](#)

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
rsq <- RSqBetaMC(std)
# Methods -----
print(rsq)
summary(rsq)
coef(rsq)
vcov(rsq)
confint(rsq, level = 0.95)
```

summary.betamc	<i>Summary Method for an Object of Class betamc</i>
----------------	---

Description

Summary Method for an Object of Class betamc

Usage

```
## S3 method for class 'betamc'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

object	Object of class betamc.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of standardized regression slopes, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
summary(std)
```

summary.diffbetamc	<i>Summary Method for an Object of Class diffbetamc</i>
--------------------	---

Description

Summary Method for an Object of Class diffbetamc

Usage

```
## S3 method for class 'diffbetamc'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

object	Object of class diffbetamc.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of differences of standardized regression slopes, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
diff <- DiffBetaMC(std)
summary(diff)
```

summary.pcorbetamc	<i>Summary Method for an Object of Class pcorbetamc</i>
--------------------	---

Description

Summary Method for an Object of Class pcorbetamc

Usage

```
## S3 method for class 'pcorbetamc'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

object	Object of class pcorbetamc.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of partial and semipartial correlation coefficients, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
pcor <- PCorBetaMC(std)
summary(pcor)
```

summary.rsqbetamc

Summary Method for an Object of Class rsqbetamc

Description

Summary Method for an Object of Class rsqbetamc

Usage

```
## S3 method for class 'rsqbetamc'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

object	Object of class rsqbetamc.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of multiple correlation coefficients (R-squared and adjusted R-squared), standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
rsq <- RSqBetaMC(std)
summary(rsq)
```

vcov.betamc

*Sampling Covariance Matrix of the Standardized Regression Slopes***Description**

Sampling Covariance Matrix of the Standardized Regression Slopes

Usage

```
## S3 method for class 'betamc'
vcov(object, ...)
```

Arguments

```
object      Object of class betamc.
...         additional arguments.
```

Value

Returns a matrix of the variance-covariance matrix of standardized slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
vcov(std)
```

vcov.diffbetamc

*Sampling Covariance Matrix of Differences of Standardized Regression Slopes***Description**

Sampling Covariance Matrix of Differences of Standardized Regression Slopes

Usage

```
## S3 method for class 'diffbetamc'
vcov(object, ...)
```

Arguments

object Object of class diffbetamc.
 ... additional arguments.

Value

Returns a matrix of the variance-covariance matrix of differences of standardized regression slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
diff <- DiffBetaMC(std)
vcov(diff)
```

vcov.pcorbetamc	<i>Sampling Covariance Matrix of Partial and Semipartial Correlation Coefficients</i>
-----------------	---

Description

Sampling Covariance Matrix of Partial and Semipartial Correlation Coefficients

Usage

```
## S3 method for class 'pcorbetamc'
vcov(object, ...)
```

Arguments

object Object of class pcorbetamc.
 ... additional arguments.

Value

Returns a matrix of the variance-covariance matrix of partial and semipartial correlation coefficients.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
pcor <- PCorBetaMC(std)
vcov(pcor)
```

vcov.rsqbetamc

*Sampling Covariance Matrix of Multiple Correlation Coefficients***Description**

Sampling Covariance Matrix of Multiple Correlation Coefficients

Usage

```
## S3 method for class 'rsqbetamc'
vcov(object, ...)
```

Arguments

```
object      Object of class rsqbetamc.
...         additional arguments.
```

Value

Returns a matrix of the variance-covariance matrix of multiple correlation coefficients.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaMC(object, R = 100)
# use a large R, for example, R = 20000 for actual research
rsq <- RSqBetaMC(std)
vcov(rsq)
```

Index

* Beta Monte Carlo Functions

BetaMC, [2](#)
DiffBetaMC, [11](#)
PCorBetaMC, [12](#)
RSqBetaMC, [17](#)

* betaMC

BetaMC, [2](#)
DiffBetaMC, [11](#)
PCorBetaMC, [12](#)
RSqBetaMC, [17](#)

* data

nas1982, [12](#)

* diff

DiffBetaMC, [11](#)

* methods

coef.betamc, [4](#)
coef.diffbetamc, [5](#)
coef.pcorbetamc, [6](#)
coef.rsqbetamc, [6](#)
confint.betamc, [7](#)
confint.diffbetamc, [8](#)
confint.pcorbetamc, [9](#)
confint.rsqbetamc, [10](#)
print.betamc, [13](#)
print.diffbetamc, [14](#)
print.pcorbetamc, [15](#)
print.rsqbetamc, [16](#)
summary.betamc, [18](#)
summary.diffbetamc, [18](#)
summary.pcorbetamc, [19](#)
summary.rsqbetamc, [20](#)
vcov.betamc, [21](#)
vcov.diffbetamc, [21](#)
vcov.pcorbetamc, [22](#)
vcov.rsqbetamc, [23](#)

* pcor

PCorBetaMC, [12](#)

* rsq

RSqBetaMC, [17](#)

* std

BetaMC, [2](#)

BetaMC, [2](#), [11](#), [13](#), [17](#)

coef.betamc, [4](#)
coef.diffbetamc, [5](#)
coef.pcorbetamc, [6](#)
coef.rsqbetamc, [6](#)
confint.betamc, [7](#)
confint.diffbetamc, [8](#)
confint.pcorbetamc, [9](#)
confint.rsqbetamc, [10](#)

DiffBetaMC, [4](#), [11](#), [13](#), [17](#)

nas1982, [12](#)

PCorBetaMC, [4](#), [11](#), [12](#), [17](#)
print.betamc, [13](#)
print.diffbetamc, [14](#)
print.pcorbetamc, [15](#)
print.rsqbetamc, [16](#)

RSqBetaMC, [4](#), [11](#), [13](#), [17](#)

summary.betamc, [18](#)
summary.diffbetamc, [18](#)
summary.pcorbetamc, [19](#)
summary.rsqbetamc, [20](#)

vcov.betamc, [21](#)
vcov.diffbetamc, [21](#)
vcov.pcorbetamc, [22](#)
vcov.rsqbetamc, [23](#)