Package 'betaMC'

November 5, 2026

Title Monte Carlo for Regression Effect Sizes

Version 1.3.4.9000

Description Generates Monte Carlo confidence intervals
for standardized regression coefficients (beta) and other effect sizes,
including multiple correlation, semipartial correlations,
improvement in R-squared, squared partial correlations,
and differences in standardized regression coefficients,
for models fitted by lm().
'betaMC' combines ideas from Monte Carlo confidence intervals for the indirect effect
(Pesigan and Cheung, 2024 <doi:10.3758/s13428-023-02114-4>)
and the sampling covariance matrix of regression coefficients
(Dudgeon, 2017 <doi:10.1007/s11336-017-9563-z>)
to generate confidence intervals effect sizes in regression.

URL https://github.com/jeksterslab/betaMC,
https://jeksterslab.github.io/betaMC/

BugReports https://github.com/jeksterslab/betaMC/issues

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

Depends R (>= 3.5.0)

Imports Rcpp, stats

LinkingTo Rcpp, RcppArmadillo

Suggests knitr, rmarkdown, testthat, MASS, mice, Amelia, betaDelta,
betaSandwich, betaNB

Config/roxygen2/version 8.1.1.9000

NeedsCompilation yes

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:
<https://orcid.org/0000-0003-4818-8420>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

BetaMC . . . 2
coef.betamc . . . 4
confint.betamc . . . 4
DeltaRSqMC . . . 5
DiffBetaMC . . . 7
FSqMC . . . 8
MC . . . 10
MCMI . . . 12
nas1982 . . . 15
PCorMC . . . 16
print.betamc . . . 17
print.mc . . . 18
RSqMC . . . 19
SCorMC . . . 20
summary.betamc . . . 22
summary.mc . . . 22
vcov.betamc . . . 23

Index **25**

`BetaMC` *Estimate Standardized Regression Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method*

Description

Estimate Standardized Regression Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
BetaMC(object, alpha = c(0.05, 0.01, 0.001), std_y = TRUE, std_x = NULL)
```

Arguments

`object`	Object of class `mc`, that is, the output of the `MC()` function.
`alpha`	Numeric vector. Significance level α.
`std_y`	Logical. Standardize y.
`std_x`	Character vector or `NULL`. Names of the regressors to standardize. `NULL` (default) standardizes all regressors; `character(0)` standardizes none.

Details

By default, both y and the regressors are standardized. With `std_y = FALSE`, y is left in its original units ($b_j\sigma_{x_j}$); with `std_x`, only the named regressors are standardized (for example, `std_x = character(0)` gives b_j/σ_y, and leaving a dummy variable out of `std_x` keeps its 0-1 contrast). The standard deviations are taken from each draw.

The vector of standardized regression coefficients ($\hat{\boldsymbol{\beta}}$) is derived from each randomly generated vector of parameter estimates. Confidence intervals are generated by obtaining percentiles corresponding to $100(1-\alpha)\%$ from the generated sampling distribution of $\hat{\boldsymbol{\beta}}$, where α is the significance level.

Value

Returns an object of class `betamc` which is a list with the following elements:

call Function call.

args Function arguments.

thetahatstar Sampling distribution of $\hat{\boldsymbol{\beta}}$.

vcov Sampling variance-covariance matrix of $\hat{\boldsymbol{\beta}}$.

est Vector of estimated $\hat{\boldsymbol{\beta}}$.

fun Function used ("BetaMC").

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Monte Carlo Functions: `DeltaRSqMC()`, `DiffBetaMC()`, `FSqMC()`, `MC()`, `MCMI()`, `PCorMC()`, `RSqMC()`, `SCorMC()`

Examples

```
# Data ------------------------------------------------------------------------
data("nas1982", package = "betaMC")

# Fit Model in lm -------------------------------------------------------------
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# MC --------------------------------------------------------------------------
mc <- MC(
  object,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)

# BetaMC ----------------------------------------------------------------------
out <- BetaMC(mc, alpha = 0.05)

## Methods --------------------------------------------------------------------
```

```
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

`coef.betamc` *Estimated Parameter Method for an Object of Class* `betamc`

Description

Estimated Parameter Method for an Object of Class `betamc`

Usage

```
## S3 method for class 'betamc'
coef(object, ...)
```

Arguments

`object`	Object of Class `betamc`, that is, the output of the `BetaMC()`, `RSqMC()`, `SCorMC()`, `DeltaRSqMC()`, `PCorMC()`, or `DiffBetaMC()` functions.
`...`	additional arguments.

Value

Returns a vector of estimated parameters.

Author(s)

Ivan Jacob Agaloos Pesigan

`confint.betamc` *Confidence Intervals Method for an Object of Class* `betamc`

Description

Confidence Intervals Method for an Object of Class `betamc`

Usage

```
## S3 method for class 'betamc'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

`object`	Object of Class `betamc`, that is, the output of the `BetaMC()`, `RSqMC()`, `SCorMC()`, `DeltaRSqMC()`, `PCorMC()`, or `DiffBetaMC()` functions.
`parm`	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
`level`	the confidence level required.
`...`	additional arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

`DeltaRSqMC` *Estimate Improvement in R-Squared and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method*

Description

Estimate Improvement in R-Squared and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
DeltaRSqMC(object, alpha = c(0.05, 0.01, 0.001))
```

Arguments

`object`	Object of class `mc`, that is, the output of the `MC()` function.
`alpha`	Numeric vector. Significance level α.

Details

The vector of improvement in R-squared (ΔR^2) is derived from each randomly generated vector of parameter estimates. Confidence intervals are generated by obtaining percentiles corresponding to $100(1 - \alpha)\%$ from the generated sampling distribution of ΔR^2, where α is the significance level.

Value

Returns an object of class `betamc` which is a list with the following elements:

call Function call.

args Function arguments.

thetahatstar Sampling distribution of ΔR^2.

vcov Sampling variance-covariance matrix of ΔR^2.

est Vector of estimated ΔR^2.

fun Function used ("DeltaRSqMC").

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Monte Carlo Functions: `BetaMC()`, `DiffBetaMC()`, `FSqMC()`, `MC()`, `MCMI()`, `PCorMC()`, `RSqMC()`, `SCorMC()`

Examples

```
# Data ------------------------------------------------------------------------
data("nas1982", package = "betaMC")

# Fit Model in lm -------------------------------------------------------------
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# MC --------------------------------------------------------------------------
mc <- MC(
  object,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)

# DeltaRSqMC ------------------------------------------------------------------
out <- DeltaRSqMC(mc, alpha = 0.05)

## Methods --------------------------------------------------------------------
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

DiffBetaMC *Estimate Differences of Standardized Slopes and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method*

Description

Estimate Differences of Standardized Slopes and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
DiffBetaMC(object, alpha = c(0.05, 0.01, 0.001))
```

Arguments

object	Object of class mc, that is, the output of the MC() function.
alpha	Numeric vector. Significance level α.

Details

The vector of differences of standardized regression slopes is derived from each randomly generated vector of parameter estimates. Confidence intervals are generated by obtaining percentiles corresponding to $100(1 - \alpha)\%$ from the generated sampling distribution of differences of standardized regression slopes, where α is the significance level.

Value

Returns an object of class betamc which is a list with the following elements:

call Function call.

args Function arguments.

thetahatstar Sampling distribution of differences of standardized regression slopes.

vcov Sampling variance-covariance matrix of differences of standardized regression slopes.

est Vector of estimated differences of standardized regression slopes.

fun Function used ("DiffBetaMC").

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Monte Carlo Functions: BetaMC(), DeltaRSqMC(), FSqMC(), MC(), MCMI(), PCorMC(), RSqMC(), SCorMC()

Examples

```
# Data ------------------------------------------------------------------------
data("nas1982", package = "betaMC")

# Fit Model in lm -------------------------------------------------------------
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# MC --------------------------------------------------------------------------
mc <- MC(
  object,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)

# DiffBetaMC ------------------------------------------------------------------
out <- DiffBetaMC(mc, alpha = 0.05)

## Methods --------------------------------------------------------------------
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

`FSqMC` *Estimate Cohen's f-Squared and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method*

Description

Estimate Cohen's f-Squared and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
FSqMC(object, alpha = c(0.05, 0.01, 0.001))
```

Arguments

`object`	Object of class `mc`, that is, the output of the `MC()` function.
`alpha`	Numeric vector. Significance level α.

Details

Cohen's f^2 for the whole model, $f^2 = R^2/(1 - R^2)$, and the local f^2 of each regressor, $f_j^2 = sr_j^2/(1 - R^2)$, where sr_j is the semipartial correlation, are derived from each randomly generated vector of parameter estimates. Confidence intervals are generated by obtaining percentiles corresponding to $100(1 - \alpha)\%$ from the generated sampling distribution, where α is the significance level.

Value

Returns an object of class `betamc` which is a list with the following elements:

call Function call.

args Function arguments.

thetahatstar Sampling distribution of f^2 (column `fsq`) and the local f^2 (one column per regressor).

est Vector of estimates.

fun Function used ("FSqMC").

Author(s)

Ivan Jacob Agaloos Pesigan

References

Selya, A. S., Rose, J. S., Dierker, L. C., Hedeker, D., & Mermelstein, R. J. (2012). A practical guide to calculating Cohen's f2, a measure of local effect size, from PROC MIXED. *Frontiers in Psychology*, *3*, 111. doi:10.3389/fpsyg.2012.00111

See Also

Other Beta Monte Carlo Functions: `BetaMC()`, `DeltaRSqMC()`, `DiffBetaMC()`, `MC()`, `MCMI()`, `PCorMC()`, `RSqMC()`, `SCorMC()`

Examples

```
# Data ------------------------------------------------------------------------
data("nas1982", package = "betaMC")

# Fit Model in lm -------------------------------------------------------------
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# MC --------------------------------------------------------------------------
mc <- MC(
  object,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)

# FSqMC -----------------------------------------------------------------------
out <- FSqMC(mc, alpha = 0.05)

## Methods --------------------------------------------------------------------
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

MC *Generate the Sampling Distribution of Regression Parameters Using the Monte Carlo Method*

Description

Generate the Sampling Distribution of Regression Parameters Using the Monte Carlo Method

Usage

```
MC(
  object,
  R = 20000L,
  type = "hc3",
  g1 = 1,
  g2 = 1.5,
  k = 0.7,
  decomposition = "eigen",
  pd = TRUE,
  tol = 1e-06,
  fixed_x = FALSE,
  seed = NULL
)
```

Arguments

object	Object of class lm.
R	Positive integer. Number of Monte Carlo replications.
type	Character string. Sampling covariance matrix type. Possible values are "mvn", "adf", "hc0", "hc1", "hc2", "hc3", "hc4", "hc4m", and "hc5". type = "mvn" uses the normal-theory sampling covariance matrix. type = "adf" uses the asymptotic distribution-free sampling covariance matrix. type = "hc0" through "hc5" uses different versions of heteroskedasticity-consistent sampling covariance matrix.
g1	Numeric. g1 value for type = "hc4m".
g2	Numeric. g2 value for type = "hc4m".
k	Numeric. Constant for type = "hc5"
decomposition	Character string. Matrix decomposition of the sampling variance-covariance matrix for the data generation. If decomposition = "chol", use Cholesky decomposition. If decomposition = "eigen", use eigenvalue decomposition. If decomposition = "svd", use singular value decomposition.
pd	Logical. If pd = TRUE, check if the sampling variance-covariance matrix is positive definite using tol.
tol	Numeric. Tolerance used for pd.

`fixed_x`	Logical. If `fixed_x = TRUE`, treat the regressors as fixed. If `fixed_x = FALSE`, treat the regressors as random.
`seed`	Integer. Seed number for reproducibility.

Details

Let the parameter vector of the unstandardized regression model be given by

$$\boldsymbol{\theta} = \left\{\mathbf{b}, \sigma^2, \text{vech}\left(\boldsymbol{\Sigma}_{\mathbf{XX}}\right)\right\}$$

where $\mathbf{b}$ is the vector of regression slopes, σ^2 is the error variance, and $\text{vech}\left(\boldsymbol{\Sigma}_{\mathbf{XX}}\right)$ is the vector of unique elements of the covariance matrix of the regressor variables. The empirical sampling distribution of $\boldsymbol{\theta}$ is generated using the Monte Carlo method, that is, random values of parameter estimates are sampled from the multivariate normal distribution using the estimated parameter vector as the mean vector and the specified sampling covariance matrix using the `type` argument as the covariance matrix. A replacement sampling approach is implemented to ensure that the model-implied covariance matrix is positive definite.

Value

Returns an object of class `mc` which is a list with the following elements:

call Function call.

args Function arguments.

lm_process Processed `lm` object.

scale Sampling variance-covariance matrix of parameter estimates.

location Parameter estimates.

thetahatstar Sampling distribution of parameter estimates (a matrix, one draw per row).

vechsigmacap Sampling distribution of the half-vectorization of the model-implied covariance matrix (a matrix, one draw per row).

es Sampling distribution of the effect sizes (a list of matrices).

fun Function used ("MC").

Author(s)

Ivan Jacob Agaloos Pesigan

References

Dudgeon, P. (2017). Some improvements in confidence intervals for standardized regression coefficients. *Psychometrika*, *82*(4), 928–951. doi:10.1007/s113360179563z

MacKinnon, D. P., Lockwood, C. M., & Williams, J. (2004). Confidence limits for the indirect effect: Distribution of the product and resampling methods. *Multivariate Behavioral Research*, *39*(1), 99-128. doi:10.1207/s15327906mbr3901_4

Pesigan, I. J. A., & Cheung, S. F. (2024). Monte Carlo confidence intervals for the indirect effect with missing data. *Behavior Research Methods*. doi:10.3758/s13428023021144

Preacher, K. J., & Selig, J. P. (2012). Advantages of Monte Carlo confidence intervals for indirect effects. *Communication Methods and Measures*, *6*(2), 77–98. doi:10.1080/19312458.2012.679848

See Also

Other Beta Monte Carlo Functions: BetaMC(), DeltaRSqMC(), DiffBetaMC(), FSqMC(), MCMI(), PCorMC(), RSqMC(), SCorMC()

Examples

```
# Data ------------------------------------------------------------------------
data("nas1982", package = "betaMC")

# Fit Model in lm -------------------------------------------------------------
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# MC --------------------------------------------------------------------------
mc <- MC(
  object,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)
mc
# The `mc` object can be passed as the first argument
# to the following functions
#   - BetaMC
#   - DeltaRSqMC
#   - DiffBetaMC
#   - PCorMC
#   - RSqMC
#   - SCorMC
```

MCMI *Generate the Sampling Distribution of Regression Parameters Using the Monte Carlo Method for Data with Missing Values*

Description

Generate the Sampling Distribution of Regression Parameters Using the Monte Carlo Method for Data with Missing Values

Usage

```
MCMI(
  object,
  mi,
  R = 20000L,
  type = "hc3",
  g1 = 1,
  g2 = 1.5,
  k = 0.7,
```

```
  decomposition = "eigen",
  pd = TRUE,
  tol = 1e-06,
  fixed_x = FALSE,
  seed = NULL
)
```

Arguments

object	Object of class lm.
mi	Object of class mids (output of mice::mice()), object of class amelia (output of Amelia::amelia()), or a list of multiply imputed data sets.
R	Positive integer. Number of Monte Carlo replications.
type	Character string. Sampling covariance matrix type. Possible values are "mvn", "adf", "hc0", "hc1", "hc2", "hc3", "hc4", "hc4m", and "hc5". type = "mvn" uses the normal-theory sampling covariance matrix. type = "adf" uses the asymptotic distribution-free sampling covariance matrix. type = "hc0" through "hc5" uses different versions of heteroskedasticity-consistent sampling covariance matrix.
g1	Numeric. g1 value for type = "hc4m".
g2	Numeric. g2 value for type = "hc4m".
k	Numeric. Constant for type = "hc5"
decomposition	Character string. Matrix decomposition of the sampling variance-covariance matrix for the data generation. If decomposition = "chol", use Cholesky decomposition. If decomposition = "eigen", use eigenvalue decomposition. If decomposition = "svd", use singular value decomposition.
pd	Logical. If pd = TRUE, check if the sampling variance-covariance matrix is positive definite using tol.
tol	Numeric. Tolerance used for pd.
fixed_x	Logical. If fixed_x = TRUE, treat the regressors as fixed. If fixed_x = FALSE, treat the regressors as random.
seed	Integer. Seed number for reproducibility.

Details

Multiple imputation is used to deal with missing values in a data set. The vector of parameter estimates and the corresponding sampling covariance matrix are estimated for each of the imputed data sets. Results are combined to arrive at the pooled vector of parameter estimates and the corresponding sampling covariance matrix. The pooled estimates are then used to generate the sampling distribution of regression parameters. See MC() for more details on the Monte Carlo method.

Value

Returns an object of class mc which is a list with the following elements:

call Function call.

args Function arguments.

lm_process Processed `lm` object.

scale Sampling variance-covariance matrix of parameter estimates.

location Parameter estimates.

thetahatstar Sampling distribution of parameter estimates (a matrix, one draw per row).

vechsigmacap Sampling distribution of the half-vectorization of the model-implied covariance matrix (a matrix, one draw per row).

es Sampling distribution of the effect sizes (a list of matrices).

fun Function used ("MCMI").

Author(s)

Ivan Jacob Agaloos Pesigan

References

Dudgeon, P. (2017). Some improvements in confidence intervals for standardized regression coefficients. *Psychometrika*, *82*(4), 928–951. doi:10.1007/s113360179563z

MacKinnon, D. P., Lockwood, C. M., & Williams, J. (2004). Confidence limits for the indirect effect: Distribution of the product and resampling methods. *Multivariate Behavioral Research*, *39*(1), 99-128. doi:10.1207/s15327906mbr3901_4

Pesigan, I. J. A., & Cheung, S. F. (2024). Monte Carlo confidence intervals for the indirect effect with missing data. *Behavior Research Methods*. doi:10.3758/s13428023021144

Preacher, K. J., & Selig, J. P. (2012). Advantages of Monte Carlo confidence intervals for indirect effects. *Communication Methods and Measures*, *6*(2), 77–98. doi:10.1080/19312458.2012.679848

See Also

Other Beta Monte Carlo Functions: `BetaMC()`, `DeltaRSqMC()`, `DiffBetaMC()`, `FSqMC()`, `MC()`, `PCorMC()`, `RSqMC()`, `SCorMC()`

Examples

```
# Data ------------------------------------------------------------------------
data("nas1982", package = "betaMC")
nas1982_missing <- mice::ampute(nas1982)$amp # data set with missing values

# Multiple Imputation
mi <- mice::mice(nas1982_missing, m = 5, seed = 42, print = FALSE)

# Fit Model in lm -------------------------------------------------------------
## Note that this does not deal with missing values.
## The fitted model (`object`) is updated with each imputed data
## within the `MCMI()` function.
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982_missing)

# Monte Carlo -----------------------------------------------------------------
```

```
mc <- MCMI(
  object,
  mi = mi,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)
mc
# The `mc` object can be passed as the first argument
# to the following functions
#   - BetaMC
#   - DeltaRSqMC
#   - DiffBetaMC
#   - PCorMC
#   - RSqMC
#   - SCorMC
```

`nas1982` *1982 National Academy of Sciences Doctoral Programs Data*

Description

1982 National Academy of Sciences Doctoral Programs Data

Usage

```
nas1982
```

Format

Ratings of 46 doctoral programs in psychology in the USA with the following variables:

QUALITY Program quality ratings.

NFACUL Number of faculty members in the program.

NGRADS Number of program graduates.

PCTSUPP Percentage of program graduates who received support.

PCTGRT Percent of faculty members holding research grants.

NARTIC Number of published articles attributed to program faculty member.

PCTPUB Percent of faculty with one or more published article.

References

National Research Council. (1982). *An assessment of research-doctorate programs in the United States: Social and behavioral sciences*. doi:10.17226/9781. Reproduced with permission from the National Academy of Sciences, Courtesy of the National Academies Press, Washington, D.C.

PCorMC *Estimate Squared Partial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method*

Description

Estimate Squared Partial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
PCorMC(object, alpha = c(0.05, 0.01, 0.001))
```

Arguments

object	Object of class mc, that is, the output of the MC() function.
alpha	Numeric vector. Significance level α.

Details

The vector of squared partial correlation coefficients (r_p^2) is derived from each randomly generated vector of parameter estimates. Confidence intervals are generated by obtaining percentiles corresponding to $100(1-\alpha)\%$ from the generated sampling distribution of r_p^2, where α is the significance level.

Value

Returns an object of class betamc which is a list with the following elements:

call Function call.

args Function arguments.

thetahatstar Sampling distribution of r_p^2.

vcov Sampling variance-covariance matrix of r_p^2.

est Vector of estimated r_p^2.

fun Function used ("PCorMC").

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Monte Carlo Functions: BetaMC(), DeltaRSqMC(), DiffBetaMC(), FSqMC(), MC(), MCMI(), RSqMC(), SCorMC()

Examples

```
# Data ------------------------------------------------------------------------
data("nas1982", package = "betaMC")

# Fit Model in lm -------------------------------------------------------------
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# MC --------------------------------------------------------------------------
mc <- MC(
  object,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)

# PCorMC ----------------------------------------------------------------------
out <- PCorMC(mc, alpha = 0.05)

## Methods --------------------------------------------------------------------
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

---

print.betamc *Print Method for an Object of Class* betamc

Description

Print Method for an Object of Class betamc

Usage

```
## S3 method for class 'betamc'
print(x, alpha = NULL, digits = 4, ...)
```

Arguments

x	Object of Class betamc, that is, the output of the BetaMC(), RSqMC(), SCorMC(), DeltaRSqMC(), PCorMC(), or DiffBetaMC() functions.
alpha	Numeric vector. Significance level α. If alpha = NULL, use the argument alpha used in x.
digits	Digits to print.
...	additional arguments.

Value

Prints a matrix of estimates, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

`print.mc` *Print Method for an Object of Class* `mc`

Description

Print Method for an Object of Class `mc`

Usage

```
## S3 method for class 'mc'
print(x, ...)
```

Arguments

`x`	Object of Class `mc`.
`...`	additional arguments.

Value

Prints the first set of simulated parameter estimates and model-implied covariance matrix.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
mc <- MC(object, R = 100)
print(mc)
```

RSqMC *Estimate Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared) and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method*

Description

Estimate Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared) and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
RSqMC(object, alpha = c(0.05, 0.01, 0.001))
```

Arguments

`object`	Object of class `mc`, that is, the output of the `MC()` function.
`alpha`	Numeric vector. Significance level α.

Details

R-squared (R^2) and adjusted R-squared ($\bar{R}^2$) are derived from each randomly generated vector of parameter estimates. Confidence intervals are generated by obtaining percentiles corresponding to $100(1-\alpha)\%$ from the generated sampling distribution of R^2 and $\bar{R}^2$, where α is the significance level.

Value

Returns an object of class `betamc` which is a list with the following elements:

call Function call.

args Function arguments.

thetahatstar Sampling distribution of R^2 and $\bar{R}^2$.

vcov Sampling variance-covariance matrix of R^2 and $\bar{R}^2$.

est Vector of estimated R^2 and $\bar{R}^2$.

fun Function used ("RSqMC").

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Monte Carlo Functions: `BetaMC()`, `DeltaRSqMC()`, `DiffBetaMC()`, `FSqMC()`, `MC()`, `MCMI()`, `PCorMC()`, `SCorMC()`

Examples

```
# Data ------------------------------------------------------------------------
data("nas1982", package = "betaMC")

# Fit Model in lm -------------------------------------------------------------
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# MC --------------------------------------------------------------------------
mc <- MC(
  object,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)

# RSqMC -----------------------------------------------------------------------
out <- RSqMC(mc, alpha = 0.05)

## Methods --------------------------------------------------------------------
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

`SCorMC` *Estimate Semipartial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method*

Description

Estimate Semipartial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using the Monte Carlo Method

Usage

```
SCorMC(object, alpha = c(0.05, 0.01, 0.001))
```

Arguments

`object`	Object of class `mc`, that is, the output of the `MC()` function.
`alpha`	Numeric vector. Significance level α.

Details

The vector of semipartial correlation coefficients (r_s) is derived from each randomly generated vector of parameter estimates. Confidence intervals are generated by obtaining percentiles corresponding to $100(1-\alpha)\%$ from the generated sampling distribution of r_s, where α is the significance level.

Value

Returns an object of class `betamc` which is a list with the following elements:

call Function call.

args Function arguments.

thetahatstar Sampling distribution of r_s.

vcov Sampling variance-covariance matrix of r_s.

est Vector of estimated r_s.

fun Function used ("SCorMC").

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Monte Carlo Functions: `BetaMC()`, `DeltaRSqMC()`, `DiffBetaMC()`, `FSqMC()`, `MC()`, `MCMI()`, `PCorMC()`, `RSqMC()`

Examples

```
# Data ------------------------------------------------------------------------
data("nas1982", package = "betaMC")

# Fit Model in lm -------------------------------------------------------------
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# MC --------------------------------------------------------------------------
mc <- MC(
  object,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)

# SCorMC ----------------------------------------------------------------------
out <- SCorMC(mc, alpha = 0.05)

## Methods --------------------------------------------------------------------
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

summary.betamc *Summary Method for an Object of Class* betamc

Description

Summary Method for an Object of Class betamc

Usage

```
## S3 method for class 'betamc'
summary(object, alpha = NULL, digits = 4, ...)
```

Arguments

object	Object of Class betamc, that is, the output of the BetaMC(), RSqMC(), SCorMC(), DeltaRSqMC(), PCorMC(), or DiffBetaMC() functions.
alpha	Numeric vector. Significance level α. If alpha = NULL, use the argument alpha used in object.
digits	Digits to print.
...	additional arguments.

Value

Returns a matrix of estimates, standard errors, number of Monte Carlo replications, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

summary.mc *Summary Method for an Object of Class* mc

Description

Summary Method for an Object of Class mc

Usage

```
## S3 method for class 'mc'
summary(object, digits = 4, ...)
```

Arguments

object	Object of Class mc, that is, the output of the MC() function.
digits	Digits to print.
...	additional arguments.

Value

Returns a list with the following elements:

mean Mean of the sampling distribution of $\hat{\theta}$.

var Variance of the sampling distribution of $\hat{\theta}$.

bias Monte Carlo simulation bias.

rmse Monte Carlo simulation root mean square error.

location Location parameter used in the Monte Carlo simulation.

scale Scale parameter used in the Monte Carlo simulation.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
# Fit the regression model
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
mc <- MC(object, R = 100)
summary(mc)
```

---

vcov.betamc *Sampling Variance-Covariance Matrix Method for an Object of Class* betamc

---

Description

Sampling Variance-Covariance Matrix Method for an Object of Class betamc

Usage

```
## S3 method for class 'betamc'
vcov(object, ...)
```

Arguments

object	Object of Class betamc, that is, the output of the BetaMC(), RSqMC(), SCorMC(), DeltaRSqMC(), PCorMC(), or DiffBetaMC() functions.
...	additional arguments.

Value

Returns the variance-covariance matrix of estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

Index

∗ **Beta Monte Carlo Functions**
BetaMC, 2
DeltaRSqMC, 5
DiffBetaMC, 7
FSqMC, 8
MC, 10
MCMI, 12
PCorMC, 16
RSqMC, 19
SCorMC, 20
∗ **betaMC**
BetaMC, 2
DeltaRSqMC, 5
DiffBetaMC, 7
FSqMC, 8
MC, 10
MCMI, 12
PCorMC, 16
RSqMC, 19
SCorMC, 20
∗ **data**
nas1982, 15
∗ **deltarsq**
DeltaRSqMC, 5
∗ **diff**
DiffBetaMC, 7
∗ **fsq**
FSqMC, 8
∗ **mc**
MC, 10
MCMI, 12
∗ **methods**
coef.betamc, 4
confint.betamc, 4
print.betamc, 17
print.mc, 18
summary.betamc, 22
summary.mc, 22
vcov.betamc, 23
∗ **pcor**
PCorMC, 16
∗ **rsq**
RSqMC, 19
∗ **scor**
SCorMC, 20
∗ **std**
BetaMC, 2

Amelia::amelia(), *13*

BetaMC, 2
BetaMC(), *6, 7*, *9*, *12*, *14*, *16*, *19*, *21*

coef.betamc, 4
confint.betamc, 4

DeltaRSqMC, 5
DeltaRSqMC(), *3*, *7*, *9*, *12*, *14*, *16*, *19*, *21*
DiffBetaMC, 7
DiffBetaMC(), *3*, *6*, *9*, *12*, *14*, *16*, *19*, *21*

FSqMC, 8
FSqMC(), *3*, *6, 7*, *12*, *14*, *16*, *19*, *21*

MC, 10
MC(), *3*, *6, 7*, *9*, *14*, *16*, *19*, *21*
MCMI, 12
MCMI(), *3*, *6, 7*, *9*, *12*, *16*, *19*, *21*
mice::mice(), *13*

nas1982, 15

PCorMC, 16
PCorMC(), *3*, *6, 7*, *9*, *12*, *14*, *19*, *21*
print.betamc, 17
print.mc, 18

RSqMC, 19
RSqMC(), *3*, *6, 7*, *9*, *12*, *14*, *16*, *21*

SCorMC, 20

SCorMC(), *3*, *6*, *7*, *9*, *12*, *14*, *16*, *19*
summary.betamc, 22
summary.mc, 22

vcov.betamc, 23