

# Package ‘betaNB’

June 21, 2024

**Title** Bootstrap for Regression Effect Sizes

**Version** 1.0.4.9000

**Description** Generates nonparametric bootstrap confidence intervals (Efron & Tibshirani, 1993: <[doi:10.1201/9780429246593](https://doi.org/10.1201/9780429246593)>) for standardized regression coefficients (beta) and other effect sizes, including multiple correlation, semipartial correlations, improvement in R-squared, squared partial correlations, and differences in standardized regression coefficients, for models fitted by lm().

**URL** <https://github.com/jeksterslab/betaNB>,  
<https://jeksterslab.github.io/betaNB/>

**BugReports** <https://github.com/jeksterslab/betaNB/issues>

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**Depends** R (>= 3.5.0)

**Imports** stats

**Suggests** knitr, rmarkdown, testthat

**RoxygenNote** 7.3.1

**NeedsCompilation** no

**Author** Ivan Jacob Agaloos Pesigan [aut, cre, cph]  
(<<https://orcid.org/0000-0003-4818-8420>>)

**Maintainer** Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

## Contents

|                          |   |
|--------------------------|---|
| BetaNB . . . . .         | 2 |
| coef.betanb . . . . .    | 3 |
| confint.betanb . . . . . | 4 |

|                          |    |
|--------------------------|----|
| DeltaRSqNB . . . . .     | 5  |
| DiffBetaNB . . . . .     | 6  |
| nas1982 . . . . .        | 8  |
| NB . . . . .             | 8  |
| PCorNB . . . . .         | 10 |
| print.betanb . . . . .   | 11 |
| print.nb . . . . .       | 12 |
| RSqNB . . . . .          | 13 |
| SCorNB . . . . .         | 14 |
| summary.betanb . . . . . | 16 |
| vcov.betanb . . . . .    | 16 |

## Index 18

---

|        |   |
|--------|---|
| BetaNB | <i>Estimate Standardized Regression Coefficients and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping</i> |
|--------|---|

---

### Description

Estimate Standardized Regression Coefficients and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping

### Usage

```
BetaNB(object, alpha = c(0.05, 0.01, 0.001))
```

### Arguments

|        |   |
|--------|---|
| object | Object of class nb, that is, the output of the NB() function. |
| alpha  | Numeric vector. Significance level $\alpha$ .                 |

### Details

The vector of standardized regression coefficients ( $\hat{\beta}$ ) is estimated from bootstrap samples. Confidence intervals are generated by obtaining percentiles corresponding to  $100(1 - \alpha)\%$  from the generated sampling distribution of  $\hat{\beta}$ , where  $\alpha$  is the significance level.

### Value

Returns an object of class betanb which is a list with the following elements:

- call** Function call.
- args** Function arguments.
- thetahatstar** Sampling distribution of  $\hat{\beta}$ .
- jackknife** Jackknife estimates.
- est** Vector of estimated  $\hat{\beta}$ .
- fun** Function used ("BetaNB").

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Nonparametric Bootstrap Functions: [DeltaRSqNB\(\)](#), [DiffBetaNB\(\)](#), [NB\(\)](#), [PCorNB\(\)](#), [RSqNB\(\)](#), [SCorNB\(\)](#)

**Examples**

```
# Data -----
data("nas1982", package = "betaNB")

# Fit Model in lm -----
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# NB -----
nb <- NB(
  object,
  R = 100, # use a large value e.g., 5000L for actual research
  seed = 0508
)

# BetaNB -----
out <- BetaNB(nb, alpha = 0.05)

## Methods -----
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

---

coef.betanb

*Estimated Parameter Method for an Object of Class betanb*


---

**Description**

Estimated Parameter Method for an Object of Class betanb

**Usage**

```
## S3 method for class 'betanb'
coef(object, ...)
```

**Arguments**

`object`      Object of Class `betanb`, that is, the output of the `BetaNB()`, `RSqNB()`, `SCorNB()`, `DeltaRSqNB()`, `PCorNB()`, or `DiffBetaNB()` functions.

`...`      additional arguments.

**Value**

Returns a vector of estimated parameters.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|                             |   |
|-----------------------------|---|
| <code>confint.betanb</code> | <i>Confidence Intervals Method for an Object of Class <code>betanb</code></i> |
|-----------------------------|---|

---

**Description**

Confidence Intervals Method for an Object of Class `betanb`

**Usage**

```
## S3 method for class 'betanb'
confint(object, parm = NULL, level = 0.95, type = "pc", ...)
```

**Arguments**

`object`      Object of Class `betanb`, that is, the output of the `BetaNB()`, `RSqNB()`, `SCorNB()`, `DeltaRSqNB()`, `PCorNB()`, or `DiffBetaNB()` functions.

`parm`      a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.

`level`      the confidence level required.

`type`      Character string. Confidence interval type, that is, `type = "pc"` for percentile; `type = "bc"` for bias corrected; `type = "bca"` for bias corrected and accelerated.

`...`      additional arguments.

**Value**

Returns a matrix of confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

DeltaRSqNB

---

*Estimate Improvement in R-Squared and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping*


---

**Description**

Estimate Improvement in R-Squared and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping

**Usage**

```
DeltaRSqNB(object, alpha = c(0.05, 0.01, 0.001))
```

**Arguments**

|               |   |
|---------------|---|
| <b>object</b> | Object of class nb, that is, the output of the NB() function. |
| <b>alpha</b>  | Numeric vector. Significance level $\alpha$ .                 |

**Details**

The vector of improvement in R-squared ( $\Delta R^2$ ) is estimated from bootstrap samples. Confidence intervals are generated by obtaining percentiles corresponding to  $100(1 - \alpha)\%$  from the generated sampling distribution of  $\Delta R^2$ , where  $\alpha$  is the significance level.

**Value**

Returns an object of class betanb which is a list with the following elements:

**call** Function call.

**args** Function arguments.

**thetahatstar** Sampling distribution of  $\Delta R^2$ .

**vcov** Sampling variance-covariance matrix of  $\Delta R^2$ .

**est** Vector of estimated  $\Delta R^2$ .

**fun** Function used ("DeltaRSqNB").

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Nonparametric Bootstrap Functions: [BetaNB\(\)](#), [DiffBetaNB\(\)](#), [NB\(\)](#), [PCorNB\(\)](#), [RSqNB\(\)](#), [SCorNB\(\)](#)

## Examples

```
# Data -----
data("nas1982", package = "betaNB")

# Fit Model in lm -----
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# NB -----
nb <- NB(
  object,
  R = 100, # use a large value e.g., 5000L for actual research
  seed = 0508
)

# DeltaRSqNB -----
out <- DeltaRSqNB(nb, alpha = 0.05)

## Methods -----
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

---

DiffBetaNB

---

*Estimate Differences of Standardized Slopes and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping*


---

## Description

Estimate Differences of Standardized Slopes and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping

## Usage

```
DiffBetaNB(object, alpha = c(0.05, 0.01, 0.001))
```

## Arguments

|        |   |
|--------|---|
| object | Object of class nb, that is, the output of the NB() function. |
| alpha  | Numeric vector. Significance level $\alpha$ .                 |

## Details

The vector of differences of standardized regression slopes is estimated from bootstrap samples. Confidence intervals are generated by obtaining percentiles corresponding to  $100(1 - \alpha)\%$  from the generated sampling distribution of differences of standardized regression slopes, where  $\alpha$  is the significance level.

**Value**

Returns an object of class `betanb` which is a list with the following elements:

**call** Function call.

**args** Function arguments.

**thetahatstar** Sampling distribution of differences of standardized regression slopes.

**vcov** Sampling variance-covariance matrix of differences of standardized regression slopes.

**est** Vector of estimated differences of standardized regression slopes.

**fun** Function used ("DiffBetaNB").

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Nonparametric Bootstrap Functions: [BetaNB\(\)](#), [DeltaRSqNB\(\)](#), [NB\(\)](#), [PCorNB\(\)](#), [RSqNB\(\)](#), [SCorNB\(\)](#)

**Examples**

```
# Data -----
data("nas1982", package = "betaNB")

# Fit Model in lm -----
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# NB -----
nb <- NB(
  object,
  R = 100, # use a large value e.g., 5000L for actual research
  seed = 0508
)

# DiffBetaNB -----
out <- DiffBetaNB(nb, alpha = 0.05)

## Methods -----
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

nas1982

*1982 National Academy of Sciences Doctoral Programs Data***Description**

1982 National Academy of Sciences Doctoral Programs Data

**Usage**

nas1982

**Format**

Ratings of 46 doctoral programs in psychology in the USA with the following variables:

**QUALITY** Program quality ratings.**NFACUL** Number of faculty members in the program.**NGRADS** Number of program graduates.**PCTSUPP** Percentage of program graduates who received support.**PCTGRT** Percent of faculty members holding research grants.**NARTIC** Number of published articles attributed to program faculty member.**PCTPUB** Percent of faculty with one or more published article.**References**

National Research Council. (1982). *An assessment of research-doctorate programs in the United States: Social and behavioral sciences*. doi:10.17226/9781. Reproduced with permission from the National Academy of Sciences, Courtesy of the National Academies Press, Washington, D.C.

NB

*Generate the Sampling Distribution of Sample Covariances Using Nonparametric Bootstrapping***Description**

Generate the Sampling Distribution of Sample Covariances Using Nonparametric Bootstrapping

**Usage**

NB(object, R = 5000L, seed = NULL)



**Arguments**

|                     |   |
|---------------------|---|
| <code>object</code> | Object of class <code>lm</code> .                   |
| <code>R</code>      | Positive integer. Number of bootstrap replications. |
| <code>seed</code>   | Integer. Seed number for reproducibility.           |

**Value**

Returns an object of class `nb` which is a list with the following elements:

**call** Function call.

**args** Function arguments.

**lm\_process** Processed `lm` object.

**thetahatstar** Sampling distribution of sample covariances.

**jackknife** Jackknife estimates.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**References**

Efron, B., & Tibshirani, R. J. (1993) *An introduction to the bootstrap*. Chapman & Hall.

**See Also**

Other Beta Nonparametric Bootstrap Functions: [BetaNB\(\)](#), [DeltaRSqNB\(\)](#), [DiffBetaNB\(\)](#), [PCorNB\(\)](#), [RSqNB\(\)](#), [SCorNB\(\)](#)

**Examples**

```
# Data -----
data("nas1982", package = "betaNB")

# Fit Model in lm -----
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# NB -----
nb <- NB(
  object,
  R = 100, # use a large value e.g., 20000L for actual research
  seed = 0508
)
nb
# The `nb` object can be passed as the first argument
# to the following functions
#   - BetaNB
#   - DeltaRSqNB
#   - DiffBetaNB
#   - PCorNB
```

```
# - RSqNB
# - SCorNB
```

PCorNB

*Estimate Squared Partial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping*

## Description

Estimate Squared Partial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping

## Usage

```
PCorNB(object, alpha = c(0.05, 0.01, 0.001))
```

## Arguments

**object** Object of class nb, that is, the output of the NB() function.  
**alpha** Numeric vector. Significance level  $\alpha$ .

## Details

The vector of squared partial correlation coefficients ( $r_p^2$ ) is estimated from bootstrap samples. Confidence intervals are generated by obtaining percentiles corresponding to  $100(1 - \alpha)\%$  from the generated sampling distribution of  $r_p^2$ , where  $\alpha$  is the significance level.

## Value

Returns an object of class betanb which is a list with the following elements:

**call** Function call.  
**args** Function arguments.  
**thetahatstar** Sampling distribution of  $r_p^2$ .  
**vcov** Sampling variance-covariance matrix of  $r_p^2$ .  
**est** Vector of estimated  $r_p^2$ .  
**fun** Function used ("PCorNB").

## Author(s)

Ivan Jacob Agaloos Pesigan

## See Also

Other Beta Nonparametric Bootstrap Functions: [BetaNB\(\)](#), [DeltaRSqNB\(\)](#), [DiffBetaNB\(\)](#), [NB\(\)](#), [RSqNB\(\)](#), [SCorNB\(\)](#)

**Examples**

```

# Data -----
data("nas1982", package = "betaNB")

# Fit Model in lm -----
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# NB -----
nb <- NB(
  object,
  R = 100, # use a large value e.g., 5000L for actual research
  seed = 0508
)

# PCorNB -----
out <- PCorNB(nb, alpha = 0.05)

## Methods -----
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)

```

---

print.betanb

---

*Print Method for an Object of Class betanb*


---

**Description**

Print Method for an Object of Class betanb

**Usage**

```

## S3 method for class 'betanb'
print(x, alpha = NULL, type = "pc", digits = 4, ...)

```

**Arguments**

|        |  |
|--------|--|
| x      | Object of Class betanb, that is, the output of the BetaNB(), RSqNB(), SCorNB(), DeltaRSqNB(), PCorNB(), or DiffBetaNB() functions.                               |
| alpha  | Numeric vector. Significance level $\alpha$ . If alpha = NULL, use the argument alpha used in x.   |
| type   | Charater string. Confidence interval type, that is, type = "pc" for percentile; type = "bc" for bias corrected; type = "bca" for bias corrected and accelerated. |
| digits | Digits to print.   |
| ...    | additional arguments.  |

**Value**

Prints a matrix of estimates, standard errors, number of bootstrap replications, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

print.nb

*Print Method for an Object of Class nb*

---

**Description**

Print Method for an Object of Class nb

**Usage**

```
## S3 method for class 'nb'  
print(x, ...)
```

**Arguments**

|     |                       |
|-----|-----------------------|
| x   | Object of Class nb.   |
| ... | additional arguments. |

**Value**

Prints the first six bootstrap covariance matrices.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)  
nb <- NB(object, R = 100)  
print(nb)
```

---

|       |   |
|-------|---|
| RSqNB | <i>Estimate Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared) and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping</i> |
|-------|---|

---

## Description

Estimate Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared) and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping

## Usage

```
RSqNB(object, alpha = c(0.05, 0.01, 0.001))
```

## Arguments

|               |   |
|---------------|---|
| <b>object</b> | Object of class nb, that is, the output of the NB() function. |
| <b>alpha</b>  | Numeric vector. Significance level $\alpha$ .                 |

## Details

R-squared ( $R^2$ ) and adjusted R-squared ( $\bar{R}^2$ ) is estimated from bootstrap samples. Confidence intervals are generated by obtaining percentiles corresponding to  $100(1 - \alpha)\%$  from the generated sampling distribution of  $R^2$  and  $\bar{R}^2$ , where  $\alpha$  is the significance level.

## Value

Returns an object of class betanb which is a list with the following elements:

- call** Function call.
- args** Function arguments.
- thetahatstar** Sampling distribution of  $R^2$  and  $\bar{R}^2$ .
- vcov** Sampling variance-covariance matrix of  $R^2$  and  $\bar{R}^2$ .
- est** Vector of estimated  $R^2$  and  $\bar{R}^2$ .
- fun** Function used ("RSqNB").

## Author(s)

Ivan Jacob Agaloos Pesigan

## See Also

Other Beta Nonparametric Bootstrap Functions: [BetaNB\(\)](#), [DeltaRSqNB\(\)](#), [DiffBetaNB\(\)](#), [NB\(\)](#), [PCorNB\(\)](#), [SCorNB\(\)](#)

## Examples

```
# Data -----
data("nas1982", package = "betaNB")

# Fit Model in lm -----
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# NB -----
nb <- NB(
  object,
  R = 100, # use a large value e.g., 5000L for actual research
  seed = 0508
)

# RSqNB -----
out <- RSqNB(nb, alpha = 0.05)

## Methods -----
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

---

SCorNB

*Estimate Semipartial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping*

---

## Description

Estimate Semipartial Correlation Coefficients and Generate the Corresponding Sampling Distribution Using Nonparametric Bootstrapping

## Usage

```
SCorNB(object, alpha = c(0.05, 0.01, 0.001))
```

## Arguments

|        |   |
|--------|---|
| object | Object of class nb, that is, the output of the NB() function. |
| alpha  | Numeric vector. Significance level $\alpha$ .                 |

## Details

The vector of semipartial correlation coefficients ( $r_s$ ) is estimated from bootstrap samples. Confidence intervals are generated by obtaining percentiles corresponding to  $100(1 - \alpha)\%$  from the generated sampling distribution of  $r_s$ , where  $\alpha$  is the significance level.

**Value**

Returns an object of class `betanb` which is a list with the following elements:

**call** Function call.

**args** Function arguments.

**thetahatstar** Sampling distribution of  $r_s$ .

**vcov** Sampling variance-covariance matrix of  $r_s$ .

**est** Vector of estimated  $r_s$ .

**fun** Function used ("SCorNB").

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Nonparametric Bootstrap Functions: [BetaNB\(\)](#), [DeltaRSqNB\(\)](#), [DiffBetaNB\(\)](#), [NB\(\)](#), [PCorNB\(\)](#), [RSqNB\(\)](#)

**Examples**

```
# Data -----
data("nas1982", package = "betanb")

# Fit Model in lm -----
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)

# NB -----
nb <- NB(
  object,
  R = 100, # use a large value e.g., 5000L for actual research
  seed = 0508
)

# SCorNB -----
out <- SCorNB(nb, alpha = 0.05)

## Methods -----
print(out)
summary(out)
coef(out)
vcov(out)
confint(out, level = 0.95)
```

---

|                |   |
|----------------|---|
| summary.betanb | <i>Summary Method for an Object of Class betanb</i> |
|----------------|---|

---

**Description**

Summary Method for an Object of Class betanb

**Usage**

```
## S3 method for class 'betanb'
summary(object, alpha = NULL, type = "pc", digits = 4, ...)
```

**Arguments**

|        |   |
|--------|---|
| object | Object of Class betanb, that is, the output of the BetaNB(), RSqNB(), SCorNB(), DeltaRSqNB(), PCorNB(), or DiffBetaNB() functions.                                |
| alpha  | Numeric vector. Significance level $\alpha$ . If alpha = NULL, use the argument alpha used in object.   |
| type   | Character string. Confidence interval type, that is, type = "pc" for percentile; type = "bc" for bias corrected; type = "bca" for bias corrected and accelerated. |
| digits | Digits to print.  |
| ...    | additional arguments.   |

**Value**

Returns a matrix of estimates, standard errors, number of bootstrap replications, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|             |   |
|-------------|---|
| vcov.betanb | <i>Sampling Variance-Covariance Matrix Method for an Object of Class betanb</i> |
|-------------|---|

---

**Description**

Sampling Variance-Covariance Matrix Method for an Object of Class betanb

**Usage**

```
## S3 method for class 'betanb'
vcov(object, ...)
```



**Arguments**

|                     |   |
|---------------------|---|
| <code>object</code> | Object of Class <code>betanb</code> , that is, the output of the <code>BetaNB()</code> , <code>RSqNB()</code> , <code>SCorNB()</code> , <code>DeltaRSqNB()</code> , <code>PCorNB()</code> , or <code>DiffBetaNB()</code> functions. |
| <code>...</code>    | additional arguments.   |

**Value**

Returns the variance-covariance matrix of estimates.

**Author(s)**

Ivan Jacob Agaloos Pesigan

# Index

## \* **Beta Nonparametric Bootstrap Functions**

BetaNB, [2](#)  
DeltaRSqNB, [5](#)  
DiffBetaNB, [6](#)  
NB, [8](#)  
PCorNB, [10](#)  
RSqNB, [13](#)  
SCorNB, [14](#)

## \* **betaNB**

BetaNB, [2](#)  
DeltaRSqNB, [5](#)  
DiffBetaNB, [6](#)  
NB, [8](#)  
PCorNB, [10](#)  
RSqNB, [13](#)  
SCorNB, [14](#)

## \* **data**

nas1982, [8](#)

## \* **deltarsq**

DeltaRSqNB, [5](#)

## \* **diff**

DiffBetaNB, [6](#)

## \* **methods**

coef.betanb, [3](#)  
confint.betanb, [4](#)  
print.betanb, [11](#)  
print.nb, [12](#)  
summary.betanb, [16](#)  
vcov.betanb, [16](#)

## \* **nb**

NB, [8](#)

## \* **pcor**

PCorNB, [10](#)

## \* **rsq**

RSqNB, [13](#)

## \* **scor**

SCorNB, [14](#)

## \* **std**

BetaNB, [2](#)

BetaNB, [2](#), [5](#), [7](#), [9](#), [10](#), [13](#), [15](#)

coef.betanb, [3](#)  
confint.betanb, [4](#)

DeltaRSqNB, [3](#), [5](#), [7](#), [9](#), [10](#), [13](#), [15](#)  
DiffBetaNB, [3](#), [5](#), [6](#), [9](#), [10](#), [13](#), [15](#)

nas1982, [8](#)  
NB, [3](#), [5](#), [7](#), [8](#), [10](#), [13](#), [15](#)

PCorNB, [3](#), [5](#), [7](#), [9](#), [10](#), [13](#), [15](#)  
print.betanb, [11](#)  
print.nb, [12](#)

RSqNB, [3](#), [5](#), [7](#), [9](#), [10](#), [13](#), [15](#)

SCorNB, [3](#), [5](#), [7](#), [9](#), [10](#), [13](#), [14](#)  
summary.betanb, [16](#)

vcov.betanb, [16](#)