

# Package ‘betaSandwich’

May 9, 2023

**Title** Robust Confidence Intervals for Standardized Regression Coefficients

**Version** 1.0.4.9000

**Description** Generates robust confidence intervals for standardized regression coefficients using heteroskedasticity-consistent standard errors for models fitted by `lm()` as described in Dudgeon (2017) <[doi:10.1007/s11336-017-9563-z](https://doi.org/10.1007/s11336-017-9563-z)>. A description of the package and code examples are presented in Pesigan, Sun, and Cheung (2023) <[doi:10.1080/00273171.2023.2201277](https://doi.org/10.1080/00273171.2023.2201277)>.

**URL** <https://github.com/jeksterslab/betaSandwich>,  
<https://jeksterslab.github.io/betaSandwich/>

**BugReports** <https://github.com/jeksterslab/betaSandwich/issues>

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**Depends** R (>= 3.5.0)

**Suggests** knitr, rmarkdown, testthat, betaDelta

**RoxygenNote** 7.2.3

**NeedsCompilation** no

**Author** Ivan Jacob Agaloos Pesigan [aut, cre, cph]  
(<<https://orcid.org/0000-0003-4818-8420>>)

**Maintainer** Ivan Jacob Agaloos Pesigan <[r.jeksterslab@gmail.com](mailto:r.jeksterslab@gmail.com)>

## R topics documented:

BetaADF . . . . .	2
BetaHC . . . . .	4
BetaN . . . . .	5
coef.betasandwich . . . . .	7
coef.diffbetasandwich . . . . .	8

coef.rsqbetasandwich . . . . .	9
confint.betasandwich . . . . .	10
confint.diffbetasandwich . . . . .	11
confint.rsqbetasandwich . . . . .	12
DiffBetaSandwich . . . . .	13
nas1982 . . . . .	14
print.betasandwich . . . . .	14
print.diffbetasandwich . . . . .	15
print.rsqbetasandwich . . . . .	16
RSqBetaSandwich . . . . .	17
summary.betasandwich . . . . .	18
summary.diffbetasandwich . . . . .	19
summary.rsqbetasandwich . . . . .	20
vcov.betasandwich . . . . .	21
vcov.diffbetasandwich . . . . .	22
vcov.rsqbetasandwich . . . . .	23
<b>Index</b>	<b>25</b>

---

BetaADF	<i>Estimate Standardized Regression Coefficients and the Corresponding Sampling Covariance Matrix Using the Asymptotic Distribution-Free Approach</i>
---------	---

---

**Description**

Estimate Standardized Regression Coefficients and the Corresponding Sampling Covariance Matrix Using the Asymptotic Distribution-Free Approach

**Usage**

BetaADF(object)

**Arguments**

object                      Object of class lm.

**Details**

Note that while the calculation in `BetaADF()` is different from `betaDelta::BetaDelta()` with `type = "adf"`, the results are numerically equivalent. `BetaADF()` is appropriate when sample sizes are moderate to large ( $n > 250$ ). `BetaHC()` is recommended in most situations.

**Value**

Returns an object of class `betasandwich` which is a list with the following elements:

**call** Function call.

**args** Function arguments.

**lm\_process** Processed `lm` object.

**gamma\_n** Asymptotic covariance matrix of the sample covariance matrix assuming multivariate normality.

**gamma\_hc** Asymptotic covariance matrix HC correction.

**gamma** Asymptotic covariance matrix of the sample covariance matrix.

**acov** Asymptotic covariance matrix of the standardized slopes.

**vcov** Sampling covariance matrix of the standardized slopes.

**est** Vector of standardized slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**References**

Browne, M. W. (1984). Asymptotically distribution-free methods for the analysis of covariance structures. *British Journal of Mathematical and Statistical Psychology*, 37(1), 62–83. doi:[10.1111/j.20448317.1984.tb00789.x](https://doi.org/10.1111/j.20448317.1984.tb00789.x)

Dudgeon, P. (2017). Some improvements in confidence intervals for standardized regression coefficients. *Psychometrika*, 82(4), 928–951. doi:[10.1007/s113360179563z](https://doi.org/10.1007/s113360179563z)

Pesigan, I. J. A., Sun, R. W., & Cheung, S. F. (2023). `betaDelta` and `betaSandwich`: Confidence intervals for standardized regression coefficients in R. *Multivariate Behavioral Research*. doi:[10.1080/00273171.2023.2201277](https://doi.org/10.1080/00273171.2023.2201277)

**See Also**

Other Beta Sandwich Functions: `BetaHC()`, `BetaN()`, `DiffBetaSandwich()`, `RSqBetaSandwich()`, `coef.betasandwich()`, `coef.diffbetasandwich()`, `coef.rsqbetasandwich()`, `confint.betasandwich()`, `confint.diffbetasandwich()`, `confint.rsqbetasandwich()`, `print.betasandwich()`, `print.diffbetasandwich()`, `print.rsqbetasandwich()`, `summary.betasandwich()`, `summary.diffbetasandwich()`, `summary.rsqbetasandwich()`, `vcov.betasandwich()`, `vcov.diffbetasandwich()`, `vcov.rsqbetasandwich()`

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaADF(object)
# Methods -----
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)
```

---

BetaHC	<i>Estimate Standardized Regression Coefficients and the Corresponding Robust Sampling Covariance Matrix Using the Heteroskedasticity Consistent Approach</i>
--------	---

---

### Description

Estimate Standardized Regression Coefficients and the Corresponding Robust Sampling Covariance Matrix Using the Heteroskedasticity Consistent Approach

### Usage

```
BetaHC(object, type = "hc3", g1 = 1, g2 = 1.5, k = 0.7)
```

### Arguments

<b>object</b>	Object of class <code>lm</code> .
<b>type</b>	Character string. Correction type. Possible values are "hc0", "hc1", "hc2", "hc3", "hc4", "hc4m", and "hc5".
<b>g1</b>	Numeric. g1 value for type = "hc4m".
<b>g2</b>	Numeric. g2 value for type = "hc4m".
<b>k</b>	Numeric. Constant k for type = "hc5" $0 \leq k \leq 1$ .

### Value

Returns an object of class `betasandwich` which is a list with the following elements:

**call** Function call.

**args** Function arguments.

**lm\_process** Processed `lm` object.

**gamma\_n** Asymptotic covariance matrix of the sample covariance matrix assuming multivariate normality.

**gamma\_hc** Asymptotic covariance matrix HC correction.

**gamma** Asymptotic covariance matrix of the sample covariance matrix.

**acov** Asymptotic covariance matrix of the standardized slopes.

**vcov** Sampling covariance matrix of the standardized slopes.

**est** Vector of standardized slopes.

### Author(s)

Ivan Jacob Agaloos Pesigan

References

Dudgeon, P. (2017). Some improvements in confidence intervals for standardized regression coefficients. *Psychometrika*, 82(4), 928–951. doi:10.1007/s113360179563z

Pesigan, I. J. A., Sun, R. W., & Cheung, S. F. (2023). betaDelta and betaSandwich: Confidence intervals for standardized regression coefficients in R. *Multivariate Behavioral Research*. doi:10.1080/00273171.2023.2201277

See Also

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
# Methods -----
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)
```

---

BetaN	<i>Estimate Standardized Regression Coefficients and the Corresponding Sampling Covariance Matrix Assuming Multivariate Normality</i>
-------	---

---

Description

Estimate Standardized Regression Coefficients and the Corresponding Sampling Covariance Matrix Assuming Multivariate Normality

Usage

```
BetaN(object)
```

Arguments

object                      Object of class lm.

Details

Note that while the calculation in [BetaN\(\)](#) is different from [betaDelta::BetaDelta\(\)](#) with type = "mvn", the results are numerically equivalent. [BetaN\(\)](#) assumes multivariate normality. [BetaHC\(\)](#) is recommended in most situations.

**Value**

Returns an object of class `betasandwich` which is a list with the following elements:

**call** Function call.

**args** Function arguments.

**lm\_process** Processed `lm` object.

**gamma\_n** Asymptotic covariance matrix of the sample covariance matrix assuming multivariate normality.

**gamma\_hc** Asymptotic covariance matrix HC correction.

**gamma** Asymptotic covariance matrix of the sample covariance matrix.

**acov** Asymptotic covariance matrix of the standardized slopes.

**vcov** Sampling covariance matrix of the standardized slopes.

**est** Vector of standardized slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**References**

Dudgeon, P. (2017). Some improvements in confidence intervals for standardized regression coefficients. *Psychometrika*, 82(4), 928–951. doi:[10.1007/s113360179563z](https://doi.org/10.1007/s113360179563z)

Pesigan, I. J. A., Sun, R. W., & Cheung, S. F. (2023). `betaDelta` and `betaSandwich`: Confidence intervals for standardized regression coefficients in R. *Multivariate Behavioral Research*. doi:[10.1080/00273171.2023.2201277](https://doi.org/10.1080/00273171.2023.2201277)

**See Also**

Other Beta Sandwich Functions: `BetaADF()`, `BetaHC()`, `DiffBetaSandwich()`, `RSqBetaSandwich()`, `coef.betasandwich()`, `coef.diffbetasandwich()`, `coef.rsqbetasandwich()`, `confint.betasandwich()`, `confint.diffbetasandwich()`, `confint.rsqbetasandwich()`, `print.betasandwich()`, `print.diffbetasandwich()`, `print.rsqbetasandwich()`, `summary.betasandwich()`, `summary.diffbetasandwich()`, `summary.rsqbetasandwich()`, `vcov.betasandwich()`, `vcov.diffbetasandwich()`, `vcov.rsqbetasandwich()`

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaN(object)
# Methods -----
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)
```

---

coef.betasandwich	<i>Standardized Regression Slopes</i>
-------------------	---------------------------------------

---

## Description

Standardized Regression Slopes

## Usage

```
## S3 method for class 'betasandwich'  
coef(object, ...)
```

## Arguments

object	Object of class betasandwich.
...	additional arguments.

## Value

Returns a vector of standardized regression slopes.

## Author(s)

Ivan Jacob Agaloos Pesigan

## See Also

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

## Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)  
std <- BetaHC(object)  
coef(std)
```

---

coef.diffbetasandwich *Differences of Standardized Regression Slopes*

---

## Description

Differences of Standardized Regression Slopes

## Usage

```
## S3 method for class 'diffbetasandwich'  
coef(object, ...)
```

## Arguments

object	Object of class diffbetasandwich.
...	additional arguments.

## Value

Returns a vector of differences of standardized regression slopes.

## Author(s)

Ivan Jacob Agaloos Pesigan

## See Also

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

## Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)  
std <- BetaHC(object)  
diff <- DiffBetaSandwich(std)  
coef(diff)
```



---

coef.rsqbetasandwich	<i>Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared)</i>
----------------------	---

---

## Description

Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared)

## Usage

```
## S3 method for class 'rsqbetasandwich'
coef(object, ...)
```

## Arguments

object	Object of class rsqbetasandwich.
...	additional arguments.

## Value

Returns a vector of multiple correlation coefficients (R-squared and adjusted R-squared)

## Author(s)

Ivan Jacob Agaloos Pesigan

## See Also

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

## Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
coef(rsq)
```

---

confint.betasandwich    *Confidence Intervals for Standardized Regression Slopes*

---

## Description

Confidence Intervals for Standardized Regression Slopes

## Usage

```
## S3 method for class 'betasandwich'
confint(object, parm = NULL, level = 0.95, ...)
```

## Arguments

object	Object of class betasandwich.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

## Value

Returns a matrix of confidence intervals.

## Author(s)

Ivan Jacob Agaloos Pesigan

## See Also

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

## Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
confint(std, level = 0.95)
```

---

 confint.diffbetasandwich

*Confidence Intervals for Differences of Standardized Regression Slopes*

---

## Description

Confidence Intervals for Differences of Standardized Regression Slopes

## Usage

```
## S3 method for class 'diffbetasandwich'
confint(object, parm = NULL, level = 0.95, ...)
```

## Arguments

object	Object of class diffbetasandwich.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

## Value

Returns a matrix of confidence intervals.

## Author(s)

Ivan Jacob Agaloos Pesigan

## See Also

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

## Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
confint(diff, level = 0.95)
```

---

confint.rsqbetasandwich

*Confidence Intervals for Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared)*

---

## Description

Confidence Intervals for Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared)

## Usage

```
## S3 method for class 'rsqbetasandwich'
confint(object, parm = NULL, level = 0.95, ...)
```

## Arguments

object	Object of class rsqbetasandwich.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

## Value

Returns a matrix of confidence intervals.

## Author(s)

Ivan Jacob Agaloos Pesigan

## See Also

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

## Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
confint(rsq, level = 0.95)
```

---

DiffBetaSandwich	<i>Estimate Differences of Standardized Slopes and the Corresponding Sampling Covariance Matrix</i>
------------------	---

---

**Description**

Estimate Differences of Standardized Slopes and the Corresponding Sampling Covariance Matrix

**Usage**

```
DiffBetaSandwich(object)
```

**Arguments**

**object** Object of class `betasandwich`, that is, the output of the `BetaHC()`, `BetaN()`, or `BetaADF()` functions.

**Value**

Returns an object of class `diffbetasandwich` which is a list with the following elements:

**call** Function call.

**fit** The argument object.

**vcov** Sampling covariance matrix of differences of standardized slopes.

**est** Vector of differences of standardized slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: `BetaADF()`, `BetaHC()`, `BetaN()`, `RSqBetaSandwich()`, `coef.betasandwich()`, `coef.diffbetasandwich()`, `coef.rsqbetasandwich()`, `confint.betasandwich()`, `confint.diffbetasandwich()`, `confint.rsqbetasandwich()`, `print.betasandwich()`, `print.diffbetasandwich()`, `print.rsqbetasandwich()`, `summary.betasandwich()`, `summary.diffbetasandwich()`, `summary.rsqbetasandwich()`, `vcov.betasandwich()`, `vcov.diffbetasandwich()`, `vcov.rsqbetasandwich()`

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
# Methods -----
print(diff)
summary(diff)
coef(diff)
vcov(diff)
```

```
confint(diff, level = 0.95)
```

---

nas1982

---

1982 National Academy of Sciences Doctoral Programs Data

---

### Description

1982 National Academy of Sciences Doctoral Programs Data

### Usage

```
nas1982
```

### Format

Ratings of 46 doctoral programs in psychology in the USA with the following variables:

**QUALITY** Program quality ratings.

**NFACUL** Number of faculty members in the program.

**NGRADS** Number of program graduates.

**PCTSUPP** Percentage of program graduates who received support.

**PCTGRT** Percent of faculty members holding research grants.

**NARTIC** Number of published articles attributed to program faculty member.

**PCTPUB** Percent of faculty with one or more published article.

### References

National Research Council. (1982). *An assessment of research-doctorate programs in the United States: Social and behavioral sciences*. doi:10.17226/9781. Reproduced with permission from the National Academy of Sciences, Courtesy of the National Academies Press, Washington, D.C.

---

print.betasandwich

---

Print Method for an Object of Class betasandwich

---

### Description

Print Method for an Object of Class betasandwich

### Usage

```
## S3 method for class 'betasandwich'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

**Arguments**

x	Object of class betasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

**Value**

Returns a matrix of standardized regression slopes, standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
print(std)
```

---

```
print.diffbetasandwich
```

*Print Method for an Object of Class diffbetasandwich*

---

**Description**

Print Method for an Object of Class diffbetasandwich

**Usage**

```
## S3 method for class 'diffbetasandwich'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

**Arguments**

<code>x</code>	Object of class <code>diffbetasandwich</code> .
<code>alpha</code>	Significance level.
<code>digits</code>	Digits to print.
<code>...</code>	additional arguments.

**Value**

Returns a matrix of differences of standardized regression slopes, standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: `BetaADF()`, `BetaHC()`, `BetaN()`, `DiffBetaSandwich()`, `RSqBetaSandwich()`, `coef.betasandwich()`, `coef.diffbetasandwich()`, `coef.rsqbetasandwich()`, `confint.betasandwich()`, `confint.diffbetasandwich()`, `confint.rsqbetasandwich()`, `print.betasandwich()`, `print.rsqbetasandwich()`, `summary.betasandwich()`, `summary.diffbetasandwich()`, `summary.rsqbetasandwich()`, `vcov.betasandwich()`, `vcov.diffbetasandwich()`, `vcov.rsqbetasandwich()`

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
print(diff)
```

---

`print.rsqbetasandwich` *Print Method for an Object of Class rsqbetasandwich*

---

**Description**

Print Method for an Object of Class `rsqbetasandwich`

**Usage**

```
## S3 method for class 'rsqbetasandwich'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```



**Arguments**

<code>x</code>	Object of class <code>rsqbetasandwich</code> .
<code>alpha</code>	Significance level.
<code>digits</code>	Digits to print.
<code>...</code>	additional arguments.

**Value**

Returns a matrix of multiple correlation coefficients (R-squared and adjusted R-squared), standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
print(rsq)
```

---

RSqBetaSandwich	<i>Estimate Multiple Correlation Coefficients (R-squared and adjusted R-squared) and the Corresponding Sampling Covariance Matrix</i>
-----------------	---

---

**Description**

Estimate Multiple Correlation Coefficients (R-squared and adjusted R-squared) and the Corresponding Sampling Covariance Matrix

**Usage**

```
RSqBetaSandwich(object)
```

**Arguments**

<code>object</code>	Object of class <code>betasandwich</code> , that is, the output of the <a href="#">BetaHC()</a> , <a href="#">BetaN()</a> , or <a href="#">BetaADF()</a> functions.
---------------------	---

**Value**

Returns an object of class `rsqbetasandwich` which is a list with the following elements:

**call** Function call.

**fit** The argument object.

**vcov** Sampling covariance matrix of multiple correlation coefficients (R-squared and adjusted R-squared).

**est** Vector of multiple correlation coefficients (R-squared and adjusted R-squared).

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: `BetaADF()`, `BetaHC()`, `BetaN()`, `DiffBetaSandwich()`, `coef.betasandwich()`, `coef.diffbetasandwich()`, `coef.rsqbetasandwich()`, `confint.betasandwich()`, `confint.diffbetasandwich()`, `confint.rsqbetasandwich()`, `print.betasandwich()`, `print.diffbetasandwich()`, `print.rsqbetasandwich()`, `summary.betasandwich()`, `summary.diffbetasandwich()`, `summary.rsqbetasandwich()`, `vcov.betasandwich()`, `vcov.diffbetasandwich()`, `vcov.rsqbetasandwich()`

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
# Methods -----
print(rsq)
summary(rsq)
coef(rsq)
vcov(rsq)
confint(rsq, level = 0.95)
```

---

`summary.betasandwich`    *Summary Method for an Object of Class betasandwich*

---

**Description**

Summary Method for an Object of Class `betasandwich`

**Usage**

```
## S3 method for class 'betasandwich'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

**Arguments**

object	Object of class betasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

**Value**

Returns a matrix of standardized regression slopes, standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
summary(std)
```

---

summary.diffbetasandwich

*Summary Method for an Object of Class diffbetasandwich*

---

**Description**

Summary Method for an Object of Class diffbetasandwich

**Usage**

```
## S3 method for class 'diffbetasandwich'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

**Arguments**

object	Object of class diffbetasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

**Value**

Returns a matrix of differences of standardized regression slopes, standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
summary(diff)
```

---

```
summary.rsqbetasandwich
```

*Summary Method for an Object of Class rsqbetasandwich*

---

**Description**

Summary Method for an Object of Class rsqbetasandwich

**Usage**

```
## S3 method for class 'rsqbetasandwich'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

**Arguments**

object	Object of class rsqbetasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

**Value**

Returns a matrix of multiple correlation coefficients (R-squared and adjusted R-squared), standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
summary(rsq)
```

---

vcov.betasandwich

*Sampling Covariance Matrix of the Standardized Regression Slopes*


---

**Description**

Sampling Covariance Matrix of the Standardized Regression Slopes

**Usage**

```
## S3 method for class 'betasandwich'
vcov(object, ...)
```

**Arguments**

object	Object of class betasandwich.
...	additional arguments.

**Value**

Returns a matrix of the variance-covariance matrix of standardized slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
vcov(std)
```

---

vcov.diffbetasandwich *Sampling Covariance Matrix of Differences of Standardized Regression Slopes*

---

**Description**

Sampling Covariance Matrix of Differences of Standardized Regression Slopes

**Usage**

```
## S3 method for class 'diffbetasandwich'
vcov(object, ...)
```

**Arguments**

object	Object of class diffbetasandwich.
...	additional arguments.

**Value**

Returns a matrix of the variance-covariance matrix of differences of standardized regression slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.rsqbetasandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
vcov(diff)
```

---

vcov.rsqbetasandwich	<i>Sampling Covariance Matrix of Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared)</i>
----------------------	---

---

**Description**

Sampling Covariance Matrix of Multiple Correlation Coefficients (R-Squared and Adjusted R-Squared)

**Usage**

```
## S3 method for class 'rsqbetasandwich'
vcov(object, ...)
```

**Arguments**

object	Object of class rsqbetasandwich.
...	additional arguments.

**Value**

Returns a matrix of the variance-covariance matrix of multiple correlation coefficients (R-squared and adjusted R-squared).

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#), [coef.betasandwich\(\)](#), [coef.diffbetasandwich\(\)](#), [coef.rsqbetasandwich\(\)](#), [confint.betasandwich\(\)](#), [confint.diffbetasandwich\(\)](#), [confint.rsqbetasandwich\(\)](#), [print.betasandwich\(\)](#), [print.diffbetasandwich\(\)](#), [print.rsqbetasandwich\(\)](#), [summary.betasandwich\(\)](#), [summary.diffbetasandwich\(\)](#), [summary.rsqbetasandwich\(\)](#), [vcov.betasandwich\(\)](#), [vcov.diffbetasandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
vcov(rsq)
```



# Index

## \* **Beta Sandwich Functions**

BetaADF, 2  
BetaHC, 4  
BetaN, 5  
coef.betasandwich, 7  
coef.diffbetasandwich, 8  
coef.rsqbetasandwich, 9  
confint.betasandwich, 10  
confint.diffbetasandwich, 11  
confint.rsqbetasandwich, 12  
DiffBetaSandwich, 13  
print.betasandwich, 14  
print.diffbetasandwich, 15  
print.rsqbetasandwich, 16  
RSqBetaSandwich, 17  
summary.betasandwich, 18  
summary.diffbetasandwich, 19  
summary.rsqbetasandwich, 20  
vcov.betasandwich, 21  
vcov.diffbetasandwich, 22  
vcov.rsqbetasandwich, 23

## \* **betaSandwich**

BetaADF, 2  
BetaHC, 4  
BetaN, 5  
DiffBetaSandwich, 13  
RSqBetaSandwich, 17

## \* **data**

nas1982, 14

## \* **diff**

DiffBetaSandwich, 13

## \* **methods**

coef.betasandwich, 7  
coef.diffbetasandwich, 8  
coef.rsqbetasandwich, 9  
confint.betasandwich, 10  
confint.diffbetasandwich, 11  
confint.rsqbetasandwich, 12  
print.betasandwich, 14

print.diffbetasandwich, 15  
print.rsqbetasandwich, 16  
summary.betasandwich, 18  
summary.diffbetasandwich, 19  
summary.rsqbetasandwich, 20  
vcov.betasandwich, 21  
vcov.diffbetasandwich, 22  
vcov.rsqbetasandwich, 23

## \* **rsq**

RSqBetaSandwich, 17

## \* **std**

BetaADF, 2  
BetaHC, 4  
BetaN, 5

BetaADF, 2, 5–13, 15–24

BetaADF(), 2, 13, 17

betaDelta::BetaDelta(), 2, 5

BetaHC, 3, 4, 6–13, 15–24

BetaHC(), 2, 5, 13, 17

BetaN, 3, 5, 5, 7–13, 15–24

BetaN(), 5, 13, 17

coef.betasandwich, 3, 5, 6, 7, 8–13, 15–24

coef.diffbetasandwich, 3, 5–7, 8, 9–13,  
15–24

coef.rsqbetasandwich, 3, 5–8, 9, 10–13,  
15–24

confint.betasandwich, 3, 5–9, 10, 11–13,  
15–24

confint.diffbetasandwich, 3, 5–10, 11, 12,  
13, 15–24

confint.rsqbetasandwich, 3, 5–11, 12, 13,  
15–24

DiffBetaSandwich, 3, 5–12, 13, 15–24

nas1982, 14

print.betasandwich, 3, 5–13, 14, 16–24

`print.diffbetasandwich`, 3, 5–13, 15, 15,  
17–24  
`print.rsqbetasandwich`, 3, 5–13, 15, 16, 16,  
18–24  
`RSqBetaSandwich`, 3, 5–13, 15–17, 17, 19–24  
`summary.betasandwich`, 3, 5–13, 15–18, 18,  
20–24  
`summary.diffbetasandwich`, 3, 5–13, 15–19,  
19, 21–24  
`summary.rsqbetasandwich`, 3, 5–13, 15–20,  
20, 22–24  
`vcov.betasandwich`, 3, 5–13, 15–21, 21, 23,  
24  
`vcov.diffbetasandwich`, 3, 5–13, 15–22, 22,  
24  
`vcov.rsqbetasandwich`, 3, 5–13, 15–23, 23