

# betaSandwich: Methods

Ivan Jacob Agaloos Pesigan

## 1 HC

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
```

```
out <- BetaHC(object, type = "hc3")
str(out)

#> List of 8
#> $ call      : language BetaHC(object = object, type = "hc3")
#> $ lm        :List of 12
#> ..$ coefficients : Named num [1:4] 10.3592 0.0842 0.216 0.1126
#> .. ..- attr(*, "names")= chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ residuals    : Named num [1:46] -3.068 -0.688 2.675 2.052 4.039 ...
#> .. ..- attr(*, "names")= chr [1:46] "1" "2" "3" "4" ...
#> ..$ effects      : Named num [1:46] -187.4 51.49 27.59 -16.11 4.51 ...
#> .. ..- attr(*, "names")= chr [1:46] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP" ...
#> ..$ rank         : int 4
#> ..$ fitted.values: Named num [1:46] 15.1 23.7 26.3 33.9 40 ...
#> .. ..- attr(*, "names")= chr [1:46] "1" "2" "3" "4" ...
#> ..$ assign       : int [1:4] 0 1 2 3
#> ..$ qr           :List of 5
#> .. ..$ qr      : num [1:46, 1:4] -6.782 0.147 0.147 0.147 0.147 ...
#> .. .. ..- attr(*, "dimnames")=List of 2
#> .. .. ..$ : chr [1:46] "1" "2" "3" "4" ...
#> .. .. ..$ : chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> .. .. ..- attr(*, "assign")= int [1:4] 0 1 2 3
#> .. ..$ qraux: num [1:4] 1.15 1.04 1.06 1.09
#> .. ..$ pivot: int [1:4] 1 2 3 4
#> .. ..$ tol   : num 1e-07
#> .. ..$ rank  : int 4
#> .. ..- attr(*, "class")= chr "qr"
#> ..$ df.residual : int 42
#> ..$ xlevels     : Named list()
#> ..$ call        : language lm(formula = QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
#> ..$ terms       :Classes 'terms', 'formula' language QUALITY ~ NARTIC + PCTGRT + PCTSUPP
```

```

#> .. ..- attr(*, "variables")= language list(QUALITY, NARTIC, PCTGRT, PCTSUPP)
#> .. ..- attr(*, "factors")= int [1:4, 1:3] 0 1 0 0 0 0 1 0 0 0 ...
#> .. ..- attr(*, "dimnames")=List of 2
#> .. ..$ : chr [1:4] "QUALITY" "NARTIC" "PCTGRT" "PCTSUPP"
#> .. ..$ : chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> .. ..- attr(*, "term.labels")= chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> .. ..- attr(*, "order")= int [1:3] 1 1 1
#> .. ..- attr(*, "intercept")= int 1
#> .. ..- attr(*, "response")= int 1
#> .. ..- attr(*, ".Environment")=<environment: 0x5632b7b5e3e0>
#> .. ..- attr(*, "predvars")= language list(QUALITY, NARTIC, PCTGRT, PCTSUPP)
#> .. ..- attr(*, "dataClasses")= Named chr [1:4] "numeric" "numeric" "numeric" "numeric"
#> .. ..- attr(*, "names")= chr [1:4] "QUALITY" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ model : 'data.frame': 46 obs. of 4 variables:
#> ..$ QUALITY: int [1:46] 12 23 29 36 44 21 40 42 24 30 ...
#> ..$ NARTIC : int [1:46] 14 61 68 49 130 65 79 187 32 50 ...
#> ..$ PCTGRT : int [1:46] 8 3 13 63 53 29 35 40 19 8 ...
#> ..$ PCTSUPP: int [1:46] 16 67 66 52 64 59 81 65 87 43 ...
#> ..- attr(*, "terms")=Classes 'terms', 'formula' language QUALITY ~ NARTIC + PCTGRT + PCTSUPP
#> .. ..- attr(*, "variables")= language list(QUALITY, NARTIC, PCTGRT, PCTSUPP)
#> .. ..- attr(*, "factors")= int [1:4, 1:3] 0 1 0 0 0 0 1 0 0 0 ...
#> .. ..- attr(*, "dimnames")=List of 2
#> .. ..$ : chr [1:4] "QUALITY" "NARTIC" "PCTGRT" "PCTSUPP"
#> .. ..$ : chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> .. ..- attr(*, "term.labels")= chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> .. ..- attr(*, "order")= int [1:3] 1 1 1
#> .. ..- attr(*, "intercept")= int 1
#> .. ..- attr(*, "response")= int 1
#> .. ..- attr(*, ".Environment")=<environment: 0x5632b7b5e3e0>
#> .. ..- attr(*, "predvars")= language list(QUALITY, NARTIC, PCTGRT, PCTSUPP)
#> .. ..- attr(*, "dataClasses")= Named chr [1:4] "numeric" "numeric" "numeric" "numeric"
#> .. ..- attr(*, "names")= chr [1:4] "QUALITY" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..- attr(*, "class")= chr "lm"
#> $ lm_process:List of 21
#> ..$ x : num [1:46, 1:4] 12 23 29 36 44 21 40 42 24 30 ...
#> .. ..- attr(*, "dimnames")=List of 2
#> .. ..$ : chr [1:46] "1" "2" "3" "4" ...
#> .. ..$ : chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> .. ..- attr(*, "assign")= int [1:4] 0 1 2 3
#> ..$ dims : int [1:2] 46 4
#> ..$ n : int 46
#> ..$ k : int 4
#> ..$ p : num 3
#> ..$ q : num 10
#> ..$ df : int 42

```

```

#> ..$ pinv_of_dcap          : num [1:10, 1:16] 1 0 0 0 0 0 0 0 0 0 ...
#> ..$ varnames              : chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ xnames                : chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ sigmacap              : num [1:4, 1:4] 101 455 129 138 455 ...
#> ..$- attr(*, "dimnames")=List of 2
#> ..$ : chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ : chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ vechsigmacap          : num [1:10] 101 455 129 138 3507 ...
#> ..$ sigma                 : Named num [1:4] 10.1 59.2 18.3 23.5
#> ..$- attr(*, "names")= chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ sigmacap_consistent   : num [1:4, 1:4] 99.2 444.7 125.9 135 444.7 ...
#> ..$- attr(*, "dimnames")=List of 2
#> ..$ : chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ : chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ vechsigmacap_consistent: num [1:10] 99.2 444.7 125.9 135 3430.9 ...
#> ..$ rhocap                : num [1:4, 1:4] 1 0.762 0.7 0.582 0.762 ...
#> ..$- attr(*, "dimnames")=List of 2
#> ..$ : chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ : chr [1:4] "(Intercept)" "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ betastar              : Named num [1:3] 0.495 0.391 0.263
#> ..$- attr(*, "names")= chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ beta                  : Named num [1:3] 0.0842 0.216 0.1126
#> ..$- attr(*, "names")= chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ theta                 : Named num [1:10] 8.42e-02 2.16e-01 1.13e-01 2.12e+01 3.51e+03 ...
#> ..$- attr(*, "names")= chr [1:10] "NARTIC" "PCTGRT" "PCTSUPP" "" ...
#> ..$ dif_betastar          : Named num [1:3] 0.104 0.232 0.128
#> ..$- attr(*, "names")= chr [1:3] "NARTIC-PCTGRT" "NARTIC-PCTSUPP" "PCTGRT-PCTSUPP"
#> ..$ dif_beta              : Named num [1:3] -0.1318 -0.0284 0.1034
#> ..$- attr(*, "names")= chr [1:3] "NARTIC-PCTGRT" "NARTIC-PCTSUPP" "PCTGRT-PCTSUPP"
#> $ type                    : chr "hc3"
#> $ gamma                   : num [1:10, 1:10] 15816 82462 20721 23289 461150 ...
#> $ acov                    : num [1:10, 1:10] 0.2717 -0.1586 -0.0856 -0.3865 8.7763 ...
#> $ vcov                    : num [1:3, 1:3] 0.00617 -0.0036 -0.00194 -0.0036 0.0067 ...
#> ..$- attr(*, "dimnames")=List of 2
#> ..$ : chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> ..$ : chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> $ est                      : Named num [1:3] 0.495 0.391 0.263
#> ..$- attr(*, "names")= chr [1:3] "NARTIC" "PCTGRT" "PCTSUPP"
#> - attr(*, "class")= chr [1:2] "betasandwich" "list"

BetaHC(object, type = "hc3")

#> Call:
#> BetaHC(object = object, type = "hc3")
#>
#> Standardized regression slopes with HC3 standard errors:

```

```
#>      est      se      t      p  0.05%  0.5%  2.5% 97.5% 99.5% 99.95%
#> NARTIC  0.4951 0.0786 6.3025 0.0000  0.2172 0.2832 0.3366 0.6537 0.7071 0.7731
#> PCTGRT  0.3915 0.0818 4.7831 0.0000  0.1019 0.1707 0.2263 0.5567 0.6123 0.6810
#> PCTSUPP 0.2632 0.0855 3.0786 0.0037 -0.0393 0.0325 0.0907 0.4358 0.4940 0.5658
```

## print

```
print(out)

#> Call:
#> BetaHC(object = object, type = "hc3")
#>
#> Standardized regression slopes with HC3 standard errors:
#>      est      se      t      p  0.05%  0.5%  2.5% 97.5% 99.5% 99.95%
#> NARTIC  0.4951 0.0786 6.3025 0.0000  0.2172 0.2832 0.3366 0.6537 0.7071 0.7731
#> PCTGRT  0.3915 0.0818 4.7831 0.0000  0.1019 0.1707 0.2263 0.5567 0.6123 0.6810
#> PCTSUPP 0.2632 0.0855 3.0786 0.0037 -0.0393 0.0325 0.0907 0.4358 0.4940 0.5658
```

## coef

```
coef(out)

#> NULL
```

## vcov

```
vcov(out)

#>      NARTIC      PCTGRT      PCTSUPP
#> NARTIC  0.006172168 -0.003602529 -0.001943469
#> PCTGRT -0.003602529  0.006699155 -0.002443584
#> PCTSUPP -0.001943469 -0.002443584  0.007311625
```

## confint

```
confint(out, level = 0.95)

#>      2.5%      97.5%
#> NARTIC  0.33659828 0.6536920
#> PCTGRT  0.22631203 0.5566654
#> PCTSUPP 0.09068548 0.4358099
```

## summary

```
summary(out)

#> Call:
#> BetaHC(object = object, type = "hc3")
#>
#> Standardized regression slopes with HC3 standard errors:
#>      est      se      t      p  0.05%  0.5%  2.5% 97.5% 99.5% 99.95%
#> NARTIC  0.4951 0.0786 6.3025 0.0000  0.2172 0.2832 0.3366 0.6537 0.7071 0.7731
#> PCTGRT  0.3915 0.0818 4.7831 0.0000  0.1019 0.1707 0.2263 0.5567 0.6123 0.6810
#> PCTSUPP 0.2632 0.0855 3.0786 0.0037 -0.0393 0.0325 0.0907 0.4358 0.4940 0.5658
```

## 2 Multivariate Normal

```
object <- lm(rating ~ ., data = attitude)
```

```
out <- BetaN(object)
str(out)

#> List of 8
#> $ call      : language BetaN(object = object)
#> $ lm        :List of 12
#> ..$ coefficients : Named num [1:7] 10.7871 0.6132 -0.0731 0.3203 0.0817 ...
#> .. ..- attr(*, "names")= chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> ..$ residuals    : Named num [1:30] -8.11 1.647 1.061 -0.227 6.546 ...
#> .. ..- attr(*, "names")= chr [1:30] "1" "2" "3" "4" ...
#> ..$ effects      : Named num [1:30] -354.011 54.107 2.742 11.715 -0.971 ...
#> .. ..- attr(*, "names")= chr [1:30] "(Intercept)" "complaints" "privileges" "learning" ...
#> ..$ rank         : int 7
#> ..$ fitted.values: Named num [1:30] 51.1 61.4 69.9 61.2 74.5 ...
#> .. ..- attr(*, "names")= chr [1:30] "1" "2" "3" "4" ...
#> ..$ assign       : int [1:7] 0 1 2 3 4 5 6
#> ..$ qr           :List of 5
#> .. ..$ qr        : num [1:30, 1:7] -5.477 0.183 0.183 0.183 0.183 ...
#> .. .. ..- attr(*, "dimnames")=List of 2
#> .. .. ..$ : chr [1:30] "1" "2" "3" "4" ...
#> .. .. ..$ : chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> .. .. ..- attr(*, "assign")= int [1:7] 0 1 2 3 4 5 6
#> .. ..$ qraux: num [1:7] 1.18 1 1.29 1.1 1.07 ...
#> .. ..$ pivot: int [1:7] 1 2 3 4 5 6 7
#> .. ..$ tol   : num 1e-07
#> .. ..$ rank  : int 7
```

```

#> .. ..- attr(*, "class")= chr "qr"
#> ..$ df.residual : int 23
#> ..$ xlevels : Named list()
#> ..$ call : language lm(formula = rating ~ ., data = attitude)
#> ..$ terms :Classes 'terms', 'formula' language rating ~ complaints + privileges + learning + raises
#> .. .. ..- attr(*, "variables")= language list(rating, complaints, privileges, learning, raises, ...)
#> .. .. ..- attr(*, "factors")= int [1:7, 1:6] 0 1 0 0 0 0 0 0 1 ...
#> .. .. ..- attr(*, "dimnames")=List of 2
#> .. .. .. ..$ : chr [1:7] "rating" "complaints" "privileges" "learning" "raises" "critical" "advance"
#> .. .. .. ..$ : chr [1:6] "complaints" "privileges" "learning" "raises" "critical" "advance"
#> .. .. ..- attr(*, "term.labels")= chr [1:6] "complaints" "privileges" "learning" "raises" "critical" "advance"
#> .. .. ..- attr(*, "order")= int [1:6] 1 1 1 1 1 1
#> .. .. ..- attr(*, "intercept")= int 1
#> .. .. ..- attr(*, "response")= int 1
#> .. .. ..- attr(*, ".Environment")=<environment: 0x5632b7b5e3e0>
#> .. .. ..- attr(*, "predvars")= language list(rating, complaints, privileges, learning, raises, critical, advance)
#> .. .. ..- attr(*, "dataClasses")= Named chr [1:7] "numeric" "numeric" "numeric" "numeric" "numeric" "numeric" "numeric"
#> .. .. ..- attr(*, "names")= chr [1:7] "rating" "complaints" "privileges" "learning" "raises" "critical" "advance"
#> ..$ model : 'data.frame': 30 obs. of 7 variables:
#> .. ..$ rating : num [1:30] 43 63 71 61 81 43 58 71 72 67 ...
#> .. ..$ complaints: num [1:30] 51 64 70 63 78 55 67 75 82 61 ...
#> .. ..$ privileges: num [1:30] 30 51 68 45 56 49 42 50 72 45 ...
#> .. ..$ learning : num [1:30] 39 54 69 47 66 44 56 55 67 47 ...
#> .. ..$ raises : num [1:30] 61 63 76 54 71 54 66 70 71 62 ...
#> .. ..$ critical : num [1:30] 92 73 86 84 83 49 68 66 83 80 ...
#> .. ..$ advance : num [1:30] 45 47 48 35 47 34 35 41 31 41 ...
#> .. ..- attr(*, "terms")=Classes 'terms', 'formula' language rating ~ complaints + privileges + learning + raises
#> .. .. ..- attr(*, "variables")= language list(rating, complaints, privileges, learning, raises, critical, advance)
#> .. .. ..- attr(*, "factors")= int [1:7, 1:6] 0 1 0 0 0 0 0 0 1 ...
#> .. .. ..- attr(*, "dimnames")=List of 2
#> .. .. .. ..$ : chr [1:7] "rating" "complaints" "privileges" "learning" "raises" "critical" "advance"
#> .. .. .. ..$ : chr [1:6] "complaints" "privileges" "learning" "raises" "critical" "advance"
#> .. .. ..- attr(*, "term.labels")= chr [1:6] "complaints" "privileges" "learning" "raises" "critical" "advance"
#> .. .. ..- attr(*, "order")= int [1:6] 1 1 1 1 1 1
#> .. .. ..- attr(*, "intercept")= int 1
#> .. .. ..- attr(*, "response")= int 1
#> .. .. ..- attr(*, ".Environment")=<environment: 0x5632b7b5e3e0>
#> .. .. ..- attr(*, "predvars")= language list(rating, complaints, privileges, learning, raises, critical, advance)
#> .. .. ..- attr(*, "dataClasses")= Named chr [1:7] "numeric" "numeric" "numeric" "numeric" "numeric" "numeric" "numeric"
#> .. .. ..- attr(*, "names")= chr [1:7] "rating" "complaints" "privileges" "learning" "raises" "critical" "advance"
#> ..- attr(*, "class")= chr "lm"
#> $ lm_process:List of 21
#> ..$ x : num [1:30, 1:7] 43 63 71 61 81 43 58 71 72 67 ...
#> .. ..- attr(*, "dimnames")=List of 2
#> .. .. ..$ : chr [1:30] "1" "2" "3" "4" ...

```

```

#> .. ..$ : chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> .. ..- attr(*, "assign")= int [1:7] 0 1 2 3 4 5 6
#> ..$ dims : int [1:2] 30 7
#> ..$ n : int 30
#> ..$ k : int 7
#> ..$ p : num 6
#> ..$ q : num 28
#> ..$ df : int 23
#> ..$ pinv_of_dcap : num [1:28, 1:49] 1 0 0 0 0 0 0 0 0 0 ...
#> ..$ varnames : chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> ..$ xnames : chr [1:6] "complaints" "privileges" "learning" "raises" ...
#> ..$ sigmacap : num [1:7, 1:7] 148.2 133.8 63.5 89.1 74.7 ...
#> .. ..- attr(*, "dimnames")=List of 2
#> .. ..$ : chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> .. ..$ : chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> ..$ vechsigmacap : num [1:28] 148.2 133.8 63.5 89.1 74.7 ...
#> ..$ sigma : Named num [1:7] 12.2 13.3 12.2 11.7 10.4 ...
#> .. ..- attr(*, "names")= chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> ..$ sigmacap_consistent : num [1:7, 1:7] 143.2 129.3 61.3 86.1 72.2 ...
#> .. ..- attr(*, "dimnames")=List of 2
#> .. ..$ : chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> .. ..$ : chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> ..$ vechsigmacap_consistent: num [1:28] 143.2 129.3 61.3 86.1 72.2 ...
#> ..$ rhocap : num [1:7, 1:7] 1 0.825 0.426 0.624 0.59 ...
#> .. ..- attr(*, "dimnames")=List of 2
#> .. ..$ : chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> .. ..$ : chr [1:7] "(Intercept)" "complaints" "privileges" "learning" ...
#> ..$ betastar : Named num [1:6] 0.6707 -0.0734 0.3089 0.0698 0.0312 ...
#> .. ..- attr(*, "names")= chr [1:6] "complaints" "privileges" "learning" "raises" ...
#> ..$ beta : Named num [1:6] 0.6132 -0.0731 0.3203 0.0817 0.0384 ...
#> .. ..- attr(*, "names")= chr [1:6] "complaints" "privileges" "learning" "raises" ...
#> ..$ theta : Named num [1:28] 0.6132 -0.0731 0.3203 0.0817 0.0384 ...
#> .. ..- attr(*, "names")= chr [1:28] "complaints" "privileges" "learning" "raises" ...
#> ..$ dif_betastar : Named num [1:15] 0.744 0.362 0.601 0.64 0.854 ...
#> .. ..- attr(*, "names")= chr [1:15] "complaints-privileges" "complaints-learning" "complaints-raises" ...
#> ..$ dif_beta : Named num [1:15] 0.686 0.293 0.531 0.575 0.83 ...
#> .. ..- attr(*, "names")= chr [1:15] "complaints-privileges" "complaints-learning" "complaints-raises" ...
#> $ type : chr "mvn"
#> $ gamma : num [1:28, 1:28] 43909 39644 18807 26405 22133 ...
#> $ acov : num [1:28, 1:28] 0.61594 -0.19143 -0.27973 -0.41435 -0.00727 ...
#> $ vcov : num [1:6, 1:6] 0.020531 -0.006381 -0.009324 -0.013812 -0.000242 ...
#> ..- attr(*, "dimnames")=List of 2
#> .. ..$ : chr [1:6] "complaints" "privileges" "learning" "raises" ...
#> .. ..$ : chr [1:6] "complaints" "privileges" "learning" "raises" ...
#> $ est : Named num [1:6] 0.6707 -0.0734 0.3089 0.0698 0.0312 ...

```

```
#>   ..- attr(*, "names")= chr [1:6] "complaints" "privileges" "learning" "raises" ...
#>   - attr(*, "class")= chr [1:2] "betasandwich" "list"
```

```
BetaN(object)
```

```
#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#>      est      se      t      p    0.05%    0.5%    2.5%  97.5%  99.5%
#> complaints  0.6707 0.1433  4.6810 0.0001  0.1309  0.2685  0.3743 0.9671 1.0730
#> privileges -0.0734 0.1197 -0.6136 0.5455 -0.5243 -0.4094 -0.3210 0.1741 0.2625
#> learning    0.3089 0.1431  2.1580 0.0416 -0.2304 -0.0929  0.0128 0.6049 0.7107
#> raises      0.0698 0.1657  0.4213 0.6774 -0.5545 -0.3954 -0.2730 0.4126 0.5350
#> critical    0.0312 0.1047  0.2980 0.7684 -0.3632 -0.2627 -0.1854 0.2478 0.3251
#> advance    -0.1835 0.1338 -1.3717 0.1834 -0.6874 -0.5590 -0.4602 0.0932 0.1920
#>      99.95%
#> complaints 1.2106
#> privileges 0.3774
#> learning    0.8481
#> raises      0.6941
#> critical    0.4256
#> advance     0.3205
```

## print

```
print(out)
```

```
#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#>      est      se      t      p    0.05%    0.5%    2.5%  97.5%  99.5%
#> complaints  0.6707 0.1433  4.6810 0.0001  0.1309  0.2685  0.3743 0.9671 1.0730
#> privileges -0.0734 0.1197 -0.6136 0.5455 -0.5243 -0.4094 -0.3210 0.1741 0.2625
#> learning    0.3089 0.1431  2.1580 0.0416 -0.2304 -0.0929  0.0128 0.6049 0.7107
#> raises      0.0698 0.1657  0.4213 0.6774 -0.5545 -0.3954 -0.2730 0.4126 0.5350
#> critical    0.0312 0.1047  0.2980 0.7684 -0.3632 -0.2627 -0.1854 0.2478 0.3251
#> advance    -0.1835 0.1338 -1.3717 0.1834 -0.6874 -0.5590 -0.4602 0.0932 0.1920
#>      99.95%
#> complaints 1.2106
#> privileges 0.3774
#> learning    0.8481
#> raises      0.6941
#> critical    0.4256
```



```
#> advance      0.3205
```

## coef

```
coef(out)
```

```
#> NULL
```

## vcov

```
vcov(out)
```

```
#>               complaints      privileges      learning      raises      critical
#> complaints  0.0205314876 -0.0063811296 -0.009324286 -0.013811718 -0.0002422133
#> privileges -0.0063811296  0.0143201460 -0.002170471  0.001552377 -0.0002768442
#> learning   -0.0093242861 -0.0021704714  0.020484826 -0.004998152  0.0028372586
#> raises     -0.0138117179  0.0015523774 -0.004998152  0.027456049 -0.0048713593
#> critical   -0.0002422133 -0.0002768442  0.002837259 -0.004871359  0.0109607636
#> advance    0.0096650976 -0.0029432354 -0.006326814 -0.009305030 -0.0017608366
#>               advance
#> complaints  0.009665098
#> privileges -0.002943235
#> learning   -0.006326814
#> raises     -0.009305030
#> critical   -0.001760837
#> advance    0.017890011
```

## confint

```
confint(out, level = 0.95)
```

```
#>               2.5%      97.5%
#> complaints  0.37431113 0.96713928
#> privileges -0.32097709 0.17412223
#> learning    0.01279319 0.60494730
#> raises     -0.27296210 0.41258553
#> critical   -0.18537560 0.24777510
#> advance    -0.46015474 0.09322584
```

## summary

```
summary(out)

#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#>      est      se      t      p    0.05%    0.5%    2.5%  97.5%  99.5%
#> complaints 0.6707 0.1433  4.6810 0.0001  0.1309  0.2685  0.3743 0.9671 1.0730
#> privileges -0.0734 0.1197 -0.6136 0.5455 -0.5243 -0.4094 -0.3210 0.1741 0.2625
#> learning    0.3089 0.1431  2.1580 0.0416 -0.2304 -0.0929  0.0128 0.6049 0.7107
#> raises      0.0698 0.1657  0.4213 0.6774 -0.5545 -0.3954 -0.2730 0.4126 0.5350
#> critical    0.0312 0.1047  0.2980 0.7684 -0.3632 -0.2627 -0.1854 0.2478 0.3251
#> advance     -0.1835 0.1338 -1.3717 0.1834 -0.6874 -0.5590 -0.4602 0.0932 0.1920
#>      99.95%
#> complaints 1.2106
#> privileges 0.3774
#> learning   0.8481
#> raises     0.6941
#> critical   0.4256
#> advance    0.3205
```

## References

- Dudgeon, P. (2017). Some improvements in confidence intervals for standardized regression coefficients. *Psychometrika*, 82(4), 928–951. <https://doi.org/10.1007/s11336-017-9563-z>
- R Core Team. (2022). *R: A language and environment for statistical computing*. R Foundation for Statistical Computing. Vienna, Austria. <https://www.R-project.org/>