

betaSandwich: Internal Tests

Ivan Jacob Agaloos Pesigan

Tests

```
#> test-betaSandwich-beta-sandwich-adj
#> Test passed
#> Call:
#> BetaADF(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#> Call:
#> BetaADF(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#> Test passed

#> test-betaSandwich-beta-sandwich-hc
#> Test passed
#> Call:
#> BetaHC(object = object, type = "hc0")
#>
#> Standardized regression slopes with HC0 standard errors:
#> Call:
#> BetaHC(object = object, type = "hc0")
#>
#> Standardized regression slopes with HC0 standard errors:
#> Test passed
#> Call:
#> BetaHC(object = object, type = "hc1")
#>
#> Standardized regression slopes with HC1 standard errors:
#> Call:
#> BetaHC(object = object, type = "hc1")
#>
#> Standardized regression slopes with HC1 standard errors:
#> Test passed
#> Call:
#> BetaHC(object = object, type = "hc2")
```

```

#>
#> Standardized regression slopes with HC2 standard errors:
#> Call:
#> BetaHC(object = object, type = "hc2")
#>
#> Standardized regression slopes with HC2 standard errors:
#> Test passed
#> Call:
#> BetaHC(object = object, type = "hc3")
#>
#> Standardized regression slopes with HC3 standard errors:
#> Call:
#> BetaHC(object = object, type = "hc3")
#>
#> Standardized regression slopes with HC3 standard errors:
#> Test passed
#> Call:
#> BetaHC(object = object, type = "hc4")
#>
#> Standardized regression slopes with HC4 standard errors:
#> Call:
#> BetaHC(object = object, type = "hc4")
#>
#> Standardized regression slopes with HC4 standard errors:
#> Test passed
#> Call:
#> BetaHC(object = object, type = "hc4m")
#>
#> Standardized regression slopes with HC4M standard errors:
#> Call:
#> BetaHC(object = object, type = "hc4m")
#>
#> Standardized regression slopes with HC4M standard errors:
#> Test passed
#> Call:
#> BetaHC(object = object, type = "hc5")
#>
#> Standardized regression slopes with HC5 standard errors:
#> Call:
#> BetaHC(object = object, type = "hc5")
#>
#> Standardized regression slopes with HC5 standard errors:
#> Test passed
#> test-betaSandwich-beta-sandwich-methods
#> Call:

```

```

#> BetaHC(object = object)
#>
#> Standardized regression slopes with HC3 standard errors:
#>      est      se      t      p  0.05%  0.5%  2.5%  97.5%  99.5% 99.95%
#> NARTIC  0.4951 0.0786 6.3025 0.0000  0.2172 0.2832 0.3366 0.6537 0.7071 0.7731
#> PCTGRT  0.3915 0.0818 4.7831 0.0000  0.1019 0.1707 0.2263 0.5567 0.6123 0.6810
#> PCTSUPP 0.2632 0.0855 3.0786 0.0037 -0.0393 0.0325 0.0907 0.4358 0.4940 0.5658
#> Call:
#> BetaHC(object = object)
#>
#> Standardized regression slopes with HC3 standard errors:
#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#>      est      se      t      p  0.05%  0.5%  2.5%  97.5%  99.5% 99.95%
#> NARTIC  0.4951 0.0759 6.5272 0.000  0.2268 0.2905 0.3421 0.6482 0.6998 0.7635
#> PCTGRT  0.3915 0.0770 5.0824 0.000  0.1190 0.1837 0.2360 0.5469 0.5993 0.6640
#> PCTSUPP 0.2632 0.0747 3.5224 0.001 -0.0011 0.0616 0.1124 0.4141 0.4649 0.5276
#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#> Call:
#> BetaADF(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#>      est      se      t      p  0.05%  0.5%  2.5%  97.5%  99.5% 99.95%
#> NARTIC  0.4951 0.0674 7.3490 0.0000  0.2568 0.3134 0.3592 0.6311 0.6769 0.7335
#> PCTGRT  0.3915 0.0710 5.5164 0.0000  0.1404 0.2000 0.2483 0.5347 0.5830 0.6426
#> PCTSUPP 0.2632 0.0769 3.4231 0.0014 -0.0088 0.0558 0.1081 0.4184 0.4707 0.5353
#> Call:
#> BetaADF(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#> Call:
#> BetaHC(object = object)
#>
#> Standardized regression slopes with HC3 standard errors:
#>      est      se      t p  0.05%  0.5%  2.5%  97.5%  99.5% 99.95%
#> NARTIC 0.7622 0.0645 11.8222 0 0.5349 0.5886 0.6322 0.8921 0.9357 0.9895
#> Call:
#> BetaHC(object = object)
#>
#> Standardized regression slopes with HC3 standard errors:

```

```

#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#>      est      se      t p 0.05%  0.5%  2.5% 97.5% 99.5% 99.95%
#> NARTIC 0.7622 0.0618 12.3341 0 0.5443 0.5958 0.6376 0.8867 0.9285  0.98
#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#> Call:
#> BetaADF(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#>      est      se      t p 0.05%  0.5%  2.5% 97.5% 99.5% 99.95%
#> NARTIC 0.7622 0.0604 12.625 0 0.5493 0.5996 0.6405 0.8838 0.9247  0.975
#> Call:
#> BetaADF(object = object)
#>
#> Standardized regression slopes with MVN standard errors:

#> test-betaSandwich-beta-sandwich-mvn

#> Test passed
#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#> Call:
#> BetaN(object = object)
#>
#> Standardized regression slopes with MVN standard errors:
#> Test passed

#> test-betaSandwich-diff-beta-sandwich-methods

#> Call:
#> DiffBetaSandwich(object = BetaN(object))
#>
#> Difference between standardized regression coefficients with MVN standard errors:
#>      est      se      z      p 0.05%  0.5%  2.5% 97.5%
#> NARTIC-PCTGRT 0.1037 0.1357 0.7640 0.4449 -0.3428 -0.2458 -0.1623 0.3696
#> NARTIC-PCTSUPP 0.2319 0.1252 1.8524 0.0640 -0.1800 -0.0906 -0.0135 0.4773
#> PCTGRT-PCTSUPP 0.1282 0.1227 1.0451 0.2960 -0.2755 -0.1878 -0.1123 0.3688
#>      99.5% 99.95%
#> NARTIC-PCTGRT 0.4531 0.5501
#> NARTIC-PCTSUPP 0.5544 0.6438

```

```

#> PCTGRT-PCTSUPP 0.4443 0.5320
#> Call:
#> DiffBetaSandwich(object = BetaN(object))
#>
#> Difference between standardized regression coefficients with MVN standard errors:
#> Call:
#> DiffBetaSandwich(object = BetaADF(object))
#>
#> Difference between standardized regression coefficients with MVN standard errors:
#>
#>      est      se      z      p    0.05%    0.5%    2.5%  97.5%
#> NARTIC-PCTGRT  0.1037 0.1212 0.8555 0.3923 -0.2950 -0.2084 -0.1338 0.3411
#> NARTIC-PCTSUPP 0.2319 0.1181 1.9642 0.0495 -0.1566 -0.0722  0.0005 0.4633
#> PCTGRT-PCTSUPP 0.1282 0.1215 1.0555 0.2912 -0.2716 -0.1847 -0.1099 0.3664
#>
#>      99.5% 99.95%
#> NARTIC-PCTGRT  0.4158 0.5024
#> NARTIC-PCTSUPP 0.5360 0.6204
#> PCTGRT-PCTSUPP 0.4412 0.5281
#> Call:
#> DiffBetaSandwich(object = BetaADF(object))
#>
#> Difference between standardized regression coefficients with MVN standard errors:
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc0"))
#>
#> Difference between standardized regression coefficients with HC0 standard errors:
#>
#>      est      se      z      p    0.05%    0.5%    2.5%  97.5%
#> NARTIC-PCTGRT  0.1037 0.1201 0.8629 0.3882 -0.2916 -0.2058 -0.1318 0.3391
#> NARTIC-PCTSUPP 0.2319 0.1169 1.9840 0.0473 -0.1527 -0.0692  0.0028 0.4610
#> PCTGRT-PCTSUPP 0.1282 0.1201 1.0674 0.2858 -0.2671 -0.1812 -0.1072 0.3637
#>
#>      99.5% 99.95%
#> NARTIC-PCTGRT  0.4131 0.4989
#> NARTIC-PCTSUPP 0.5330 0.6165
#> PCTGRT-PCTSUPP 0.4377 0.5236
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc0"))
#>
#> Difference between standardized regression coefficients with HC0 standard errors:
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc1"))
#>
#> Difference between standardized regression coefficients with HC1 standard errors:
#>
#>      est      se      z      p    0.05%    0.5%    2.5%  97.5%
#> NARTIC-PCTGRT  0.1037 0.1257 0.8245 0.4097 -0.3100 -0.2202 -0.1427 0.3501
#> NARTIC-PCTSUPP 0.2319 0.1223 1.8958 0.0580 -0.1706 -0.0832 -0.0078 0.4716
#> PCTGRT-PCTSUPP 0.1282 0.1257 1.0199 0.3078 -0.2855 -0.1956 -0.1182 0.3747
#>
#>      99.5% 99.95%

```

```

#> NARTIC-PCTGRT 0.4275 0.5173
#> NARTIC-PCTSUPP 0.5470 0.6344
#> PCTGRT-PCTSUPP 0.4521 0.5420
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc1"))
#>
#> Difference between standardized regression coefficients with HC1 standard errors:
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc2"))
#>
#> Difference between standardized regression coefficients with HC2 standard errors:
#>
#>      est      se      z      p    0.05%    0.5%    2.5%  97.5%
#> NARTIC-PCTGRT 0.1037 0.1302 0.7960 0.4260 -0.3248 -0.2318 -0.1516 0.3589
#> NARTIC-PCTSUPP 0.2319 0.1240 1.8704 0.0614 -0.1761 -0.0875 -0.0111 0.4749
#> PCTGRT-PCTSUPP 0.1282 0.1284 0.9990 0.3178 -0.2942 -0.2024 -0.1234 0.3798
#>
#>      99.5% 99.95%
#> NARTIC-PCTGRT 0.4391 0.5321
#> NARTIC-PCTSUPP 0.5513 0.6399
#> PCTGRT-PCTSUPP 0.4589 0.5506
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc2"))
#>
#> Difference between standardized regression coefficients with HC2 standard errors:
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc3"))
#>
#> Difference between standardized regression coefficients with HC3 standard errors:
#>
#>      est      se      z      p    0.05%    0.5%    2.5%  97.5%
#> NARTIC-PCTGRT 0.1037 0.1417 0.7316 0.4644 -0.3626 -0.2613 -0.1741 0.3814
#> NARTIC-PCTSUPP 0.2319 0.1318 1.7595 0.0785 -0.2018 -0.1076 -0.0264 0.4902
#> PCTGRT-PCTSUPP 0.1282 0.1375 0.9329 0.3509 -0.3241 -0.2259 -0.1412 0.3977
#>
#>      99.5% 99.95%
#> NARTIC-PCTGRT 0.4686 0.5699
#> NARTIC-PCTSUPP 0.5714 0.6656
#> PCTGRT-PCTSUPP 0.4823 0.5806
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc3"))
#>
#> Difference between standardized regression coefficients with HC3 standard errors:
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc4"))
#>
#> Difference between standardized regression coefficients with HC4 standard errors:
#>
#>      est      se      z      p    0.05%    0.5%    2.5%  97.5%
#> NARTIC-PCTGRT 0.1037 0.1452 0.7138 0.4753 -0.3742 -0.2704 -0.1809 0.3883
#> NARTIC-PCTSUPP 0.2319 0.1296 1.7892 0.0736 -0.1946 -0.1020 -0.0221 0.4859

```

```

#> PCTGRT-PCTSUPP 0.1282 0.1361 0.9420 0.3462 -0.3197 -0.2224 -0.1386 0.3951
#>          99.5% 99.95%
#> NARTIC-PCTGRT 0.4777 0.5815
#> NARTIC-PCTSUPP 0.5658 0.6584
#> PCTGRT-PCTSUPP 0.4789 0.5762
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc4"))
#>
#> Difference between standardized regression coefficients with HC4 standard errors:
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc4m"))
#>
#> Difference between standardized regression coefficients with HC4M standard errors:
#>      est      se      z      p    0.05%    0.5%    2.5% 97.5%
#> NARTIC-PCTGRT 0.1037 0.1465 0.7077 0.4791 -0.3783 -0.2736 -0.1834 0.3907
#> NARTIC-PCTSUPP 0.2319 0.1338 1.7331 0.0831 -0.2084 -0.1128 -0.0304 0.4941
#> PCTGRT-PCTSUPP 0.1282 0.1406 0.9123 0.3616 -0.3343 -0.2338 -0.1473 0.4037
#>          99.5% 99.95%
#> NARTIC-PCTGRT 0.4809 0.5856
#> NARTIC-PCTSUPP 0.5766 0.6722
#> PCTGRT-PCTSUPP 0.4903 0.5908
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc4m"))
#>
#> Difference between standardized regression coefficients with HC4M standard errors:
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc5"))
#>
#> Difference between standardized regression coefficients with HC5 standard errors:
#>      est      se      z      p    0.05%    0.5%    2.5% 97.5%
#> NARTIC-PCTGRT 0.1037 0.1312 0.7899 0.4296 -0.3282 -0.2344 -0.1536 0.3609
#> NARTIC-PCTSUPP 0.2319 0.1227 1.8906 0.0587 -0.1717 -0.0841 -0.0085 0.4723
#> PCTGRT-PCTSUPP 0.1282 0.1274 1.0067 0.3141 -0.2909 -0.1999 -0.1214 0.3779
#>          99.5% 99.95%
#> NARTIC-PCTGRT 0.4417 0.5355
#> NARTIC-PCTSUPP 0.5478 0.6355
#> PCTGRT-PCTSUPP 0.4564 0.5474
#> Call:
#> DiffBetaSandwich(object = BetaHC(object, type = "hc5"))
#>
#> Difference between standardized regression coefficients with HC5 standard errors:
#> test-betaSandwich-diff-beta-sandwich
#> Test passed
#> Test passed
#> Test passed

```

```

#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> Test passed
#> test-betaSandwich-r-sq-beta-sandwich-methods

#> Call:
#> RSqBetaSandwich(object = BetaN(object))
#>
#> Multiple correlation with MVN standard errors:
#>      est      se      t      p    0.05%    0.5%    2.5%  97.5%  99.5%
#> rsq.rsq 0.8045 4.1345 0.1946 0.8467 -13.8224 -10.3507 -7.5393 9.1483 11.9598
#> adj.adj 0.7906 4.4299 0.1785 0.8592 -14.8811 -11.1615 -8.1492 9.7304 12.7426
#>      99.95%
#> rsq.rsq 15.4314
#> adj.adj 16.4622
#> Call:
#> RSqBetaSandwich(object = BetaN(object))
#>
#> Multiple correlation with MVN standard errors:
#> Call:
#> RSqBetaSandwich(object = BetaADF(object))
#>
#> Multiple correlation with MVN standard errors:
#>      est      se      t      p    0.05%    0.5%    2.5%  97.5%  99.5%
#> rsq.rsq 0.8045 3.6172 0.2224 0.8251 -11.9923 -8.9550 -6.4953 8.1044 10.5640
#> adj.adj 0.7906 3.8756 0.2040 0.8394 -12.9203 -9.6661 -7.0307 8.6118 11.2472
#>      99.95%
#> rsq.rsq 13.6014
#> adj.adj 14.5015
#> Call:
#> RSqBetaSandwich(object = BetaADF(object))
#>
#> Multiple correlation with MVN standard errors:
#> Call:

```



```

#> RSqBetaSandwich(object = BetaHC(object))
#>
#> Multiple correlation with HC3 standard errors:
#>      est      se      t      p    0.05%    0.5%    2.5%   97.5%   99.5%
#> rsq.rsq 0.8045 3.9483 0.2038 0.8395 -13.1636  -9.8483 -7.1635  8.7725 11.4573
#> adj.adj 0.7906 4.2303 0.1869 0.8527 -14.1753 -10.6231 -7.7466  9.3277 12.2043
#>      99.95%
#> rsq.rsq 14.7726
#> adj.adj 15.7564
#> Call:
#> RSqBetaSandwich(object = BetaHC(object))
#>
#> Multiple correlation with HC3 standard errors:
#> Call:
#> RSqBetaSandwich(object = BetaN(object))
#>
#> Multiple correlation with MVN standard errors:
#>      est      se      t      p    0.05%    0.5%    2.5%   97.5%   99.5%
#> rsq.rsq 0.5809 8.8646 0.0655 0.948 -30.6739 -23.285 -17.2845 18.4463 24.4468
#> adj.adj 0.5714 9.0661 0.0630 0.950 -31.3937 -23.837 -17.7001 18.8428 24.9797
#>      99.95%
#> rsq.rsq 31.8357
#> adj.adj 32.5365
#> Call:
#> RSqBetaSandwich(object = BetaN(object))
#>
#> Multiple correlation with MVN standard errors:
#> Call:
#> RSqBetaSandwich(object = BetaADF(object))
#>
#> Multiple correlation with MVN standard errors:
#>      est      se      t      p    0.05%    0.5%    2.5%   97.5%   99.5%
#> rsq.rsq 0.5809 8.5690 0.0678 0.9463 -29.6315 -22.4891 -16.6887 17.8505 23.6509
#> adj.adj 0.5714 8.7637 0.0652 0.9483 -30.3277 -23.0230 -17.0907 18.2335 24.1657
#>      99.95%
#> rsq.rsq 30.7933
#> adj.adj 31.4704
#> Call:
#> RSqBetaSandwich(object = BetaADF(object))
#>
#> Multiple correlation with MVN standard errors:
#> Call:
#> RSqBetaSandwich(object = BetaHC(object))
#>
#> Multiple correlation with HC3 standard errors:

```

```

#>      est      se      t      p    0.05%    0.5%    2.5%    97.5%    99.5%
#> rsq.rsq 0.5809 8.9208 0.0651 0.9484 -30.8720 -23.4363 -17.3978 18.5596 24.5981
#> adj.adj 0.5714 9.1235 0.0626 0.9503 -31.5964 -23.9917 -17.8159 18.9586 25.1344
#>      99.95%
#> rsq.rsq 32.0338
#> adj.adj 32.7391
#> Call:
#> RSqBetaSandwich(object = BetaHC(object))
#>
#> Multiple correlation with HC3 standard errors:
#> test-betaSandwich-r-sq-beta-sandwich
#> Call:
#> RSqBetaSandwich(object = BetaN(object))
#>
#> Multiple correlation with MVN standard errors:
#> Test passed
#> Call:
#> RSqBetaSandwich(object = BetaADF(object))
#>
#> Multiple correlation with MVN standard errors:
#> Test passed
#> Call:
#> RSqBetaSandwich(object = BetaHC(object))
#>
#> Multiple correlation with HC3 standard errors:
#> Test passed
#> Call:
#> RSqBetaSandwich(object = BetaN(object))
#>
#> Multiple correlation with MVN standard errors:
#> Test passed
#> Call:
#> RSqBetaSandwich(object = BetaADF(object))
#>
#> Multiple correlation with MVN standard errors:
#> Test passed
#> Call:
#> RSqBetaSandwich(object = BetaHC(object))
#>
#> Multiple correlation with HC3 standard errors:
#> Test passed
#> [[1]]
#> [[1]][[1]]
#> [[1]][[1]]$value
#> [[1]][[1]]$value[[1]]

```

```

#> [1] TRUE
#>
#>
#> [[1]][[1]]$visible
#> [1] TRUE
#>
#>
#> [[1]][[2]]
#> [[1]][[2]]$value
#> [[1]][[2]]$value[[1]]
#> [1] TRUE
#>
#>
#> [[1]][[2]]$visible
#> [1] TRUE
#>
#>
#> [[1]][[3]]
#> [[1]][[3]]$value
#> [[1]][[3]]$value[[1]]
#>      2.5%      97.5%
#> 0.6404985 0.8838331
#>
#>
#> [[1]][[3]]$visible
#> [1] TRUE
#>
#>
#> [[1]][[4]]
#> [[1]][[4]]$value
#> [[1]][[4]]$value[[1]]
#> [1] TRUE
#>
#>
#> [[1]][[4]]$visible
#> [1] TRUE
#>
#>
#> [[1]][[5]]
#> [[1]][[5]]$value
#> [[1]][[5]]$value[[1]]
#>      2.5%      97.5%
#> NARTIC-PCTGRT -0.153558897 0.3608717
#> NARTIC-PCTSUPP -0.008509607 0.4723045
#> PCTGRT-PCTSUPP -0.121440586 0.3779227

```

```

#>
#>
#> [[1]][[5]]$visible
#> [1] TRUE
#>
#>
#> [[1]][[6]]
#> [[1]][[6]]$value
#> [[1]][[6]]$value[[1]]
#> [1] TRUE
#>
#>
#> [[1]][[6]]$visible
#> [1] TRUE
#>
#>
#> [[1]][[7]]
#> [[1]][[7]]$value
#> [[1]][[7]]$value[[1]]
#>          2.5%    97.5%
#> rsq.rsq -17.39776 18.55955
#> adj.adj -17.81589 18.95863
#>
#>
#> [[1]][[7]]$visible
#> [1] TRUE
#>
#>
#> [[1]][[8]]
#> [[1]][[8]]$value
#> [[1]][[8]]$value[[1]]
#> [1] TRUE
#>
#>
#> [[1]][[8]]$visible
#> [1] TRUE

```

Environment

```
ls()
```

```
#> [1] "nas1982" "root"    "tex_file"
```

Class

```
#> [[1]]  
#> [1] "data.frame"  
#>  
#> [[2]]  
#> [1] "root_criterion"  
#>  
#> [[3]]  
#> [1] "character"
```

References

R Core Team. (2023). *R: A language and environment for statistical computing*. R Foundation for Statistical Computing. Vienna, Austria. <https://www.R-project.org/>