Package 'betaSandwich'

October 7, 2022

Title Robust Confidence Intervals for Standardized Regression Coefficients
Version 1.0.2.9000
Description Generates robust confidence intervals for standardized regression coefficients using heteroskedasticity-consistent standard errors for models fitted by lm() as described in Dudgeon (2017) <doi:10.1007 s11336-017-9563-z="">.</doi:10.1007>
<pre>URL https://github.com/jeksterslab/betaSandwich,</pre>
https://jeksterslab.github.io/betaSandwich/
BugReports https://github.com/jeksterslab/betaSandwich/issues
License MIT + file LICENSE
Encoding UTF-8
LazyData true
Roxygen list(markdown = TRUE)
Depends R ($>= 3.5.0$), methods
Suggests knitr, rmarkdown, testthat
RoxygenNote 7.2.1
NeedsCompilation no
Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (https://orcid.org/0000-0003-4818-8420)
Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com></r.jeksterslab@gmail.com>
R topics documented:
BetaHC
BetaN
coef.betasandwich
nas1982
print.betasandwich
summary.betasandwich
vcov.betasandwich

2 BetaHC

Index 9

BetaHC	Estimate Standardized Regression Coefficients and Robust Sampling Covariance Matrix

Description

Estimate Standardized Regression Coefficients and Robust Sampling Covariance Matrix

Usage

```
BetaHC(object, type = "hc3", g1 = 1, g2 = 1.5, k = 0.7)
```

Arguments

object	Object of class 1m.
type	Character string. Correction type. Possible values are "hc0", "hc1", "hc2", "hc3", "hc4", "hc4m", and "hc5".
g1	Numeric. g1 value for type = "hc4m" or type = "hc5".
g2	Numeric. g2 value for type = "hc4m".
k	Numeric. Constant for type = "hc5"

Value

Returns an object of class betaSandwich which is a list with the following elements:

call Function call.

type Standard error type.

beta Vector of standardized slopes.

vcov Sampling covariance matrix of the standardized slopes.

n Sample size.

p Number of regressors.

df n-p-1 degrees of freedom

Author(s)

Ivan Jacob Agaloos Pesigan

References

Dudgeon, P. (2017). Some improvements in confidence intervals for standardized regression coefficients. *Psychometrika*, 82(4), 928–951. doi:10.1007/s113360179563z

See Also

Other Beta Sandwich Functions: BetaN()

BetaN 3

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
# Methods ------
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)</pre>
```

BetaN

Estimate Standardized Regression Coefficients and Sampling Covariance Matrix Assuming Multivariate Normality

Description

Estimate Standardized Regression Coefficients and Sampling Covariance Matrix Assuming Multivariate Normality

Usage

```
BetaN(object)
```

Arguments

object

Object of class 1m.

Value

Returns an object of class betaSandwich which is a list with the following elements:

call Function call.

type Standard error type.

beta Vector of standardized slopes.

vcov Sampling covariance matrix of the standardized slopes.

n Sample size.

p Number of regressors.

df n-p-1 degrees of freedom

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Beta Sandwich Functions: BetaHC()

4 coef.betasandwich

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaN(object)
# Methods ------
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)</pre>
```

coef.betasandwich

Standardized Regression Slopes

Description

Standardized Regression Slopes

Usage

```
## S3 method for class 'betasandwich'
coef(object, ...)
```

Arguments

objectObject of class betaSandwich.additional arguments.

Value

Returns a vector of standardized regression slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY \sim NARTIC + PCTGRT + PCTSUPP, data = nas1982) std <- BetaHC(object) coef(std)
```

confint.betasandwich 5

confint.betasandwich Robust Confidence Intervals for Standardized Regression Slopes

Description

Robust Confidence Intervals for Standardized Regression Slopes

Usage

```
## S3 method for class 'betasandwich'
confint(object, parm = NULL, level = 0.95, ...)
```

Arguments

object Object of class betaSandwich.

parm a specification of which parameters are to be given confidence intervals, either

a vector of numbers or a vector of names. If missing, all parameters are consid-

ered.

level the confidence level required.

... additional arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
confint(std, level = 0.95)</pre>
```

nas1982

1982 National Academy of Sciences Doctoral Programs Data

Description

1982 National Academy of Sciences Doctoral Programs Data

Usage

nas1982

6 print.betasandwich

Format

Ratings of 46 doctoral programs in psychology in the USA with the following variables:

QUALITY Program quality ratings.

NFACUL Number of faculty members in the program.

NGRADS Number of program graduates.

PCTSUPP Percentage of program graduates who received support.

PCTGRT Percent of faculty members holding research grants.

NARTIC Number of published articles attributed to program faculty member.

PCTPUB Percent of faculty with one or more published article.

References

National Research Council. (1982). An assessment of research-doctorate programs in the United States: Social and behavioral sciences. doi:10.17226/9781. Reproduced with permission from the National Academy of Sciences, Courtesy of the National Academies Press, Washington, D.C.

print.betasandwich

Print Method for an Object of Class betaSandwich

Description

Print Method for an Object of Class betaSandwich

Usage

```
## S3 method for class 'betasandwich' print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

x Object of class betaSandwich.

alpha Significance level.
digits Digits to print.

... additional arguments.

Value

Returns a matrix of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

summary.betasandwich 7

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
print(std)</pre>
```

summary.betasandwich Summary Method for an Object of Class betaSandwich

Description

Summary Method for an Object of Class betaSandwich

Usage

```
## S3 method for class 'betasandwich' summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

Arguments

object Object of class betaSandwich.

alpha Significance level.

digits Digits to print.

... additional arguments.

Value

Returns a matrix of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
summary(std)</pre>
```

8 vcov.betasandwich

vcov.betasandwich	Robust Sampling Covariance Matrix of the Standardized Regression Slopes

Description

Robust Sampling Covariance Matrix of the Standardized Regression Slopes

Usage

```
## S3 method for class 'betasandwich'
vcov(object, ...)
```

Arguments

```
object Object of class betaSandwich. ... additional arguments.
```

Value

Returns a matrix of the variance-covariance matrix of standardized slopes.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
vcov(std)</pre>
```

Index

```
* Beta Sandwich Functions
    BetaHC, 2
    BetaN, 3
*\ beta Sandwich
    BetaHC, 2
    BetaN, 3
* data
    nas1982, 5
*\ methods
    coef.betasandwich, 4
    confint.betasandwich, 5
    print.betasandwich, 6
    summary.betasandwich, 7
    \verb|vcov.betas| and \verb|wich|, 8
BetaHC, 2, 3
BetaN, 2, 3
{\tt coef.betas} {\tt andwich, 4}
\verb|confint.betas| and wich, 5|
nas1982, 5
print.betasandwich, 6
summary.betasandwich, 7
vcov.betasandwich, 8
```