

# Package ‘betaSandwich’

February 10, 2023

**Title** Robust Confidence Intervals for Standardized Regression Coefficients

**Version** 1.0.3.9000

**Description** Generates robust confidence intervals for standardized regression coefficients using heteroskedasticity-consistent standard errors for models fitted by `lm()` as described in Dudgeon (2017) <[doi:10.1007/s11336-017-9563-z](https://doi.org/10.1007/s11336-017-9563-z)>.

**URL** <https://github.com/jeksterslab/betaSandwich>,  
<https://jeksterslab.github.io/betaSandwich/>

**BugReports** <https://github.com/jeksterslab/betaSandwich/issues>

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**Depends** R (>= 3.5.0)

**Imports** methods

**Suggests** knitr, rmarkdown, testthat

**RoxygenNote** 7.2.3

**NeedsCompilation** no

**Author** Ivan Jacob Agaloos Pesigan [aut, cre, cph]  
(<<https://orcid.org/0000-0003-4818-8420>>)

**Maintainer** Ivan Jacob Agaloos Pesigan <[r.jeksterslab@gmail.com](mailto:r.jeksterslab@gmail.com)>

## R topics documented:

BetaADF . . . . .	2
BetaHC . . . . .	3
BetaN . . . . .	5
coef.betasandwich . . . . .	6
coef.diffbetasandwich . . . . .	7
coef.rsqbetasandwich . . . . .	7

confint.betasandwich . . . . .	8
confint.diffbetasandwich . . . . .	9
confint.rsqbetasandwich . . . . .	10
DiffBetaSandwich . . . . .	11
nas1982 . . . . .	12
print.betasandwich . . . . .	12
print.diffbetasandwich . . . . .	13
print.rsqbetasandwich . . . . .	14
RSqBetaSandwich . . . . .	15
summary.betasandwich . . . . .	16
summary.diffbetasandwich . . . . .	16
summary.rsqbetasandwich . . . . .	17
vcov.betasandwich . . . . .	18
vcov.diffbetasandwich . . . . .	19
vcov.rsqbetasandwich . . . . .	19

<b>Index</b>	<b>21</b>
--------------	-----------

---

BetaADF	<i>Estimate Standardized Regression Coefficients and Sampling Covariance Matrix Using the Asymptotic Distribution-Free Approach</i>
---------	---

---

## Description

Estimate Standardized Regression Coefficients and Sampling Covariance Matrix Using the Asymptotic Distribution-Free Approach

## Usage

BetaADF(object)

## Arguments

object            Object of class `lm`.

## Details

Note that while the calculation in `BetaADF()` is different from `betaDelta::BetaDelta()` with `type = "adf"`, the results are numerically equivalent. `BetaADF()` is appropriate when sample sizes are moderate to large ( $n > 250$ ). `BetaHC()` is recommended in most situations.

## Value

Returns an object of class `betasandwich` which is a list with the following elements:

**call** Function call.

**lm** Object of class `lm`.

**lm\_process** Pre-processed object of class `lm`.

**type** Standard error type.  
**gamman** Asymptotic covariance matrix of the sample covariance matrix assuming multivariate normality.  
**gammahc** Asymptotic covariance matrix HC correction.  
**gamma** Asymptotic covariance matrix of the sample covariance matrix.  
**acov** Asymptotic covariance matrix of the standardized slopes.  
**vcov** Sampling covariance matrix of the standardized slopes.  
**est** Vector of standardized slopes.

### Author(s)

Ivan Jacob Agaloos Pesigan

### See Also

Other Beta Sandwich Functions: [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#)

### Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaADF(object)
# Methods -----
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)
```

---

BetaHC	<i>Estimate Standardized Regression Coefficients and Robust Sampling Covariance Matrix</i>
--------	--

---

### Description

Estimate Standardized Regression Coefficients and Robust Sampling Covariance Matrix

### Usage

```
BetaHC(object, type = "hc3", g1 = 1, g2 = 1.5, k = 0.7)
```

### Arguments

<b>object</b>	Object of class <code>lm</code> .
<b>type</b>	Character string. Correction type. Possible values are "hc0", "hc1", "hc2", "hc3", "hc4", "hc4m", and "hc5".
<b>g1</b>	Numeric. g1 value for type = "hc4m" or type = "hc5".
<b>g2</b>	Numeric. g2 value for type = "hc4m".
<b>k</b>	Numeric. Constant for type = "hc5"

**Value**

Returns an object of class `betasandwich` which is a list with the following elements:

**call** Function call.

**lm** Object of class `lm`.

**lm\_process** Pre-processed object of class `lm`.

**type** Standard error type.

**gamman** Asymptotic covariance matrix of the sample covariance matrix assuming multivariate normality.

**gammahc** Asymptotic covariance matrix HC correction.

**gamma** Asymptotic covariance matrix of the sample covariance matrix.

**acov** Asymptotic covariance matrix of the standardized slopes.

**vcov** Sampling covariance matrix of the standardized slopes.

**est** Vector of standardized slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**References**

Dudgeon, P. (2017). Some improvements in confidence intervals for standardized regression coefficients. *Psychometrika*, 82(4), 928–951. doi:[10.1007/s113360179563z](https://doi.org/10.1007/s113360179563z)

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
# Methods -----
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)
```

---

BetaN	<i>Estimate Standardized Regression Coefficients and Sampling Covariance Matrix Assuming Multivariate Normality</i>
-------	---

---

**Description**

Estimate Standardized Regression Coefficients and Sampling Covariance Matrix Assuming Multivariate Normality

**Usage**

BetaN(object)

**Arguments**

object            Object of class `lm`.

**Details**

Note that while the calculation in `BetaN()` is different from `betaDelta::BetaDelta()` with `type = "mvn"`, the results are numerically equivalent. `BetaN()` assumes multivariate normality. `BetaHC()` is recommended in most situations.

**Value**

Returns an object of class `betasandwich` which is a list with the following elements:

**call** Function call.

**lm** Object of class `lm`.

**lm\_process** Pre-processed object of class `lm`.

**type** Standard error type.

**gamman** Asymptotic covariance matrix of the sample covariance matrix assuming multivariate normality.

**gammahc** Asymptotic covariance matrix HC correction.

**gamma** Asymptotic covariance matrix of the sample covariance matrix.

**acov** Asymptotic covariance matrix of the standardized slopes.

**vcov** Sampling covariance matrix of the standardized slopes.

**est** Vector of standardized slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [DiffBetaSandwich\(\)](#), [RSqBetaSandwich\(\)](#)

**Examples**

```

object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaN(object)
# Methods -----
print(std)
summary(std)
coef(std)
vcov(std)
confint(std, level = 0.95)

```

---

coef.betasandwich	<i>Standardized Regression Slopes</i>
-------------------	---------------------------------------

---

**Description**

Standardized Regression Slopes

**Usage**

```

## S3 method for class 'betasandwich'
coef(object, ...)

```

**Arguments**

object	Object of class betasandwich.
...	additional arguments.

**Value**

Returns a vector of standardized regression slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```

object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
coef(std)

```

---

coef.diffbetasandwich *Differences of Standardized Regression Slopes*

---

**Description**

Differences of Standardized Regression Slopes

**Usage**

```
## S3 method for class 'diffbetasandwich'  
coef(object, ...)
```

**Arguments**

object	Object of class diffbetasandwich.
...	additional arguments.

**Value**

Returns a vector of differences of standardized regression slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)  
std <- BetaHC(object)  
diff <- DiffBetaSandwich(std)  
coef(diff)
```

---

coef.rsqbetasandwich *Differences of Standardized Regression Slopes*

---

**Description**

Differences of Standardized Regression Slopes

**Usage**

```
## S3 method for class 'rsqbetasandwich'  
coef(object, ...)
```

**Arguments**

object            Object of class rsqbetasandwich.  
 ...              additional arguments.

**Value**

Returns a vector of differences of standardized regression slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
coef(rsq)
```

---

confint.betasandwich    *Confidence Intervals for Standardized Regression Slopes*

---

**Description**

Confidence Intervals for Standardized Regression Slopes

**Usage**

```
## S3 method for class 'betasandwich'
confint(object, parm = NULL, level = 0.95, ...)
```

**Arguments**

object            Object of class betasandwich.  
 parm             a specification of which parameters are to be given confidence intervals, either  
                   a vector of numbers or a vector of names. If missing, all parameters are consid-  
                   ered.  
 level            the confidence level required.  
 ...              additional arguments.

**Value**

Returns a matrix of confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan



**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
confint(std, level = 0.95)
```

---

```
confint.diffbetasandwich
```

*Confidence Intervals for Differences of Standardized Regression Slopes*

---

**Description**

Confidence Intervals for Differences of Standardized Regression Slopes

**Usage**

```
## S3 method for class 'diffbetasandwich'
confint(object, parm = NULL, level = 0.95, ...)
```

**Arguments**

object	Object of class diffbetasandwich.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
...	additional arguments.

**Value**

Returns a matrix of confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
confint(diff, level = 0.95)
```

---

```
confint.rsqbetasandwich
```

*Confidence Intervals for Differences of Standardized Regression Slopes*

---

## Description

Confidence Intervals for Differences of Standardized Regression Slopes

## Usage

```
## S3 method for class 'rsqbetasandwich'
confint(object, parm = NULL, level = 0.95, ...)
```

## Arguments

<code>object</code>	Object of class <code>rsqbetasandwich</code> .
<code>parm</code>	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
<code>level</code>	the confidence level required.
<code>...</code>	additional arguments.

## Value

Returns a matrix of confidence intervals.

## Author(s)

Ivan Jacob Agaloos Pesigan

## Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
confint(rsq, level = 0.95)
```

---

DiffBetaSandwich	<i>Estimate Differences of Standardized Slopes and Sampling Covariance Matrix</i>
------------------	---

---

**Description**

Estimate Differences of Standardized Slopes and Sampling Covariance Matrix

**Usage**

```
DiffBetaSandwich(object)
```

**Arguments**

**object** Object of class betasandwich, that is, the output of the BetaHC(), BetaN(), or BetaADF() functions.

**Value**

Returns an object of class diffbetasandwich which is a list with the following elements:

**fit** The argument object.

**vcov** Sampling covariance matrix of differences of standardized slopes.

**est** Vector of differences of standardized slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [RSqBetaSandwich\(\)](#)

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
# Methods -----
print(diff)
summary(diff)
coef(diff)
vcov(diff)
confint(diff, level = 0.95)
```

nas1982

*1982 National Academy of Sciences Doctoral Programs Data***Description**

1982 National Academy of Sciences Doctoral Programs Data

**Usage**

nas1982

**Format**

Ratings of 46 doctoral programs in psychology in the USA with the following variables:

**QUALITY** Program quality ratings.**NFACUL** Number of faculty members in the program.**NGRADS** Number of program graduates.**PCTSUPP** Percentage of program graduates who received support.**PCTGRT** Percent of faculty members holding research grants.**NARTIC** Number of published articles attributed to program faculty member.**PCTPUB** Percent of faculty with one or more published article.**References**

National Research Council. (1982). *An assessment of research-doctorate programs in the United States: Social and behavioral sciences*. doi:10.17226/9781. Reproduced with permission from the National Academy of Sciences, Courtesy of the National Academies Press, Washington, D.C.

print.betasandwich

*Print Method for an Object of Class betasandwich***Description**

Print Method for an Object of Class betasandwich

**Usage**

```
## S3 method for class 'betasandwich'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

**Arguments**

x	Object of class betasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

**Value**

Returns a matrix of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
print(std)
```

---

```
print.diffbetasandwich
```

*Print Method for an Object of Class diffbetasandwich*

---

**Description**

Print Method for an Object of Class diffbetasandwich

**Usage**

```
## S3 method for class 'diffbetasandwich'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

**Arguments**

x	Object of class diffbetasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

**Value**

Returns a matrix of differences of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
print(diff)
```

---

print.rsqbetasandwich *Print Method for an Object of Class rsqbetasandwich*

---

**Description**

Print Method for an Object of Class rsqbetasandwich

**Usage**

```
## S3 method for class 'rsqbetasandwich'
print(x, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

**Arguments**

x	Object of class rsqbetasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

**Value**

Returns a matrix of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
print(rsq)
```

---

RSqBetaSandwich	<i>Estimate Multiple Correlation Coefficients (R-squared and adjusted R-squared) and Sampling Covariance Matrix</i>
-----------------	---

---

## Description

Estimate Multiple Correlation Coefficients (R-squared and adjusted R-squared) and Sampling Covariance Matrix

## Usage

```
RSqBetaSandwich(object)
```

## Arguments

**object** Object of class `betasandwich`, that is, the output of the `BetaHC()`, `BetaN()`, or `BetaADF()` functions.

## Value

Returns an object of class `rsqbetasandwich` which is a list with the following elements:

**fit** The argument object.

**vcov** Sampling covariance matrix of multiple correlation coefficients (R-squared and adjusted R-squared).

**est** Vector of multiple correlation coefficients (R-squared and adjusted R-squared).

## Author(s)

Ivan Jacob Agaloos Pesigan

## See Also

Other Beta Sandwich Functions: [BetaADF\(\)](#), [BetaHC\(\)](#), [BetaN\(\)](#), [DiffBetaSandwich\(\)](#)

## Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
# Methods -----
print(rsq)
summary(rsq)
coef(rsq)
vcov(rsq)
confint(rsq, level = 0.95)
```

---

summary.betasandwich    *Summary Method for an Object of Class betasandwich*

---

### Description

Summary Method for an Object of Class betasandwich

### Usage

```
## S3 method for class 'betasandwich'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

### Arguments

object	Object of class betasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

### Value

Returns a matrix of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

### Author(s)

Ivan Jacob Agaloos Pesigan

### Examples

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
summary(std)
```

---

summary.diffbetasandwich  
*Summary Method for an Object of Class diffbetasandwich*

---

### Description

Summary Method for an Object of Class diffbetasandwich

### Usage

```
## S3 method for class 'diffbetasandwich'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```



**Arguments**

object	Object of class diffbetasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

**Value**

Returns a matrix of differences of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
summary(diff)
```

---

summary.rsqbetasandwich

*Summary Method for an Object of Class rsqbetasandwich*

---

**Description**

Summary Method for an Object of Class rsqbetasandwich

**Usage**

```
## S3 method for class 'rsqbetasandwich'
summary(object, alpha = c(0.05, 0.01, 0.001), digits = 4, ...)
```

**Arguments**

object	Object of class rsqbetasandwich.
alpha	Significance level.
digits	Digits to print.
...	additional arguments.

**Value**

Returns a matrix of standardized regression slopes, standard errors, test statistics, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
summary(rsq)
```

---

vcov.betasandwich

*Sampling Covariance Matrix of the Standardized Regression Slopes*

---

**Description**

Sampling Covariance Matrix of the Standardized Regression Slopes

**Usage**

```
## S3 method for class 'betasandwich'
vcov(object, ...)
```

**Arguments**

object	Object of class betasandwich.
...	additional arguments.

**Value**

Returns a matrix of the variance-covariance matrix of standardized slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
vcov(std)
```

---

vcov.diffbetasandwich    *Sampling Covariance Matrix of Differences of Standardized Regression Slopes*

---

**Description**

Sampling Covariance Matrix of Differences of Standardized Regression Slopes

**Usage**

```
## S3 method for class 'diffbetasandwich'
vcov(object, ...)
```

**Arguments**

object                  Object of class diffbetasandwich.  
...                      additional arguments.

**Value**

Returns a matrix of the variance-covariance matrix of differences of standardized regression slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
diff <- DiffBetaSandwich(std)
vcov(diff)
```

---

vcov.rsqbetasandwich    *Sampling Covariance Matrix of Differences of Standardized Regression Slopes*

---

**Description**

Sampling Covariance Matrix of Differences of Standardized Regression Slopes

**Usage**

```
## S3 method for class 'rsqbetasandwich'
vcov(object, ...)
```

**Arguments**

<code>object</code>	Object of class <code>rsqbetasandwich</code> .
<code>...</code>	additional arguments.

**Value**

Returns a matrix of the variance-covariance matrix of differences of standardized regression slopes.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**Examples**

```
object <- lm(QUALITY ~ NARTIC + PCTGRT + PCTSUPP, data = nas1982)
std <- BetaHC(object)
rsq <- RSqBetaSandwich(std)
vcov(rsq)
```

# Index

## \* **Beta Sandwich Functions**

BetaADF, [2](#)  
BetaHC, [3](#)  
BetaN, [5](#)  
DiffBetaSandwich, [11](#)  
RSqBetaSandwich, [15](#)

## \* **betaSandwich**

BetaADF, [2](#)  
BetaHC, [3](#)  
BetaN, [5](#)  
DiffBetaSandwich, [11](#)  
RSqBetaSandwich, [15](#)

## \* **data**

nas1982, [12](#)

## \* **diff**

DiffBetaSandwich, [11](#)

## \* **methods**

coef.betasandwich, [6](#)  
coef.diffbetasandwich, [7](#)  
coef.rsqbetasandwich, [7](#)  
confint.betasandwich, [8](#)  
confint.diffbetasandwich, [9](#)  
confint.rsqbetasandwich, [10](#)  
print.betasandwich, [12](#)  
print.diffbetasandwich, [13](#)  
print.rsqbetasandwich, [14](#)  
summary.betasandwich, [16](#)  
summary.diffbetasandwich, [16](#)  
summary.rsqbetasandwich, [17](#)  
vcov.betasandwich, [18](#)  
vcov.diffbetasandwich, [19](#)  
vcov.rsqbetasandwich, [19](#)

## \* **rsq**

RSqBetaSandwich, [15](#)

BetaADF, [2](#), [4](#), [5](#), [11](#), [15](#)

BetaHC, [3](#), [3](#), [5](#), [11](#), [15](#)

BetaN, [3](#), [4](#), [5](#), [11](#), [15](#)

coef.betasandwich, [6](#)

coef.diffbetasandwich, [7](#)  
coef.rsqbetasandwich, [7](#)  
confint.betasandwich, [8](#)  
confint.diffbetasandwich, [9](#)  
confint.rsqbetasandwich, [10](#)

DiffBetaSandwich, [3–5](#), [11](#), [15](#)

nas1982, [12](#)

print.betasandwich, [12](#)  
print.diffbetasandwich, [13](#)  
print.rsqbetasandwich, [14](#)

RSqBetaSandwich, [3–5](#), [11](#), [15](#)

summary.betasandwich, [16](#)  
summary.diffbetasandwich, [16](#)  
summary.rsqbetasandwich, [17](#)

vcov.betasandwich, [18](#)  
vcov.diffbetasandwich, [19](#)  
vcov.rsqbetasandwich, [19](#)