

Package ‘dynTools’

June 11, 2026

Title Dynamic Modeling Utilities

Version 0.0.0.9000

Description Utility functions for data preparation when fitting dynamic models.

URL <https://github.com/jeksterslab/dynTools>,
<https://jeksterslab.github.io/dynTools/>

BugReports <https://github.com/jeksterslab/dynTools/issues>

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Depends R (>= 4.1.0)

Suggests knitr, rmarkdown, testthat

Config/roxygen2/version 8.0.0.9000

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0003-4818-8420>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

CheckDynData	2
DeleteInitialNA	3
DeltaTByID	5
DetrendByID	6
ElapsedTimeByID	8
FilterByID	9
InitialNA	11
InsertNA	12
LagByID	14
MakeClockTime	15

PlotByID	16
RegularizeTimeByID	19
ReplaceMissingCode	20
ResolveDuplicateIDTime	22
RoundClockTime	23
ScaleByID	24
SubsetByID	26
SummaryByID	28
Index	30

CheckDynData	<i>Check Dynamic Modeling Data</i>
--------------	------------------------------------

Description

The function checks whether a data frame has the variables and structure required by the dynamic modeling utility functions.

Usage

```
CheckDynData(  
  data,  
  id,  
  time,  
  observed,  
  covariates = NULL,  
  require_unique = TRUE,  
  require_numeric_time = TRUE,  
  require_numeric_observed = TRUE,  
  require_numeric_covariates = FALSE,  
  min_rows = 2L  
)
```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.

require_unique Logical. If TRUE, require unique id-time combinations.
 require_numeric_time Logical. If TRUE, require the time variable to be numeric.
 require_numeric_observed Logical. If TRUE, require observed variables to be numeric.
 require_numeric_covariates Logical. If TRUE, require covariates to be numeric.
 min_rows Positive integer. Minimum number of rows required per ID.

Value

Returns TRUE invisibly if all checks pass.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:2, each = 3),
  time = rep(1:3, times = 2),
  y1 = rnorm(6),
  y2 = rnorm(6)
)
CheckDynData(
  data = data,
  id = "id",
  time = "time",
  observed = c("y1", "y2")
)
```

DeleteInitialNA

Delete for NAs in Initial Row By ID

Description

The function removes initial rows by ID if they contain missing values. This process is repeated until the first row per ID no longer has missing observations.

Usage

```
DeleteInitialNA(data, id, time, observed, covariates = NULL)
```

Arguments

<code>data</code>	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
<code>id</code>	Character string. A character string of the name of the ID variable in the data.
<code>time</code>	Character string. A character string of the name of the TIME variable in the data.
<code>observed</code>	Character vector. A vector of character strings of the names of the observed variables in the data.
<code>covariates</code>	Character vector. A vector of character strings of the names of the covariates in the data.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:2, each = 5),
  time = rep(1:5, times = 2),
  y1 = c(NA, NA, 3, 4, 5, 10, 11, 12, 13, 14),
  y2 = c(NA, 2, 3, 4, 5, 10, 11, 12, 13, 14),
  y3 = c(1, NA, 3, 4, 5, 10, 11, 12, 13, 14)
)
data

DeleteInitialNA(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:3)
)
```

DeltaTByID

*Summarize Time Intervals by ID***Description**

The function returns a diagnostic table describing the spacing of the time variable within each ID.

Usage

```
DeltaTByID(
  data,
  id,
  time,
  observed = NULL,
  covariates = NULL,
  tolerance = sqrt(.Machine$double.eps)
)
```

Arguments

<code>data</code>	Data frame. A data frame object.
<code>id</code>	Character string. A character string of the name of the ID variable in the data.
<code>time</code>	Character string. A character string of the name of the TIME variable in the data.
<code>observed</code>	Character vector. Optional vector of character strings of the names of the observed variables in the data.
<code>covariates</code>	Character vector. Optional vector of character strings of the names of the covariates in the data.
<code>tolerance</code>	Numeric. Tolerance used to determine whether the time intervals are regular.

Value

Returns a data frame with one row per ID.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:2, each = 3),
  time = c(1, 2, 3, 1, 3, 4),
  y = rnorm(6)
)
data

DeltaTByID(
  data = data,
  id = "id",
  time = "time",
  observed = "y"
)
```

DetrendByID

Detrend Observed Variables by ID

Description

The function removes polynomial time trends from observed variables within each ID. Missing observed values are ignored when estimating the trend and remain missing in the residualized variables.

Usage

```
DetrendByID(
  data,
  id,
  time,
  observed,
  covariates = NULL,
  degree = 1L,
  replace = FALSE,
  prefix = "detrend"
)
```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.

observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
degree	Non-negative integer. Degree of the polynomial trend. Use degree = 0 for mean centering by ID.
replace	Logical. If TRUE, replace observed variables with residualized variables. If FALSE, append residualized variables to the data frame.
prefix	Character string. Prefix for residualized variables when replace = FALSE.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:2, each = 4),
  time = rep(1:4, times = 2),
  y = rep(1:4, times = 2)
)
data

DetrendByID(
  data = data,
  id = "id",
  time = "time",
  observed = "y",
  degree = 1
)
```

ElapsedTimeByID	<i>Create Elapsed Time by ID</i>
-----------------	----------------------------------

Description

The function creates an elapsed-time variable within ID. For date-time variables, elapsed time is computed with `difftime()`. For numeric time variables, elapsed time is computed by subtraction, optionally converting from `input_units` to `units`.

Usage

```
ElapsedTimeByID(
  data,
  id,
  time,
  output = "time_elapsed",
  units = "days",
  origin = c("by_id", "global"),
  input_units = NULL,
  replace = FALSE
)
```

Arguments

<code>data</code>	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
<code>id</code>	Character string. A character string of the name of the ID variable in the data.
<code>time</code>	Character string. A character string of the name of the TIME variable in the data.
<code>output</code>	Character string. Name of the elapsed-time variable.
<code>units</code>	Character string. Units for the output elapsed time.
<code>origin</code>	Character string. If <code>origin = "by_id"</code> , each ID's origin is its own minimum non-missing time. If <code>origin = "global"</code> , all IDs use the global minimum non-missing time.
<code>input_units</code>	Character string or NULL. Units of numeric input time. If NULL, numeric time is assumed to already be in the desired output scale and only subtraction is performed.
<code>replace</code>	Logical. If TRUE, replace the original time variable. If FALSE, append output.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = c(1, 1, 2, 2),
  datetime = as.POSIXct(
    c(
      "2020-01-01 00:00:00",
      "2020-01-02 00:00:00",
      "2020-01-03 12:00:00",
      "2020-01-04 00:00:00"
    ),
    tz = "UTC"
  )
)
data

ElapsedTimeByID(
  data = data,
  id = "id",
  time = "datetime",
  output = "time",
  units = "days"
)
```

FilterByID

Filter Dynamic Modeling Data by ID

Description

The function removes IDs that do not satisfy minimum data requirements.

Usage

```
FilterByID(
  data,
  id,
  time,
  observed,
```

```

    covariates = NULL,
    min_rows = 2L,
    min_complete = 2L,
    max_prop_missing = 1,
    allow_initial_na = TRUE,
    allow_all_missing = FALSE
  )

```

Arguments

<code>data</code>	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
<code>id</code>	Character string. A character string of the name of the ID variable in the data.
<code>time</code>	Character string. A character string of the name of the TIME variable in the data.
<code>observed</code>	Character vector. A vector of character strings of the names of the observed variables in the data.
<code>covariates</code>	Character vector. A vector of character strings of the names of the covariates in the data.
<code>min_rows</code>	Non-negative integer. Minimum number of rows required per ID.
<code>min_complete</code>	Non-negative integer. Minimum number of complete observed rows required per ID.
<code>max_prop_missing</code>	Numeric. Maximum allowed proportion of missing values across observed variables.
<code>allow_initial_na</code>	Logical. If FALSE, remove IDs where the initial row contains missing values.
<code>allow_all_missing</code>	Logical. If FALSE, remove IDs where all observed values are missing.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:3, each = 3),
  time = rep(1:3, times = 3),
  y = c(1, 2, 3, NA, NA, 4, NA, NA, NA)
)
data

FilterByID(
  data = data,
  id = "id",
  time = "time",
  observed = "y",
  min_complete = 2
)
```

InitialNA

*Check for NAs in Initial Row By ID***Description**

The function checks if there are missing values for the initial row by ID.

Usage

```
InitialNA(data, id, time, observed, covariates = NULL)
```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.

Value

Returns a vector of ID numbers where the initial row has any missing value.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:2, each = 5),
  time = rep(1:5, times = 2),
  y1 = c(NA, NA, 3, 4, 5, 10, 11, 12, 13, 14),
  y2 = c(NA, 2, 3, 4, 5, 10, 11, 12, 13, 14),
  y3 = c(1, NA, 3, 4, 5, 10, 11, 12, 13, 14)
)
data

InitialNA(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:3)
)
```

InsertNA

Insert NAs for Missing Observations

Description

The function creates a sequence of time values. It starts with the smallest time value as the starting point and the largest time value as the endpoint. The sequence is incremented by `delta_t`. This new sequence is combined with the existing empirical time values. For any specific time value where there are no observations, NAs are inserted.

Usage

```
InsertNA(data, id, time, observed, covariates = NULL, delta_t)
```

Arguments

<code>data</code>	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
-------------------	---

id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
delta_t	Positive number. Time interval.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = c(1, 1, 1, 2, 2, 2),
  time = c(1, 2, 4, 1, 3, 4),
  y1 = c(10, 11, 13, 20, 22, 23),
  y2 = c(5, 6, 8, 15, 17, 18)
)
data

InsertNA(
  data = data,
  id = "id",
  time = "time",
  observed = c("y1", "y2"),
  delta_t = 1
)
```

LagByID

*Create Lagged Variables by ID***Description**

The function creates lagged observed variables within ID. Lagged values never cross ID boundaries.

Usage

```
LagByID(data, id, time, observed, covariates = NULL, lags = 1L, prefix = "lag")
```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
lags	Positive integer vector. Lags to create.
prefix	Character string. Prefix for the lagged variable names.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:2, each = 3),
  time = rep(1:3, times = 2),
  y1 = rnorm(6),
  y2 = rnorm(6)
)
data

LagByID(
  data = data,
  id = "id",
  time = "time",
  observed = c("y1", "y2"),
  lags = 1
)
```

MakeClockTime

Make Clock Time

Description

The function combines a date and a clock time into a POSIXct vector. Clock time can be supplied as decimal hours, for example 13.5, or as a character time, for example "13:30" or "13:30:00".

Usage

```
MakeClockTime(
  date,
  time,
  tz = "UTC",
  date_formats = c("%m/%d/%y", "%m/%d/%Y", "%Y-%m-%d"),
  invalid = c("NA", "error")
)
```

Arguments

date	Date vector. Dates can be supplied as Date, POSIXt, or character values.
time	Numeric or character vector. Clock time in decimal hours, "HH:MM", or "HH:MM:SS" format.
tz	Character string. Time zone passed to as.POSIXct().
date_formats	Character vector. Date formats used to parse character dates.
invalid	Character string. If invalid = "NA", invalid clock times are returned as NA. If invalid = "error", invalid clock times throw an error.

Value

Returns a POSIXct vector.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
MakeClockTime(
  date = "2020-01-02",
  time = 13.5,
  tz = "America/New_York"
)
```

```
MakeClockTime(
  date = "01/02/20",
  time = "13:30",
  tz = "America/New_York"
)
```

PlotByID

Plot Observed Variables by ID

Description

The function creates one time-series plot for each observed variable. Within each plot, trajectories are overlaid by ID.

Usage

```
PlotByID(
  data,
  id,
  time,
  observed,
  ids = NULL,
  times = NULL,
  type = "b",
  pch = NULL,
```

```

    lty = NULL,
    col = NULL,
    xlab = NULL,
    ylab = NULL,
    main = NULL,
    xlim = NULL,
    ylim = NULL,
    legend = FALSE,
    ask = NULL,
    ...
  )

```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
ids	Optional vector. ID values to plot. If NULL, all available IDs are plotted.
times	Optional vector of time values. If NULL, all available time points are plotted. If supplied, the range of times is used to subset the data. For example, times = c(0, 9) plots all rows with time values from 0 to 9, inclusive.
type	Character string. Plot type passed to <code>graphics::lines()</code> . Default is "b".
pch	Optional vector of plotting characters. If NULL, plotting characters are generated automatically by ID. Recycled to match the number of plotted IDs.
lty	Optional vector of line types. If NULL, line types are generated automatically by ID. Recycled to match the number of plotted IDs.
col	Optional vector of colors. If NULL, colors are generated automatically by ID. Recycled to match the number of plotted IDs.
xlab	Optional character string. Label for the x-axis. If NULL, the name of the time variable is used.
ylab	Optional character string. Label for the y-axis. If NULL, the observed variable name is used.
main	Optional character string. Plot title prefix. If NULL, the observed variable name is used.
xlim	Optional vector of length 2. Limits for the x-axis.
ylim	Optional numeric vector of length 2. Limits for the y-axis. If NULL, limits are computed separately for each observed variable.
legend	Logical. If TRUE, add a legend identifying IDs.

ask Logical. If TRUE, ask before drawing the next observed-variable plot. The default is TRUE in interactive sessions when plotting more than one observed variable.

... Additional arguments passed to `graphics::lines()`.

Value

Invisibly returns the IDs that were plotted.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: `CheckDynData()`, `DeleteInitialNA()`, `DeltaTByID()`, `DetrendByID()`, `ElapsedTimeByID()`, `FilterByID()`, `InitialNA()`, `InsertNA()`, `LagByID()`, `MakeClockTime()`, `RegularizeTimeByID()`, `ReplaceMissingCode()`, `ResolveDuplicateIDTime()`, `RoundClockTime()`, `ScaleByID()`, `SubsetByID()`, `SummaryByID()`

Examples

```
data <- data.frame(
  id = rep(1:4, each = 5),
  time = rep(1:5, times = 4),
  y1 = c(
    1, 2, 3, 4, 5,
    2, 3, 4, 5, 6,
    3, 4, 5, 6, 7,
    4, 5, 6, 7, 8
  ),
  y2 = c(
    5, 4, 3, 2, 1,
    6, 5, 4, 3, 2,
    7, 6, 5, 4, 3,
    8, 7, 6, 5, 4
  ),
  y3 = c(
    1, 1, 2, 2, 3,
    2, 2, 3, 3, 4,
    3, 3, 4, 4, 5,
    4, 4, 5, 5, 6
  )
)
data

PlotByID(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:3),
  ask = FALSE
```

```

)

PlotByID(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:3),
  ids = 1:3,
  times = c(1, 3),
  legend = TRUE,
  ask = FALSE
)

```

RegularizeTimeByID	<i>Regularize Time by ID</i>
--------------------	------------------------------

Description

The function inserts rows with missing values so that time follows a regular grid. A global grid uses the same time sequence for every ID. An ID-specific grid uses each ID's own minimum and maximum observed time values.

Usage

```

RegularizeTimeByID(
  data,
  id,
  time,
  observed,
  covariates = NULL,
  delta_t,
  grid = c("global", "by_id")
)

```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.

covariates	Character vector. A vector of character strings of the names of the covariates in the data.
delta_t	Positive number. Time interval.
grid	Character string. If grid = "global", use one time grid from the global minimum to the global maximum time value. If grid = "by_id", use an ID-specific time grid from each ID's minimum to maximum time value.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = c(1, 1, 2, 2),
  time = c(1, 3, 1, 2),
  y = c(10, 12, 20, 21)
)
data

RegularizeTimeByID(
  data = data,
  id = "id",
  time = "time",
  observed = "y",
  delta_t = 1,
  grid = "by_id"
)
```

ReplaceMissingCode

Replace Missing-Value Codes

Description

The function replaces user-specified missing-value codes with NA in a data frame. The replacement is applied column by column and preserves the original column classes whenever possible.

Usage

```
ReplaceMissingCode(data, values = c(-999, "-999"), columns = names(data))
```

Arguments

data	Data frame.
values	Vector. Values to replace with NA.
columns	Character vector. Names of the columns where replacement should be applied. If NULL, no columns are modified.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = 1:3,
  y = c(1, -999, 3),
  x = c("a", "-999", "c"),
  stringsAsFactors = FALSE
)
data

ReplaceMissingCode(
  data = data,
  values = c(-999, "-999")
)
```

ResolveDuplicateIDTime

Resolve Duplicate ID-Time Rows

Description

The function resolves exact duplicate id-time rows using a simple deterministic rule. This is useful before inserting missing rows on a time grid because grid-completion functions generally require unique id-time combinations.

Usage

```
ResolveDuplicateIDTime(
  data,
  id,
  time,
  observed = NULL,
  covariates = NULL,
  method = c("first", "last", "max_complete"),
  order_by = NULL,
  decreasing = FALSE
)
```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
method	Character string. Rule used to choose one row from each duplicated id-time group. If method = "first", keep the first row after sorting by id and time. If method = "last", keep the last row after sorting by id and time. If method = "max_complete", keep the row with the largest number of non-missing values in observed.
order_by	Character vector. Optional columns used to break ties after the main method rule.
decreasing	Logical. If TRUE, sort order_by columns in decreasing order.

Value

Returns a data frame with unique id-time rows.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = c(1, 1, 1),
  time = c(0, 0, 1),
  y1 = c(NA, 1, 2),
  y2 = c(NA, 1, 3)
)
data

ResolveDuplicateIDTime(
  data = data,
  id = "id",
  time = "time",
  observed = c("y1", "y2"),
  method = "max_complete"
)
```

RoundClockTime

Round Clock Time

Description

The function rounds, floors, or ceilings clock times to a specified unit. It supports POSIXt, Date, and numeric time values.

Usage

```
RoundClockTime(
  x,
  unit = "hour",
  method = c("round", "floor", "ceiling"),
  origin = "1970-01-01",
  tz = "UTC"
)
```

Arguments

x	A POSIXt, Date, or numeric vector.
unit	Character string. Unit to round to. Supported values are "second", "minute", "hour", "day", and their plural forms.
method	Character string. One of "round", "floor", or "ceiling".
origin	Origin for numeric time values. Only used if x is numeric.
tz	Character string. Time zone used when numeric time values are converted to POSIXct.

Value

Returns a vector with rounded times.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
x <- as.POSIXct(
  "2020-01-01 10:31:00",
  tz = "America/New_York"
)

RoundClockTime(
  x = x,
  unit = "hour"
)
```

ScaleByID	<i>Scale by ID</i>
-----------	--------------------

Description

The function scales the data by ID.

Usage

```
ScaleByID(
  data,
  id,
  time,
  observed,
  covariates = NULL,
  scale = TRUE,
  obs_skip = NULL,
  cov_skip = NULL
)
```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
scale	Logical. If scale = TRUE, standardize by id. If scale = FALSE, mean center by id.
obs_skip	Character vector. A vector of character strings of the names of the observed variables to skip centering/scaling.
cov_skip	Character vector. A vector of character strings of the names of the covariates to skip centering/scaling.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [SubsetByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:3, each = 4),
  time = rep(1:4, times = 3),
  y1 = c(
    1, 2, 3, 4,
    10, 11, 12, 13,
    20, 22, 24, 26
  ),
  y2 = c(
    4, 3, 2, 1,
    13, 12, 11, 10,
    26, 24, 22, 20
  )
)
data

ScaleByID(
  data = data,
  id = "id",
  time = "time",
  observed = c("y1", "y2")
)

ScaleByID(
  data = data,
  id = "id",
  time = "time",
  observed = c("y1", "y2"),
  scale = FALSE
)
```

SubsetByID

*Subset Data Set by ID***Description**

The function creates a list of data frames for each ID.

Usage

```
SubsetByID(data, id, time, observed, covariates = NULL)
```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
------	---

id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.

Value

Returns a list by ID numbers.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SummaryByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:3, each = 4),
  time = rep(1:4, times = 3),
  y1 = c(
    1, 2, 3, 4,
    10, 11, 12, 13,
    20, 21, 22, 23
  ),
  y2 = c(
    4, 3, 2, 1,
    13, 12, 11, 10,
    23, 22, 21, 20
  )
)
data

SubsetByID(
  data = data,
  id = "id",
  time = "time",
  observed = c("y1", "y2")
)
```

SummaryByID

*Summarize Dynamic Modeling Data by ID***Description**

The function returns a diagnostic table with one row per ID.

Usage

```
SummaryByID(data, id, time, observed, covariates = NULL)
```

Arguments

<code>data</code>	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
<code>id</code>	Character string. A character string of the name of the ID variable in the data.
<code>time</code>	Character string. A character string of the name of the TIME variable in the data.
<code>observed</code>	Character vector. A vector of character strings of the names of the observed variables in the data.
<code>covariates</code>	Character vector. A vector of character strings of the names of the covariates in the data.

Value

Returns a data frame with one row per ID.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [CheckDynData\(\)](#), [DeleteInitialNA\(\)](#), [DeltaTByID\(\)](#), [DetrendByID\(\)](#), [ElapsedTimeByID\(\)](#), [FilterByID\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#), [LagByID\(\)](#), [MakeClockTime\(\)](#), [PlotByID\(\)](#), [RegularizeTimeByID\(\)](#), [ReplaceMissingCode\(\)](#), [ResolveDuplicateIDTime\(\)](#), [RoundClockTime\(\)](#), [ScaleByID\(\)](#), [SubsetByID\(\)](#)

Examples

```
data <- data.frame(
  id = rep(1:2, each = 3),
  time = rep(1:3, times = 2),
  y1 = c(1, NA, 3, 4, 5, 6),
  y2 = c(1, 2, 3, NA, NA, NA)
```

```
)  
data  
  
SummaryByID(  
  data = data,  
  id = "id",  
  time = "time",  
  observed = c("y1", "y2")  
)
```

Index

* **Dynamic Modeling Utility Functions**

- CheckDynData, 2
- DeleteInitialNA, 3
- DeltaTByID, 5
- DetrendByID, 6
- ElapsedTimeByID, 8
- FilterByID, 9
- InitialNA, 11
- InsertNA, 12
- LagByID, 14
- MakeClockTime, 15
- PlotByID, 16
- RegularizeTimeByID, 19
- ReplaceMissingCode, 20
- ResolveDuplicateIDTime, 22
- RoundClockTime, 23
- ScaleByID, 24
- SubsetByID, 26
- SummaryByID, 28

* **data**

- CheckDynData, 2
- DeleteInitialNA, 3
- DeltaTByID, 5
- DetrendByID, 6
- ElapsedTimeByID, 8
- FilterByID, 9
- InitialNA, 11
- InsertNA, 12
- LagByID, 14
- MakeClockTime, 15
- RegularizeTimeByID, 19
- ReplaceMissingCode, 20
- ResolveDuplicateIDTime, 22
- RoundClockTime, 23
- ScaleByID, 24
- SubsetByID, 26
- SummaryByID, 28

* **dynTools**

- CheckDynData, 2

- DeleteInitialNA, 3
- DeltaTByID, 5
- DetrendByID, 6
- ElapsedTimeByID, 8
- FilterByID, 9
- InitialNA, 11
- InsertNA, 12
- LagByID, 14
- MakeClockTime, 15
- PlotByID, 16
- RegularizeTimeByID, 19
- ReplaceMissingCode, 20
- ResolveDuplicateIDTime, 22
- RoundClockTime, 23
- ScaleByID, 24
- SubsetByID, 26
- SummaryByID, 28

* **plot**

- PlotByID, 16

- CheckDynData, 2
- CheckDynData(), 4, 5, 7, 9, 10, 12–14, 16, 18, 20, 21, 23–25, 27, 28
- DeleteInitialNA, 3
- DeleteInitialNA(), 3, 5, 7, 9, 10, 12–14, 16, 18, 20, 21, 23–25, 27, 28
- DeltaTByID, 5
- DeltaTByID(), 3, 4, 7, 9, 10, 12–14, 16, 18, 20, 21, 23–25, 27, 28
- DetrendByID, 6
- DetrendByID(), 3–5, 9, 10, 12–14, 16, 18, 20, 21, 23–25, 27, 28
- ElapsedTimeByID, 8
- ElapsedTimeByID(), 3–5, 7, 10, 12–14, 16, 18, 20, 21, 23–25, 27, 28
- FilterByID, 9
- FilterByID(), 3–5, 7, 9, 12–14, 16, 18, 20, 21, 23–25, 27, 28

graphics::lines(), 17, 18

InitialNA, 11

InitialNA(), 3–5, 7, 9, 10, 13, 14, 16, 18, 20,
21, 23–25, 27, 28

InsertNA, 12

InsertNA(), 3–5, 7, 9, 10, 12, 14, 16, 18, 20,
21, 23–25, 27, 28

LagByID, 14

LagByID(), 3–5, 7, 9, 10, 12, 13, 16, 18, 20,
21, 23–25, 27, 28

MakeClockTime, 15

MakeClockTime(), 3–5, 7, 9, 10, 12–14, 18,
20, 21, 23–25, 27, 28

PlotByID, 16

PlotByID(), 3–5, 7, 9, 10, 12–14, 16, 20, 21,
23–25, 27, 28

RegularizeTimeByID, 19

RegularizeTimeByID(), 3–5, 7, 9, 10, 12–14,
16, 18, 21, 23–25, 27, 28

ReplaceMissingCode, 20

ReplaceMissingCode(), 3–5, 7, 9, 10, 12–14,
16, 18, 20, 23–25, 27, 28

ResolveDuplicateIDTime, 22

ResolveDuplicateIDTime(), 3–5, 7, 9, 10,
12–14, 16, 18, 20, 21, 24, 25, 27, 28

RoundClockTime, 23

RoundClockTime(), 3–5, 7, 9, 10, 12–14, 16,
18, 20, 21, 23, 25, 27, 28

ScaleByID, 24

ScaleByID(), 3–5, 7, 9, 10, 12–14, 16, 18, 20,
21, 23, 24, 27, 28

SubsetByID, 26

SubsetByID(), 3–5, 7, 9, 10, 12–14, 16, 18,
20, 21, 23–25, 28

SummaryByID, 28

SummaryByID(), 3–5, 7, 9, 10, 12–14, 16, 18,
20, 21, 23–25, 27