

# Package ‘dynUtils’

March 18, 2024

**Title** Dynamic Modeling Utilities

**Version** 0.0.0.9000

**Description** Utility functions for data preparation when fitting dynamic models.

**URL** <https://github.com/jeksterslab/dynUtils>,  
<https://jeksterslab.github.io/dynUtils/>

**BugReports** <https://github.com/jeksterslab/dynUtils/issues>

**License** GPL (>= 3)

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**VignetteBuilder** knitr

**Depends** R (>= 3.5.0)

**Suggests** knitr, rmarkdown, testthat, simStateSpace

**RoxygenNote** 7.3.1

**NeedsCompilation** no

**Author** Ivan Jacob Agaloos Pesigan [aut, cre, cph]  
(<https://orcid.org/0000-0003-4818-8420>)

**Maintainer** Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

## R topics documented:

DeleteInitialNA . . . . .	2
InitialNA . . . . .	3
InsertNA . . . . .	5
print.dynutillist . . . . .	7
SubsetByID . . . . .	8
<b>Index</b>	<b>10</b>

DeleteInitialNA

*Delete for NAs in Initial Row By ID***Description**

Deletes the initial row by ID if there are missing values. The function does this recursively until the first row per ID does not have missing observations.

**Usage**

```
DeleteInitialNA(data, id, time, observed, covariates = NULL, ncores = NULL)
```

**Arguments**

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
ncores	Positive integer. Number of cores to use. If ncores = NULL, use a single core. Consider using multiple cores when number of individuals is large.

**Value**

Returns a data frame.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Dynamic Modeling Utility Functions: [InitialNA\(\)](#), [InsertNA\(\)](#), [SubsetByID\(\)](#)

**Examples**

```

# prepare parameters
set.seed(42)
## number of individuals
n <- 5
## time points
time <- 5
## dynamic structure
p <- 3
mu0 <- rep(x = 0, times = p)
sigma0 <- 0.001 * diag(p)
sigma0_l <- t(chol(sigma0))
alpha <- rep(x = 0, times = p)
beta <- 0.50 * diag(p)
psi <- 0.001 * diag(p)
psi_l <- t(chol(psi))

library(simStateSpace)
ssm <- SimSSMVARFixed(
  n = n,
  time = time,
  mu0 = mu0,
  sigma0_l = sigma0_l,
  alpha = alpha,
  beta = beta,
  psi_l = psi_l,
  type = 0
)
data <- as.data.frame(ssm)
# Replace first row with NA
data[1, paste0("y", 1:p)] <- NA
DeleteInitialNA(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:p),
)

```

InitialNA

*Check for NAs in Initial Row By ID***Description**

Check for NAs in Initial Row By ID

**Usage**

```
InitialNA(data, id, time, observed, covariates = NULL, ncores = NULL)
```

**Arguments**

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
ncores	Positive integer. Number of cores to use. If ncores = NULL, use a single core. Consider using multiple cores when number of individuals is large.

**Value**

Returns a vector of ID numbers where the initial row has any missing value.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Dynamic Modeling Utility Functions: [DeleteInitialNA\(\)](#), [InsertNA\(\)](#), [SubsetByID\(\)](#)

**Examples**

```
# prepare parameters
set.seed(42)
## number of individuals
n <- 5
## time points
time <- 5
## dynamic structure
p <- 3
mu0 <- rep(x = 0, times = p)
sigma0 <- 0.001 * diag(p)
sigma0_l <- t(chol(sigma0))
alpha <- rep(x = 0, times = p)
beta <- 0.50 * diag(p)
psi <- 0.001 * diag(p)
psi_l <- t(chol(psi))

library(simStateSpace)
ssm <- SimSSMVARFixed(
  n = n,
  time = time,
```

```

    mu0 = mu0,
    sigma0_l = sigma0_l,
    alpha = alpha,
    beta = beta,
    psi_l = psi_l,
    type = 0
  )
data <- as.data.frame(ssm)
# Replace first row with NA
data[1, paste0("y", 1:p)] <- NA
InitialNA(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:p),
)

```

---

InsertNA

---

*Insert NAs for Missing Observations*


---

## Description

Creates a sequence of time values using the smallest time-interval as starting point and the largest time-interval as end point with `delta_t` increments. This new sequence is added to the empirical time values. Rows with no observations for each specific time value are inserted as NAs.

## Usage

```
InsertNA(data, id, time, observed, covariates = NULL, delta_t, ncores = NULL)
```

## Arguments

<code>data</code>	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
<code>id</code>	Character string. A character string of the name of the ID variable in the data.
<code>time</code>	Character string. A character string of the name of the TIME variable in the data.
<code>observed</code>	Character vector. A vector of character strings of the names of the observed variables in the data.
<code>covariates</code>	Character vector. A vector of character strings of the names of the covariates in the data.
<code>delta_t</code>	Positive number. Time interval.
<code>ncores</code>	Positive integer. Number of cores to use. If <code>ncores = NULL</code> , use a single core. Consider using multiple cores when number of individuals is large.

**Value**

Returns a data frame.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**See Also**

Other Dynamic Modeling Utility Functions: [DeleteInitialNA\(\)](#), [InitialNA\(\)](#), [SubsetByID\(\)](#)

**Examples**

```
# prepare parameters
set.seed(42)
## number of individuals
n <- 5
## time points
time <- 5
## dynamic structure
p <- 3
mu0 <- rep(x = 0, times = p)
sigma0 <- 0.001 * diag(p)
sigma0_l <- t(chol(sigma0))
alpha <- rep(x = 0, times = p)
beta <- 0.50 * diag(p)
psi <- 0.001 * diag(p)
psi_l <- t(chol(psi))

library(simStateSpace)
ssm <- SimSSMVARFixed(
  n = n,
  time = time,
  mu0 = mu0,
  sigma0_l = sigma0_l,
  alpha = alpha,
  beta = beta,
  psi_l = psi_l,
  type = 0
)
data <- as.data.frame(ssm)
InsertNA(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:p),
  delta_t = 0.10
)
```

---

print.dynutillist	<i>Print Method for Object of Class dynutillist</i>
-------------------	---

---

## Description

Print Method for Object of Class dynutillist

## Usage

```
## S3 method for class 'dynutillist'  
print(x, ...)
```

## Arguments

x	an object of class dynutillist.
...	further arguments.

## Author(s)

Ivan Jacob Agaloos Pesigan

## Examples

```
# prepare parameters  
set.seed(42)  
## number of individuals  
n <- 5  
## time points  
time <- 5  
## dynamic structure  
p <- 3  
mu0 <- rep(x = 0, times = p)  
sigma0 <- 0.001 * diag(p)  
sigma0_l <- t(chol(sigma0))  
alpha <- rep(x = 0, times = p)  
beta <- 0.50 * diag(p)  
psi <- 0.001 * diag(p)  
psi_l <- t(chol(psi))  
  
library(simStateSpace)  
ssm <- SimSSMVARFixed(  
  n = n,  
  time = time,  
  mu0 = mu0,  
  sigma0_l = sigma0_l,  
  alpha = alpha,  
  beta = beta,  
  psi_l = psi_l,  
  type = 0
```

```

)
data <- as.data.frame(ssm)
out <- SubsetByID(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:p)
)
print(out)

```

SubsetByID

*Subset Data Set by ID***Description**

Creates a list of data frames for each ID.

**Usage**

```
SubsetByID(data, id, time, observed, covariates = NULL, ncores = NULL)
```

**Arguments**

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
ncores	Positive integer. Number of cores to use. If ncores = NULL, use a single core. Consider using multiple cores when number of individuals is large.

**Value**

Returns a list by ID numbers.

**Author(s)**

Ivan Jacob Agaloos Pesigan



**See Also**

Other Dynamic Modeling Utility Functions: [DeleteInitialNA\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#)

**Examples**

```
# prepare parameters
set.seed(42)
## number of individuals
n <- 5
## time points
time <- 5
## dynamic structure
p <- 3
mu0 <- rep(x = 0, times = p)
sigma0 <- 0.001 * diag(p)
sigma0_l <- t(chol(sigma0))
alpha <- rep(x = 0, times = p)
beta <- 0.50 * diag(p)
psi <- 0.001 * diag(p)
psi_l <- t(chol(psi))

library(simStateSpace)
ssm <- SimSSMVARFixed(
  n = n,
  time = time,
  mu0 = mu0,
  sigma0_l = sigma0_l,
  alpha = alpha,
  beta = beta,
  psi_l = psi_l,
  type = 0
)
data <- as.data.frame(ssm)
SubsetByID(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:p)
)
```

# Index

## \* **Dynamic Modeling Utility Functions**

DeleteInitialNA, [2](#)

InitialNA, [3](#)

InsertNA, [5](#)

SubsetByID, [8](#)

## \* **data**

DeleteInitialNA, [2](#)

InitialNA, [3](#)

InsertNA, [5](#)

SubsetByID, [8](#)

## \* **dynUtils**

DeleteInitialNA, [2](#)

InitialNA, [3](#)

InsertNA, [5](#)

SubsetByID, [8](#)

## \* **methods**

print.dynutillist, [7](#)

DeleteInitialNA, [2](#), [4](#), [6](#), [9](#)

InitialNA, [2](#), [3](#), [6](#), [9](#)

InsertNA, [2](#), [4](#), [5](#), [9](#)

print.dynutillist, [7](#)

SubsetByID, [2](#), [4](#), [6](#), [8](#)