

Package ‘dynUtils’

March 18, 2024

Title Dynamic Modeling Utilities

Version 0.0.0.9000

Description Utility functions for data preparation when fitting dynamic models.

URL <https://github.com/jeksterslab/dynUtils>,
<https://jeksterslab.github.io/dynUtils/>

BugReports <https://github.com/jeksterslab/dynUtils/issues>

License GPL (>= 3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Depends R (>= 3.5.0)

Suggests knitr, rmarkdown, testthat, simStateSpace

RoxygenNote 7.3.1

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<https://orcid.org/0000-0003-4818-8420>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

R topics documented:

DeleteInitialNA	2
InitialNA	3
InsertNA	5
print.dynutillist	6
SubsetByID	8

Index	10
--------------	-----------

DeleteInitialNA

*Delete for NAs in Initial Row By ID***Description**

Delete for NAs in Initial Row By ID

Usage

DeleteInitialNA(data, id, time, observed, covariates = NULL, ncores = NULL)

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
ncores	Positive integer. Number of cores to use. If ncores = NULL, use a single core. Consider using multiple cores when number of individuals is large.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See AlsoOther Dynamic Modeling Utility Functions: [InitialNA\(\)](#), [InsertNA\(\)](#), [SubsetByID\(\)](#)**Examples**

```
# prepare parameters
set.seed(42)
## number of individuals
n <- 5
## time points
time <- 5
```

```
## dynamic structure
p <- 3
mu0 <- rep(x = 0, times = p)
sigma0 <- 0.001 * diag(p)
sigma0_l <- t(chol(sigma0))
alpha <- rep(x = 0, times = p)
beta <- 0.50 * diag(p)
psi <- 0.001 * diag(p)
psi_l <- t(chol(psi))

library(simStateSpace)
ssm <- SimSSMVARFixed(
  n = n,
  time = time,
  mu0 = mu0,
  sigma0_l = sigma0_l,
  alpha = alpha,
  beta = beta,
  psi_l = psi_l,
  type = 0
)
data <- as.data.frame(ssm)
# Replace first row with NA
data[1, paste0("y", 1:p)] <- NA
DeleteInitialNA(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:p),
)
```

InitialNA

*Check for NAs in Initial Row By ID***Description**

Check for NAs in Initial Row By ID

Usage

InitialNA(data, id, time, observed, covariates = NULL, ncores = NULL)

Arguments

data Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.

id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
ncores	Positive integer. Number of cores to use. If ncores = NULL, use a single core. Consider using multiple cores when number of individuals is large.

Value

Returns a vector of ID numbers where the initial row has any missing value.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [DeleteInitialNA\(\)](#), [InsertNA\(\)](#), [SubsetByID\(\)](#)

Examples

```
# prepare parameters
set.seed(42)
## number of individuals
n <- 5
## time points
time <- 5
## dynamic structure
p <- 3
mu0 <- rep(x = 0, times = p)
sigma0 <- 0.001 * diag(p)
sigma0_l <- t(chol(sigma0))
alpha <- rep(x = 0, times = p)
beta <- 0.50 * diag(p)
psi <- 0.001 * diag(p)
psi_l <- t(chol(psi))

library(simStateSpace)
ssm <- SimSSMVARFixed(
  n = n,
  time = time,
  mu0 = mu0,
  sigma0_l = sigma0_l,
  alpha = alpha,
  beta = beta,
  psi_l = psi_l,
  type = 0
```

```

)
data <- as.data.frame(ssm)
# Replace first row with NA
data[1, paste0("y", 1:p)] <- NA
InitialNA(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:p),
)

```

InsertNA

*Insert NAs for Missing Observations***Description**

Insert NAs for Missing Observations

Usage

```
InsertNA(data, id, time, observed, covariates = NULL, delta_t, ncores = NULL)
```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
delta_t	Positive number. Time interval.
ncores	Positive integer. Number of cores to use. If ncores = NULL, use a single core. Consider using multiple cores when number of individuals is large.

Value

Returns a data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Dynamic Modeling Utility Functions: [DeleteInitialNA\(\)](#), [InitialNA\(\)](#), [SubsetByID\(\)](#)

Examples

```
# prepare parameters
set.seed(42)
## number of individuals
n <- 5
## time points
time <- 5
## dynamic structure
p <- 3
mu0 <- rep(x = 0, times = p)
sigma0 <- 0.001 * diag(p)
sigma0_l <- t(chol(sigma0))
alpha <- rep(x = 0, times = p)
beta <- 0.50 * diag(p)
psi <- 0.001 * diag(p)
psi_l <- t(chol(psi))

library(simStateSpace)
ssm <- SimSSMVARFixed(
  n = n,
  time = time,
  mu0 = mu0,
  sigma0_l = sigma0_l,
  alpha = alpha,
  beta = beta,
  psi_l = psi_l,
  type = 0
)
data <- as.data.frame(ssm)
InsertNA(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:p),
  delta_t = 0.10
)
```

```
print.dynutillist
```

Print Method for Object of Class dynutillist

Description

Print Method for Object of Class dynutillist

Usage

```
## S3 method for class 'dynutillist'  
print(x, ...)
```

Arguments

x an object of class `dynutillist`.
... further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
# prepare parameters  
set.seed(42)  
## number of individuals  
n <- 5  
## time points  
time <- 5  
## dynamic structure  
p <- 3  
mu0 <- rep(x = 0, times = p)  
sigma0 <- 0.001 * diag(p)  
sigma0_l <- t(chol(sigma0))  
alpha <- rep(x = 0, times = p)  
beta <- 0.50 * diag(p)  
psi <- 0.001 * diag(p)  
psi_l <- t(chol(psi))  
  
library(simStateSpace)  
ssm <- SimSSMVARFixed(  
  n = n,  
  time = time,  
  mu0 = mu0,  
  sigma0_l = sigma0_l,  
  alpha = alpha,  
  beta = beta,  
  psi_l = psi_l,  
  type = 0  
)  
data <- as.data.frame(ssm)  
out <- SubsetByID(  
  data = data,  
  id = "id",  
  time = "time",  
  observed = paste0("y", 1:p)  
)  
print(out)
```

SubsetByID

*Subset Data Set by ID***Description**

Subset Data Set by ID

Usage

SubsetByID(data, id, time, observed, covariates = NULL, ncores = NULL)

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), a column indicating subject-specific measurement occasions (i.e., a TIME variable), at least one column of observed values.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
covariates	Character vector. A vector of character strings of the names of the covariates in the data.
ncores	Positive integer. Number of cores to use. If ncores = NULL, use a single core. Consider using multiple cores when number of individuals is large.

Value

Returns a list by ID numbers.

Author(s)

Ivan Jacob Agaloos Pesigan

See AlsoOther Dynamic Modeling Utility Functions: [DeleteInitialNA\(\)](#), [InitialNA\(\)](#), [InsertNA\(\)](#)**Examples**

```
# prepare parameters
set.seed(42)
## number of individuals
n <- 5
## time points
time <- 5
```



```
## dynamic structure
p <- 3
mu0 <- rep(x = 0, times = p)
sigma0 <- 0.001 * diag(p)
sigma0_l <- t(chol(sigma0))
alpha <- rep(x = 0, times = p)
beta <- 0.50 * diag(p)
psi <- 0.001 * diag(p)
psi_l <- t(chol(psi))

library(simStateSpace)
ssm <- SimSSMVARFixed(
  n = n,
  time = time,
  mu0 = mu0,
  sigma0_l = sigma0_l,
  alpha = alpha,
  beta = beta,
  psi_l = psi_l,
  type = 0
)
data <- as.data.frame(ssm)
SubsetByID(
  data = data,
  id = "id",
  time = "time",
  observed = paste0("y", 1:p)
)
```

Index

* **Dynamic Modeling Utility Functions**

DeleteInitialNA, [2](#)

InitialNA, [3](#)

InsertNA, [5](#)

SubsetByID, [8](#)

* **data**

DeleteInitialNA, [2](#)

InitialNA, [3](#)

InsertNA, [5](#)

SubsetByID, [8](#)

* **dynUtils**

DeleteInitialNA, [2](#)

InitialNA, [3](#)

InsertNA, [5](#)

SubsetByID, [8](#)

* **methods**

print.dynutillist, [6](#)

DeleteInitialNA, [2](#), [4](#), [6](#), [8](#)

InitialNA, [2](#), [3](#), [6](#), [8](#)

InsertNA, [2](#), [4](#), [5](#), [8](#)

print.dynutillist, [6](#)

SubsetByID, [2](#), [4](#), [6](#), [8](#)