

Package ‘fitCTVARMx’

July 27, 2024

Title Fit the Continuous-Time Vector Autoregressive Model

Version 0.0.0.9000

Description Fit the continuous-time vector autoregressive model using the 'OpenMx' package.

URL <https://github.com/jeksterslab/fitCTVARMx>,
<https://jeksterslab.github.io/fitCTVARMx/>

BugReports <https://github.com/jeksterslab/fitCTVARMx/issues>

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Depends R (>= 3.0.0), OpenMx

Imports stats

Suggests knitr, rmarkdown, testthat, simStateSpace

RoxygenNote 7.3.2

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<https://orcid.org/0000-0003-4818-8420>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

coef.fitctvaridmx	2
coef.fitctvarmx	2
FitCTVARIDMx	3
FitCTVARMx	6
print.fitctvaridmx	10
print.fitctvarmx	10
summary.fitctvaridmx	11
summary.fitctvarmx	11
vcov.fitctvaridmx	12
vcov.fitctvarmx	12

coef.fitctvaridmx	Parameter Estimates
-------------------	---------------------

Description

Parameter Estimates

Usage

```
## S3 method for class 'fitctvaridmx'  
coef(object, iota = FALSE, sigma = FALSE, theta = FALSE, ...)
```

Arguments

object	Object of class fitctvaridmx.
iota	Logical. If iota = TRUE, include estimates of the iota vector, if available. If iota = FALSE, exclude estimates of the iota vector.
sigma	Logical. If sigma = TRUE, include estimates of the sigma matrix, if available. If sigma = FALSE, exclude estimates of the sigma matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
...	additional arguments.

Value

Returns a list of vectors of parameter estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

coef.fitctvarmx	Parameter Estimates
-----------------	---------------------

Description

Parameter Estimates

Usage

```
## S3 method for class 'fitctvarmx'  
coef(object, iota = FALSE, sigma = FALSE, theta = FALSE, ...)
```

Arguments

object	Object of class fitctvarmx.
iota	Logical. If iota = TRUE, include estimates of the iota vector, if available. If iota = FALSE, exclude estimates of the iota vector.
sigma	Logical. If sigma = TRUE, include estimates of the sigma matrix, if available. If sigma = FALSE, exclude estimates of the sigma matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
...	additional arguments.

Value

Returns a vector of parameter estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

FitCTVARIDMx	<i>Fit the First Order Continuous-Time Vector Autoregressive Model by ID</i>
--------------	--

Description

Fit the First Order Continuous-Time Vector Autoregressive Model by ID

Usage

```
FitCTVARIDMx(
  data,
  observed,
  id,
  time,
  iota_fixed = TRUE,
  iota_start = NULL,
  iota_lbound = NULL,
  iota_ubound = NULL,
  phi_start = NULL,
  phi_lbound = NULL,
  phi_ubound = NULL,
  sigma_diag = TRUE,
  sigma_start = NULL,
  sigma_lbound = NULL,
  sigma_ubound = NULL,
  theta_fixed = TRUE,
  theta_start = NULL,
```

```

theta_lbound = NULL,
theta_ubound = NULL,
mu0_fixed = TRUE,
mu0_start = NULL,
mu0_lbound = NULL,
mu0_ubound = NULL,
sigma0_fixed = TRUE,
sigma0_diag = TRUE,
sigma0_start = NULL,
sigma0_lbound = NULL,
sigma0_ubound = NULL,
try = 1000,
ncores = NULL
)

```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), and at least one column of observed values.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
iota_fixed	Logical. If <code>iota_fixed = TRUE</code> , the dynamic model intercept vector <code>iota</code> is fixed at zero. If <code>iota_fixed = FALSE</code> , the dynamic model intercept vector <code>iota</code> is estimated.
iota_start	Optional starting values for <code>iota</code> . If <code>iota_fixed = TRUE</code> , <code>iota_start</code> will be used as fixed values. If <code>iota_fixed = FALSE</code> , <code>iota_start</code> will be used as starting values.
iota_lbound	Optional lower bound for <code>iota</code> . Ignored if <code>iota_fixed = TRUE</code> .
iota_ubound	Optional upper bound for <code>iota</code> . Ignored if <code>iota_fixed = TRUE</code> .
phi_start	Numeric matrix. Optional starting values for <code>phi</code> .
phi_lbound	Numeric matrix. Optional lower bound for <code>phi</code> .
phi_ubound	Numeric matrix. Optional upper bound for <code>phi</code> .
sigma_diag	Logical. If <code>sigma_diag = TRUE</code> , <code>sigma</code> is a diagonal matrix.
sigma_start	Numeric matrix. Optional starting values for <code>sigma</code> .
sigma_lbound	Numeric matrix. Optional lower bound for <code>sigma</code> .
sigma_ubound	Optional upper bound for <code>sigma</code> .
theta_fixed	Logical. If <code>theta_fixed = TRUE</code> , the measurement error matrix <code>theta</code> is fixed to zero. If <code>theta_fixed = FALSE</code> , estimate the diagonal measurement error matrix <code>theta</code> .
theta_start	Optional starting values for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .

theta_lbound	Optional lower bound for theta. Ignored if theta_fixed = TRUE.
theta_ubound	Optional upper bound for theta. Ignored if theta_fixed = TRUE.
mu0_fixed	Logical. If mu0_fixed = TRUE, initial mean vector mu0 is fixed. If mu0_fixed = FALSE, initial mean vector mu0 is estimated.
mu0_start	Optional starting values for mu0. If mu0_fixed = TRUE, mu0_start will be used as fixed values. If mu0_fixed = FALSE, mu0_start will be used as starting values.
mu0_lbound	Optional lower bound for mu0. Ignored if mu0_fixed = TRUE.
mu0_ubound	Optional upper bound for mu0. Ignored if mu0_fixed = TRUE.
sigma0_fixed	Logical. If sigma0_fixed = TRUE, initial mean vector sigma0 is fixed. If sigma0_fixed = FALSE, initial mean vector sigma0 is estimated.
sigma0_diag	Logical. If sigma0_diag = TRUE, sigma0 is a diagonal matrix.
sigma0_start	Optional starting values for sigma0. If sigma0_fixed = TRUE, sigma0_start will be used as fixed values. If sigma0_fixed = FALSE, sigma0_start will be used as starting values.
sigma0_lbound	Optional lower bound for sigma0. Ignored if sigma0_fixed = TRUE.
sigma0_ubound	Optional upper bound for sigma0. Ignored if sigma0_fixed = TRUE.
try	Positive integer. Number of extra optimization tries.
ncores	Positive integer. Number of cores to use.

Author(s)

Ivan Jacob Agaloos Pesigan

References

- Hunter, M. D. (2017). State space modeling in an open source, modular, structural equation modeling environment. *Structural Equation Modeling: A Multidisciplinary Journal*, 25(2), 307–324. doi:10.1080/10705511.2017.1369354
- Neale, M. C., Hunter, M. D., Pritikin, J. N., Zahery, M., Brick, T. R., Kirkpatrick, R. M., Estabrook, R., Bates, T. C., Maes, H. H., & Boker, S. M. (2015). OpenMx 2.0: Extended structural equation and statistical modeling. *Psychometrika*, 81(2), 535–549. doi:10.1007/s1133601494358

See Also

Other CTVAR Functions: [FitCTVARMx\(\)](#)

Examples

```
## Not run:
# Generate data using the simStateSpace package-----
set.seed(42)
phi_mu <- matrix(
  data = c(
    -0.357, 0.771, -0.450,
    0.0, -0.511, 0.729,
```

```

      0, 0, -0.693
    ),
    nrow = 3
  )
  phi_sigma <- diag(3 * 3)
  phi <- simStateSpace::SimPhiN(
    n = 5,
    phi = phi_mu,
    vcov_phi_vec_l = t(chol(phi_sigma))
  )
  sim <- simStateSpace::SimSSMOUIVary(
    n = 5,
    time = 100,
    delta_t = 0.10,
    mu0 = list(rep(x = 0, times = 3)),
    sigma0_l = list(t(chol(diag(3)))),
    mu = list(rep(x = 0, times = 3)),
    phi = phi,
    sigma_l = list(t(chol(diag(3)))),
    nu = list(rep(x = 0, times = 3)),
    lambda = list(diag(3)),
    theta_l = list(matrix(data = 0, nrow = 3, ncol = 3))
  )
  data <- as.data.frame(sim)

  # Fit the model-----
  library(fitCTVARMx)
  fit <- FitCTVARIDMx(
    data = data,
    observed = c("y1", "y2", "y3"),
    id = "id"
  )
  print(fit)
  summary(fit)
  coef(fit)
  vcov(fit)

  ## End(Not run)

```

Description

Fit the First-Order Continuous-Time Vector Autoregressive Model

Usage

```
FitCTVARMx(
```

```

data,
observed,
id,
time,
iota_fixed = TRUE,
iota_start = NULL,
iota_lbound = NULL,
iota_ubound = NULL,
phi_start = NULL,
phi_lbound = NULL,
phi_ubound = NULL,
sigma_diag = TRUE,
sigma_start = NULL,
sigma_lbound = NULL,
sigma_ubound = NULL,
theta_fixed = TRUE,
theta_start = NULL,
theta_lbound = NULL,
theta_ubound = NULL,
mu0_fixed = TRUE,
mu0_start = NULL,
mu0_lbound = NULL,
mu0_ubound = NULL,
sigma0_fixed = TRUE,
sigma0_diag = TRUE,
sigma0_start = NULL,
sigma0_lbound = NULL,
sigma0_ubound = NULL,
try = 1000,
ncores = NULL
)

```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), and at least one column of observed values.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
id	Character string. A character string of the name of the ID variable in the data.
time	Character string. A character string of the name of the TIME variable in the data.
iota_fixed	Logical. If <code>iota_fixed = TRUE</code> , the dynamic model intercept vector <code>iota</code> is fixed at zero. If <code>iota_fixed = FALSE</code> , the dynamic model intercept vector <code>iota</code> is estimated.
iota_start	Optional starting values for <code>iota</code> . If <code>iota_fixed = TRUE</code> , <code>iota_start</code> will be used as fixed values. If <code>iota_fixed = FALSE</code> , <code>iota_start</code> will be used as starting values.

<code>iota_lbound</code>	Optional lower bound for <code>iota</code> . Ignored if <code>iota_fixed = TRUE</code> .
<code>iota_ubound</code>	Optional upper bound for <code>iota</code> . Ignored if <code>iota_fixed = TRUE</code> .
<code>phi_start</code>	Numeric matrix. Optional starting values for <code>phi</code> .
<code>phi_lbound</code>	Numeric matrix. Optional lower bound for <code>phi</code> .
<code>phi_ubound</code>	Numeric matrix. Optional upper bound for <code>phi</code> .
<code>sigma_diag</code>	Logical. If <code>sigma_diag = TRUE</code> , <code>sigma</code> is a diagonal matrix.
<code>sigma_start</code>	Numeric matrix. Optional starting values for <code>sigma</code> .
<code>sigma_lbound</code>	Numeric matrix. Optional lower bound for <code>sigma</code> .
<code>sigma_ubound</code>	Optional upper bound for <code>sigma</code> .
<code>theta_fixed</code>	Logical. If <code>theta_fixed = TRUE</code> , the measurement error matrix <code>theta</code> is fixed to zero. If <code>theta_fixed = FALSE</code> , estimate the diagonal measurement error matrix <code>theta</code> .
<code>theta_start</code>	Optional starting values for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .
<code>theta_lbound</code>	Optional lower bound for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .
<code>theta_ubound</code>	Optional upper bound for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .
<code>mu0_fixed</code>	Logical. If <code>mu0_fixed = TRUE</code> , initial mean vector <code>mu0</code> is fixed. If <code>mu0_fixed = FALSE</code> , initial mean vector <code>mu0</code> is estimated.
<code>mu0_start</code>	Optional starting values for <code>mu0</code> . If <code>mu0_fixed = TRUE</code> , <code>mu0_start</code> will be used as fixed values. If <code>mu0_fixed = FALSE</code> , <code>mu0_start</code> will be used as starting values.
<code>mu0_lbound</code>	Optional lower bound for <code>mu0</code> . Ignored if <code>mu0_fixed = TRUE</code> .
<code>mu0_ubound</code>	Optional upper bound for <code>mu0</code> . Ignored if <code>mu0_fixed = TRUE</code> .
<code>sigma0_fixed</code>	Logical. If <code>sigma0_fixed = TRUE</code> , initial mean vector <code>sigma0</code> is fixed. If <code>sigma0_fixed = FALSE</code> , initial mean vector <code>sigma0</code> is estimated.
<code>sigma0_diag</code>	Logical. If <code>sigma0_diag = TRUE</code> , <code>sigma0</code> is a diagonal matrix.
<code>sigma0_start</code>	Optional starting values for <code>sigma0</code> . If <code>sigma0_fixed = TRUE</code> , <code>sigma0_start</code> will be used as fixed values. If <code>sigma0_fixed = FALSE</code> , <code>sigma0_start</code> will be used as starting values.
<code>sigma0_lbound</code>	Optional lower bound for <code>sigma0</code> . Ignored if <code>sigma0_fixed = TRUE</code> .
<code>sigma0_ubound</code>	Optional upper bound for <code>sigma0</code> . Ignored if <code>sigma0_fixed = TRUE</code> .
<code>try</code>	Positive integer. Number of extra optimization tries.
<code>ncores</code>	Positive integer. Number of cores to use.

Value

Returns an object of class `fitctvarmx` which is a list with the following elements:

call Function call.

args List of function arguments.

fun Function used ("FitCTVARMx").

output A fitted OpenMx model.

Author(s)

Ivan Jacob Agaloos Pesigan

References

Hunter, M. D. (2017). State space modeling in an open source, modular, structural equation modeling environment. *Structural Equation Modeling: A Multidisciplinary Journal*, 25(2), 307–324. doi:[10.1080/10705511.2017.1369354](https://doi.org/10.1080/10705511.2017.1369354)

Neale, M. C., Hunter, M. D., Pritikin, J. N., Zahery, M., Brick, T. R., Kirkpatrick, R. M., Estabrook, R., Bates, T. C., Maes, H. H., & Boker, S. M. (2015). OpenMx 2.0: Extended structural equation and statistical modeling. *Psychometrika*, 81(2), 535–549. doi:[10.1007/s1133601494358](https://doi.org/10.1007/s1133601494358)

See Also

Other CTVAR Functions: [FitCTVARIDMx\(\)](#)

Examples

```
## Not run:
# Generate data using the simStateSpace package-----
set.seed(42)
sim <- simStateSpace::SimSSMOUFixed(
  n = 5,
  time = 100,
  delta_t = 0.10,
  mu0 = rep(x = 0, times = 3),
  sigma0_l = t(chol(diag(3))),
  mu = rep(x = 0, times = 3),
  phi = matrix(
    data = c(
      -0.357, 0.771, -0.450,
      0.0, -0.511, 0.729,
      0, 0, -0.693
    ),
    nrow = 3
  ),
  sigma_l = t(chol(diag(3))),
  nu = rep(x = 0, times = 3),
  lambda = diag(3),
  theta_l = matrix(data = 0, nrow = 3, ncol = 3)
)
data <- as.data.frame(sim)

# Fit the model-----
library(fitCTVARMx)
fit <- FitCTVARMx(
  data = data,
  observed = c("y1", "y2", "y3"),
  id = "id"
)
print(fit)
```

```
summary(fit)
coef(fit)
vcov(fit)

## End(Not run)
```

```
print.fitctvaridmx      Print Method for Object of Class fitctvaridmx
```

Description

Print Method for Object of Class fitctvaridmx

Usage

```
## S3 method for class 'fitctvaridmx'
print(x, means = TRUE, ...)
```

Arguments

x	an object of class fitctvaridmx.
means	Logical. If means = TRUE, return means. Otherwise, the function returns raw estimates.
...	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

```
print.fitctvarmx      Print Method for Object of Class fitctvarmx
```

Description

Print Method for Object of Class fitctvarmx

Usage

```
## S3 method for class 'fitctvarmx'
print(x, ...)
```

Arguments

x	an object of class fitctvarmx.
...	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

summary.fitctvaridmx *Summary Method for Object of Class fitctvaridmx*

Description

Summary Method for Object of Class fitctvaridmx

Usage

```
## S3 method for class 'fitctvaridmx'  
summary(object, means = TRUE, ...)
```

Arguments

object	an object of class fitctvaridmx.
means	Logical. If means = TRUE, return means. Otherwise, the function returns raw estimates.
...	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

summary.fitctvarmx *Summary Method for Object of Class fitctvarmx*

Description

Summary Method for Object of Class fitctvarmx

Usage

```
## S3 method for class 'fitctvarmx'  
summary(object, ...)
```

Arguments

object	an object of class fitctvarmx.
...	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

vcov.fitctvaridmx	<i>Sampling Covariance Matrix of the Parameter Estimates</i>
-------------------	--

Description

Sampling Covariance Matrix of the Parameter Estimates

Usage

```
## S3 method for class 'fitctvaridmx'  
vcov(object, iota = FALSE, sigma = FALSE, theta = FALSE, ...)
```

Arguments

object	Object of class fitctvaridmx.
iota	Logical. If iota = TRUE, include estimates of the iota vector, if available. If iota = FALSE, exclude estimates of the iota vector.
sigma	Logical. If sigma = TRUE, include estimates of the sigma matrix, if available. If sigma = FALSE, exclude estimates of the sigma matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
...	additional arguments.

Value

Returns a list of sampling variance-covariance matrices.

Author(s)

Ivan Jacob Agaloos Pesigan

vcov.fitctvarmx	<i>Sampling Covariance Matrix of the Parameter Estimates</i>
-----------------	--

Description

Sampling Covariance Matrix of the Parameter Estimates

Usage

```
## S3 method for class 'fitctvarmx'  
vcov(object, iota = FALSE, sigma = FALSE, theta = FALSE, ...)
```

Arguments

object	Object of class fitctvarmx.
iota	Logical. If <code>iota = TRUE</code> , include estimates of the <code>iota</code> vector, if available. If <code>iota = FALSE</code> , exclude estimates of the <code>iota</code> vector.
sigma	Logical. If <code>sigma = TRUE</code> , include estimates of the <code>sigma</code> matrix, if available. If <code>sigma = FALSE</code> , exclude estimates of the <code>sigma</code> matrix.
theta	Logical. If <code>theta = TRUE</code> , include estimates of the <code>theta</code> matrix, if available. If <code>theta = FALSE</code> , exclude estimates of the <code>theta</code> matrix.
...	additional arguments.

Value

Returns a list of sampling variance-covariance matrices.

Author(s)

Ivan Jacob Agaloos Pesigan

Index

- * **CTVAR Functions**
 - FitCTVARIDMx, [3](#)
 - FitCTVARMx, [6](#)
- * **fitCTVARMx**
 - FitCTVARIDMx, [3](#)
 - FitCTVARMx, [6](#)
- * **fit**
 - FitCTVARIDMx, [3](#)
 - FitCTVARMx, [6](#)
- * **methods**
 - coef.fitctvaridmx, [2](#)
 - coef.fitctvarmx, [2](#)
 - print.fitctvaridmx, [10](#)
 - print.fitctvarmx, [10](#)
 - summary.fitctvaridmx, [11](#)
 - summary.fitctvarmx, [11](#)
 - vcov.fitctvaridmx, [12](#)
 - vcov.fitctvarmx, [12](#)

coef.fitctvaridmx, [2](#)
coef.fitctvarmx, [2](#)

FitCTVARIDMx, [3](#), [9](#)
FitCTVARMx, [5](#), [6](#)

print.fitctvaridmx, [10](#)
print.fitctvarmx, [10](#)

summary.fitctvaridmx, [11](#)
summary.fitctvarmx, [11](#)

vcov.fitctvaridmx, [12](#)
vcov.fitctvarmx, [12](#)