

Package ‘fitDTVARMx’

July 2, 2024

Title Fit The Discrete-Time Vector Autoregressive Model

Version 0.0.0.9000

Description Fit the discrete-time vector autoregressive model using the 'OpenMx' package.

URL <https://github.com/jeksterslab/fitDTVARMx>,
<https://jeksterslab.github.io/fitDTVARMx/>

BugReports <https://github.com/jeksterslab/fitDTVARMx/issues>

License GPL (>= 3)

Encoding UTF-8

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Depends R (>= 3.0.0), OpenMx

Imports stats

Suggests knitr, rmarkdown, testthat

RoxygenNote 7.3.2

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<https://orcid.org/0000-0003-4818-8420>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

FitDTVARIDMx	2
print.fitdtvaridmx	3
summary.fitdtvaridmx	3
Index	4

FitDTVARIDMx

Fit First Order Discrete-Time Vector Autoregressive Model by ID

Description

Fit First Order Discrete-Time Vector Autoregressive Model by ID

Usage

```
FitDTVARIDMx(
  data,
  observed,
  id,
  beta_start = NULL,
  beta_lbound = NULL,
  beta_ubound = NULL,
  psi_start = NULL,
  psi_lbound = NULL,
  psi_ubound = NULL,
  try = 1000,
  ncores = NULL
)
```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), and at least one column of observed values.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
id	Character string. A character string of the name of the ID variable in the data.
beta_start	Optional starting values for beta.
beta_lbound	Optional lower bound for beta.
beta_ubound	Optional upper bound for beta.
psi_start	Optional starting values for psi.
psi_lbound	Optional lower bound for psi.
psi_ubound	Optional upper bound for psi.
try	Positive integer. Number of extra tries for OpenMx::mxTryHard() .
ncores	Positive integer. Number of cores to use.

Author(s)

Ivan Jacob Agaloos Pesigan

print.fitdtvaridmx *Print Method for Object of Class fitdtvaridmx*

Description

Print Method for Object of Class fitdtvaridmx

Usage

```
## S3 method for class 'fitdtvaridmx'  
print(x, means = TRUE, ...)
```

Arguments

x	an object of class fitdtvaridmx.
means	Logical. If means = TRUE, return means. Otherwise, the function returns raw estimates.
...	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

summary.fitdtvaridmx *Summary Method for Object of Class fitdtvaridmx*

Description

Summary Method for Object of Class fitdtvaridmx

Usage

```
## S3 method for class 'fitdtvaridmx'  
summary(object, means = TRUE, ...)
```

Arguments

object	an object of class fitdtvaridmx.
means	Logical. If means = TRUE, return means. Otherwise, the function returns raw estimates.
...	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

Index

- * **Meta-Analysis of VAR Functions**

- FitDTVARIDMx, [2](#)

- * **fit**

- FitDTVARIDMx, [2](#)

- * **metaVAR**

- FitDTVARIDMx, [2](#)

- * **methods**

- print.fitdtvaridmx, [3](#)

- summary.fitdtvaridmx, [3](#)

FitDTVARIDMx, [2](#)

OpenMx::mxTryHard(), [2](#)

print.fitdtvaridmx, [3](#)

summary.fitdtvaridmx, [3](#)