

Package ‘fitDTVARMx’

July 25, 2024

Title Fit the Discrete-Time Vector Autoregressive Model

Version 0.0.0.9000

Description Fit the discrete-time vector autoregressive model using the 'OpenMx' package.

URL <https://github.com/jeksterslab/fitDTVARMx>,
<https://jeksterslab.github.io/fitDTVARMx/>

BugReports <https://github.com/jeksterslab/fitDTVARMx/issues>

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Depends R (>= 3.0.0), OpenMx

Imports stats

Suggests knitr, rmarkdown, testthat, simStateSpace

RoxygenNote 7.3.2

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<https://orcid.org/0000-0003-4818-8420>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

coef.fittedvaridmx	2
coef.fittedvarmx	2
FitDTVARIDMx	3
FitDTVARMx	6
print.fittedvaridmx	10
print.fittedvarmx	10
summary.fittedvaridmx	11
summary.fittedvarmx	11
vcov.fittedvaridmx	12
vcov.fittedvarmx	12

coef.fitdtvaridmx	<i>Parameter Estimates</i>
-------------------	----------------------------

Description

Parameter Estimates

Usage

```
## S3 method for class 'fitdtvaridmx'  
coef(object, alpha = FALSE, psi = FALSE, theta = FALSE, ...)
```

Arguments

object	Object of class fitdtvaridmx.
alpha	Logical. If alpha = TRUE, include estimates of the alpha vector, if available. If alpha = FALSE, exclude estimates of the alpha vector.
psi	Logical. If psi = TRUE, include estimates of the psi matrix, if available. If psi = FALSE, exclude estimates of the psi matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
...	additional arguments.

Value

Returns a list of vectors of parameter estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

coef.fitdtvarmx	<i>Parameter Estimates</i>
-----------------	----------------------------

Description

Parameter Estimates

Usage

```
## S3 method for class 'fitdtvarmx'  
coef(object, alpha = FALSE, psi = FALSE, theta = FALSE, ...)
```

Arguments

object	Object of class fitdtdvarmx.
alpha	Logical. If alpha = TRUE, include estimates of the alpha vector, if available. If alpha = FALSE, exclude estimates of the alpha vector.
psi	Logical. If psi = TRUE, include estimates of the psi matrix, if available. If psi = FALSE, exclude estimates of the psi matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
...	additional arguments.

Value

Returns a vector of parameter estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

FitDTVARIDMx

Fit the First-Order Discrete-Time Vector Autoregressive Model by ID

Description

Fit the First-Order Discrete-Time Vector Autoregressive Model by ID

Usage

```
FitDTVARIDMx(
  data,
  observed,
  id,
  alpha_fixed = TRUE,
  alpha_start = NULL,
  alpha_lbound = NULL,
  alpha_ubound = NULL,
  beta_start = NULL,
  beta_lbound = NULL,
  beta_ubound = NULL,
  psi_diag = TRUE,
  psi_start = NULL,
  psi_lbound = NULL,
  psi_ubound = NULL,
  theta_fixed = TRUE,
  theta_start = NULL,
  theta_lbound = NULL,
  theta_ubound = NULL,
```

```

mu0_fixed = TRUE,
mu0_start = NULL,
mu0_lbound = NULL,
mu0_ubound = NULL,
sigma0_fixed = TRUE,
sigma0_diag = TRUE,
sigma0_start = NULL,
sigma0_lbound = NULL,
sigma0_ubound = NULL,
try = 1000,
ncores = NULL
)

```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), and at least one column of observed values.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
id	Character string. A character string of the name of the ID variable in the data.
alpha_fixed	Logical. If <code>alpha_fixed = TRUE</code> , the dynamic model intercept vector <code>alpha</code> is fixed at zero. If <code>alpha_fixed = FALSE</code> , the dynamic model intercept vector <code>alpha</code> is estimated.
alpha_start	Optional starting values for <code>alpha</code> . If <code>alpha_fixed = TRUE</code> , <code>alpha_start</code> will be used as fixed values. If <code>alpha_fixed = FALSE</code> , <code>alpha_start</code> will be used as starting values.
alpha_lbound	Optional lower bound for <code>alpha</code> . Ignored if <code>alpha_fixed = TRUE</code> .
alpha_ubound	Optional upper bound for <code>alpha</code> . Ignored if <code>alpha_fixed = TRUE</code> .
beta_start	Numeric matrix. Optional starting values for <code>beta</code> .
beta_lbound	Numeric matrix. Optional lower bound for <code>beta</code> .
beta_ubound	Numeric matrix. Optional upper bound for <code>beta</code> .
psi_diag	Logical. If <code>psi_diag = TRUE</code> , <code>psi</code> is a diagonal matrix.
psi_start	Numeric matrix. Optional starting values for <code>psi</code> .
psi_lbound	Numeric matrix. Optional lower bound for <code>psi</code> .
psi_ubound	Optional upper bound for <code>psi</code> .
theta_fixed	Logical. If <code>theta_fixed = TRUE</code> , the measurement error matrix <code>theta</code> is fixed to zero. If <code>theta_fixed = FALSE</code> , estimate the diagonal measurement error matrix <code>theta</code> .
theta_start	Optional starting values for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .
theta_lbound	Optional lower bound for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .
theta_ubound	Optional upper bound for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .
mu0_fixed	Logical. If <code>mu0_fixed = TRUE</code> , initial mean vector <code>mu0</code> is fixed. If <code>mu0_fixed = FALSE</code> , initial mean vector <code>mu0</code> is estimated.

<code>mu0_start</code>	Optional starting values for <code>mu0</code> . If <code>mu0_fixed = TRUE</code> , <code>mu0_start</code> will be used as fixed values. If <code>mu0_fixed = FALSE</code> , <code>mu0_start</code> will be used as starting values.
<code>mu0_lbound</code>	Optional lower bound for <code>mu0</code> . Ignored if <code>mu0_fixed = TRUE</code> .
<code>mu0_ubound</code>	Optional upper bound for <code>mu0</code> . Ignored if <code>mu0_fixed = TRUE</code> .
<code>sigma0_fixed</code>	Logical. If <code>sigma0_fixed = TRUE</code> , initial mean vector <code>sigma0</code> is fixed. If <code>sigma0_fixed = FALSE</code> , initial mean vector <code>sigma0</code> is estimated.
<code>sigma0_diag</code>	Logical. If <code>sigma0_diag = TRUE</code> , <code>sigma0</code> is a diagonal matrix.
<code>sigma0_start</code>	Optional starting values for <code>sigma0</code> . If <code>sigma0_fixed = TRUE</code> , <code>sigma0_start</code> will be used as fixed values. If <code>sigma0_fixed = FALSE</code> , <code>sigma0_start</code> will be used as starting values.
<code>sigma0_lbound</code>	Optional lower bound for <code>sigma0</code> . Ignored if <code>sigma0_fixed = TRUE</code> .
<code>sigma0_ubound</code>	Optional upper bound for <code>sigma0</code> . Ignored if <code>sigma0_fixed = TRUE</code> .
<code>try</code>	Positive integer. Number of extra optimization tries.
<code>ncores</code>	Positive integer. Number of cores to use.

Value

Returns an object of class `fitdtvaridmx` which is a list with the following elements:

call Function call.

args List of function arguments.

fun Function used ("FitDTVARIDMx").

output A list of fitted OpenMx models.

Author(s)

Ivan Jacob Agaloos Pesigan

References

Hunter, M. D. (2017). State space modeling in an open source, modular, structural equation modeling environment. *Structural Equation Modeling: A Multidisciplinary Journal*, 25(2), 307–324. doi:10.1080/10705511.2017.1369354

Neale, M. C., Hunter, M. D., Pritikin, J. N., Zahery, M., Brick, T. R., Kirkpatrick, R. M., Estabrook, R., Bates, T. C., Maes, H. H., & Boker, S. M. (2015). OpenMx 2.0: Extended structural equation and statistical modeling. *Psychometrika*, 81(2), 535–549. doi:10.1007/s1133601494358

See Also

Other DTVAR Functions: [FitDTVARMx\(\)](#)

Examples

```
## Not run:
# Generate data using the simStateSpace package-----
set.seed(42)
beta_mu <- matrix(
  data = c(
    0.7, 0.5, -0.1,
    0.0, 0.6, 0.4,
    0, 0, 0.5
  ),
  nrow = 3
)
beta_sigma <- diag(3 * 3)
beta <- simStateSpace::SimBetaN(
  n = 5,
  beta = beta_mu,
  vcov_beta_vec_l = t(chol(beta_sigma))
)
sim <- simStateSpace::SimSSMVARIVary(
  n = 5,
  time = 100,
  mu0 = list(rep(x = 0, times = 3)),
  sigma0_l = list(t(chol(diag(3))))),
  alpha = list(rep(x = 0, times = 3)),
  beta = beta,
  psi_l = list(t(chol(diag(3))))
)
data <- as.data.frame(sim)

# Fit the model-----
library(fitDTVARMx)
fit <- FitDTVARIDMx(
  data = data,
  observed = c("y1", "y2", "y3"),
  id = "id"
)
print(fit)
summary(fit)
coef(fit)
vcov(fit)

## End(Not run)
```

Description

Fit the First-Order Discrete-Time Vector Autoregressive Model

Usage

```
FitDTVARMx(
  data,
  observed,
  id,
  alpha_fixed = TRUE,
  alpha_start = NULL,
  alpha_lbound = NULL,
  alpha_ubound = NULL,
  beta_start = NULL,
  beta_lbound = NULL,
  beta_ubound = NULL,
  psi_diag = TRUE,
  psi_start = NULL,
  psi_lbound = NULL,
  psi_ubound = NULL,
  theta_fixed = TRUE,
  theta_start = NULL,
  theta_lbound = NULL,
  theta_ubound = NULL,
  mu0_fixed = TRUE,
  mu0_start = NULL,
  mu0_lbound = NULL,
  mu0_ubound = NULL,
  sigma0_fixed = TRUE,
  sigma0_diag = TRUE,
  sigma0_start = NULL,
  sigma0_lbound = NULL,
  sigma0_ubound = NULL,
  try = 1000,
  ncores = NULL
)
```

Arguments

<code>data</code>	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), and at least one column of observed values.
<code>observed</code>	Character vector. A vector of character strings of the names of the observed variables in the data.
<code>id</code>	Character string. A character string of the name of the ID variable in the data.
<code>alpha_fixed</code>	Logical. If <code>alpha_fixed = TRUE</code> , the dynamic model intercept vector <code>alpha</code> is fixed at zero. If <code>alpha_fixed = FALSE</code> , the dynamic model intercept vector <code>alpha</code> is estimated.
<code>alpha_start</code>	Optional starting values for <code>alpha</code> . If <code>alpha_fixed = TRUE</code> , <code>alpha_start</code> will be used as fixed values. If <code>alpha_fixed = FALSE</code> , <code>alpha_start</code> will be used as starting values.

<code>alpha_lbound</code>	Optional lower bound for alpha. Ignored if <code>alpha_fixed = TRUE</code> .
<code>alpha_ubound</code>	Optional upper bound for alpha. Ignored if <code>alpha_fixed = TRUE</code> .
<code>beta_start</code>	Numeric matrix. Optional starting values for beta.
<code>beta_lbound</code>	Numeric matrix. Optional lower bound for beta.
<code>beta_ubound</code>	Numeric matrix. Optional upper bound for beta.
<code>psi_diag</code>	Logical. If <code>psi_diag = TRUE</code> , <code>psi</code> is a diagonal matrix.
<code>psi_start</code>	Numeric matrix. Optional starting values for psi.
<code>psi_lbound</code>	Numeric matrix. Optional lower bound for psi.
<code>psi_ubound</code>	Optional upper bound for psi.
<code>theta_fixed</code>	Logical. If <code>theta_fixed = TRUE</code> , the measurement error matrix <code>theta</code> is fixed to zero. If <code>theta_fixed = FALSE</code> , estimate the diagonal measurement error matrix <code>theta</code> .
<code>theta_start</code>	Optional starting values for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .
<code>theta_lbound</code>	Optional lower bound for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .
<code>theta_ubound</code>	Optional upper bound for <code>theta</code> . Ignored if <code>theta_fixed = TRUE</code> .
<code>mu0_fixed</code>	Logical. If <code>mu0_fixed = TRUE</code> , initial mean vector <code>mu0</code> is fixed. If <code>mu0_fixed = FALSE</code> , initial mean vector <code>mu0</code> is estimated.
<code>mu0_start</code>	Optional starting values for <code>mu0</code> . If <code>mu0_fixed = TRUE</code> , <code>mu0_start</code> will be used as fixed values. If <code>mu0_fixed = FALSE</code> , <code>mu0_start</code> will be used as starting values.
<code>mu0_lbound</code>	Optional lower bound for <code>mu0</code> . Ignored if <code>mu0_fixed = TRUE</code> .
<code>mu0_ubound</code>	Optional upper bound for <code>mu0</code> . Ignored if <code>mu0_fixed = TRUE</code> .
<code>sigma0_fixed</code>	Logical. If <code>sigma0_fixed = TRUE</code> , initial mean vector <code>sigma0</code> is fixed. If <code>sigma0_fixed = FALSE</code> , initial mean vector <code>sigma0</code> is estimated.
<code>sigma0_diag</code>	Logical. If <code>sigma0_diag = TRUE</code> , <code>sigma0</code> is a diagonal matrix.
<code>sigma0_start</code>	Optional starting values for <code>sigma0</code> . If <code>sigma0_fixed = TRUE</code> , <code>sigma0_start</code> will be used as fixed values. If <code>sigma0_fixed = FALSE</code> , <code>sigma0_start</code> will be used as starting values.
<code>sigma0_lbound</code>	Optional lower bound for <code>sigma0</code> . Ignored if <code>sigma0_fixed = TRUE</code> .
<code>sigma0_ubound</code>	Optional upper bound for <code>sigma0</code> . Ignored if <code>sigma0_fixed = TRUE</code> .
<code>try</code>	Positive integer. Number of extra optimization tries.
<code>ncores</code>	Positive integer. Number of cores to use.

Value

Returns an object of class `fitdtvarmx` which is a list with the following elements:

call Function call.

args List of function arguments.

fun Function used ("FitDTVARMx").

output A fitted OpenMx model.

Author(s)

Ivan Jacob Agaloos Pesigan

References

Hunter, M. D. (2017). State space modeling in an open source, modular, structural equation modeling environment. *Structural Equation Modeling: A Multidisciplinary Journal*, 25(2), 307–324. doi:[10.1080/10705511.2017.1369354](https://doi.org/10.1080/10705511.2017.1369354)

Neale, M. C., Hunter, M. D., Pritikin, J. N., Zahery, M., Brick, T. R., Kirkpatrick, R. M., Estabrook, R., Bates, T. C., Maes, H. H., & Boker, S. M. (2015). OpenMx 2.0: Extended structural equation and statistical modeling. *Psychometrika*, 81(2), 535–549. doi:[10.1007/s1133601494358](https://doi.org/10.1007/s1133601494358)

See Also

Other DTVAR Functions: [FitDTVARIDMx\(\)](#)

Examples

```
## Not run:
# Generate data using the simStateSpace package-----
set.seed(42)
sim <- simStateSpace::SimSSMVARFixed(
  n = 5,
  time = 100,
  mu0 = rep(x = 0, times = 3),
  sigma0_l = t(chol(diag(3))),
  alpha = rep(x = 0, times = 3),
  beta = matrix(
    data = c(
      0.7, 0.5, -0.1,
      0.0, 0.6, 0.4,
      0, 0, 0.5
    ),
    nrow = 3
  ),
  psi_l = t(chol(diag(3)))
)
data <- as.data.frame(sim)

# Fit the model-----
library(fitDTVARMx)
fit <- FitDTVARMx(
  data = data,
  observed = c("y1", "y2", "y3"),
  id = "id"
)
print(fit)
summary(fit)
coef(fit)
vcov(fit)
```

```
## End(Not run)
```

`print.fitdtvaridmx` *Print Method for Object of Class fitdtvaridmx*

Description

Print Method for Object of Class fitdtvaridmx

Usage

```
## S3 method for class 'fitdtvaridmx'  
print(x, means = TRUE, ...)
```

Arguments

<code>x</code>	an object of class fitdtvaridmx.
<code>means</code>	Logical. If <code>means = TRUE</code> , return means. Otherwise, the function returns raw estimates.
<code>...</code>	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

`print.fitdtvarmx` *Print Method for Object of Class fitdtvarmx*

Description

Print Method for Object of Class fitdtvarmx

Usage

```
## S3 method for class 'fitdtvarmx'  
print(x, ...)
```

Arguments

<code>x</code>	an object of class fitdtvarmx.
<code>...</code>	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

summary.fitdtvaridmx *Summary Method for Object of Class fitdtvaridmx*

Description

Summary Method for Object of Class fitdtvaridmx

Usage

```
## S3 method for class 'fitdtvaridmx'  
summary(object, means = TRUE, ...)
```

Arguments

object	an object of class fitdtvaridmx.
means	Logical. If means = TRUE, return means. Otherwise, the function returns raw estimates.
...	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

summary.fitdtvarmx *Summary Method for Object of Class fitdtvarmx*

Description

Summary Method for Object of Class fitdtvarmx

Usage

```
## S3 method for class 'fitdtvarmx'  
summary(object, ...)
```

Arguments

object	an object of class fitdtvarmx.
...	further arguments.

Author(s)

Ivan Jacob Agaloos Pesigan

vcov.fitdvaridmx	<i>Sampling Covariance Matrix of the Parameter Estimates</i>
------------------	--

Description

Sampling Covariance Matrix of the Parameter Estimates

Usage

```
## S3 method for class 'fitdvaridmx'  
vcov(object, alpha = FALSE, psi = FALSE, theta = FALSE, ...)
```

Arguments

object	Object of class fitdvaridmx.
alpha	Logical. If alpha = TRUE, include estimates of the alpha vector, if available. If alpha = FALSE, exclude estimates of the alpha vector.
psi	Logical. If psi = TRUE, include estimates of the psi matrix, if available. If psi = FALSE, exclude estimates of the psi matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
...	additional arguments.

Value

Returns a list of sampling variance-covariance matrices.

Author(s)

Ivan Jacob Agaloos Pesigan

vcov.fitdvarmx	<i>Sampling Covariance Matrix of the Parameter Estimates</i>
----------------	--

Description

Sampling Covariance Matrix of the Parameter Estimates

Usage

```
## S3 method for class 'fitdvarmx'  
vcov(object, alpha = FALSE, psi = FALSE, theta = FALSE, ...)
```

Arguments

object	Object of class fittedvarmx.
alpha	Logical. If alpha = TRUE, include estimates of the alpha vector, if available. If alpha = FALSE, exclude estimates of the alpha vector.
psi	Logical. If psi = TRUE, include estimates of the psi matrix, if available. If psi = FALSE, exclude estimates of the psi matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
...	additional arguments.

Value

Returns a list of sampling variance-covariance matrices.

Author(s)

Ivan Jacob Agaloos Pesigan

Index

- * **DTVAR Functions**
 - FitDTVARIDMx, [3](#)
 - FitDTVARMx, [6](#)
- * **fitDTVARMx**
 - FitDTVARIDMx, [3](#)
 - FitDTVARMx, [6](#)
- * **fit**
 - FitDTVARIDMx, [3](#)
 - FitDTVARMx, [6](#)
- * **methods**
 - coef.fitdtvaridmx, [2](#)
 - coef.fitdtvarmx, [2](#)
 - print.fitdtvaridmx, [10](#)
 - print.fitdtvarmx, [10](#)
 - summary.fitdtvaridmx, [11](#)
 - summary.fitdtvarmx, [11](#)
 - vcov.fitdtvaridmx, [12](#)
 - vcov.fitdtvarmx, [12](#)

coef.fitdtvaridmx, [2](#)
coef.fitdtvarmx, [2](#)

FitDTVARIDMx, [3](#), [9](#)
FitDTVARMx, [5](#), [6](#)

print.fitdtvaridmx, [10](#)
print.fitdtvarmx, [10](#)

summary.fitdtvaridmx, [11](#)
summary.fitdtvarmx, [11](#)

vcov.fitdtvaridmx, [12](#)
vcov.fitdtvarmx, [12](#)