

# Package ‘fitDTVARMx’

July 2, 2024

**Title** Fit The Discrete-Time Vector Autoregressive Model

**Version** 0.0.0.9000

**Description** Fit the discrete-time vector autoregressive model using the 'OpenMx' package.

**URL** <https://github.com/jeksterslab/fitDTVARMx>,  
<https://jeksterslab.github.io/fitDTVARMx/>

**BugReports** <https://github.com/jeksterslab/fitDTVARMx/issues>

**License** GPL (>= 3)

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**VignetteBuilder** knitr

**Depends** R (>= 3.0.0), OpenMx

**Imports** stats

**Suggests** knitr, rmarkdown, testthat

**RoxygenNote** 7.3.2

**NeedsCompilation** no

**Author** Ivan Jacob Agaloos Pesigan [aut, cre, cph]  
(<<https://orcid.org/0000-0003-4818-8420>>)

**Maintainer** Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

## Contents

FitDTVARIDMx . . . . .	2
print.fitdtvaridmx . . . . .	3
summary.fitdtvaridmx . . . . .	3
<b>Index</b>	<b>4</b>

FitDTVARIDMx

*Fit First Order Discrete-Time Vector Autoregressive Model by ID***Description**

Fit First Order Discrete-Time Vector Autoregressive Model by ID

**Usage**

```
FitDTVARIDMx(
  data,
  observed,
  id,
  beta_start = NULL,
  beta_lbound = NULL,
  beta_ubound = NULL,
  psi_start = NULL,
  psi_lbound = NULL,
  psi_ubound = NULL,
  try = 1000,
  ncores = NULL
)
```

**Arguments**

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), and at least one column of observed values.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
id	Character string. A character string of the name of the ID variable in the data.
beta_start	Optional starting values for beta.
beta_lbound	Optional lower bound for beta.
beta_ubound	Optional upper bound for beta.
psi_start	Optional starting values for psi.
psi_lbound	Optional lower bound for psi.
psi_ubound	Optional upper bound for psi.
try	Positive integer. Number of extra tries for <a href="#">OpenMx::mxTryHard()</a> .
ncores	Positive integer. Number of cores to use.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

```
print.fitdtvaridmx
```

*Print Method for Object of Class fitdtvaridmx*

---

**Description**

Print Method for Object of Class fitdtvaridmx

**Usage**

```
## S3 method for class 'fitdtvaridmx'
print(x, means = TRUE, ...)
```

**Arguments**

x	an object of class fitdtvaridmx.
means	Logical. If means = TRUE, return means. Otherwise, the function returns raw estimates.
...	further arguments.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

```
summary.fitdtvaridmx
```

*Summary Method for Object of Class fitdtvaridmx*

---

**Description**

Summary Method for Object of Class fitdtvaridmx

**Usage**

```
## S3 method for class 'fitdtvaridmx'
summary(object, means = TRUE, ...)
```

**Arguments**

object	an object of class fitdtvaridmx.
means	Logical. If means = TRUE, return means. Otherwise, the function returns raw estimates.
...	further arguments.

**Author(s)**

Ivan Jacob Agaloos Pesigan

# Index

- \* **Meta-Analysis of VAR Functions**

- FitDTVARIDMx, [2](#)

- \* **fit**

- FitDTVARIDMx, [2](#)

- \* **metaVAR**

- FitDTVARIDMx, [2](#)

- \* **methods**

- print.fitdtvaridmx, [3](#)

- summary.fitdtvaridmx, [3](#)

FitDTVARIDMx, [2](#)

OpenMx::mxTryHard(), [2](#)

print.fitdtvaridmx, [3](#)

summary.fitdtvaridmx, [3](#)