

Package ‘fitVARMxID’

February 13, 2026

Title Fit the Vector Autoregressive Model for Multiple Individuals

Version 1.0.2

Description Fit the vector autoregressive model for multiple individuals using the 'OpenMx' package (Hunter, 2017 <[doi:10.1080/10705511.2017.1369354](https://doi.org/10.1080/10705511.2017.1369354)>).

URL <https://github.com/jeksterslab/fitVARMxID>,
<https://jeksterslab.github.io/fitVARMxID/>

BugReports <https://github.com/jeksterslab/fitVARMxID/issues>

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

Depends R (>= 4.1.0), OpenMx (>= 2.22.10)

Imports stats, methods

Suggests knitr, rmarkdown, testthat, simStateSpace (>= 1.2.14)

RoxygenNote 7.3.3.9000

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0003-4818-8420>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

coef.varmxid	2
converged	3
FitVARMxID	4
LDL	13
print.varmxid	14
Softplus	16
summary.varmxid	17
vcov.varmxid	18

Index	21
--------------	-----------

coef.varmxid

*Parameter Estimates***Description**

Parameter Estimates

Usage

```
## S3 method for class 'varmxid'
coef(
  object,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  diag_cov = "var",
  converged = TRUE,
  grad_tol = 0.01,
  hess_tol = 1e-08,
  vanishing_theta = TRUE,
  theta_tol = 0.001,
  ...
)
```

Arguments

object	Object of class varmxid.
mu	Logical. If mu = TRUE, include estimates of the mu vector, if available. If mu = FALSE, exclude estimates of the mu vector.
alpha	Logical. If alpha = TRUE, include estimates of the alpha vector, if available. If alpha = FALSE, exclude estimates of the alpha vector.
beta	Logical. If beta = TRUE, include estimates of the beta matrix, if available. If beta = FALSE, exclude estimates of the beta matrix.
nu	Logical. If nu = TRUE, include estimates of the nu vector, if available. If nu = FALSE, exclude estimates of the nu vector.
psi	Logical. If psi = TRUE, include estimates of the psi matrix, if available. If psi = FALSE, exclude estimates of the psi matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
diag_cov	Character string. If diag_cov = "var", psi and theta are in the original metric variance/covariance metric. If diag_cov = "logvar", the diagonal elements of psi and theta are the log of the variances and the off-diagonal elements are the

	elements in L in the LDL ' decomposition. If diag_cov = "softplusvar", the diagonal elements of psi and theta are the softplus of the variances and the off-diagonal elements are the elements in L in the LDL ' decomposition.
converged	Logical. Only include converged cases.
grad_tol	Numeric scalar. Tolerance for the maximum absolute gradient if converged = TRUE.
hess_tol	Numeric scalar. Tolerance for Hessian eigenvalues; eigenvalues must be strictly greater than this value if converged = TRUE.
vanishing_theta	Logical. Test for measurement error variance going to zero if converged = TRUE.
theta_tol	Numeric. Tolerance for vanishing theta test if converged and theta_tol are TRUE.
...	additional arguments.

Value

Returns a list of vectors of parameter estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

converged	<i>Check Model Convergence</i>
-----------	--------------------------------

Description

Evaluate whether OpenMx fit has converged successfully.

Usage

```
converged(object, ...)

## S3 method for class 'varmxid'
converged(
  object,
  grad_tol = 0.01,
  hess_tol = 1e-08,
  vanishing_theta = TRUE,
  theta_tol = 0.001,
  prop = FALSE,
  ...
)
```

Arguments

object	A fit object.
...	Passed to and/or used by methods.
grad_tol	Numeric scalar. Tolerance for the maximum absolute gradient if converged = TRUE.
hess_tol	Numeric scalar. Tolerance for Hessian eigenvalues; eigenvalues must be strictly greater than this value if converged = TRUE.
vanishing_theta	Logical. Test for measurement error variance going to zero if converged = TRUE.
theta_tol	Numeric. Tolerance for vanishing theta test if converged and theta_tol are TRUE.
prop	Logical. If prop = FALSE, a named logical vector indicating, for each individual fit, whether the convergence criteria are met. If prop = TRUE, the proportion of cases that converged.

Details

Convergence is defined by three criteria:

1. Status code equals 0L.
2. The maximum absolute gradient is below grad_tol.
3. The Hessian is positive definite with all eigenvalues greater than hess_tol.
4. If vanishing_theta = TRUE, the model additionally checks that the diagonal elements of the measurement error covariance matrix (Θ) are not vanishingly small, where “small” is defined by theta_tol.

Value

For the varmxid method: If prop = FALSE, a named logical vector indicating, for each individual fit, whether the convergence criteria are met. If prop = TRUE, the proportion of cases that converged.

Author(s)

Ivan Jacob Agaloos Pesigan

FitVARMxID

Fit the First-Order Vector Autoregressive Model by ID

Description

The function fits the first-order vector autoregressive model for each unit ID.

Usage

```
FitVARMxID(  
  data,  
  observed,  
  id,  
  ct = FALSE,  
  time = NULL,  
  center = TRUE,  
  mu_fixed = FALSE,  
  mu_free = NULL,  
  mu_values = NULL,  
  mu_lbound = NULL,  
  mu_ubound = NULL,  
  alpha_fixed = FALSE,  
  alpha_free = NULL,  
  alpha_values = NULL,  
  alpha_lbound = NULL,  
  alpha_ubound = NULL,  
  beta_fixed = FALSE,  
  beta_free = NULL,  
  beta_values = NULL,  
  beta_lbound = NULL,  
  beta_ubound = NULL,  
  psi_diag = FALSE,  
  psi_d_free = NULL,  
  psi_d_values = NULL,  
  psi_d_lbound = NULL,  
  psi_d_ubound = NULL,  
  psi_l_free = NULL,  
  psi_l_values = NULL,  
  psi_l_lbound = NULL,  
  psi_l_ubound = NULL,  
  nu_fixed = TRUE,  
  nu_free = NULL,  
  nu_values = NULL,  
  nu_lbound = NULL,  
  nu_ubound = NULL,  
  theta_diag = TRUE,  
  theta_fixed = TRUE,  
  theta_d_free = NULL,  
  theta_d_values = NULL,  
  theta_d_lbound = NULL,  
  theta_d_ubound = NULL,  
  theta_d_equal = FALSE,  
  theta_l_free = NULL,  
  theta_l_values = NULL,  
  theta_l_lbound = NULL,  
  theta_l_ubound = NULL,
```

```

mu0_fixed = TRUE,
mu0_func = FALSE,
mu0_free = NULL,
mu0_values = NULL,
mu0_lbound = NULL,
mu0_ubound = NULL,
sigma0_fixed = TRUE,
sigma0_func = FALSE,
sigma0_diag = FALSE,
sigma0_d_free = NULL,
sigma0_d_values = NULL,
sigma0_d_lbound = NULL,
sigma0_d_ubound = NULL,
sigma0_l_free = NULL,
sigma0_l_values = NULL,
sigma0_l_lbound = NULL,
sigma0_l_ubound = NULL,
robust = FALSE,
tries_explore = 100,
tries_local = 10,
max_attempts = 10,
grad_tol = 0.01,
hess_tol = 1e-08,
eps = 1e-06,
factor = 10,
overwrite = FALSE,
path = getwd(),
prefix = "FitVARMxID",
seed = NULL,
silent = FALSE,
ncores = NULL,
clean = TRUE
)

```

Arguments

data	Data frame. A data frame object of data for potentially multiple subjects that contain a column of subject ID numbers (i.e., an ID variable), and at least one column of observed values.
observed	Character vector. A vector of character strings of the names of the observed variables in the data.
id	Character string. A character string of the name of the ID variable in the data.
ct	Logical. If TRUE, fit a continuous-time vector autoregressive model. If FALSE, fit a discrete-time vector autoregressive model.
time	Character string. A character string of the name of the TIME variable in the data. Used when ct = TRUE.
center	Logical. If TRUE, use the mean-centered (mean-reverting) state equation. Note that when center = TRUE, alpha is implied and the set-point mu is estimated.

<code>mu_fixed</code>	Logical. If TRUE, the dynamic model set-point vector <code>mu</code> is fixed. If FALSE, <code>mu</code> is estimated.
<code>mu_free</code>	Logical vector indicating which elements of <code>mu</code> are freely estimated. If NULL, all elements are free. Ignored if <code>mu_fixed</code> = TRUE.
<code>mu_values</code>	Numeric vector of values for <code>mu</code> . If <code>mu_fixed</code> = TRUE, these are fixed values. If <code>mu_fixed</code> = FALSE, these are starting values. If NULL, defaults to a vector of zeros.
<code>mu_lbound</code>	Numeric vector of lower bounds for <code>mu</code> . If NULL, no lower bounds are set. Ignored if <code>mu_fixed</code> = TRUE.
<code>mu_ubound</code>	Numeric vector of upper bounds for <code>mu</code> . If NULL, no upper bounds are set. Ignored if <code>mu_fixed</code> = TRUE.
<code>alpha_fixed</code>	Logical. If TRUE, the dynamic model intercept vector <code>alpha</code> is fixed. If FALSE, <code>alpha</code> is estimated.
<code>alpha_free</code>	Logical vector indicating which elements of <code>alpha</code> are freely estimated. If NULL, all elements are free. Ignored if <code>alpha_fixed</code> = TRUE.
<code>alpha_values</code>	Numeric vector of values for <code>alpha</code> . If <code>alpha_fixed</code> = TRUE, these are fixed values. If <code>alpha_fixed</code> = FALSE, these are starting values. If NULL, defaults to a vector of zeros.
<code>alpha_lbound</code>	Numeric vector of lower bounds for <code>alpha</code> . If NULL, no lower bounds are set. Ignored if <code>alpha_fixed</code> = TRUE.
<code>alpha_ubound</code>	Numeric vector of upper bounds for <code>alpha</code> . If NULL, no upper bounds are set. Ignored if <code>alpha_fixed</code> = TRUE.
<code>beta_fixed</code>	Logical. If TRUE, the dynamic model coefficient matrix <code>beta</code> is fixed. If FALSE, <code>beta</code> is estimated.
<code>beta_free</code>	Logical matrix indicating which elements of <code>beta</code> are freely estimated. If NULL, all elements are free. Ignored if <code>beta_fixed</code> = TRUE.
<code>beta_values</code>	Numeric matrix of values for <code>beta</code> . If <code>beta_fixed</code> = TRUE, these are fixed values. If <code>beta_fixed</code> = FALSE, these are starting values. If NULL, defaults to a zero matrix.
<code>beta_lbound</code>	Numeric matrix of lower bounds for <code>beta</code> . If NULL, defaults to -1.5. Ignored if <code>beta_fixed</code> = TRUE.
<code>beta_ubound</code>	Numeric matrix of upper bounds for <code>beta</code> . If NULL, defaults to +1.5. Ignored if <code>beta_fixed</code> = TRUE.
<code>psi_diag</code>	Logical. If TRUE, <code>psi</code> is diagonal. If FALSE, <code>psi</code> is symmetric.
<code>psi_d_free</code>	Logical vector indicating free/fixed status of the elements of <code>psi_d</code> . If NULL, all element of <code>psi_d</code> are free.
<code>psi_d_values</code>	Numeric vector with starting values for <code>psi_d</code> . If NULL, defaults to a vector of ones.
<code>psi_d_lbound</code>	Numeric vector with lower bounds for <code>psi_d</code> . If NULL, no lower bounds are set.
<code>psi_d_ubound</code>	Numeric vector with upper bounds for <code>psi_d</code> . If NULL, no upper bounds are set.
<code>psi_l_free</code>	Logical matrix indicating which strictly-lower-triangular elements of <code>psi_l</code> are free. Ignored if <code>psi_diag</code> = TRUE.

psi_l_values	Numeric matrix of starting values for the strictly-lower-triangular elements of psi_l. If NULL, defaults to a null matrix.
psi_l_lbound	Numeric matrix with lower bounds for psi_l. If NULL, no lower bounds are set.
psi_l_ubound	Numeric matrix with upper bounds for psi_l. If NULL, no upper bounds are set.
nu_fixed	Logical. If TRUE, the measurement model intercept vector nu is fixed. If FALSE, nu is estimated.
nu_free	Logical vector indicating which elements of nu are freely estimated. If NULL, all elements are free. Ignored if nu_fixed = TRUE.
nu_values	Numeric vector of values for nu. If nu_fixed = TRUE, these are fixed values. If nu_fixed = FALSE, these are starting values. If NULL, defaults to a vector of zeros.
nu_lbound	Numeric vector of lower bounds for nu. If NULL, no lower bounds are set. Ignored if nu_fixed = TRUE.
nu_ubound	Numeric vector of upper bounds for nu. If NULL, no upper bounds are set. Ignored if nu_fixed = TRUE.
theta_diag	Logical. If TRUE, theta is diagonal. If FALSE, theta is symmetric.
theta_fixed	Logical. If TRUE, the measurement error matrix theta is fixed to SoftPlus(theta_d_values). If FALSE, only diagonal elements are estimated (off-diagonals fixed to zero).
theta_d_free	Logical vector indicating free/fixed status of the diagonal parameters theta_d. If NULL, all element of theta_d are free.
theta_d_values	Numeric vector with starting values for theta_d. If theta_fixed = TRUE, these are fixed values. If theta_fixed = FALSE, these are starting values. If NULL, defaults to an identity matrix.
theta_d_lbound	Numeric vector with lower bounds for theta_d. If NULL, no lower bounds are set.
theta_d_ubound	Numeric vector with upper bounds for theta_d. If NULL, no upper bounds are set.
theta_d_equal	Logical. When TRUE, all free diagonal elements of theta_d are constrained to be equal and estimated as a single shared parameter (theta_eq). Ignored if no diagonal elements are free.
theta_l_free	Logical matrix indicating which strictly-lower-triangular elements of theta_l are free. Ignored if theta_diag = TRUE.
theta_l_values	Numeric matrix of starting values for the strictly-lower-triangular elements of theta_l. If NULL, defaults to a null matrix.
theta_l_lbound	Numeric matrix with lower bounds for theta_l. If NULL, no lower bounds are set.
theta_l_ubound	Numeric matrix with upper bounds for theta_l. If NULL, no upper bounds are set.
mu0_fixed	Logical. If TRUE, the initial mean vector mu0 is fixed. If FALSE, mu0 is estimated.
mu0_func	Logical. If TRUE and mu0_fixed = TRUE, mu0 is fixed to $(I - \beta)^{-1}\alpha$.
mu0_free	Logical vector indicating which elements of mu0 are freely estimated.

<code>mu0_values</code>	Numeric vector of values for μ_0 . If <code>mu0_fixed = TRUE</code> , these are fixed values. If <code>mu0_fixed = FALSE</code> , these are starting values. If <code>NULL</code> , defaults to a vector of zeros.
<code>mu0_lbound</code>	Numeric vector of lower bounds for μ_0 . If <code>NULL</code> , no lower bounds are set. Ignored if <code>mu0_fixed = TRUE</code> .
<code>mu0_ubound</code>	Numeric vector of upper bounds for μ_0 . If <code>NULL</code> , no upper bounds are set. Ignored if <code>mu0_fixed = TRUE</code> .
<code>sigma0_fixed</code>	Logical. If <code>TRUE</code> , the initial covariance matrix σ_0 is fixed. If <code>FALSE</code> , σ_0 is estimated.
<code>sigma0_func</code>	Logical. If <code>TRUE</code> and <code>sigma0_fixed = TRUE</code> , σ_0 is fixed to $(I - \beta \otimes \beta)^{-1} \text{Vec}(\Psi)$.
<code>sigma0_diag</code>	Logical. If <code>TRUE</code> , σ_0 is diagonal. If <code>FALSE</code> , σ_0 is symmetric.
<code>sigma0_d_free</code>	Logical vector indicating free/fixed status of the elements of σ_0_d . If <code>NULL</code> , all element of σ_0_d are free.
<code>sigma0_d_values</code>	Numeric vector with starting values for σ_0_d . If <code>NULL</code> , defaults to a vector of ones.
<code>sigma0_d_lbound</code>	Numeric vector with lower bounds for σ_0_d . If <code>NULL</code> , no lower bounds are set.
<code>sigma0_d_ubound</code>	Numeric vector with upper bounds for σ_0_d . If <code>NULL</code> , no upper bounds are set.
<code>sigma0_l_free</code>	Logical matrix indicating which strictly-lower-triangular elements of σ_0_l are free. Ignored if <code>sigma0_diag = TRUE</code> .
<code>sigma0_l_values</code>	Numeric matrix of starting values for the strictly-lower-triangular elements of σ_0_l . If <code>NULL</code> , defaults to a null matrix.
<code>sigma0_l_lbound</code>	Numeric matrix with lower bounds for σ_0_l . If <code>NULL</code> , no lower bounds are set.
<code>sigma0_l_ubound</code>	Numeric matrix with upper bounds for σ_0_l . If <code>NULL</code> , no upper bounds are set.
<code>robust</code>	Logical. If <code>TRUE</code> , calculate robust (sandwich) sampling variance-covariance matrix.
<code>tries_explore</code>	Integer. Number of extra tries for the wide exploration phase using <code>OpenMx::mxTryHardWideSearch()</code> with <code>checkHess = FALSE</code> .
<code>tries_local</code>	Integer. Number of extra tries for local polishing via <code>OpenMx::mxTryHard()</code> when gradients remain above tolerance.
<code>max_attempts</code>	Integer. Maximum number of remediation attempts after the first Hessian computation fails the criteria. Each attempt may nudge off bounds, refit locally without the Hessian, and, on the last attempt, relax bounds.
<code>grad_tol</code>	Numeric. Tolerance for the maximum absolute gradient. Smaller values are stricter.

hess_tol	Numeric. Minimum allowable Hessian eigenvalue. Smaller values are less strict.
eps	Numeric. Proximity threshold to detect parameters on their bounds and to nudge them inward by $10 * \text{eps}$.
factor	Numeric. Multiplicative factor to relax parameter bounds on the final remediation attempt. Lower bounds are divided by factor and upper bounds are multiplied by factor.
overwrite	Logical. If TRUE, existing intermediate files are overwritten. Defaults to FALSE.
path	Character string. Directory in which to save intermediate files.
prefix	Alphanumeric character string. Prefix to use when naming intermediate files.
seed	Random seed for reproducibility.
silent	Logical. If TRUE, suppresses messages during the model fitting stage.
ncores	Positive integer. Number of cores to use.
clean	Logical. If TRUE, clean intermediate files saved in path.

Details

Measurement Model:

By default, the measurement model is given by

$$\mathbf{y}_{i,t} = \boldsymbol{\eta}_{i,t}.$$

However, the full measurement model can be parameterized as follows

$$\mathbf{y}_{i,t} = \boldsymbol{\nu}_i + \boldsymbol{\Lambda} \boldsymbol{\eta}_{i,t} + \boldsymbol{\varepsilon}_{i,t}, \quad \text{with} \quad \boldsymbol{\varepsilon}_{i,t} \sim \mathcal{N}(\mathbf{0}, \boldsymbol{\Theta}_i)$$

where $\mathbf{y}_{i,t}$, $\boldsymbol{\eta}_{i,t}$, and $\boldsymbol{\varepsilon}_{i,t}$ are random variables and $\boldsymbol{\nu}_i$, $\boldsymbol{\Lambda}$, and $\boldsymbol{\Theta}_i$ are model parameters. $\mathbf{y}_{i,t}$ represents a vector of observed random variables, $\boldsymbol{\eta}_{i,t}$ a vector of latent random variables, and $\boldsymbol{\varepsilon}_{i,t}$ a vector of random measurement errors, at time t and individual i . $\boldsymbol{\nu}_i$ denotes a vector of intercepts (fixed to a null vector by default), $\boldsymbol{\Lambda}$ a matrix of factor loadings, and $\boldsymbol{\Theta}_i$ the covariance matrix of $\boldsymbol{\varepsilon}$. In this model, $\boldsymbol{\Lambda}$ is an identity matrix and $\boldsymbol{\Theta}_i$ is a diagonal matrix.

Discrete-Time Dynamic Structure:

The dynamic structure is given by

$$\boldsymbol{\eta}_{i,t} = \boldsymbol{\alpha}_i + \boldsymbol{\beta}_i \boldsymbol{\eta}_{i,t-1} + \boldsymbol{\zeta}_{i,t}, \quad \text{with} \quad \boldsymbol{\zeta}_{i,t} \sim \mathcal{N}(\mathbf{0}, \boldsymbol{\Psi}_i)$$

where $\boldsymbol{\eta}_{i,t}$, $\boldsymbol{\eta}_{i,t-1}$, and $\boldsymbol{\zeta}_{i,t}$ are random variables, and $\boldsymbol{\alpha}_i$, $\boldsymbol{\beta}_i$, and $\boldsymbol{\Psi}_i$ are model parameters. Here, $\boldsymbol{\eta}_{i,t}$ is a vector of latent variables at time t and individual i , $\boldsymbol{\eta}_{i,t-1}$ represents a vector of latent variables at time $t-1$ and individual i , and $\boldsymbol{\zeta}_{i,t}$ represents a vector of dynamic noise at time t and individual i . $\boldsymbol{\alpha}_i$ denotes a vector of intercepts, $\boldsymbol{\beta}_i$ a matrix of autoregression and cross regression coefficients, and $\boldsymbol{\Psi}_i$ the covariance matrix of $\boldsymbol{\zeta}_{i,t}$.

If center = TRUE, the dynamic structure is parameterized as follows

$$\boldsymbol{\eta}_{i,t} = \boldsymbol{\mu}_i + \boldsymbol{\beta}_i (\boldsymbol{\eta}_{i,t-1} - \boldsymbol{\mu}_i) + \boldsymbol{\zeta}_{i,t}$$

where $\boldsymbol{\mu}_i$ is equilibrium level of the latent state toward which the system is pulled over time.

Continuous-Time Dynamic Structure:

The continuous-time parameterization, when `ct = TRUE`, for the dynamic structure is given by

$$d\boldsymbol{\eta}_{i,t} = (\boldsymbol{\alpha}_i + \boldsymbol{\beta}_i \boldsymbol{\eta}_{i,t-1}) dt + \boldsymbol{\Psi}_i^{\frac{1}{2}} d\mathbf{W}_{i,t}$$

note that $d\mathbf{W}$ is a Wiener process or Brownian motion, which represents random fluctuations.

If `center = TRUE`, the dynamic structure is parameterized as follows

$$d\boldsymbol{\eta}_{i,t} = \boldsymbol{\beta}_i (\boldsymbol{\eta}_{i,t-1} - \boldsymbol{\mu}_i) dt + \boldsymbol{\Psi}_i^{\frac{1}{2}} d\mathbf{W}_{i,t}$$

Value

Returns an object of class `varmxid` which is a list with the following elements:

call Function call.

args List of function arguments.

fun Function used ("FitVARMxID").

output A list of fitted OpenMx models.

robust A list of output from `OpenMx::mxRobustSE()` with argument `details = TRUE` for each id if `robust = TRUE`.

Author(s)

Ivan Jacob Agaloos Pesigan

References

Hunter, M. D. (2017). State space modeling in an open source, modular, structural equation modeling environment. *Structural Equation Modeling: A Multidisciplinary Journal*, 25(2), 307–324. doi:10.1080/10705511.2017.1369354

Neale, M. C., Hunter, M. D., Pritikin, J. N., Zahery, M., Brick, T. R., Kirkpatrick, R. M., Estabrook, R., Bates, T. C., Maes, H. H., & Boker, S. M. (2015). OpenMx 2.0: Extended structural equation and statistical modeling. *Psychometrika*, 81(2), 535–549. doi:10.1007/s1133601494358

See Also

Other VAR Functions: `LDL()`, `Softplus()`

Examples

```
if (requireNamespace("simStateSpace")) {
  # Generate data using the simStateSpace package-----
  set.seed(42)
  k <- 2
  n <- 5
  time <- 1000
  alpha <- rep(x = 5, times = k)
  beta <- matrix(
    data = c(.5, .0, .2, .5),
```

```

    nrow = k,
    ncol = k
  )
  psi <- matrix(
    data = c(exp(-4.1), exp(-3.9), exp(-3.9), exp(-3.2)),
    nrow = k,
    ncol = k
  )
  psi_l <- t(chol(psi))
  mu0 <- c(solve(diag(k) - beta) %*% alpha)
  sigma0 <- matrix(
    data = c(
      solve(diag(k * k) - beta %*% beta) %*% c(psi)
    ),
    nrow = k,
    ncol = k
  )
  sigma0_l <- t(chol(sigma0))
  sim <- simStateSpace::SimSSMVARIVary(
    n = n,
    time,
    mu0 = list(mu0),
    sigma0_l = list(sigma0_l),
    alpha = list(alpha),
    beta = simStateSpace::SimBetaN(
      n = n,
      beta = beta,
      vcov_beta_vec_l = t(chol(0.1 * diag(k * k)))
    ),
    psi_l = list(psi_l)
  )
  data <- as.data.frame(sim)

# Fit the model-----
# center = TRUE
library(fitVARMxID)
fit <- FitVARMxID(
  data = data,
  observed = paste0("y", seq_len(k)),
  id = "id",
  center = TRUE
)
print(fit)
summary(fit)
coef(fit)
vcov(fit)
converged(fit)

# Fit the model-----
# center = FALSE
library(fitVARMxID)
fit <- FitVARMxID(
  data = data,

```

```

    observed = paste0("y", seq_len(k)),
    id = "id",
    center = FALSE
  )
  print(fit)
  summary(fit)
  coef(fit)
  vcov(fit)
  converged(fit)
}

```

LDL

LDL' Decomposition of a Symmetric Positive-Definite Matrix

Description

Performs an LDL' factorization of a symmetric positive-definite matrix X , such that

$$X = LDL^{\top},$$

where L is unit lower-triangular (ones on the diagonal) and D is diagonal.

Usage

LDL(x)

Arguments

x Numeric matrix. Must be symmetric positive-definite.

Details

This function returns both the unit lower-triangular factor L and the diagonal factor D . The strictly lower-triangular part of L is also provided for convenience. The function additionally computes an unconstrained vector d_uc such that $\text{softplus}(d_uc) = d_vec$, using $\text{softplus}^{-1}(y) = \log(\exp(y) + 1)$ for stable back-transformation.

Value

A list with components:

<code>l_mat_unit</code>	Unit lower-triangular matrix L .
<code>l_mat_strict</code>	Strictly lower-triangular part of L .
<code>d_mat</code>	Diagonal matrix D .
<code>d_vec</code>	Vector of diagonal entries of D .
<code>d_uc</code>	Unconstrained vector with $\text{softplus}(d_uc) = d_vec$.

x	Original input matrix.
y	Reconstructed matrix LDL^T .
diff	Difference $x - y$.

See Also

Other VAR Functions: [FitVARMxID\(\)](#), [Softplus\(\)](#)

Examples

```
set.seed(123)
A <- matrix(rnorm(16), 4, 4)
S <- crossprod(A) + diag(1e-6, 4) # SPD
out <- LDL(S)
max(abs(out$diff))
```

print.varmxid	<i>Print Method for Object of Class varmxid</i>
---------------	---

Description

Print Method for Object of Class varmxid

Usage

```
## S3 method for class 'varmxid'
print(
  x,
  means = FALSE,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  diag_cov = "var",
  converged = TRUE,
  grad_tol = 0.01,
  hess_tol = 1e-08,
  vanishing_theta = TRUE,
  theta_tol = 0.001,
  digits = 4,
  ...
)
```

Arguments

<code>x</code>	an object of class <code>varmxid</code> .
<code>means</code>	Logical. If <code>means = TRUE</code> , return means. Otherwise, the function returns raw estimates.
<code>mu</code>	Logical. If <code>mu = TRUE</code> , include estimates of the <code>mu</code> vector, if available. If <code>mu = FALSE</code> , exclude estimates of the <code>mu</code> vector.
<code>alpha</code>	Logical. If <code>alpha = TRUE</code> , include estimates of the <code>alpha</code> vector, if available. If <code>alpha = FALSE</code> , exclude estimates of the <code>alpha</code> vector.
<code>beta</code>	Logical. If <code>beta = TRUE</code> , include estimates of the <code>beta</code> matrix, if available. If <code>beta = FALSE</code> , exclude estimates of the <code>beta</code> matrix.
<code>nu</code>	Logical. If <code>nu = TRUE</code> , include estimates of the <code>nu</code> vector, if available. If <code>nu = FALSE</code> , exclude estimates of the <code>nu</code> vector.
<code>psi</code>	Logical. If <code>psi = TRUE</code> , include estimates of the <code>psi</code> matrix, if available. If <code>psi = FALSE</code> , exclude estimates of the <code>psi</code> matrix.
<code>theta</code>	Logical. If <code>theta = TRUE</code> , include estimates of the <code>theta</code> matrix, if available. If <code>theta = FALSE</code> , exclude estimates of the <code>theta</code> matrix.
<code>diag_cov</code>	Character string. If <code>diag_cov = "var"</code> , <code>psi</code> and <code>theta</code> are in the original metric variance/covariance metric. If <code>diag_cov = "logvar"</code> , the diagonal elements of <code>psi</code> and <code>theta</code> are the log of the variances and the off-diagonal elements are the elements in <code>L</code> in the LDL' decomposition. If <code>diag_cov = "softplusvar"</code> , the diagonal elements of <code>psi</code> and <code>theta</code> are the softplus of the variances and the off-diagonal elements are the elements in <code>L</code> in the LDL' decomposition.
<code>converged</code>	Logical. Only include converged cases.
<code>grad_tol</code>	Numeric scalar. Tolerance for the maximum absolute gradient if <code>converged = TRUE</code> .
<code>hess_tol</code>	Numeric scalar. Tolerance for Hessian eigenvalues; eigenvalues must be strictly greater than this value if <code>converged = TRUE</code> .
<code>vanishing_theta</code>	Logical. Test for measurement error variance going to zero if <code>converged = TRUE</code> .
<code>theta_tol</code>	Numeric. Tolerance for vanishing <code>theta</code> test if <code>converged</code> and <code>theta_tol</code> are <code>TRUE</code> .
<code>digits</code>	Integer indicating the number of decimal places to display.
<code>...</code>	further arguments.

Value

Prints means or raw estimates depending the the value of the argument `means`.

Author(s)

Ivan Jacob Agaloos Pesigan

Softplus

*Softplus and Inverse Softplus Transformations***Description**

The softplus transformation maps unconstrained real values to the positive real line. This is useful when parameters (e.g., variances) must be strictly positive. The inverse softplus transformation recovers the unconstrained value from a positive input.

Usage

```
Softplus(x)
```

```
InvSoftplus(x)
```

Arguments

`x` Numeric vector or matrix. Input values to be transformed.

Details

- $\text{Softplus}(x) = \log(1 + \exp(x))$
- $\text{InvSoftplus}(x) = \log(\exp(x) - 1)$

For numerical stability, these functions use `log1p()` and `expm1()` internally.

Value

- `Softplus()`: numeric vector or matrix of strictly positive values.
- `InvSoftplus()`: numeric vector or matrix of unconstrained values.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other VAR Functions: [FitVARMxID\(\)](#), [LDL\(\)](#)

Examples

```
# Apply softplus to unconstrained values
x <- c(-5, 0, 5)
y <- Softplus(x)

# Recover unconstrained values
x_recovered <- InvSoftplus(y)

y
```


x_recovered

summary.varmxid

Summary Method for Object of Class varmxid

Description

Summary Method for Object of Class varmxid

Usage

```
## S3 method for class 'varmxid'
summary(
  object,
  means = FALSE,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  diag_cov = "var",
  converged = TRUE,
  grad_tol = 0.01,
  hess_tol = 1e-08,
  vanishing_theta = TRUE,
  theta_tol = 0.001,
  digits = 4,
  ...
)
```

Arguments

object	an object of class varmxid.
means	Logical. If means = TRUE, return means. Otherwise, the function returns raw estimates.
mu	Logical. If mu = TRUE, include estimates of the mu vector, if available. If mu = FALSE, exclude estimates of the mu vector.
alpha	Logical. If alpha = TRUE, include estimates of the alpha vector, if available. If alpha = FALSE, exclude estimates of the alpha vector.
beta	Logical. If beta = TRUE, include estimates of the beta matrix, if available. If beta = FALSE, exclude estimates of the beta matrix.
nu	Logical. If nu = TRUE, include estimates of the nu vector, if available. If nu = FALSE, exclude estimates of the nu vector.

psi	Logical. If psi = TRUE, include estimates of the psi matrix, if available. If psi = FALSE, exclude estimates of the psi matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
diag_cov	Character string. If diag_cov = "var", psi and theta are in the original metric variance/covariance metric. If diag_cov = "logvar", the diagonal elements of psi and theta are the log of the variances and the off-diagonal elements are the elements in L in the LDL ' decomposition. If diag_cov = "softplusvar", the diagonal elements of psi and theta are the softplus of the variances and the off-diagonal elements are the elements in L in the LDL ' decomposition.
converged	Logical. Only include converged cases.
grad_tol	Numeric scalar. Tolerance for the maximum absolute gradient if converged = TRUE.
hess_tol	Numeric scalar. Tolerance for Hessian eigenvalues; eigenvalues must be strictly greater than this value if converged = TRUE.
vanishing_theta	Logical. Test for measurement error variance going to zero if converged = TRUE.
theta_tol	Numeric. Tolerance for vanishing theta test if converged and theta_tol are TRUE.
digits	Integer indicating the number of decimal places to display.
...	further arguments.

Value

Returns means or raw estimates depending the the value of the argument means.

Author(s)

Ivan Jacob Agaloos Pesigan

vcov.varmxid	<i>Sampling Covariance Matrix of the Parameter Estimates</i>
--------------	--

Description

Sampling Covariance Matrix of the Parameter Estimates

Usage

```
## S3 method for class 'varmxid'
vcov(
  object,
  mu = TRUE,
  alpha = TRUE,
```

```

    beta = TRUE,
    nu = TRUE,
    psi = TRUE,
    theta = TRUE,
    diag_cov = "var",
    converged = TRUE,
    grad_tol = 0.01,
    hess_tol = 1e-08,
    vanishing_theta = TRUE,
    theta_tol = 0.001,
    robust = FALSE,
    ...
)

```

Arguments

object	Object of class varmxid.
mu	Logical. If mu = TRUE, include estimates of the mu vector, if available. If mu = FALSE, exclude estimates of the mu vector.
alpha	Logical. If alpha = TRUE, include estimates of the alpha vector, if available. If alpha = FALSE, exclude estimates of the alpha vector.
beta	Logical. If beta = TRUE, include estimates of the beta matrix, if available. If beta = FALSE, exclude estimates of the beta matrix.
nu	Logical. If nu = TRUE, include estimates of the nu vector, if available. If nu = FALSE, exclude estimates of the nu vector.
psi	Logical. If psi = TRUE, include estimates of the psi matrix, if available. If psi = FALSE, exclude estimates of the psi matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
diag_cov	Character string. If diag_cov = "var", psi and theta are in the original metric variance/covariance metric. If diag_cov = "logvar", the diagonal elements of psi and theta are the log of the variances and the off-diagonal elements are the elements in L in the LDL' decomposition. If diag_cov = "softplusvar", the diagonal elements of psi and theta are the softplus of the variances and the off-diagonal elements are the elements in L in the LDL' decomposition.
converged	Logical. Only include converged cases.
grad_tol	Numeric scalar. Tolerance for the maximum absolute gradient if converged = TRUE.
hess_tol	Numeric scalar. Tolerance for Hessian eigenvalues; eigenvalues must be strictly greater than this value if converged = TRUE.
vanishing_theta	Logical. Test for measurement error variance going to zero if converged = TRUE.
theta_tol	Numeric. Tolerance for vanishing theta test if converged and theta_tol are TRUE.

robust	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix.
...	additional arguments.

Value

Returns a list of sampling variance-covariance matrices.

Author(s)

Ivan Jacob Agaloos Pesigan

Index

* VAR Functions

FitVARMxID, [4](#)

LDL, [13](#)

Softplus, [16](#)

* fitVARMxID

FitVARMxID, [4](#)

LDL, [13](#)

Softplus, [16](#)

* fit

FitVARMxID, [4](#)

* methods

coef.varmxid, [2](#)

converged, [3](#)

print.varmxid, [14](#)

summary.varmxid, [17](#)

vcov.varmxid, [18](#)

* misc

LDL, [13](#)

Softplus, [16](#)

coef.varmxid, [2](#)

converged, [3](#)

FitVARMxID, [4](#), [14](#), [16](#)

InvSoftplus (Softplus), [16](#)

LDL, [11](#), [13](#), [16](#)

OpenMx::imxRobustSE(), [11](#)

print.varmxid, [14](#)

Softplus, [11](#), [14](#), [16](#)

summary.varmxid, [17](#)

vcov.varmxid, [18](#)