

Package ‘manMetaVAR’

August 3, 2025

Title Multivariate Meta-Analysis of Vector Autoregressive Model
Coefficients

Version 0.9.1

Description Research compendium for the manuscript
Pesigan, I. J. A., et al. (In Preparation).
Multivariate Meta-Analysis of Vector Autoregressive Model Coefficients.
<doi:10.0000/0000000000>.

URL <https://github.com/jeksterslab/manMetaVAR>,
<https://jeksterslab.github.io/manMetaVAR/>,
<https://osf.io/uenr7/>, <https://doi.org/10.0000/0000000000>

BugReports <https://github.com/jeksterslab/manMetaVAR/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

Depends R (>= 4.0.0), OpenMx, fitDTVARMx, metaVAR

Imports simStateSpace, mlVAR, rjags, coda

Remotes jeksterslab/fitDTVARMx, jeksterslab/metaVAR

Suggests knitr, rmarkdown, testthat

RoxygenNote 7.3.2

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0003-4818-8420>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

Compress	2
FitDTVAR	3

FitJAGS	3
FitMetaVAR	4
FitMLVAR	5
GenData	6
params	6
Sim	7
SimFitDTVAR	7
SimFitJAGS	8
SimFitMetaVAR	9
SimFitMLVAR	10
SimFN	11
SimGenData	11
SimProj	12
Index	13

Compress	<i>Compress Replication</i>
----------	-----------------------------

Description

Compress Replication

Usage

Compress(taskid, repid, output_folder)

Arguments

- taskid Positive integer. Task ID.
- repid Positive integer. Replication ID.
- output_folder Character string. Output folder.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

FitDTVAR*Fit the Model using the fitDTVARMx Package*

Description

The function fits the model using the [fitDTVARMx](#) package.

Usage

```
FitDTVAR(data, ncores = NULL)
```

Arguments

<code>data</code>	R object. Output of the GenData() function.
<code>ncores</code>	Positive integer. Number of cores to use.

See Also

Other Model Fitting Functions: [FitJAGS\(\)](#), [FitMLVAR\(\)](#)

Examples

```
## Not run:
set.seed(42)
data <- GenData(taskid = 1)
fit <- FitDTVAR(
  data = data,
  ncores = parallel::detectCores()
)
summary(fit)

## End(Not run)
```

FitJAGS*Fit the Model using JAGS*

Description

The function fits the model using JAGS.

Usage

```
FitJAGS(
  data,
  n.chains = 4,
  n.adapt = 2000,
  n.iter = 10000,
  max_iter = 10000,
  seed = NULL
)
```

Arguments

<code>data</code>	R object. Output of the GenData() function.
<code>n.chains</code>	the number of parallel chains for the model
<code>n.adapt</code>	the number of iterations for adaptation. See adapt for details. If <code>n.adapt = 0</code> then no adaptation takes place.
<code>n.iter</code>	number of iterations to monitor
<code>max_iter</code>	Positive integer. Maximum number of reruns.
<code>seed</code>	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMLVAR\(\)](#)

Examples

```
## Not run:
set.seed(42)
data <- GenData(taskid = 1)
fit <- FitJAGS(data = data)
summary(fit)

## End(Not run)
```

FitMetaVAR

Multivariate Meta-Analysis using the metaVAR Package

Description

The function performs multivariate meta-analysis using the [metaVAR](#) package.

Usage

```
FitMetaVAR(fit, ncores = NULL)
```

Arguments

fit	R object. Output of the FitDTVARmX() function.
ncores	Positive integer. Number of cores to use.

Examples

```
## Not run:
set.seed(42)
data <- GenData(taskid = 1)
fit <- FitDTVAR(
  data = data,
  ncores = parallel::detectCores()
)
pooled <- FitMetaVAR(
  fit = fit,
  ncores = parallel::detectCores()
)
summary(pooled)

## End(Not run)
```

FitMLVAR

Fit the Model using the mlVAR Package

Description

The function fits the model using the [mlVAR](#) package.

Usage

```
FitMLVAR(data)
```

Arguments

data	R object. Output of the GenData() function.
------	---

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitJAGS\(\)](#)

Examples

```
## Not run:
set.seed(42)
data <- GenData(taskid = 1)
fit <- FitMLVAR(data = data)
summary(fit)

## End(Not run)
```

GenData

Simulate Data

Description

The function simulates data using the `simStateSpace::SimSSMIVary()` function.

Usage

```
GenData(taskid)
```

Arguments

taskid Positive integer. Task ID.

Examples

```
## Not run:
set.seed(42)
data <- GenData(taskid = 1)

## End(Not run)
```

params

Simulation Parameters

Description

Simulation Parameters

Usage

```
params
```

Format

A dataframe with 25 rows and 3 columns:

taskid Simulation Task ID.

n Sample size.

time Number of measurement occasions.

Author(s)

Ivan Jacob Agaloos Pesigan

Sim	<i>Simulation Replication</i>
-----	-------------------------------

Description

Simulation Replication

Usage

```
Sim(taskid, repid, output_folder, overwrite, integrity, seed)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
seed	Integer. Random seed.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitDTVAR	<i>Simulation Replication - FitDTVAR</i>
-------------	--

Description

Simulation Replication - FitDTVAR

Usage

```
SimFitDTVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitJAGS

Simulation Replication - FitJAGS

Description

Simulation Replication - FitJAGS

Usage

```
SimFitJAGS(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMetaVAR

Simulation Replication - FitMetaVAR

Description

Simulation Replication - FitMetaVAR

Usage

```
SimFitMetaVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMLVAR

Simulation Replication - FitMLVAR

Description

Simulation Replication - FitMLVAR

Usage

```
SimFitMLVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFN	<i>Simulation File Name</i>
-------	-----------------------------

Description

Simulation File Name

Usage

```
SimFN(output_type, output_folder, suffix)
```

Arguments

output_type	Character string. Output type. Valid values include "data", "fit-dt-var-mx", "fit-meta-var-mx", "fit-ml-var", and "fit-jags".
output_folder	Character string. Output folder.
suffix	Character string. Output of <code>manCTMed::SimSuffix()</code> .

Value

Returns a character string file name with the `output_folder` in the OS-specific format.

SimGenData	<i>Simulation Replication - GenData</i>
------------	---

Description

Simulation Replication - GenData

Usage

```
SimGenData(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimProj

Simulation Project Name

Description

Simulation Project Name

Usage

SimProj()

Value

Returns the project name as a character string.

Author(s)

Ivan Jacob Agaloos Pesigan

Index

- * **Compression Functions**
 - Compress, [2](#)
- * **Data Generation Functions**
 - GenData, [6](#)
- * **Meta-Analysis Functions**
 - FitMetaVAR, [4](#)
- * **Model Fitting Functions**
 - FitDTVAR, [3](#)
 - FitJAGS, [3](#)
 - FitMLVAR, [5](#)
- * **compress**
 - Compress, [2](#)
- * **data**
 - params, [6](#)
- * **fit**
 - FitDTVAR, [3](#)
 - FitJAGS, [3](#)
 - FitMLVAR, [5](#)
 - SimFitDTVAR, [7](#)
 - SimFitJAGS, [8](#)
 - SimFitMetaVAR, [9](#)
 - SimFitMLVAR, [10](#)
- * **gendata**
 - GenData, [6](#)
 - SimGenData, [11](#)
- * **manCTMed**
 - SimFN, [11](#)
- * **manMetaVAR**
 - Compress, [2](#)
 - FitDTVAR, [3](#)
 - FitJAGS, [3](#)
 - FitMetaVAR, [4](#)
 - FitMLVAR, [5](#)
 - GenData, [6](#)
 - Sim, [7](#)
 - SimFitDTVAR, [7](#)
 - SimFitJAGS, [8](#)
 - SimFitMetaVAR, [9](#)
 - SimFitMLVAR, [10](#)
- SimGenData, [11](#)
 - SimProj, [12](#)
- * **meta**
 - FitMetaVAR, [4](#)
- * **parameters**
 - params, [6](#)
- * **simulation**
 - Sim, [7](#)
 - SimFitDTVAR, [7](#)
 - SimFitJAGS, [8](#)
 - SimFitMetaVAR, [9](#)
 - SimFitMLVAR, [10](#)
 - SimFN, [11](#)
 - SimGenData, [11](#)
 - SimProj, [12](#)
- adapt, [4](#)
- Compress, [2](#)
- FitDTVAR, [3, 4, 5](#)
- fitDTVARMx, [3](#)
- FitDTVARMx(), [5](#)
- FitJAGS, [3, 3, 5](#)
- FitMetaVAR, [4](#)
- FitMLVAR, [3, 4, 5](#)
- GenData, [6](#)
- GenData(), [3–5](#)
- metaVAR, [4](#)
- mlVAR, [5](#)
- params, [6](#)
- Sim, [7](#)
- SimFitDTVAR, [7](#)
- SimFitJAGS, [8](#)
- SimFitMetaVAR, [9](#)
- SimFitMLVAR, [10](#)
- SimFN, [11](#)

SimGenData, [11](#)

SimProj, [12](#)

simStateSpace::SimSSMIVary(), [6](#)