

# Package ‘manMetaVAR’

February 25, 2026

**Title** Multivariate Meta-Analysis of Vector Autoregressive Model Coefficients

**Version** 0.9.7

**Description** Research compendium for the manuscript  
Pesigan, I. J. A., et al. (In Preparation).  
Multivariate Meta-Analysis of Vector Autoregressive Model Coefficients.  
<[doi:10.0000/0000000000](https://doi.org/10.0000/0000000000)>.

**URL** <https://github.com/jeksterslab/manMetaVAR>,  
<https://jeksterslab.github.io/manMetaVAR/>,  
<https://osf.io/uenr7/>, <https://doi.org/10.0000/0000000000>

**BugReports** <https://github.com/jeksterslab/manMetaVAR/issues>

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**Depends** R (>= 4.5.0), OpenMx (>= 2.22.10), fitVARMxID (>= 1.0.2),  
metaDyn

**Imports** stats, utils, simStateSpace

**Remotes** jeksterslab/fitVARMxID, jeksterslab/metaDyn

**Suggests** knitr, rmarkdown, testthat

**RoxygenNote** 7.3.3.9000

**NeedsCompilation** no

**Author** Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:  
<<https://orcid.org/0000-0003-4818-8420>>)

**Maintainer** Ivan Jacob Agaloos Pesigan <[r.jeksterslab@gmail.com](mailto:r.jeksterslab@gmail.com)>

## Contents

|                                      |           |
|--------------------------------------|-----------|
| Check . . . . .                      | 2         |
| CheckFitDTVAR . . . . .              | 3         |
| CheckFitMetaVAR . . . . .            | 4         |
| CheckFitMplus . . . . .              | 4         |
| Compress . . . . .                   | 5         |
| FitDTVAR . . . . .                   | 6         |
| FitMetaVAR . . . . .                 | 6         |
| FitMplus . . . . .                   | 7         |
| GenData . . . . .                    | 8         |
| manmetavar-data-methods . . . . .    | 9         |
| manmetavar-dtvar-methods . . . . .   | 10        |
| manmetavar-metavar-methods . . . . . | 12        |
| manmetavar-mplus-methods . . . . .   | 13        |
| model . . . . .                      | 14        |
| MplusInput . . . . .                 | 15        |
| params . . . . .                     | 16        |
| Sim . . . . .                        | 16        |
| SimFitDTVAR . . . . .                | 18        |
| SimFitMetaVAR . . . . .              | 19        |
| SimFitMplus . . . . .                | 20        |
| SimFN . . . . .                      | 21        |
| SimGenData . . . . .                 | 21        |
| SimProj . . . . .                    | 22        |
| Sum . . . . .                        | 22        |
| SumFitMetaVARNormal . . . . .        | 24        |
| SumFitMetaVARRobust . . . . .        | 24        |
| SumFitMplus . . . . .                | 25        |
| SumFitNaive . . . . .                | 26        |
| <b>Index</b>                         | <b>27</b> |

---

Check

*Check Replication*

---

### Description

Check Replication

### Usage

Check(taskid, repid, output\_folder, metavar, mplus)

**Arguments**

|               |                                                                      |
|---------------|----------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                           |
| repid         | Positive integer. Replication ID.                                    |
| output_folder | Character string. Output folder.                                     |
| metavar       | Logical. If metavar = TRUE, fit the model using the metaDyn package. |
| mplus         | Logical. If mplus = TRUE, fit the model using DSEM in Mplus.         |

**Value**

The output is saved as an external file in output\_folder.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

CheckFitDTVAR

*Check Replication - FitDTVAR*

---

**Description**

Check Replication - FitDTVAR

**Usage**

```
CheckFitDTVAR(taskid, repid, output_folder, suffix)
```

**Arguments**

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                        |
| repid         | Positive integer. Replication ID.                                 |
| output_folder | Character string. Output folder.                                  |
| suffix        | Character string. Output of <code>manCTMed:::SimSuffix()</code> . |

**Details**

This function is executed via the Check function.

**Value**

The output is saved as an external file in output\_folder.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

**CheckFitMetaVAR***Check Replication - FitMetaVAR*

---

**Description**

Check Replication - FitMetaVAR

**Usage**

```
CheckFitMetaVAR(taskid, repid, output_folder, suffix)
```

**Arguments**

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                        |
| repid         | Positive integer. Replication ID.                                 |
| output_folder | Character string. Output folder.                                  |
| suffix        | Character string. Output of <code>manCTMed:::SimSuffix()</code> . |

**Details**

This function is executed via the Check function.

**Value**

The output is saved as an external file in `output_folder`.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

**CheckFitMplus***Check Replication - FitMplus*

---

**Description**

Check Replication - FitMplus

**Usage**

```
CheckFitMplus(taskid, repid, output_folder, suffix)
```

**Arguments**

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                        |
| repid         | Positive integer. Replication ID.                                 |
| output_folder | Character string. Output folder.                                  |
| suffix        | Character string. Output of <code>manCTMed:::SimSuffix()</code> . |

**Details**

This function is executed via the Check function.

**Value**

The output is saved as an external file in `output_folder`.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|          |                             |
|----------|-----------------------------|
| Compress | <i>Compress Replication</i> |
|----------|-----------------------------|

---

**Description**

Compress Replication

**Usage**

`Compress(taskid, repid, output_folder)`

**Arguments**

|               |                                   |
|---------------|-----------------------------------|
| taskid        | Positive integer. Task ID.        |
| repid         | Positive integer. Replication ID. |
| output_folder | Character string. Output folder.  |

**Value**

The output is saved as an external file in `output_folder`.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

FitDTVAR

*Fit the Model using the fitVARMxID Package*


---

### Description

The function fits the model using the [fitVARMxID::fitVARMxID](#) package.

### Usage

```
FitDTVAR(data, ncores = NULL, seed = NULL)
```

### Arguments

|        |                                                             |
|--------|-------------------------------------------------------------|
| data   | R object. Output of the <a href="#">GenData()</a> function. |
| ncores | Positive integer. Number of cores to use.                   |
| seed   | Integer. Random seed.                                       |

### See Also

Other Model Fitting Functions: [FitMetaVAR\(\)](#), [FitMplus\(\)](#), [MplusInput\(\)](#)

### Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitDTVAR(data = data, seed = seed)
print(fit)
summary(fit)
coef(fit)
vcov(fit)

## End(Not run)
```

---

FitMetaVAR

*Multivariate Meta-Analysis using the metaDyn Package*


---

### Description

The function performs multivariate meta-analysis using the [metaDyn::metaDyn](#) package.

### Usage

```
FitMetaVAR(fit, ncores = NULL, seed = NULL)
```

**Arguments**

|        |                                                              |
|--------|--------------------------------------------------------------|
| fit    | R object. Output of the <a href="#">FitDTVAR()</a> function. |
| ncores | Positive integer. Number of cores to use.                    |
| seed   | Integer. Random seed.                                        |

**See Also**

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMplus\(\)](#), [MplusInput\(\)](#)

**Examples**

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitDTVAR(data = data, seed = seed)
meta <- FitMetaVAR(fit = fit, seed = seed)
summary(meta)
print(meta)
coef(meta)
vcov(meta)

## End(Not run)
```

---

FitMplus

---

*Fit the Model using Mplus*


---

**Description**

The function fits the model using Mplus.

**Usage**

```
FitMplus(
  data,
  chains = 2L,
  iter = 40000L,
  fscores = NULL,
  plot = FALSE,
  wd = ".",
  mplus_bin = NULL,
  ncores = NULL,
  seed = NULL
)
```

**Arguments**

|           |                                                                                                                    |
|-----------|--------------------------------------------------------------------------------------------------------------------|
| data      | R object. Output of the <a href="#">GenData()</a> function.                                                        |
| chains    | Integer. Number of chains.                                                                                         |
| iter      | Integer. Number of iterations.                                                                                     |
| fscores   | Integer. Number of iterations for factor scores.                                                                   |
| plot      | Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.                                              |
| wd        | Character string. Working directory.                                                                               |
| mplus_bin | Character string. Path to Mplus binary. If mplus_bin = NULL, the function will try to find the appropriate binary. |
| ncores    | Positive integer. Number of cores to use.                                                                          |
| seed      | Integer. Random seed.                                                                                              |

**See Also**

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMetaVAR\(\)](#), [MplusInput\(\)](#)

**Examples**

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitMplus(data = data)
print(fit)
summary(fit)

## End(Not run)
```

---

GenData

*Simulate Data*


---

**Description**

The function simulates data using the [simStateSpace::SimSSMIVary\(\)](#) function.

**Usage**

```
GenData(taskid, seed = NULL)
```

**Arguments**

|        |                            |
|--------|----------------------------|
| taskid | Positive integer. Task ID. |
| seed   | Integer. Random seed.      |



## Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
print(data)
summary(data)
plot(data)

## End(Not run)
```

---

manmetavar-data-methods

*Methods for Objects of Class manmetavar.data*

---

## Description

This page documents the available methods for objects of class `manmetavar.data`.

## Usage

```
## S3 method for class 'manmetavar.data'
print(x, ...)

## S3 method for class 'manmetavar.data'
summary(object, ...)

## S3 method for class 'manmetavar.data'
plot(x, ...)
```

## Arguments

|                     |                                                |
|---------------------|------------------------------------------------|
| <code>x</code>      | Object of class <code>manmetavar.data</code> . |
| <code>...</code>    | additional arguments.                          |
| <code>object</code> | Object of class <code>manmetavar.data</code> . |

## Author(s)

Ivan Jacob Agaloos Pesigan

---

manmetavar-dtvar-methods

*Methods for Objects of Class manmetavar.dtvar*

---

## Description

This page documents the available methods for objects of class `manmetavar.dtvar`.

## Usage

```
## S3 method for class 'manmetavar.dtvar'
coef(
  object,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  ncores = NULL,
  ...
)
```

```
## S3 method for class 'manmetavar.dtvar'
vcov(
  object,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  robust = FALSE,
  ncores = NULL,
  ...
)
```

```
## S3 method for class 'manmetavar.dtvar'
print(
  x,
  means = FALSE,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
```

```

    digits = 4,
    ncores = NULL,
    ...
)

## S3 method for class 'manmetavar.dtvar'
summary(
  object,
  means = FALSE,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  digits = 4,
  ncores = NULL,
  ...
)
```

### Arguments

|                     |                                                                                                                                                                                               |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code> | Object of class <code>manmetavar.dtvar</code> .                                                                                                                                               |
| <code>mu</code>     | Logical. If <code>mu = TRUE</code> , include estimates of the <code>mu</code> vector, if available. If <code>mu = FALSE</code> , exclude estimates of the <code>mu</code> vector.             |
| <code>alpha</code>  | Logical. If <code>alpha = TRUE</code> , include estimates of the <code>alpha</code> vector, if available. If <code>alpha = FALSE</code> , exclude estimates of the <code>alpha</code> vector. |
| <code>beta</code>   | Logical. If <code>beta = TRUE</code> , include estimates of the <code>beta</code> matrix, if available. If <code>beta = FALSE</code> , exclude estimates of the <code>beta</code> matrix.     |
| <code>nu</code>     | Logical. If <code>nu = TRUE</code> , include estimates of the <code>nu</code> vector, if available. If <code>nu = FALSE</code> , exclude estimates of the <code>nu</code> vector.             |
| <code>psi</code>    | Logical. If <code>psi = TRUE</code> , include estimates of the <code>psi</code> matrix, if available. If <code>psi = FALSE</code> , exclude estimates of the <code>psi</code> matrix.         |
| <code>theta</code>  | Logical. If <code>theta = TRUE</code> , include estimates of the <code>theta</code> matrix, if available. If <code>theta = FALSE</code> , exclude estimates of the <code>theta</code> matrix. |
| <code>ncores</code> | Positive integer. Number of cores to use.                                                                                                                                                     |
| <code>...</code>    | additional arguments.                                                                                                                                                                         |
| <code>robust</code> | Logical. If <code>TRUE</code> , use robust (sandwich) sampling variance-covariance matrix. If <code>FALSE</code> , use normal theory sampling variance-covariance matrix.                     |
| <code>x</code>      | Object of class <code>manmetavar.dtvar</code> .                                                                                                                                               |
| <code>means</code>  | Logical. If <code>means = TRUE</code> , return means. Otherwise, the function returns raw estimates.                                                                                          |
| <code>digits</code> | Integer indicating the number of decimal places to display.                                                                                                                                   |

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

manmetavar-metavar-methods*Methods for Objects of Class manmetavar.metavar*

---

**Description**

This page documents the available methods for objects of class `manmetavar.metavar`.

**Usage**

```
## S3 method for class 'manmetavar.metavar'
coef(object, ...)

## S3 method for class 'manmetavar.metavar'
vcov(object, robust = NULL, ...)

## S3 method for class 'manmetavar.metavar'
print(x, alpha = NULL, robust = NULL, digits = 4, ...)

## S3 method for class 'manmetavar.metavar'
summary(object, alpha = NULL, robust = NULL, digits = 4, ...)

## S3 method for class 'manmetavar.metavar'
confint(object, parm = NULL, level = 0.95, robust = NULL, ...)
```

**Arguments**

|                     |                                                                                                                                                                                                                                |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code> | Object of class <code>manmetavar.metavar</code> .                                                                                                                                                                              |
| <code>...</code>    | additional arguments.                                                                                                                                                                                                          |
| <code>robust</code> | Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix. If NULL, the function will check object if robust standard errors are available. |
| <code>x</code>      | Object of class <code>manmetavar.metavar</code> .                                                                                                                                                                              |
| <code>alpha</code>  | Numeric vector. Significance level $\alpha$ .                                                                                                                                                                                  |
| <code>digits</code> | Integer indicating the number of decimal places to display.                                                                                                                                                                    |
| <code>parm</code>   | a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.                                                          |
| <code>level</code>  | the confidence level required.                                                                                                                                                                                                 |

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

manmetavar-mplus-methods

*Methods for Objects of Class manmetavar.mplus*


---

## Description

This page documents the available methods for objects of class `manmetavar.mplus`.

## Usage

```
## S3 method for class 'manmetavar.mplus'
coef(object, median = TRUE, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
vcov(object, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
summary(object, alpha = 0.05, median = TRUE, digits = 4, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
confint(object, parm = NULL, level = 0.95, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
plot(
  x,
  what = "posterior",
  parm = NULL,
  level = 0.95,
  burnin = NULL,
  legend_loc = "topright",
  ...
)
```

## Arguments

|                     |                                                                                                                                                                       |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code> | Object of class <code>manmetavar.mplus</code> .                                                                                                                       |
| <code>median</code> | Logical. If <code>median = TRUE</code> , return median of the posterior. If <code>median = FALSE</code> , return mean of the posterior.                               |
| <code>burnin</code> | Integer indicating initial samples to discard. If <code>burnin = NULL</code> , do not discard anything.                                                               |
| <code>...</code>    | additional arguments.                                                                                                                                                 |
| <code>alpha</code>  | Numeric vector. Significance level $\alpha$ .                                                                                                                         |
| <code>digits</code> | Integer indicating the number of decimal places to display.                                                                                                           |
| <code>parm</code>   | a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered. |

|            |                                                                                                                                                  |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| level      | the confidence level required.                                                                                                                   |
| x          | Object of class <code>manmetavar.mplus</code> .                                                                                                  |
| what       | Character string. If <code>what = "posterior"</code> , return posterior distribution plots. If <code>what = "trace"</code> , return trace plots. |
| legend_loc | Character string. Legend location.                                                                                                               |

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|       |                         |
|-------|-------------------------|
| model | <i>Model Parameters</i> |
|-------|-------------------------|

---

**Description**

Model Parameters

**Usage**

```
data(model)
```

**Format**

A list with 15 elements:

**k** Number of variables.

**mu\_mu** Mean of the set-point vector  $\mu$ .

**mu\_sigma** Covariance matrix of the parameter  $\mu$ .

**mu\_sigma\_l** Cholesky factor of the covariance matrix of the parameter  $\mu$ .

**beta\_mu** Mean of lagged coefficients matrix  $\beta$ .

**beta\_sigma** Covariance matrix of the parameter  $\text{vec}(\beta)$ .

**beta\_sigma\_l** Cholesky factor of the covariance matrix of the parameter  $\text{vec}(\beta)$ .

**psi** Process noise covariance matrix  $\Psi$ .

**psi\_l** Cholesky factor of the process noise covariance matrix  $\Psi$ .

**psi\_d\_ldl** uc\_d of the LDL' decomposition of the process noise covariance matrix  $\Psi$ . See [fitVARMxID::LDL\(\)](#).

**psi\_l\_ldl** s\_l of the LDL' decomposition of the process noise covariance matrix  $\Psi$ . See [fitVARMxID::LDL\(\)](#).

**ma\_fixed** Vector of fixed effects  $\theta = [\mu, \text{vec}(\beta)]'$

**ma\_random** Matrix of random effects  $\theta = [\mu, \text{vec}(\beta)]'$

**ma\_random\_d\_ldl** uc\_d of the LDL' decomposition of the random effects. See [fitVARMxID::LDL\(\)](#).

**ma\_random\_l\_ldl** s\_l of the LDL' decomposition of the random effects. See [fitVARMxID::LDL\(\)](#).

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

MplusInput

Create Mplus Input File

---

### Description

The function creates an Mplus input file.

### Usage

```
MplusInput(
  fn_data,
  fn_posterior,
  fn_factorscores,
  chains,
  iter,
  fscores,
  plot,
  ncores = NULL,
  seed = NULL
)
```

### Arguments

|                 |                                                                       |
|-----------------|-----------------------------------------------------------------------|
| fn_data         | Character string. Filename for data file.                             |
| fn_posterior    | Character string. Filename for posterior output.                      |
| fn_factorscores | Character string. Filename for factor scores output.                  |
| chains          | Integer. Number of chains.                                            |
| iter            | Integer. Number of iterations.                                        |
| fscores         | Integer. Number of iterations for factor scores.                      |
| plot            | Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file. |
| ncores          | Positive integer. Number of cores to use.                             |
| seed            | Integer. Random seed.                                                 |

### See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMetaVAR\(\)](#), [FitMplus\(\)](#)

### Examples

```
cat(
  MplusInput(
    fn_data = "data.dat",
    fn_posterior = "posterior.dat",
    fn_factorscores = "factorscores.dat",
```

```
    chains = 2L,  
    iter = 40000L,  
    fscores = 1000L,  
    plot = TRUE,  
    ncores = NULL,  
    seed = 42  
  )  
)
```

---

|        |                              |
|--------|------------------------------|
| params | <i>Simulation Parameters</i> |
|--------|------------------------------|

---

**Description**

Simulation Parameters

**Usage**

data(params)

**Format**

A dataframe with 9 rows and 3 columns:

- taskid** Simulation Task ID.
- n** Sample size.
- time** Number of measurement occassions.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|     |                               |
|-----|-------------------------------|
| Sim | <i>Simulation Replication</i> |
|-----|-------------------------------|

---

**Description**

Simulation Replication



**Usage**

```
Sim(  
  taskid,  
  repid,  
  output_folder,  
  overwrite,  
  integrity,  
  seed,  
  data,  
  metavar,  
  mplus,  
  chains,  
  iter,  
  fscores,  
  plot  
)
```

**Arguments**

|               |                                                                                           |
|---------------|-------------------------------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                                                |
| repid         | Positive integer. Replication ID.                                                         |
| output_folder | Character string. Output folder.                                                          |
| overwrite     | Logical. Overwrite existing output in output_folder.                                      |
| integrity     | Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE. |
| seed          | Integer. Random seed.                                                                     |
| data          | Logical. Simulate data.                                                                   |
| metavar       | Logical. If metavar = TRUE, fit the model using the metaDyn package.                      |
| mplus         | Logical. If mplus = TRUE, fit the model using DSEM in Mplus.                              |
| chains        | Integer. Number of chains.                                                                |
| iter          | Integer. Number of iterations.                                                            |
| fscores       | Integer. Number of iterations for factor scores.                                          |
| plot          | Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.                     |

**Value**

The output is saved as an external file in output\_folder.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

SimFitDTVAR

*Simulation Replication - FitDTVAR*


---

## Description

Simulation Replication - FitDTVAR

## Usage

```
SimFitDTVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

## Arguments

|               |                                                                                                                       |
|---------------|-----------------------------------------------------------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                                                                            |
| repid         | Positive integer. Replication ID.                                                                                     |
| output_folder | Character string. Output folder.                                                                                      |
| seed          | Integer. Random seed.                                                                                                 |
| suffix        | Character string. Output of <code>manCTMed:::SimSuffix()</code> .                                                     |
| overwrite     | Logical. Overwrite existing output in <code>output_folder</code> .                                                    |
| integrity     | Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> . |

## Details

This function is executed via the `Sim` function.

## Value

The output is saved as an external file in `output_folder`.

## Author(s)

Ivan Jacob Agaloos Pesigan

---

|               |                                            |
|---------------|--------------------------------------------|
| SimFitMetaVAR | <i>Simulation Replication - FitMetaVAR</i> |
|---------------|--------------------------------------------|

---

**Description**

Simulation Replication - FitMetaVAR

**Usage**

```
SimFitMetaVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

**Arguments**

|               |                                                                                                                       |
|---------------|-----------------------------------------------------------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                                                                            |
| repid         | Positive integer. Replication ID.                                                                                     |
| output_folder | Character string. Output folder.                                                                                      |
| seed          | Integer. Random seed.                                                                                                 |
| suffix        | Character string. Output of <code>manCTMed:::SimSuffix()</code> .                                                     |
| overwrite     | Logical. Overwrite existing output in <code>output_folder</code> .                                                    |
| integrity     | Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> . |

**Details**

This function is executed via the `Sim` function.

**Value**

The output is saved as an external file in `output_folder`.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

SimFitMplus

---

*Simulation Replication - FitMplus*


---

## Description

Simulation Replication - FitMplus

## Usage

```
SimFitMplus(
  taskid,
  repid,
  output_folder,
  seed,
  suffix,
  overwrite,
  integrity,
  chains,
  iter,
  fscores,
  plot
)
```

## Arguments

|               |                                                                                                                       |
|---------------|-----------------------------------------------------------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                                                                            |
| repid         | Positive integer. Replication ID.                                                                                     |
| output_folder | Character string. Output folder.                                                                                      |
| seed          | Integer. Random seed.                                                                                                 |
| suffix        | Character string. Output of <code>manCTMed:::SimSuffix()</code> .                                                     |
| overwrite     | Logical. Overwrite existing output in <code>output_folder</code> .                                                    |
| integrity     | Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> . |
| chains        | Integer. Number of chains.                                                                                            |
| iter          | Integer. Number of iterations.                                                                                        |
| fscores       | Integer. Number of iterations for factor scores.                                                                      |
| plot          | Logical. If <code>plot = TRUE</code> , add <code>PLOT: TYPE = PLOT3;</code> to Mplus input file.                      |

## Details

This function is executed via the `Sim` function.

## Value

The output is saved as an external file in `output_folder`.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|       |                             |
|-------|-----------------------------|
| SimFN | <i>Simulation File Name</i> |
|-------|-----------------------------|

---

**Description**

Simulation File Name

**Usage**

SimFN(output\_type, output\_folder, suffix)

**Arguments**

|               |                                                                                                                  |
|---------------|------------------------------------------------------------------------------------------------------------------|
| output_type   | Character string. Output type. Valid values include "data", "fit-dt-var-mx", "fit-meta-var-mx", and "fit-mplus". |
| output_folder | Character string. Output folder.                                                                                 |
| suffix        | Character string. Output of manCTMed:::SimSuffix().                                                              |

**Value**

Returns a character string file name with the output\_folder in the OS-specific format.

---

|            |                                         |
|------------|-----------------------------------------|
| SimGenData | <i>Simulation Replication - GenData</i> |
|------------|-----------------------------------------|

---

**Description**

Simulation Replication - GenData

**Usage**

SimGenData(taskid, repid, output\_folder, seed, suffix, overwrite, integrity)

**Arguments**

|               |                                                                                           |
|---------------|-------------------------------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                                                |
| repid         | Positive integer. Replication ID.                                                         |
| output_folder | Character string. Output folder.                                                          |
| seed          | Integer. Random seed.                                                                     |
| suffix        | Character string. Output of manCTMed:::SimSuffix().                                       |
| overwrite     | Logical. Overwrite existing output in output_folder.                                      |
| integrity     | Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE. |

**Details**

This function is executed via the Sim function.

**Value**

The output is saved as an external file in output\_folder.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

SimProj

*Simulation Project Name*

---

**Description**

Simulation Project Name

**Usage**

SimProj()

**Value**

Returns the project name as a character string.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

Sum

*Summary*

---

**Description**

Summary

**Usage**

```
Sum(  
  taskid,  
  reps,  
  output_folder,  
  overwrite,  
  integrity,  
  metavar_normal,  
  metavar_robust,  
  naive,  
  mplus,  
  ncores  
)
```

**Arguments**

|                |                                                                                                          |
|----------------|----------------------------------------------------------------------------------------------------------|
| taskid         | Positive integer. Task ID.                                                                               |
| reps           | Positive integer. Number of replications.                                                                |
| output_folder  | Character string. Output folder.                                                                         |
| overwrite      | Logical. Overwrite existing output in output_folder.                                                     |
| integrity      | Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.                |
| metavar_normal | Logical. If metavar_normal = TRUE, summarize metaVAR model using normal confidence intervals.            |
| metavar_robust | Logical. If metavar_robust = TRUE, summarize metaVAR model using robust (sandwich) confidence intervals. |
| naive          | Logical. If naive = TRUE, summarize naive estimates.                                                     |
| mplus          | Logical. If mplus = TRUE, summarize the DSEM model.                                                      |
| ncores         | Positive integer. Number of cores to use.                                                                |

**Value**

The output is saved as an external file in output\_folder.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|                     |                                            |
|---------------------|--------------------------------------------|
| SumFitMetaVARNormal | <i>Summary: Normal Theory (FitMetaVAR)</i> |
|---------------------|--------------------------------------------|

---

**Description**

Summary: Normal Theory (FitMetaVAR)

**Usage**

```
SumFitMetaVARNormal(taskid, reps, output_folder, overwrite, integrity, ncores)
```

**Arguments**

|               |                                                                                           |
|---------------|-------------------------------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                                                |
| reps          | Positive integer. Number of replications.                                                 |
| output_folder | Character string. Output folder.                                                          |
| overwrite     | Logical. Overwrite existing output in output_folder.                                      |
| integrity     | Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE. |
| ncores        | Positive integer. Number of cores to use.                                                 |

**Details**

This function is executed via the Sum function.

**Value**

The output is saved as an external file in output\_folder.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|                     |                                     |
|---------------------|-------------------------------------|
| SumFitMetaVARRobust | <i>Summary: Robust (FitMetaVAR)</i> |
|---------------------|-------------------------------------|

---

**Description**

Summary: Robust (FitMetaVAR)

**Usage**

```
SumFitMetaVARRobust(taskid, reps, output_folder, overwrite, integrity, ncores)
```



**Arguments**

|               |                                                                                           |
|---------------|-------------------------------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                                                |
| reps          | Positive integer. Number of replications.                                                 |
| output_folder | Character string. Output folder.                                                          |
| overwrite     | Logical. Overwrite existing output in output_folder.                                      |
| integrity     | Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE. |
| ncores        | Positive integer. Number of cores to use.                                                 |

**Details**

This function is executed via the Sum function.

**Value**

The output is saved as an external file in output\_folder.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|             |                           |
|-------------|---------------------------|
| SumFitMplus | <i>Summary (FitMplus)</i> |
|-------------|---------------------------|

---

**Description**

Summary (FitMplus)

**Usage**

SumFitMplus(taskid, reps, output\_folder, overwrite, integrity, ncores)

**Arguments**

|               |                                                                                           |
|---------------|-------------------------------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                                                |
| reps          | Positive integer. Number of replications.                                                 |
| output_folder | Character string. Output folder.                                                          |
| overwrite     | Logical. Overwrite existing output in output_folder.                                      |
| integrity     | Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE. |
| ncores        | Positive integer. Number of cores to use.                                                 |

**Details**

This function is executed via the Sum function.

**Value**

The output is saved as an external file in output\_folder.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

SumFitNaive

*Summary: Naive (FitMetaVAR)*

---

**Description**

Summary: Naive (FitMetaVAR)

**Usage**

```
SumFitNaive(taskid, reps, output_folder, overwrite, integrity, ncores)
```

**Arguments**

|               |                                                                                           |
|---------------|-------------------------------------------------------------------------------------------|
| taskid        | Positive integer. Task ID.                                                                |
| reps          | Positive integer. Number of replications.                                                 |
| output_folder | Character string. Output folder.                                                          |
| overwrite     | Logical. Overwrite existing output in output_folder.                                      |
| integrity     | Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE. |
| ncores        | Positive integer. Number of cores to use.                                                 |

**Details**

This function is executed via the Sum function.

**Value**

The output is saved as an external file in output\_folder.

**Author(s)**

Ivan Jacob Agaloos Pesigan

# Index

- \* **Compression Functions**
  - Compress, [5](#)
- \* **Data Generation Functions**
  - GenData, [8](#)
- \* **Model Fitting Functions**
  - FitDTVAR, [6](#)
  - FitMetaVAR, [6](#)
  - FitMplus, [7](#)
  - MplusInput, [15](#)
- \* **check**
  - Check, [2](#)
  - CheckFitDTVAR, [3](#)
  - CheckFitMetaVAR, [4](#)
  - CheckFitMplus, [4](#)
- \* **compress**
  - Compress, [5](#)
- \* **data**
  - model, [14](#)
  - params, [16](#)
- \* **fit**
  - FitDTVAR, [6](#)
  - FitMplus, [7](#)
  - MplusInput, [15](#)
  - SimFitDTVAR, [18](#)
  - SimFitMetaVAR, [19](#)
  - SimFitMplus, [20](#)
- \* **gendata**
  - GenData, [8](#)
  - SimGenData, [21](#)
- \* **manCTMed**
  - SimFN, [21](#)
- \* **manMetaVAR**
  - Check, [2](#)
  - CheckFitDTVAR, [3](#)
  - CheckFitMetaVAR, [4](#)
  - CheckFitMplus, [4](#)
  - Compress, [5](#)
  - FitDTVAR, [6](#)
  - FitMetaVAR, [6](#)

- FitMplus, [7](#)
- GenData, [8](#)
- MplusInput, [15](#)
- Sim, [16](#)
- SimFitDTVAR, [18](#)
- SimFitMetaVAR, [19](#)
- SimFitMplus, [20](#)
- SimGenData, [21](#)
- SimProj, [22](#)
- Sum, [22](#)
- SumFitMetaVARNormal, [24](#)
- SumFitMetaVARRobust, [24](#)
- SumFitMplus, [25](#)
- SumFitNaive, [26](#)

- \* **meta**
  - FitMetaVAR, [6](#)
- \* **methods**
  - manmetavar-data-methods, [9](#)
  - manmetavar-dtvar-methods, [10](#)
  - manmetavar-metavar-methods, [12](#)
  - manmetavar-mplus-methods, [13](#)
- \* **parameters**
  - model, [14](#)
  - params, [16](#)
- \* **simulation**
  - Check, [2](#)
  - CheckFitDTVAR, [3](#)
  - CheckFitMetaVAR, [4](#)
  - CheckFitMplus, [4](#)
  - Sim, [16](#)
  - SimFitDTVAR, [18](#)
  - SimFitMetaVAR, [19](#)
  - SimFitMplus, [20](#)
  - SimFN, [21](#)
  - SimGenData, [21](#)
  - SimProj, [22](#)
  - Sum, [22](#)
  - SumFitMetaVARNormal, [24](#)
  - SumFitMetaVARRobust, [24](#)

- SumFitMplus, 25
- SumFitNaive, 26
- \* **summary**
  - Sum, 22
  - SumFitMetaVARNormal, 24
  - SumFitMetaVARRobust, 24
  - SumFitMplus, 25
  - SumFitNaive, 26
- Check, 2
- CheckFitDTVAR, 3
- CheckFitMetaVAR, 4
- CheckFitMplus, 4
- coef.manmetavar.dtvvar
  - (manmetavar-dtvvar-methods), 10
- coef.manmetavar.metavar
  - (manmetavar-metavar-methods), 12
- coef.manmetavar.mplus
  - (manmetavar-mplus-methods), 13
- Compress, 5
- confint.manmetavar.metavar
  - (manmetavar-metavar-methods), 12
- confint.manmetavar.mplus
  - (manmetavar-mplus-methods), 13
- FitDTVAR, 6, 7, 8, 15
- FitDTVAR(), 7
- FitMetaVAR, 6, 6, 8, 15
- FitMplus, 6, 7, 7, 15
- fitVARMxID::fitVARMxID, 6
- fitVARMxID::LDL(), 14
- GenData, 8
- GenData(), 6, 8
- manmetavar-data-methods, 9
- manmetavar-dtvvar-methods, 10
- manmetavar-metavar-methods, 12
- manmetavar-mplus-methods, 13
- metaDyn::metaDyn, 6
- model, 14
- MplusInput, 6–8, 15
- params, 16
- plot.manmetavar.data
  - (manmetavar-data-methods), 9
- plot.manmetavar.mplus
  - (manmetavar-mplus-methods), 13
- print.manmetavar.data
  - (manmetavar-data-methods), 9
- print.manmetavar.dtvvar
  - (manmetavar-dtvvar-methods), 10
- print.manmetavar.metavar
  - (manmetavar-metavar-methods), 12
- Sim, 16
- SimFitDTVAR, 18
- SimFitMetaVAR, 19
- SimFitMplus, 20
- SimFN, 21
- SimGenData, 21
- SimProj, 22
- simStateSpace::SimSSMIVary(), 8
- Sum, 22
- SumFitMetaVARNormal, 24
- SumFitMetaVARRobust, 24
- SumFitMplus, 25
- SumFitNaive, 26
- summary.manmetavar.data
  - (manmetavar-data-methods), 9
- summary.manmetavar.dtvvar
  - (manmetavar-dtvvar-methods), 10
- summary.manmetavar.metavar
  - (manmetavar-metavar-methods), 12
- summary.manmetavar.mplus
  - (manmetavar-mplus-methods), 13
- vcov.manmetavar.dtvvar
  - (manmetavar-dtvvar-methods), 10
- vcov.manmetavar.metavar
  - (manmetavar-metavar-methods), 12
- vcov.manmetavar.mplus
  - (manmetavar-mplus-methods), 13