

Package ‘manMetaVAR’

November 11, 2025

Title Multivariate Meta-Analysis of Vector Autoregressive Model
Coefficients

Version 0.9.5

Description Research compendium for the manuscript
Pesigan, I. J. A., et al. (In Preparation).
Multivariate Meta-Analysis of Vector Autoregressive Model Coefficients.
<doi:10.0000/0000000000>.

URL <https://github.com/jeksterslab/manMetaVAR>,
<https://jeksterslab.github.io/manMetaVAR/>,
<https://osf.io/uenr7/>, <https://doi.org/10.0000/0000000000>

BugReports <https://github.com/jeksterslab/manMetaVAR/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

Depends R (>= 4.0.0), OpenMx, fitDTVARMxID, metaVAR

Imports stats, utils, simStateSpace, mlVAR, ggplot2

Remotes jeksterslab/fitDTVARMxID, jeksterslab/metaVAR

Suggests knitr, rmarkdown, testthat

RoxygenNote 7.3.3.9000

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0003-4818-8420>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

Compress	2
Dynamics	3

FigBias	4
FigCoverage	5
FigPower	5
FigRMSE	6
FitDTVVAR	7
FitMetaVAR	8
FitMLVAR	9
FitMplus	9
GenData	11
manmetavar-data-methods	11
manmetavar-dtvar-methods	12
manmetavar-metavar-methods	14
manmetavar-mlvar-methods	15
manmetavar-mplus-methods	16
MplusInput	17
params	19
Sim	19
SimFitDTVVAR	20
SimFitMetaVAR	21
SimFitMLVAR	22
SimFitMplus	23
SimFN	24
SimGenData	24
SimProj	25
Sum	26
SumFitMetaVARLB	26
SumFitMetaVARNormal	27
SumFitMLVAR	28
SumFitMplus	29
Index	30

Compress

Compress Replication

Description

Compress Replication

Usage

Compress(taskid, repid, output_folder)

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

Dynamics

Process Dynamics

Description

Process Dynamics

Usage

```
Dynamics(dynamics)
```

Arguments

dynamics 1, 2, or 3. 1 for stable reciprocal regulation, 2 for escalating co-activation, and 3 for adaptive recovery.

See Also

Other Data Generation Functions: [GenData\(\)](#)

Examples

```
# stable reciprocal regulation,  
Dynamics(dynamics = 1)  
# escalating co-activation  
Dynamics(dynamics = 2)  
# adaptive recovery  
Dynamics(dynamics = 3)
```

FigBias

*Plot Relative Bias***Description**

Plot relative bias for the fixed and random effects.

Usage

```
FigBias(results, bias = TRUE, dynamics)
```

Arguments

results	results data frame.
bias	Logical. If bias = TRUE, plot absolute bias. If bias = FALSE, plot relative bias. Note that when parameter value is equal to zero, absolute bias is used instead of relative bias.
dynamics	1, 2, or 3. 1 for stable reciprocal regulation, 2 for escalating co-activation, and 3 for adaptive recovery.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Figure Functions: [FigCoverage\(\)](#), [FigPower\(\)](#), [FigRMSE\(\)](#)

Examples

```
## Not run:
data(results, package = "manMetaVAR")
FigBias(results, dynamics = 1)

## End(Not run)
```

FigCoverage*Plot Coverage Probabilities*

Description

Plot coverage probabilities for the fixed and random effects.

Usage

```
FigCoverage(results, dynamics)
```

Arguments

results	results data frame.
dynamics	1, 2, or 3. 1 for stable reciprocal regulation, 2 for escalating co-activation, and 3 for adaptive recovery.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Figure Functions: [FigBias\(\)](#), [FigPower\(\)](#), [FigRMSE\(\)](#)

Examples

```
## Not run:  
data(results, package = "manMetaVAR")  
FigCoverage(results, dynamics = 1)  
  
## End(Not run)
```

FigPower*Plot Statistical Power*

Description

Plot statistical power probabilities for the fixed and random effects.

Usage

```
FigPower(results, dynamics)
```

Arguments

results	results data frame.
dynamics	1, 2, or 3. 1 for stable reciprocal regulation, 2 for escalating co-activation, and 3 for adaptive recovery.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Figure Functions: [FigBias\(\)](#), [FigCoverage\(\)](#), [FigRMSE\(\)](#)

Examples

```
## Not run:
data(results, package = "manMetaVAR")
FigPower(results, dynamics = 1)

## End(Not run)
```

FigRMSE

Plot RMSE

Description

Plot RMSE for the fixed and random effects.

Usage

```
FigRMSE(results, dynamics)
```

Arguments

results	results data frame.
dynamics	1, 2, or 3. 1 for stable reciprocal regulation, 2 for escalating co-activation, and 3 for adaptive recovery.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Figure Functions: [FigBias\(\)](#), [FigCoverage\(\)](#), [FigPower\(\)](#)

Examples

```
## Not run:
data(results, package = "manMetaVAR")
FigRMSE(results, dynamics = 1)

## End(Not run)
```

FitDTVAR*Fit the Model using the fitDTVARMxID Package*

Description

The function fits the model using the [fitDTVARMxID::fitDTVARMxID](#) package.

Usage

```
FitDTVAR(data, ncores = NULL, seed = NULL)
```

Arguments

data	R object. Output of the GenData() function.
ncores	Positive integer. Number of cores to use.
seed	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitMLVAR\(\)](#), [FitMetaVAR\(\)](#), [FitMplus\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
set.seed(42)
data <- GenData(taskid = 1)
fit <- FitDTVAR(
  data = data,
  ncores = parallel::detectCores()
)
print(fit)
summary(fit)
coef(fit)
vcov(fit)

## End(Not run)
```

Description

The function performs multivariate meta-analysis using the [metaVAR::metaVAR](#) package.

Usage

```
FitMetaVAR(fit, ncores = NULL)
```

Arguments

<code>fit</code>	R object. Output of the FitDTVAR() function.
<code>ncores</code>	Positive integer. Number of cores to use.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMLVAR\(\)](#), [FitMplus\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
set.seed(42)
data <- GenData(taskid = 1)
fit <- FitDTVAR(
  data = data,
  ncores = parallel::detectCores()
)
pooled <- FitMetaVAR(
  fit = fit,
  ncores = parallel::detectCores()
)
summary(pooled)
print(pooled)
coef(pooled)
vcov(pooled)

## End(Not run)
```

FitMLVAR*Fit the Model using the mlVAR Package*

Description

The function fits the model using the [mlVAR::mlVAR](#) package.

Usage

```
FitMLVAR(data, ncores = NULL)
```

Arguments

data	R object. Output of the GenData() function.
ncores	Positive integer. Number of cores to use.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMetaVAR\(\)](#), [FitMplus\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:  
set.seed(42)  
data <- GenData(taskid = 1)  
fit <- FitMLVAR(data = data)  
print(fit)  
summary(fit)  
  
## End(Not run)
```

FitMplus*Fit the Model using Mplus*

Description

The function fits the model using Mplus.

Usage

```
FitMplus(
  data,
  chains = 2L,
  iter = 120000L,
  fscores = NULL,
  plot = FALSE,
  default_priors = TRUE,
  wd = ".",
  mplus_bin = NULL,
  ncores = NULL
)
```

Arguments

<code>data</code>	R object. Output of the GenData() function.
<code>chains</code>	Integer. Number of chains.
<code>iter</code>	Integer. Number of iterations.
<code>fscores</code>	Integer. Number of iterations for factor scores.
<code>plot</code>	Logical. If <code>plot = TRUE</code> , add <code>PLOT: TYPE = PLOT3;</code> to Mplus input file.
<code>default_priors</code>	Logical. If <code>default_priors = TRUE</code> , use default priors.
<code>wd</code>	Character string. Working directory.
<code>mplus_bin</code>	Character string. Path to Mplus binary. If <code>mplus_bin = NULL</code> , the function will try to find the appropriate binary.
<code>ncores</code>	Positive integer. Number of cores to use.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMLVAR\(\)](#), [FitMetaVAR\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
set.seed(42)
data <- GenData(taskid = 1)
fit <- FitMplus(data = data)
print(fit)
summary(fit)

## End(Not run)
```

`GenData`*Simulate Data*

Description

The function simulates data using the `simStateSpace::SimSSMIVary()` function.

Usage

```
GenData(taskid)
```

Arguments

`taskid` Positive integer. Task ID.

See Also

Other Data Generation Functions: [Dynamics\(\)](#)

Examples

```
set.seed(42)
data <- GenData(taskid = 1)
print(data)
summary(data)
plot(data)
```

`manmetavar-data-methods`*Methods for Objects of Class `manmetavar.data`*

Description

This page documents the available methods for objects of class `manmetavar.data`.

Usage

```
## S3 method for class 'manmetavar.data'
print(x, ...)

## S3 method for class 'manmetavar.data'
summary(object, ...)

## S3 method for class 'manmetavar.data'
plot(x, ...)
```

Arguments

x	Object of class <code>manmetavar.data</code> .
...	additional arguments.
object	Object of class <code>manmetavar.data</code> .

Author(s)

Ivan Jacob Agaloos Pesigan

manmetavar-dtvar-methods

Methods for Objects of Class `manmetavar.dtvvar`

Description

This page documents the available methods for objects of class `manmetavar.dtvvar`.

Usage

```
## S3 method for class 'manmetavar.dtvvar'
coef(
  object,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  converged = TRUE,
  grad_tol = 0.01,
  hess_tol = 1e-08,
  vanishing_theta = TRUE,
  theta_tol = 0.001,
  ...
)
```

```
## S3 method for class 'manmetavar.dtvvar'
vcov(
  object,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  converged = TRUE,
  grad_tol = 0.01,
  hess_tol = 1e-08,
```

```

    vanishing_theta = TRUE,
    theta_tol = 0.001,
    ...
)

## S3 method for class 'manmetavar.dtvar'
print(
  x,
  means = FALSE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  converged = TRUE,
  grad_tol = 0.01,
  hess_tol = 1e-08,
  vanishing_theta = TRUE,
  theta_tol = 0.001,
  digits = 4,
  ...
)

## S3 method for class 'manmetavar.dtvar'
summary(
  object,
  means = FALSE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  converged = TRUE,
  grad_tol = 0.01,
  hess_tol = 1e-08,
  vanishing_theta = TRUE,
  theta_tol = 0.001,
  digits = 4,
  ...
)

```

Arguments

object	Object of class <code>manmetavar.dtvar</code> .
alpha	Logical. If <code>alpha = TRUE</code> , include estimates of the alpha vector, if available. If <code>alpha = FALSE</code> , exclude estimates of the alpha vector.
beta	Logical. If <code>beta = TRUE</code> , include estimates of the beta matrix, if available. If <code>beta = FALSE</code> , exclude estimates of the beta matrix.

nu	Logical. If nu = TRUE, include estimates of the nu vector, if available. If nu = FALSE, exclude estimates of the nu vector.
psi	Logical. If psi = TRUE, include estimates of the psi matrix, if available. If psi = FALSE, exclude estimates of the psi matrix.
theta	Logical. If theta = TRUE, include estimates of the theta matrix, if available. If theta = FALSE, exclude estimates of the theta matrix.
converged	Logical. Only include converged cases.
grad_tol	Numeric scalar. Tolerance for the maximum absolute gradient if converged = TRUE.
hess_tol	Numeric scalar. Tolerance for Hessian eigenvalues; eigenvalues must be strictly greater than this value if converged = TRUE.
vanishing_theta	Logical. Test for measurement error variance going to zero if converged = TRUE.
theta_tol	Numeric. Tolerance for vanishing theta test if converged and theta_tol are TRUE.
...	additional arguments.
x	Object of class manmetavar.dtvvar.
means	Logical. If means = TRUE, return means. Otherwise, the function returns raw estimates.
digits	Integer indicating the number of decimal places to display.

Author(s)

Ivan Jacob Agaloos Pesigan

manmetavar-metavar-methods

Methods for Objects of Class manmetavar.metavar

Description

This page documents the available methods for objects of class manmetavar.metavar.

Usage

```
## S3 method for class 'manmetavar.metavar'
coef(object, ...)

## S3 method for class 'manmetavar.metavar'
vcov(object, ...)

## S3 method for class 'manmetavar.metavar'
print(x, alpha = 0.05, digits = 4, ...)
```

```
## S3 method for class 'manmetavar.metavar'
summary(object, alpha = 0.05, digits = 4, ...)

## S3 method for class 'manmetavar.metavar'
confint(object, parm = NULL, level = 0.95, lb = TRUE, ...)
```

Arguments

object	Object of class <code>manmetavar.metavar</code> .
...	additional arguments.
x	Object of class <code>manmetavar.metavar</code> .
alpha	Numeric vector. Significance level α .
digits	Integer indicating the number of decimal places to display.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
lb	Logical. If TRUE, returns profile likelihood-based confidence intervals. If FALSE, returns Wald confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

manmetavar-mlvar-methods

Methods for Objects of Class `manmetavar.mlvar`

Description

This page documents the available methods for objects of class `manmetavar.mlvar`.

Usage

```
## S3 method for class 'manmetavar.mlvar'
print(
  x,
  show = c("fit", "temporal", "contemporaneous", "between"),
  digits = 4,
  ...
)

## S3 method for class 'manmetavar.mlvar'
summary(
```

```

    object,
    show = c("fit", "temporal", "contemporaneous", "between"),
    digits = 4,
    ...
)

```

Arguments

x	Object of class <code>manmetavar.mlvar</code> .
show	Tables to show.
digits	Integer indicating the number of decimal places to display.
...	additional arguments.
object	Object of class <code>manmetavar.mlvar</code> .

Author(s)

Ivan Jacob Agaloos Pesigan

manmetavar-mplus-methods

Methods for Objects of Class `manmetavar.mplus`

Description

This page documents the available methods for objects of class `manmetavar.mplus`.

Usage

```

## S3 method for class 'manmetavar.mplus'
coef(object, median = TRUE, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
vcov(object, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
summary(object, alpha = 0.05, median = TRUE, digits = 4, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
confint(object, parm = NULL, level = 0.95, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
plot(
  x,
  what = "posterior",
  parm = NULL,
  level = 0.95,

```



```

    burnin = NULL,
    legend_loc = "topright",
    ...
)

```

Arguments

object	Object of class <code>manmetavar.mplus</code> .
median	Logical. If <code>median = TRUE</code> , return median of the posterior. If <code>median = FALSE</code> , return mean of the posterior.
burnin	Integer indicating initial samples to discard. If <code>burnin = NULL</code> , do not discard anything.
...	additional arguments.
alpha	Numeric vector. Significance level α .
digits	Integer indicating the number of decimal places to display.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
x	Object of class <code>manmetavar.mplus</code> .
what	Character string. If <code>what = "posterior"</code> , return posterior distribution plots. If <code>what = "trace"</code> , return trace plots.
legend_loc	Character string. Legend location.

Author(s)

Ivan Jacob Agaloos Pesigan

MplusInput	<i>Create Mplus Input File</i>
------------	--------------------------------

Description

The function creates an Mplus input file.

Usage

```

MplusInput(
  dynamics,
  fn_data,
  fn_posterior,
  fn_factorscores,
  chains,
  iter,

```

```

    fscores,
    plot,
    default_priors,
    ncores = NULL
)

```

Arguments

dynamics	1, 2, or 3. 1 for stable reciprocal regulation, 2 for escalating co-activation, and 3 for adaptive recovery.
fn_data	Character string. Filename for data file.
fn_posterior	Character string. Filename for posterior output.
fn_factorscores	Character string. Filename for factor scores output.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.
default_priors	Logical. If default_priors = TRUE, use default priors.
ncores	Positive integer. Number of cores to use.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMLVAR\(\)](#), [FitMetaVAR\(\)](#), [FitMplus\(\)](#)

Examples

```

cat(
  MplusInput(
    dynamics = 1,
    fn_data = "data.dat",
    fn_posterior = "posterior.dat",
    fn_factorscores = "factorscores.dat",
    chains = 2L,
    iter = 60000L,
    fscores = 1000L,
    plot = TRUE,
    default_priors = TRUE,
    ncores = NULL
  )
)

```

params	<i>Simulation Parameters</i>
--------	------------------------------

Description

Simulation Parameters

Usage

data(params)

Format

A dataframe with 27 rows and 4 columns:

- taskid** Simulation Task ID.
- n** Sample size.
- time** Number of measurement occassions.
- dynamics** Process dynamics. 1 for stable reciprocal regulation, 2 for escalating co-activation, and 3 for adaptive recovery.

Author(s)

Ivan Jacob Agaloos Pesigan

Sim	<i>Simulation Replication</i>
-----	-------------------------------

Description

Simulation Replication

Usage

```
Sim(  
  taskid,  
  repid,  
  output_folder,  
  overwrite,  
  integrity,  
  seed,  
  data,  
  metavar,  
  mlvar,  
  mplus,
```

```

    chains,
    iter,
    fscores,
    plot,
    default_priors
  )

```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
seed	Integer. Random seed.
data	Logical. Simulate data.
metavar	Logical. If metavar = TRUE, fit the model using the metaVAR package.
mlvar	Logical. If mlvar = TRUE, fit the model using the mlVAR package.
mplus	Logical. If mplus = TRUE, fit the model using DSEM in Mplus.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.
default_priors	Logical. If default_priors = TRUE, use default priors.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitDTVAR

Simulation Replication - FitDTVAR

Description

Simulation Replication - FitDTVAR

Usage

```
SimFitDTVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMetaVAR

Simulation Replication - FitMetaVAR

Description

Simulation Replication - FitMetaVAR

Usage

```
SimFitMetaVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMLVAR

Simulation Replication - FitMLVAR

Description

Simulation Replication - FitMLVAR

Usage

```
SimFitMLVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of manCTMed:::SimSuffix().
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMplus

Simulation Replication - FitMplus

Description

Simulation Replication - FitMplus

Usage

```
SimFitMplus(
  taskid,
  repid,
  output_folder,
  seed,
  suffix,
  overwrite,
  integrity,
  chains,
  iter,
  fscores,
  plot,
  default_priors
)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If <code>plot = TRUE</code> , add <code>PLOT: TYPE = PLOT3</code> ; to Mplus input file.
default_priors	Logical. If <code>default_priors = TRUE</code> , use default priors.

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFN	<i>Simulation File Name</i>
-------	-----------------------------

Description

Simulation File Name

Usage

SimFN(output_type, output_folder, suffix)

Arguments

- output_type Character string. Output type. Valid values include "data", "fit-dt-var-mx", "fit-meta-var-mx", and "fit-ml-var".
- output_folder Character string. Output folder.
- suffix Character string. Output of manCTMed:::SimSuffix().

Value

Returns a character string file name with the output_folder in the OS-specific format.

SimGenData	<i>Simulation Replication - GenData</i>
------------	---

Description

Simulation Replication - GenData

Usage

SimGenData(taskid, repid, output_folder, seed, suffix, overwrite, integrity)

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

SimProj

Simulation Project Name

Description

Simulation Project Name

Usage

```
SimProj()
```

Value

Returns the project name as a character string.

Author(s)

Ivan Jacob Agaloos Pesigan

Sum	Summary
-----	---------

Description

Summary

Usage

Sum(taskid, reps, output_folder, overwrite, integrity, metavar, mlvar, mplus)

Arguments

- taskid Positive integer. Task ID.
- reps Positive integer. Number of replications.
- output_folder Character string. Output folder.
- overwrite Logical. Overwrite existing output in output_folder.
- integrity Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
- metavar Logical. If metavar = TRUE, fit the model using the metaVAR package.
- mlvar Logical. If mlvar = TRUE, fit the model using the mlVAR package.
- mplus Logical. If mplus = TRUE, fit the model using DSEM in Mplus.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMetaVARLB	Summary: Likelihood-Based (FitMetaVAR)
-----------------	--

Description

Summary: Likelihood-Based (FitMetaVAR)

Usage

SumFitMetaVARLB(taskid, reps, output_folder, overwrite, integrity)

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMetaVARNormal	<i>Summary: Normal Theory (FitMetaVAR)</i>
---------------------	--

Description

Summary: Normal Theory (FitMetaVAR)

Usage

```
SumFitMetaVARNormal(taskid, reps, output_folder, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMLVAR	<i>Summary (FitMLVAR)</i>
-------------	---------------------------

Description

Summary (FitMLVAR)

Usage

SumFitMLVAR(taskid, reps, output_folder, overwrite, integrity)

Arguments

- taskid Positive integer. Task ID.
- reps Positive integer. Number of replications.
- output_folder Character string. Output folder.
- overwrite Logical. Overwrite existing output in output_folder.
- integrity Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

`SumFitMplus`*Summary (FitMplus)*

Description

Summary (FitMplus)

Usage

```
SumFitMplus(taskid, reps, output_folder, overwrite, integrity)
```

Arguments

<code>taskid</code>	Positive integer. Task ID.
<code>reps</code>	Positive integer. Number of replications.
<code>output_folder</code>	Character string. Output folder.
<code>overwrite</code>	Logical. Overwrite existing output in <code>output_folder</code> .
<code>integrity</code>	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the `Sum` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

Index

- * **Compression Functions**
 - Compress, [2](#)
- * **Data Generation Functions**
 - Dynamics, [3](#)
 - GenData, [11](#)
- * **Figure Functions**
 - FigBias, [4](#)
 - FigCoverage, [5](#)
 - FigPower, [5](#)
 - FigRMSE, [6](#)
- * **Model Fitting Functions**
 - FitDTVAR, [7](#)
 - FitMetaVAR, [8](#)
 - FitMLVAR, [9](#)
 - FitMplus, [9](#)
 - MplusInput, [17](#)
- * **compress**
 - Compress, [2](#)
- * **data**
 - params, [19](#)
- * **figure**
 - FigBias, [4](#)
 - FigCoverage, [5](#)
 - FigPower, [5](#)
 - FigRMSE, [6](#)
- * **fit**
 - FitDTVAR, [7](#)
 - FitMLVAR, [9](#)
 - FitMplus, [9](#)
 - MplusInput, [17](#)
 - SimFitDTVAR, [20](#)
 - SimFitMetaVAR, [21](#)
 - SimFitMLVAR, [22](#)
 - SimFitMplus, [23](#)
- * **gendata**
 - Dynamics, [3](#)
 - GenData, [11](#)
 - SimGenData, [24](#)
- * **manCTMed**

- SimFN, [24](#)
- * **manMetaVAR**
 - Compress, [2](#)
 - Dynamics, [3](#)
 - FigBias, [4](#)
 - FigCoverage, [5](#)
 - FigPower, [5](#)
 - FigRMSE, [6](#)
 - FitDTVAR, [7](#)
 - FitMetaVAR, [8](#)
 - FitMLVAR, [9](#)
 - FitMplus, [9](#)
 - GenData, [11](#)
 - MplusInput, [17](#)
 - Sim, [19](#)
 - SimFitDTVAR, [20](#)
 - SimFitMetaVAR, [21](#)
 - SimFitMLVAR, [22](#)
 - SimFitMplus, [23](#)
 - SimGenData, [24](#)
 - SimProj, [25](#)
 - Sum, [26](#)
 - SumFitMetaVARLB, [26](#)
 - SumFitMetaVARNormal, [27](#)
 - SumFitMLVAR, [28](#)
 - SumFitMplus, [29](#)
- * **meta**
 - FitMetaVAR, [8](#)
- * **methods**
 - manmetavar-data-methods, [11](#)
 - manmetavar-dtvar-methods, [12](#)
 - manmetavar-metavar-methods, [14](#)
 - manmetavar-mlvar-methods, [15](#)
 - manmetavar-mplus-methods, [16](#)
- * **parameters**
 - params, [19](#)
- * **simulation**
 - Sim, [19](#)
 - SimFitDTVAR, [20](#)

- SimFitMetaVAR, 21
- SimFitMLVAR, 22
- SimFitMplus, 23
- SimFN, 24
- SimGenData, 24
- SimProj, 25
- Sum, 26
- SumFitMetaVARLB, 26
- SumFitMetaVARNormal, 27
- SumFitMLVAR, 28
- SumFitMplus, 29
- * **summary**
 - Sum, 26
 - SumFitMetaVARLB, 26
 - SumFitMetaVARNormal, 27
 - SumFitMLVAR, 28
 - SumFitMplus, 29
- coef.manmetavar.dtvvar
 - (manmetavar-dtvvar-methods), 12
- coef.manmetavar.metavar
 - (manmetavar-metavar-methods), 14
- coef.manmetavar.mplus
 - (manmetavar-mplus-methods), 16
- Compress, 2
- confint.manmetavar.metavar
 - (manmetavar-metavar-methods), 14
- confint.manmetavar.mplus
 - (manmetavar-mplus-methods), 16
- Dynamics, 3, 11
- FigBias, 4, 5, 6
- FigCoverage, 4, 5, 6
- FigPower, 4, 5, 5, 6
- FigRMSE, 4, 5, 6, 6
- FitDTVVAR, 7, 8–10, 18
- FitDTVVAR(), 8
- fitDTVARMxID::fitDTVARMxID, 7
- FitMetaVAR, 7, 8, 9, 10, 18
- FitMLVAR, 7, 8, 9, 10, 18
- FitMplus, 7, 8, 9, 9, 18
- GenData, 3, 11
- GenData(), 7, 9, 10
- manmetavar-data-methods, 11
- manmetavar-dtvvar-methods, 12
- manmetavar-metavar-methods, 14
- manmetavar-mlvar-methods, 15
- manmetavar-mplus-methods, 16
- metaVAR::metaVAR, 8
- mlVAR::mlVAR, 9
- MplusInput, 7–10, 17
- params, 19
- plot.manmetavar.data
 - (manmetavar-data-methods), 11
- plot.manmetavar.mplus
 - (manmetavar-mplus-methods), 16
- print.manmetavar.data
 - (manmetavar-data-methods), 11
- print.manmetavar.dtvvar
 - (manmetavar-dtvvar-methods), 12
- print.manmetavar.metavar
 - (manmetavar-metavar-methods), 14
- print.manmetavar.mlvar
 - (manmetavar-mlvar-methods), 15
- Sim, 19
- SimFitDTVVAR, 20
- SimFitMetaVAR, 21
- SimFitMLVAR, 22
- SimFitMplus, 23
- SimFN, 24
- SimGenData, 24
- SimProj, 25
- simStateSpace::SimSSMIVary(), 11
- Sum, 26
- SumFitMetaVARLB, 26
- SumFitMetaVARNormal, 27
- SumFitMLVAR, 28
- SumFitMplus, 29
- summary.manmetavar.data
 - (manmetavar-data-methods), 11
- summary.manmetavar.dtvvar
 - (manmetavar-dtvvar-methods), 12
- summary.manmetavar.metavar
 - (manmetavar-metavar-methods), 14
- summary.manmetavar.mlvar
 - (manmetavar-mlvar-methods), 15
- summary.manmetavar.mplus
 - (manmetavar-mplus-methods), 16

`vcov.manmetavar.dtvvar`
 (`manmetavar-dtvvar-methods`), [12](#)
`vcov.manmetavar.metavar`
 (`manmetavar-metavar-methods`),
 [14](#)
`vcov.manmetavar.mplus`
 (`manmetavar-mplus-methods`), [16](#)