

Package ‘manMetaVAR’

February 25, 2026

Title Multivariate Meta-Analysis of Vector Autoregressive Model Coefficients

Version 0.9.7

Description Research compendium for the manuscript
Pesigan, I. J. A., et al. (In Preparation).
Multivariate Meta-Analysis of Vector Autoregressive Model Coefficients.
<[doi:10.0000/0000000000](https://doi.org/10.0000/0000000000)>.

URL <https://github.com/jeksterslab/manMetaVAR>,
<https://jeksterslab.github.io/manMetaVAR/>,
<https://osf.io/uenr7/>, <https://doi.org/10.0000/0000000000>

BugReports <https://github.com/jeksterslab/manMetaVAR/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

Depends R (>= 4.5.0), OpenMx (>= 2.22.10), fitVARMxID (>= 1.0.2),
metaDyn

Imports stats, utils, simStateSpace

Remotes jeksterslab/fitVARMxID, jeksterslab/metaDyn

Suggests knitr, rmarkdown, testthat

RoxygenNote 7.3.3.9000

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0003-4818-8420>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

Check	2
CheckFitDTVAR	3
CheckFitMetaVAR	4
CheckFitMplus	4
Compress	5
FitDTVAR	6
FitMetaVAR	6
FitMplus	7
GenData	8
manmetavar-data-methods	9
manmetavar-dtvar-methods	10
manmetavar-metavar-methods	12
manmetavar-mplus-methods	13
model	14
MplusInput	15
params	16
Sim	16
SimFitDTVAR	18
SimFitMetaVAR	19
SimFitMplus	20
SimFN	21
SimGenData	21
SimProj	22
Sum	22
SumFitMetaVARNormal	24
SumFitMetaVARRobust	24
SumFitMplus	25
SumFitNaive	26
Index	27

Check

Check Replication

Description

Check Replication

Usage

Check(taskid, repid, output_folder, metavar, mplus)

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
metavar	Logical. If metavar = TRUE, fit the model using the metaDyn package.
mplus	Logical. If mplus = TRUE, fit the model using DSEM in Mplus.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

CheckFitDTVAR

Check Replication - FitDTVAR

Description

Check Replication - FitDTVAR

Usage

```
CheckFitDTVAR(taskid, repid, output_folder, suffix)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
suffix	Character string. Output of manCTMed:::SimSuffix().

Details

This function is executed via the Check function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

CheckFitMetaVAR*Check Replication - FitMetaVAR*

Description

Check Replication - FitMetaVAR

Usage

```
CheckFitMetaVAR(taskid, repid, output_folder, suffix)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .

Details

This function is executed via the Check function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

CheckFitMplus*Check Replication - FitMplus*

Description

Check Replication - FitMplus

Usage

```
CheckFitMplus(taskid, repid, output_folder, suffix)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
suffix	Character string. Output of <code>manCTMed::SimSuffix()</code> .

Details

This function is executed via the Check function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

Compress	<i>Compress Replication</i>
----------	-----------------------------

Description

Compress Replication

Usage

`Compress(taskid, repid, output_folder)`

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

FitDTVAR

Fit the Model using the fitVARMxID Package

Description

The function fits the model using the [fitVARMxID::fitVARMxID](#) package.

Usage

```
FitDTVAR(data, ncores = NULL, seed = NULL)
```

Arguments

data	R object. Output of the GenData() function.
ncores	Positive integer. Number of cores to use.
seed	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitMetaVAR\(\)](#), [FitMplus\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitDTVAR(data = data, seed = seed)
print(fit)
summary(fit)
coef(fit)
vcov(fit)

## End(Not run)
```

FitMetaVAR

Multivariate Meta-Analysis using the metaDyn Package

Description

The function performs multivariate meta-analysis using the [metaDyn::metaDyn](#) package.

Usage

```
FitMetaVAR(fit, ncores = NULL, seed = NULL)
```

Arguments

fit	R object. Output of the FitDTVAR() function.
ncores	Positive integer. Number of cores to use.
seed	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMplus\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitDTVAR(data = data, seed = seed)
meta <- FitMetaVAR(fit = fit, seed = seed)
summary(meta)
print(meta)
coef(meta)
vcov(meta)

## End(Not run)
```

FitMplus

Fit the Model using Mplus

Description

The function fits the model using Mplus.

Usage

```
FitMplus(
  data,
  chains = 2L,
  iter = 40000L,
  fscores = NULL,
  plot = FALSE,
  wd = ".",
  mplus_bin = NULL,
  ncores = NULL,
  seed = NULL
)
```

Arguments

data	R object. Output of the GenData() function.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.
wd	Character string. Working directory.
mplus_bin	Character string. Path to Mplus binary. If mplus_bin = NULL, the function will try to find the appropriate binary.
ncores	Positive integer. Number of cores to use.
seed	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMetaVAR\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitMplus(data = data)
print(fit)
summary(fit)

## End(Not run)
```

GenData

Simulate Data

Description

The function simulates data using the [simStateSpace::SimSSMIVary\(\)](#) function.

Usage

```
GenData(taskid, seed = NULL)
```

Arguments

taskid	Positive integer. Task ID.
seed	Integer. Random seed.

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
print(data)
summary(data)
plot(data)

## End(Not run)
```

manmetavar-data-methods

Methods for Objects of Class manmetavar.data

Description

This page documents the available methods for objects of class `manmetavar.data`.

Usage

```
## S3 method for class 'manmetavar.data'
print(x, ...)

## S3 method for class 'manmetavar.data'
summary(object, ...)

## S3 method for class 'manmetavar.data'
plot(x, ...)
```

Arguments

<code>x</code>	Object of class <code>manmetavar.data</code> .
<code>...</code>	additional arguments.
<code>object</code>	Object of class <code>manmetavar.data</code> .

Author(s)

Ivan Jacob Agaloos Pesigan

`manmetavar-dtvar-methods`*Methods for Objects of Class `manmetavar.dtv`*

Description

This page documents the available methods for objects of class `manmetavar.dtv`.

Usage

```
## S3 method for class 'manmetavar.dtv'
coef(
  object,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  ncores = NULL,
  ...
)
```

```
## S3 method for class 'manmetavar.dtv'
vcov(
  object,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  robust = FALSE,
  ncores = NULL,
  ...
)
```

```
## S3 method for class 'manmetavar.dtv'
print(
  x,
  means = FALSE,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
```

```

    digits = 4,
    ncores = NULL,
    ...
)

## S3 method for class 'manmetavar.dtvar'
summary(
  object,
  means = FALSE,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  digits = 4,
  ncores = NULL,
  ...
)

```

Arguments

<code>object</code>	Object of class <code>manmetavar.dtvar</code> .
<code>mu</code>	Logical. If <code>mu = TRUE</code> , include estimates of the <code>mu</code> vector, if available. If <code>mu = FALSE</code> , exclude estimates of the <code>mu</code> vector.
<code>alpha</code>	Logical. If <code>alpha = TRUE</code> , include estimates of the <code>alpha</code> vector, if available. If <code>alpha = FALSE</code> , exclude estimates of the <code>alpha</code> vector.
<code>beta</code>	Logical. If <code>beta = TRUE</code> , include estimates of the <code>beta</code> matrix, if available. If <code>beta = FALSE</code> , exclude estimates of the <code>beta</code> matrix.
<code>nu</code>	Logical. If <code>nu = TRUE</code> , include estimates of the <code>nu</code> vector, if available. If <code>nu = FALSE</code> , exclude estimates of the <code>nu</code> vector.
<code>psi</code>	Logical. If <code>psi = TRUE</code> , include estimates of the <code>psi</code> matrix, if available. If <code>psi = FALSE</code> , exclude estimates of the <code>psi</code> matrix.
<code>theta</code>	Logical. If <code>theta = TRUE</code> , include estimates of the <code>theta</code> matrix, if available. If <code>theta = FALSE</code> , exclude estimates of the <code>theta</code> matrix.
<code>ncores</code>	Positive integer. Number of cores to use.
<code>...</code>	additional arguments.
<code>robust</code>	Logical. If <code>TRUE</code> , use robust (sandwich) sampling variance-covariance matrix. If <code>FALSE</code> , use normal theory sampling variance-covariance matrix.
<code>x</code>	Object of class <code>manmetavar.dtvar</code> .
<code>means</code>	Logical. If <code>means = TRUE</code> , return means. Otherwise, the function returns raw estimates.
<code>digits</code>	Integer indicating the number of decimal places to display.

Author(s)

Ivan Jacob Agaloos Pesigan

manmetavar-metavar-methods*Methods for Objects of Class manmetavar.metavar*

Description

This page documents the available methods for objects of class `manmetavar.metavar`.

Usage

```
## S3 method for class 'manmetavar.metavar'
coef(object, ...)

## S3 method for class 'manmetavar.metavar'
vcov(object, robust = NULL, ...)

## S3 method for class 'manmetavar.metavar'
print(x, alpha = NULL, robust = NULL, digits = 4, ...)

## S3 method for class 'manmetavar.metavar'
summary(object, alpha = NULL, robust = NULL, digits = 4, ...)

## S3 method for class 'manmetavar.metavar'
confint(object, parm = NULL, level = 0.95, robust = NULL, ...)
```

Arguments

<code>object</code>	Object of class <code>manmetavar.metavar</code> .
<code>...</code>	additional arguments.
<code>robust</code>	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix. If NULL, the function will check object if robust standard errors are available.
<code>x</code>	Object of class <code>manmetavar.metavar</code> .
<code>alpha</code>	Numeric vector. Significance level α .
<code>digits</code>	Integer indicating the number of decimal places to display.
<code>parm</code>	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
<code>level</code>	the confidence level required.

Author(s)

Ivan Jacob Agaloos Pesigan

manmetavar-mplus-methods

Methods for Objects of Class manmetavar.mplus

Description

This page documents the available methods for objects of class `manmetavar.mplus`.

Usage

```
## S3 method for class 'manmetavar.mplus'
coef(object, median = TRUE, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
vcov(object, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
summary(object, alpha = 0.05, median = TRUE, digits = 4, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
confint(object, parm = NULL, level = 0.95, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
plot(
  x,
  what = "posterior",
  parm = NULL,
  level = 0.95,
  burnin = NULL,
  legend_loc = "topright",
  ...
)
```

Arguments

<code>object</code>	Object of class <code>manmetavar.mplus</code> .
<code>median</code>	Logical. If <code>median = TRUE</code> , return median of the posterior. If <code>median = FALSE</code> , return mean of the posterior.
<code>burnin</code>	Integer indicating initial samples to discard. If <code>burnin = NULL</code> , do not discard anything.
<code>...</code>	additional arguments.
<code>alpha</code>	Numeric vector. Significance level α .
<code>digits</code>	Integer indicating the number of decimal places to display.
<code>parm</code>	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.

level	the confidence level required.
x	Object of class <code>manmetavar.mplus</code> .
what	Character string. If <code>what = "posterior"</code> , return posterior distribution plots. If <code>what = "trace"</code> , return trace plots.
legend_loc	Character string. Legend location.

Author(s)

Ivan Jacob Agaloos Pesigan

model	<i>Model Parameters</i>
-------	-------------------------

Description

Model Parameters

Usage

```
data(model)
```

Format

A list with 15 elements:

k Number of variables.

mu_mu Mean of the set-point vector μ .

mu_sigma Covariance matrix of the parameter μ .

mu_sigma_l Cholesky factor of the covariance matrix of the parameter μ .

beta_mu Mean of lagged coefficients matrix β .

beta_sigma Covariance matrix of the parameter $\text{vec}(\beta)$.

beta_sigma_l Cholesky factor of the covariance matrix of the parameter $\text{vec}(\beta)$.

psi Process noise covariance matrix Ψ .

psi_l Cholesky factor of the process noise covariance matrix Ψ .

psi_d_ldl uc_d of the LDL' decomposition of the process noise covariance matrix Ψ . See [fitVARMxID::LDL\(\)](#).

psi_l_ldl s_l of the LDL' decomposition of the process noise covariance matrix Ψ . See [fitVARMxID::LDL\(\)](#).

ma_fixed Vector of fixed effects $\theta = [\mu, \text{vec}(\beta)]'$

ma_random Matrix of random effects $\theta = [\mu, \text{vec}(\beta)]'$

ma_random_d_ldl uc_d of the LDL' decomposition of the random effects. See [fitVARMxID::LDL\(\)](#).

ma_random_l_ldl s_l of the LDL' decomposition of the random effects. See [fitVARMxID::LDL\(\)](#).

Author(s)

Ivan Jacob Agaloos Pesigan

MplusInput

Create Mplus Input File

Description

The function creates an Mplus input file.

Usage

```
MplusInput(
  fn_data,
  fn_posterior,
  fn_factorscores,
  chains,
  iter,
  fscores,
  plot,
  ncores = NULL,
  seed = NULL
)
```

Arguments

fn_data	Character string. Filename for data file.
fn_posterior	Character string. Filename for posterior output.
fn_factorscores	Character string. Filename for factor scores output.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.
ncores	Positive integer. Number of cores to use.
seed	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMetaVAR\(\)](#), [FitMplus\(\)](#)

Examples

```
cat(
  MplusInput(
    fn_data = "data.dat",
    fn_posterior = "posterior.dat",
    fn_factorscores = "factorscores.dat",
```

```
    chains = 2L,  
    iter = 40000L,  
    fscores = 1000L,  
    plot = TRUE,  
    ncores = NULL,  
    seed = 42  
  )  
)
```

params	<i>Simulation Parameters</i>
--------	------------------------------

Description

Simulation Parameters

Usage

data(params)

Format

A dataframe with 9 rows and 3 columns:

- taskid** Simulation Task ID.
- n** Sample size.
- time** Number of measurement occassions.

Author(s)

Ivan Jacob Agaloos Pesigan

Sim	<i>Simulation Replication</i>
-----	-------------------------------

Description

Simulation Replication

Usage

```
Sim(  
  taskid,  
  repid,  
  output_folder,  
  overwrite,  
  integrity,  
  seed,  
  data,  
  metavar,  
  mplus,  
  chains,  
  iter,  
  fscores,  
  plot  
)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
seed	Integer. Random seed.
data	Logical. Simulate data.
metavar	Logical. If metavar = TRUE, fit the model using the metaDyn package.
mplus	Logical. If mplus = TRUE, fit the model using DSEM in Mplus.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitDTVAR

Simulation Replication - FitDTVAR

Description

Simulation Replication - FitDTVAR

Usage

```
SimFitDTVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMetaVAR	<i>Simulation Replication - FitMetaVAR</i>
---------------	--

Description

Simulation Replication - FitMetaVAR

Usage

```
SimFitMetaVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMplus

Simulation Replication - FitMplus

Description

Simulation Replication - FitMplus

Usage

```
SimFitMplus(
  taskid,
  repid,
  output_folder,
  seed,
  suffix,
  overwrite,
  integrity,
  chains,
  iter,
  fscores,
  plot
)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of <code>manCTMed:::SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If <code>plot = TRUE</code> , add <code>PLOT: TYPE = PLOT3;</code> to Mplus input file.

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFN

Simulation File Name

Description

Simulation File Name

Usage

SimFN(output_type, output_folder, suffix)

Arguments

output_type	Character string. Output type. Valid values include "data", "fit-dt-var-mx", "fit-meta-var-mx", and "fit-mplus".
output_folder	Character string. Output folder.
suffix	Character string. Output of manCTMed:::SimSuffix().

Value

Returns a character string file name with the output_folder in the OS-specific format.

SimGenData

Simulation Replication - GenData

Description

Simulation Replication - GenData

Usage

SimGenData(taskid, repid, output_folder, seed, suffix, overwrite, integrity)

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Output of manCTMed:::SimSuffix().
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimProj	<i>Simulation Project Name</i>
---------	--------------------------------

Description

Simulation Project Name

Usage

SimProj()

Value

Returns the project name as a character string.

Author(s)

Ivan Jacob Agaloos Pesigan

Sum	<i>Summary</i>
-----	----------------

Description

Summary

Usage

```
Sum(  
  taskid,  
  reps,  
  output_folder,  
  overwrite,  
  integrity,  
  metavar_normal,  
  metavar_robust,  
  naive,  
  mplus,  
  ncores  
)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
metavar_normal	Logical. If metavar_normal = TRUE, summarize metaVAR model using normal confidence intervals.
metavar_robust	Logical. If metavar_robust = TRUE, summarize metaVAR model using robust (sandwich) confidence intervals.
naive	Logical. If naive = TRUE, summarize naive estimates.
mplus	Logical. If mplus = TRUE, summarize the DSEM model.
ncores	Positive integer. Number of cores to use.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMetaVARNormal *Summary: Normal Theory (FitMetaVAR)*

Description

Summary: Normal Theory (FitMetaVAR)

Usage

```
SumFitMetaVARNormal(taskid, reps, output_folder, overwrite, integrity, ncores)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMetaVARRobust *Summary: Robust (FitMetaVAR)*

Description

Summary: Robust (FitMetaVAR)

Usage

```
SumFitMetaVARRobust(taskid, reps, output_folder, overwrite, integrity, ncores)
```


Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMplus	<i>Summary (FitMplus)</i>
-------------	---------------------------

Description

Summary (FitMplus)

Usage

SumFitMplus(taskid, reps, output_folder, overwrite, integrity, ncores)

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitNaive

Summary: Naive (FitMetaVAR)

Description

Summary: Naive (FitMetaVAR)

Usage

```
SumFitNaive(taskid, reps, output_folder, overwrite, integrity, ncores)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

Index

- * **Compression Functions**
 - Compress, [5](#)
- * **Data Generation Functions**
 - GenData, [8](#)
- * **Model Fitting Functions**
 - FitDTVAR, [6](#)
 - FitMetaVAR, [6](#)
 - FitMplus, [7](#)
 - MplusInput, [15](#)
- * **check**
 - Check, [2](#)
 - CheckFitDTVAR, [3](#)
 - CheckFitMetaVAR, [4](#)
 - CheckFitMplus, [4](#)
- * **compress**
 - Compress, [5](#)
- * **data**
 - model, [14](#)
 - params, [16](#)
- * **fit**
 - FitDTVAR, [6](#)
 - FitMplus, [7](#)
 - MplusInput, [15](#)
 - SimFitDTVAR, [18](#)
 - SimFitMetaVAR, [19](#)
 - SimFitMplus, [20](#)
- * **gendata**
 - GenData, [8](#)
 - SimGenData, [21](#)
- * **manCTMed**
 - SimFN, [21](#)
- * **manMetaVAR**
 - Check, [2](#)
 - CheckFitDTVAR, [3](#)
 - CheckFitMetaVAR, [4](#)
 - CheckFitMplus, [4](#)
 - Compress, [5](#)
 - FitDTVAR, [6](#)
 - FitMetaVAR, [6](#)

- FitMplus, [7](#)
- GenData, [8](#)
- MplusInput, [15](#)
- Sim, [16](#)
- SimFitDTVAR, [18](#)
- SimFitMetaVAR, [19](#)
- SimFitMplus, [20](#)
- SimGenData, [21](#)
- SimProj, [22](#)
- Sum, [22](#)
- SumFitMetaVARNormal, [24](#)
- SumFitMetaVARRobust, [24](#)
- SumFitMplus, [25](#)
- SumFitNaive, [26](#)

- * **meta**
 - FitMetaVAR, [6](#)
- * **methods**
 - manmetavar-data-methods, [9](#)
 - manmetavar-dtvar-methods, [10](#)
 - manmetavar-metavar-methods, [12](#)
 - manmetavar-mplus-methods, [13](#)
- * **parameters**
 - model, [14](#)
 - params, [16](#)
- * **simulation**
 - Check, [2](#)
 - CheckFitDTVAR, [3](#)
 - CheckFitMetaVAR, [4](#)
 - CheckFitMplus, [4](#)
 - Sim, [16](#)
 - SimFitDTVAR, [18](#)
 - SimFitMetaVAR, [19](#)
 - SimFitMplus, [20](#)
 - SimFN, [21](#)
 - SimGenData, [21](#)
 - SimProj, [22](#)
 - Sum, [22](#)
 - SumFitMetaVARNormal, [24](#)
 - SumFitMetaVARRobust, [24](#)

- SumFitMplus, 25
- SumFitNaive, 26
- * **summary**
 - Sum, 22
 - SumFitMetaVARNormal, 24
 - SumFitMetaVARRobust, 24
 - SumFitMplus, 25
 - SumFitNaive, 26
- Check, 2
- CheckFitDTVAR, 3
- CheckFitMetaVAR, 4
- CheckFitMplus, 4
- coef.manmetavar.dtvvar
 - (manmetavar-dtvvar-methods), 10
- coef.manmetavar.metavar
 - (manmetavar-metavar-methods), 12
- coef.manmetavar.mplus
 - (manmetavar-mplus-methods), 13
- Compress, 5
- confint.manmetavar.metavar
 - (manmetavar-metavar-methods), 12
- confint.manmetavar.mplus
 - (manmetavar-mplus-methods), 13
- FitDTVAR, 6, 7, 8, 15
- FitDTVAR(), 7
- FitMetaVAR, 6, 6, 8, 15
- FitMplus, 6, 7, 7, 15
- fitVARMxID::fitVARMxID, 6
- fitVARMxID::LDL(), 14
- GenData, 8
- GenData(), 6, 8
- manmetavar-data-methods, 9
- manmetavar-dtvvar-methods, 10
- manmetavar-metavar-methods, 12
- manmetavar-mplus-methods, 13
- metaDyn::metaDyn, 6
- model, 14
- MplusInput, 6–8, 15
- params, 16
- plot.manmetavar.data
 - (manmetavar-data-methods), 9
- plot.manmetavar.mplus
 - (manmetavar-mplus-methods), 13
- print.manmetavar.data
 - (manmetavar-data-methods), 9
- print.manmetavar.dtvvar
 - (manmetavar-dtvvar-methods), 10
- print.manmetavar.metavar
 - (manmetavar-metavar-methods), 12
- Sim, 16
- SimFitDTVAR, 18
- SimFitMetaVAR, 19
- SimFitMplus, 20
- SimFN, 21
- SimGenData, 21
- SimProj, 22
- simStateSpace::SimSSMIVary(), 8
- Sum, 22
- SumFitMetaVARNormal, 24
- SumFitMetaVARRobust, 24
- SumFitMplus, 25
- SumFitNaive, 26
- summary.manmetavar.data
 - (manmetavar-data-methods), 9
- summary.manmetavar.dtvvar
 - (manmetavar-dtvvar-methods), 10
- summary.manmetavar.metavar
 - (manmetavar-metavar-methods), 12
- summary.manmetavar.mplus
 - (manmetavar-mplus-methods), 13
- vcov.manmetavar.dtvvar
 - (manmetavar-dtvvar-methods), 10
- vcov.manmetavar.metavar
 - (manmetavar-metavar-methods), 12
- vcov.manmetavar.mplus
 - (manmetavar-mplus-methods), 13