

# From Person-Specific Dynamics to Population Inference: A Computationally Efficient Meta-Analytic Structural Equation Modeling Framework for Integrating Complex Multilevel Dynamic Models

Ivan Jacob Agaloos Pesigan<sup>1</sup>, Michael A. Russell<sup>1,2</sup>, and Sy-Miin Chow<sup>3</sup>

<sup>1</sup>Edna Bennett Pierce Prevention Research Center, The Pennsylvania State University

<sup>2</sup>Department of Biobehavioral Health, The Pennsylvania State University

<sup>3</sup>Department of Human Development and Family Studies, The Pennsylvania State University

Intensive longitudinal research often seeks population-level inference on within-person dynamics without sacrificing idiographic estimation. We introduce MetaVAR, a two-stage meta-analytic structural equation modeling (MASEM) framework for multilevel dynamic systems that combines person-specific dynamic modeling with multivariate meta-analytic synthesis. In Stage 1, person-specific vector autoregressive (VAR) models are fit to obtain each individual's dynamic parameter vector and corresponding sampling covariance matrix. In Stage 2, those parameter vectors are synthesized using a multivariate random-effects meta-analytic SEM, allowing population-level inference on average dynamics, between-person heterogeneity, and cross-parameter covariation while propagating first-stage uncertainty. In a Monte Carlo simulation, we compare MetaVAR with (a) a one-step Bayesian multilevel VAR benchmark implemented in *Mplus* under default or relatively uninformative priors and (b) an uncertainty-uncorrected two-stage fit-many-then-summarize benchmark. Results indicate that MetaVAR's clearest advantage lies in recovery of between-person heterogeneity and calibration of interval estimates for heterogeneity parameters, whereas the one-step Bayesian benchmark remains competitive for population-average effects. An ecological momentary assessment illustration on negative and positive affect further shows that MetaVAR recovers interpretable average dynamics together with substantial heterogeneity in affective set points, inertia, cross-lagged coupling, and innovation structure.

**Keywords:** vector autoregressive model, multilevel model, random-effects meta-analysis, structural equation modeling

As a prior-sensitivity analysis, we refit the Bayesian multilevel VAR using a common set of relatively weakly informative, scale-aware priors held constant across all heterogeneity conditions. Population-average set points received  $\mathcal{N}(0, 25)$  priors, whereas population-average transition coefficients received  $\mathcal{N}(0, 0.25)$  priors. The corresponding prior standard deviations of 5 and 0.5 were broad relative to the respective parameter scales. The within-person innovation covariance and between-person set-point covariance matrices received  $IW(\mathbf{I}_2, 3)$  priors. Because transition-coefficient heterogeneity was expected to occur on a substantially smaller scale, its covariance matrix received an  $IW(0.004\mathbf{I}_4, 5)$  prior. With four random transition coefficients, this specification implies marginal  $IG(1, 0.002)$  priors for the transition variances, with mode 0.001 and a heavy upper tail. Inverse-Wishart prior calibration is consequential when random-effect variances are small or near the boundary; we therefore compared results under these priors with those obtained using the *Mplus* default priors (Muthén & Muthén, 2017; Schuurman et al., 2016; van Erp et al., 2018).

For the four-variable feasibility analysis, we conducted a prior-sensitivity analysis for the reference simulation condition, with ( $n = 200$ ), ( $T = 200$ ), and the reference level of heterogeneity. Population-average set points received  $\mathcal{N}(0, 25)$  priors, whereas population-average transition coefficients received  $\mathcal{N}(0, 0.25)$  priors. The corresponding prior standard deviations of (5) and (0.5), respectively, were broad relative to the parameter scales. The four-dimensional within-person innovation covariance matrix received an  $IW(\mathbf{I}_4, 5)$  prior. In the *Mplus* implementation, the 10 unique elements of the lower triangular covariance matrix were assigned inverse-Wishart scale values element by element, with unit values for the four diagonal elements and zero values for the six off-diagonal elements, thereby defining  $\mathbf{I}_4$  as the prior scale matrix. Because the between-person covariance structures were diagonal in the four-variable model, independent  $IG(2, 0.025)$  priors were assigned to the set-point and transition-coefficient variances. Under the *Mplus* shape-scale parameterization, this inverse-gamma prior has mean (0.025), mode (0.0083), and a heavy upper tail. The prior

was calibrated to the order of magnitude of the random-effect variances specified in the reference simulation design, rather than to estimates obtained from individual replications, and was held constant across replications. We compared results under these scale-aware priors with those obtained using the Mplus default priors. This comparison follows recommendations to evaluate prior sensitivity explicitly because apparently diffuse covariance priors can be consequential when random-effect variances are small or near the boundary (Muthén & Muthén, 2017; Schuurman et al., 2016; van Erp et al., 2018).

## References

- Kurtzer, G. M., cclerget, Bauer, M. W., Kaneshiro, I., Trudgian, D., & Godlove, D. (2021). hpcng/singularity: Singularity 3.7.3. <https://doi.org/10.5281/zenodo.4667718>
- Kurtzer, G. M., Sochat, V., & Bauer, M. W. (2017). Singularity: Scientific containers for mobility of compute. *PLOS ONE*, 12(5), e0177459. <https://doi.org/10.1371/journal.pone.0177459>
- Muthén, L. K., & Muthén, B. O. (2017). *Mplus user's guide. Eighth edition*. Los Angeles, CA, Muthén & Muthén.
- Schuurman, N. K., Grasman, R. P. P., & Hamaker, E. L. (2016). A comparison of inverse-Wishart prior specifications for covariance matrices in multilevel autoregressive models. *Multivariate Behavioral Research*, 51(2-3), 185–206. <https://doi.org/10.1080/00273171.2015.1065398>
- Tange, O. (2021). GNU Parallel 20210922 ('Vindelev'). <https://doi.org/10.5281/zenodo.5523272>
- van Erp, S., Mulder, J., & Oberski, D. L. (2018). Prior sensitivity analysis in default bayesian structural equation modeling. *Psychological Methods*, 23(2), 363–388. <https://doi.org/10.1037/met0000162>
- Yoo, A. B., Jette, M. A., & Grondona, M. (2003). SLURM: Simple Linux Utility for Resource Management. In D. Feitelson, L. Rudolph, & U. Schwiegelshohn (Eds.), *Job scheduling strategies for parallel processing* (pp. 44–60). Springer Berlin Heidelberg. [https://doi.org/10.1007/10968987\\_3](https://doi.org/10.1007/10968987_3)

---

 Ivan Jacob Agaloos Pesigan;  Michael A. Russell;  Sy-Miin Chow.

This research was supported by the Prevention and Methodology Training Program (PAMT), through a T32 training grant from the National Institute on Drug Abuse (NIDA; T32 DA017629; MPIs: J. Maggs and S. Lanza), as well as by grant UL1TR002014-06 from the National Center for Advancing Translational Sciences (NCATS).

Computations for this research were performed on the Pennsylvania State University's Institute for Computational and Data Sciences' Roar supercomputer using SLURM for job scheduling (Yoo et al., 2003), GNU Parallel to run the simulations in parallel (Tange, 2021), and Apptainer to ensure a reproducible software stack (Kurtzer et al., 2017, 2021).

Correspondence concerning this article should be addressed to Ivan Jacob Agaloos Pesigan, Edna Bennett Pierce Prevention Research Center, College of Health and Human Development, The Pennsylvania State University, 320 Biobehavioral Health Building, University Park, PA 16802 or by email ([ijapesigan@psu.edu](mailto:ijapesigan@psu.edu)).