

Package ‘manMetaVAR’

October 8, 2026

Title Meta-Analytic SEM for Multilevel Dynamics

Version 0.5.8

Description Research compendium for the manuscript

Pesigan, I. J. A., Russell, M. A., & Chow, S.-M. (Under Review).

From Person-Specific Dynamics to Population Inference:

A Computationally Efficient Meta-Analytic Structural Equation Modeling Framework
for Integrating Complex Multilevel Dynamic Models.

<doi:10.0000/0000000000>.

URL <https://github.com/jeksterslab/manMetaVAR>,

<https://jeksterslab.github.io/manMetaVAR/>,

<https://osf.io/uenr7/>, <https://doi.org/10.0000/0000000000>

BugReports <https://github.com/jeksterslab/manMetaVAR/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

LazyDataCompression xz

Roxygen list(markdown = TRUE)

Depends R (>= 4.5.0), OpenMx (>= 2.22.11), fitVARMxID (>= 1.0.6),
metaDyn (>= 1.0.4)

Imports posterior, stats, utils, simStateSpace (>= 1.2.16), ggplot2

Remotes jeksterslab/fitVARMxID, jeksterslab/metaDyn

Suggests knitr, rmarkdown, testthat

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:

<<https://orcid.org/0000-0003-4818-8420>>),

Michael A. Russell [ctb] (ORCID:

<<https://orcid.org/0000-0002-3956-604X>>),

Sy-Miin Chow [ctb] (ORCID: <<https://orcid.org/0000-0003-1938-027X>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

Check	3
CheckFitDTVAR	3
CheckFitMetaVAR	4
CheckFitMplus	5
CheckFitMplusPriors	5
CheckFitNaive	6
Compress	7
diagnostics	7
FigMetricHeatmap	8
FigMplusDiagnosticsHeatmap	9
FigMplusDiagnosticsOverview	11
FigOverview	13
FitDTVAR	14
FitMetaVAR	15
FitMplus	15
FitMplusDiagnostics	17
FitNaive	18
GenData	18
LoadMplusDiagnostics	19
manmetavar-data-methods	20
manmetavar-dtvar-methods	20
manmetavar-metavar-methods	22
manmetavar-mplus-methods	24
model	25
MplusInput	26
params	27
population	28
results	28
Sim	30
SimFitDTVAR	31
SimFitMetaVAR	32
SimFitMplus	33
SimFitMplusDiagnostics	34
SimFitMplusPriors	35
SimFitMplusPriorsDiagnostics	36
SimFitNaive	37
SimFN	38
SimGenData	38
SimProj	39
simulation_diagnostics	39
Sum	40
SumDiagnostics	41
SumFitMetaVARNormal	42
SumFitMetaVARRobust	43
SumFitMplus	43
SumFitMplusDiagnostics	44

<i>Check</i>	3
SumFitMplusPriors	45
SumFitMplusPriorsDiagnostics	46
SumFitNaive	47
TabMplusDiagSensitivity	47
Index	50

Check	<i>Check Replication</i>
-------	--------------------------

Description

Check Replication

Usage

Check(taskid, repid, output_folder, naive, metavar, mplus)

Arguments

- | | |
|---------------|--|
| taskid | Positive integer. Task ID. |
| repid | Positive integer. Replication ID. |
| output_folder | Character string. Output folder. |
| naive | Logical. If naive = TRUE, fit the naive approach. |
| metavar | Logical. If metavar = TRUE, fit the model using the metaDyn package. |
| mplus | Logical. If mplus = TRUE, fit the model using DSEM in Mplus. |

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

CheckFitDTVAR

Check Replication - FitDTVAR

Description

Check Replication - FitDTVAR

Usage

```
CheckFitDTVAR(taskid, repid, output_folder, suffix)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
suffix	Character string. Simulation file suffix returned by <code>.SimSuffix()</code> .

Details

This function is executed via the Check function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

CheckFitMetaVAR*Check Replication - FitMetaVAR*

Description

Check Replication - FitMetaVAR

Usage

```
CheckFitMetaVAR(taskid, repid, output_folder, suffix)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
suffix	Character string. Simulation file suffix returned by <code>.SimSuffix()</code> .

Details

This function is executed via the Check function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

CheckFitMplus

Check Replication - FitMplus

Description

Check Replication - FitMplus

Usage

```
CheckFitMplus(taskid, repid, output_folder, suffix)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
suffix	Character string. Simulation file suffix returned by <code>.SimSuffix()</code> .

Details

This function is executed via the Check function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

CheckFitMplusPriors	<i>Check Replication - FitMplus (User Defined Priors)</i>
---------------------	---

Description

Check Replication - FitMplus (User Defined Priors)

Usage

```
CheckFitMplusPriors(taskid, repid, output_folder, suffix)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
suffix	Character string. Simulation file suffix returned by <code>.SimSuffix()</code> .

Details

This function is executed via the Check function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

CheckFitNaive	<i>Check Replication - FitNaive</i>
---------------	-------------------------------------

Description

Check Replication - FitNaive

Usage

```
CheckFitNaive(taskid, repid, output_folder, suffix)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
suffix	Character string. Simulation file suffix returned by <code>.SimSuffix()</code> .

Details

This function is executed via the Check function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

Compress	<i>Compress Replication</i>
----------	-----------------------------

Description

Compress Replication

Usage

```
Compress(taskid, repid, output_folder)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

diagnostics

Bayesian Mplus Diagnostics Across Simulation Conditions

Description

Parameter- and run-level Bayesian Mplus diagnostics for all simulation task IDs, stored separately for the default and alternative prior specifications.

Usage

```
data(diagnostics_default)
data(diagnostics_priors)
```

Format

A list with three elements:

parameters A data frame with one row per task ID, replication, prior condition, and Mplus parameter. It contains the simulation design variables, posterior SD, R-hat, bulk and tail ESS, and MCSEs.

runs A data frame with one row per task ID, replication, and prior condition containing run-level diagnostics and elapsed time.

replications Number of simulation replications represented in each task/prior cell.

The object is generated by `.setup/data-process/data-process-005-diagnostics.R` from the task-specific outputs of `SumFitMplusDiagnostics()` and `SumFitMplusPriorsDiagnostics()`.

Details

Each bundle covers 36 bivariate tasks and one prior branch, with 1,000 replications per task/prior cell: 36,000 run rows and 792,000 parameter rows (22 parameters per run). Use `LoadMplusDiagnostics()` to combine the bundles into 72,000 run rows and 1,584,000 parameter rows. The separate bundles replace `data(diagnostics)` and the earlier 10-replication bundle. Block-level failures differ from full-run gates. Primary thresholds are $R_{\text{hat}} > 1.01$, bulk/tail ESS < 400 , MCSE/SD > 0.05 ; nonfinite diagnostics fail. These are archived summaries, not new fits.

The compact parameter tables omit posterior means, medians, and interval endpoints (mean, median, ll, and ul) to reduce bundle size. Posterior SD (sd), R-hat, bulk and tail ESS, and all four MCSE columns are retained without rounding or subsampling. Run diagnostics and replication counts are unchanged. The complete posterior summaries remain in the task-specific source files.

Author(s)

Ivan Jacob Agaloos Pesigan

FigMetricHeatmap	<i>Results Heatmap</i>
------------------	------------------------

Description

Plot results heatmap.

Usage

```
FigMetricHeatmap(results, metric_name, grey_scale = FALSE, values = FALSE)
```

Arguments

results	results data frame.
metric_name	Character string. "coverage" for coverage probability, "abs_bias" for absolute bias on the parameter scale, "abs_rel_bias" for the legacy mixed relative/absolute bias display, "rmse" for RMSE, "power" for statistical power, and "type1_error" for the Type I error rate.
grey_scale	Logical. If TRUE, use a grey-scale fill suitable for black-and-white printing.
values	Logical. If TRUE, display values inside tiles.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Figure Functions: [FigMplusDiagnosticsHeatmap\(\)](#), [FigMplusDiagnosticsOverview\(\)](#), [FigOverview\(\)](#)

Examples

```
## Not run:
data(results, package = "manMetaVAR")
FigMetricHeatmap(
  results = results,
  metric_name = "coverage"
)

## End(Not run)
```

FigMplusDiagnosticsHeatmap

Bayesian Diagnostic Heatmaps Across Simulation Conditions

Description

Summarize parameter-level Mplus Bayesian diagnostics across all simulation task IDs and display them using the same design-cell-by-parameter layout as [FigMetricHeatmap\(\)](#). The function can display the two prior conditions directly or paired user-prior minus default-prior differences.

Usage

```
FigMplusDiagnosticsHeatmap(
  diagnostics,
  metric_name = "failure_rate",
  comparison = "difference",
  diagnostic = NULL,
  taskid = NULL,
  parm = NULL,
  center = "mean",
  rhat_threshold = 1.01,
  ess_threshold = 400,
  mcse_threshold = 0.05,
  relative_mcse = TRUE,
  grey_scale = FALSE,
  values = FALSE
)
```

Arguments

diagnostics	An all-task diagnostic object containing a parameters data frame, such as the diagnostics object generated by <code>.setup/data-process/data-process-z-diagnostics.R</code> . A parameter-level data frame may also be supplied directly.
metric_name	Character string. Valid values are "failure_rate", "rhat", "ess", and "mcse".
comparison	Character string. Use "levels" to show default and user-specified priors or "difference" to show paired user-prior minus default-prior differences.
diagnostic	Optional diagnostic panel names to retain. If NULL, all panels for the selected metric are displayed.
taskid	Optional positive integer task IDs to include. The default is to summarize all task IDs.
parm	Parameter names or positive integer positions to include. If NULL, all k = 2 Mplus parameters are included.
center	Character string indicating whether continuous diagnostics are summarized using the "mean" or "median" across replications. Failure rates always use the mean.

<code>rhat_threshold</code>	Numeric R-hat threshold.
<code>ess_threshold</code>	Numeric bulk and tail ESS threshold.
<code>mcse_threshold</code>	Numeric MCSE threshold.
<code>relative_mcse</code>	Logical. If TRUE, Monte Carlo standard errors are divided by the posterior standard deviation before summarizing.
<code>grey_scale</code>	Logical. If TRUE, use a grey-scale fill.
<code>values</code>	Logical. If TRUE, print summarized values inside cells.

Details

Failure rates count nonfinite diagnostic values as failures. For `comparison = "difference"`, diagnostic values are paired by task ID, replication, parameter, and diagnostic before computing user-prior minus default-prior differences. Blue cells indicate improvement under user priors and red cells indicate deterioration.

Value

A ggplot object. Its data element contains the all-task summary used in the heatmap.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Figure Functions: [FigMetricHeatmap\(\)](#), [FigMplusDiagnosticsOverview\(\)](#), [FigOverview\(\)](#)

Examples

```
## Not run:
data(diagnostics, package = "manMetaVAR")

FigMplusDiagnosticsHeatmap(
  diagnostics = diagnostics,
  metric_name = "failure_rate",
  comparison = "difference"
)

FigMplusDiagnosticsHeatmap(
  diagnostics = diagnostics,
  metric_name = "rhat",
  comparison = "levels",
  values = TRUE
)

## End(Not run)
```

FigMplusDiagnosticsOverview

Compact Bayesian Diagnostic Overview Across Simulation Conditions

Description

Summarize Mplus Bayesian diagnostic failures across all simulation task IDs at the Innovation, fixed-effect, and random-effect block level. This compact overview is intended for manuscript figures and reviewer-oriented prior sensitivity analyses. Use [FigMplusDiagnosticsHeatmap\(\)](#) for parameter-level drill-down figures.

Usage

```
FigMplusDiagnosticsOverview(
  diagnostics,
  comparison = "difference",
  diagnostic = "Any diagnostic",
  unit = "replication",
  taskid = NULL,
  target = NULL,
  rhat_threshold = 1.01,
  ess_threshold = 400,
  mcse_threshold = 0.05,
  relative_mcse = TRUE,
  grey_scale = FALSE,
  values = FALSE,
  label_threshold = 0.05
)
```

Arguments

diagnostics	An all-task diagnostics object containing a parameters data frame, or the parameter-level data frame itself.
comparison	Character string. Use "levels" to show diagnostic failure rates under each prior specification or "difference" to show paired user-prior minus default-prior differences.
diagnostic	Diagnostic failure panels to display. Available values are "Any diagnostic", "R-hat", "Bulk ESS", "Tail ESS", and "Relative MCSE" when relative_mcse = TRUE.
unit	Character string controlling the unit summarized within each design cell. "replication" classifies a replication as failed when any parameter in the selected parameter block fails. "parameter" averages failure indicators across parameter-replication pairs.
taskid	Optional positive integer task IDs to include.

target	Optional parameter blocks to include. Available values are "Innovation", "FE", and "RE".
rhat_threshold	Numeric R-hat threshold.
ess_threshold	Numeric bulk and tail ESS threshold.
mcse_threshold	Numeric MCSE threshold.
relative_mcse	Logical. If TRUE, Monte Carlo standard errors are divided by the posterior standard deviation before classifying failures.
grey_scale	Logical. If TRUE, use grey-scale fills.
values	Logical. If TRUE, print values inside sufficiently large cells.
label_threshold	Numeric value between zero and one. Labels with an absolute value smaller than this threshold are omitted. For level plots, the threshold applies directly to the failure rate.

Details

The default `unit = "replication"` answers a reviewer-friendly question: what proportion of simulation replications had at least one diagnostic problem within each parameter block? For `comparison = "difference"`, the function pairs prior specifications within task ID and replication before calculating user-prior minus default-prior differences. Negative values indicate fewer failures under user-specified priors.

Value

A ggplot object. Its data element contains the block-level summaries used in the figure.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Figure Functions: [FigMetricHeatmap\(\)](#), [FigMplusDiagnosticsHeatmap\(\)](#), [FigOverview\(\)](#)

Examples

```
## Not run:
data(diagnostics, package = "manMetaVAR")

FigMplusDiagnosticsOverview(
  diagnostics = diagnostics,
  comparison = "levels"
)

FigMplusDiagnosticsOverview(
  diagnostics = diagnostics,
  comparison = "difference",
  values = TRUE
)
```

```
## End(Not run)
```

FigOverview	<i>Results Overview</i>
-------------	-------------------------

Description

Plot results overview.

Usage

```
FigOverview(results)
```

Arguments

results results data frame.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Figure Functions: [FigMetricHeatmap\(\)](#), [FigMplusDiagnosticsHeatmap\(\)](#), [FigMplusDiagnosticsOverview\(\)](#)

Examples

```
## Not run:
data(results, package = "manMetaVAR")
FigOverview(results)

## End(Not run)
```

FitDTVAR	<i>Fit the Model using the fitVARMxID Package</i>
----------	---

Description

The function fits the model using the [fitVARMxID](#) package.

Usage

```
FitDTVAR(data, ncores = NULL, seed = NULL)
```

Arguments

data	R object. Output of the GenData() function.
ncores	Positive integer. Number of cores to use.
seed	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitMetaVAR\(\)](#), [FitMplus\(\)](#), [FitMplusDiagnostics\(\)](#), [FitNaive\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitDTVAR(data = data, seed = seed)
print(fit)
summary(fit)
coef(fit)
vcov(fit)

## End(Not run)
```

FitMetaVAR

Multivariate Meta-Analysis using the metaDyn Package

Description

The function performs multivariate meta-analysis using the [metaDyn](#) package.

Usage

```
FitMetaVAR(fit, ncores = NULL, seed = NULL)
```

Arguments

fit	R object. Output of the FitDTVAR() function.
ncores	Positive integer. Number of cores to use.
seed	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMplus\(\)](#), [FitMplusDiagnostics\(\)](#), [FitNaive\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitDTVAR(data = data, seed = seed)
meta <- FitMetaVAR(fit = fit, seed = seed)
summary(meta)
print(meta)
coef(meta)
vcov(meta)

## End(Not run)
```

FitMplus

Fit the Model using Mplus

Description

The function fits the model using Mplus.

Usage

```
FitMplus(
  data,
  chains = 2L,
  iter = 40000L,
  fscores = NULL,
  plot = FALSE,
  default_priors = TRUE,
  wd = ".",
  mplus_bin = NULL,
  ncores = NULL,
  seed = NULL
)
```

Arguments

data	R object. Output of the GenData() function.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.
default_priors	Logical. If default_priors = TRUE, use Mplus default priors.
wd	Character string. Working directory.

mplus_bin	Character string. Path to Mplus binary. If mplus_bin = NULL, the function will try to find the appropriate binary.
ncores	Positive integer. Number of cores to use.
seed	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMetaVAR\(\)](#), [FitMplusDiagnostics\(\)](#), [FitNaive\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
dsem <- FitMplus(data = data)
print(dsem)
summary(dsem)
coef(dsem)
vcov(dsem)
confint(dsem)
plot(dsem)
plot(dsem, what = "trace")

## End(Not run)
```

FitMplusDiagnostics *Posterior Diagnostics for FitMplus*

Description

The function computes parameter-level posterior summaries and Markov chain Monte Carlo diagnostics from the posterior draws saved by `FitMplus()`.

Usage

```
FitMplusDiagnostics(object, burnin = NULL, level = 0.95)
```

Arguments

object	Object of class <code>manmetavar.mplus</code> returned by <code>FitMplus()</code> .
burnin	Integer indicating the number of initial draws to discard from each chain. If <code>burnin = NULL</code> , use <code>object\$burnin</code> .
level	Numeric value indicating the credibility level.

Value

An object of class `manmetavar.mplus.diagnostics` containing a parameter-level diagnostics data frame and a run-level diagnostics data frame.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMetaVAR\(\)](#), [FitMplus\(\)](#), [FitNaive\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitMplus(data = data, seed = seed)
diagnostics <- FitMplusDiagnostics(fit)
diagnostics$parameters
diagnostics$run

## End(Not run)
```

FitNaive	<i>Naive</i>
----------	--------------

Description

The function performs the naive “fit-many-then-summarize”.

Usage

```
FitNaive(fit, seed = NULL)
```

Arguments

- `fit` R object. Output of the [FitDTVAR\(\)](#) function.
- `seed` Integer. Random seed.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMetaVAR\(\)](#), [FitMplus\(\)](#), [FitMplusDiagnostics\(\)](#), [MplusInput\(\)](#)

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
fit <- FitDTVAR(data = data, seed = seed)
naive <- FitNaive(fit = fit, seed = seed)
summary(naive)
print(naive)
coef(naive)
vcov(naive)

## End(Not run)
```

GenData

Simulate Data

Description

The function simulates data using the `simStateSpace::SimSSMIVary()` function.

Usage

```
GenData(taskid, seed = NULL)
```

Arguments

taskid	Positive integer. Task ID.
seed	Integer. Random seed.

Examples

```
## Not run:
seed <- 42
data <- GenData(taskid = 1, seed = seed)
print(data)
summary(data)
plot(data)

## End(Not run)
```

LoadMplusDiagnostics *Load Both Prior Conditions of the Bundled Mplus Diagnostics*

Description

Loads and combines diagnostics_default and diagnostics_priors for diagnostic plots and comparisons between prior specifications.

Usage

```
LoadMplusDiagnostics()
```

Value

A manmetavar.mplus.diagnostics.all object containing parameter and run diagnostics for both prior conditions, in the original combined task, method, replication, and parameter order.

Examples

```
## Not run:
diagnostics <- LoadMplusDiagnostics()
FigMplusDiagnosticsHeatmap(diagnostics, comparison = "difference")

## End(Not run)
```

manmetavar-data-methods
Methods for Objects of Class manmetavar.data

Description

This page documents the available methods for objects of class manmetavar.data.

Usage

```
## S3 method for class 'manmetavar.data'
print(x, ...)

## S3 method for class 'manmetavar.data'
summary(object, ...)

## S3 method for class 'manmetavar.data'
plot(x, ...)
```

Arguments

x	Object of class <code>manmetavar.data</code> .
...	additional arguments.
object	Object of class <code>manmetavar.data</code> .

Author(s)

Ivan Jacob Agaloos Pesigan

manmetavar-dtvar-methods

Methods for Objects of Class `manmetavar.dtvvar`

Description

This page documents the available methods for objects of class `manmetavar.dtvvar`.

Usage

```
## S3 method for class 'manmetavar.dtvvar'
coef(
  object,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  ncores = NULL,
  ...
)

## S3 method for class 'manmetavar.dtvvar'
vcov(
  object,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  robust = FALSE,
  ncores = NULL,
  ...
)
```

```
## S3 method for class 'manmetavar.dtvar'
print(
  x,
  means = FALSE,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  digits = 4,
  ncores = NULL,
  ...
)

## S3 method for class 'manmetavar.dtvar'
summary(
  object,
  means = FALSE,
  mu = TRUE,
  alpha = TRUE,
  beta = TRUE,
  nu = TRUE,
  psi = TRUE,
  theta = TRUE,
  digits = 4,
  ncores = NULL,
  ...
)
```

Arguments

object	Object of class <code>manmetavar.dtvar</code> .
mu	Logical. If <code>mu = TRUE</code> , include estimates of the <code>mu</code> vector, if available. If <code>mu = FALSE</code> , exclude estimates of the <code>mu</code> vector.
alpha	Logical. If <code>alpha = TRUE</code> , include estimates of the <code>alpha</code> vector, if available. If <code>alpha = FALSE</code> , exclude estimates of the <code>alpha</code> vector.
beta	Logical. If <code>beta = TRUE</code> , include estimates of the <code>beta</code> matrix, if available. If <code>beta = FALSE</code> , exclude estimates of the <code>beta</code> matrix.
nu	Logical. If <code>nu = TRUE</code> , include estimates of the <code>nu</code> vector, if available. If <code>nu = FALSE</code> , exclude estimates of the <code>nu</code> vector.
psi	Logical. If <code>psi = TRUE</code> , include estimates of the <code>psi</code> matrix, if available. If <code>psi = FALSE</code> , exclude estimates of the <code>psi</code> matrix.
theta	Logical. If <code>theta = TRUE</code> , include estimates of the <code>theta</code> matrix, if available. If <code>theta = FALSE</code> , exclude estimates of the <code>theta</code> matrix.
ncores	Positive integer. Number of cores to use.

...	additional arguments.
robust	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix.
x	Object of class <code>manmetavar.dtvvar</code> .
means	Logical. If <code>means = TRUE</code> , return means. Otherwise, the function returns raw estimates.
digits	Integer indicating the number of decimal places to display.

Author(s)

Ivan Jacob Agaloos Pesigan

manmetavar-metavar-methods

Methods for Objects of Class `manmetavar.metavar`

Description

This page documents the available methods for objects of class `manmetavar.metavar`.

This page documents the available methods for objects of class `manmetavar.naive`.

Usage

```
## S3 method for class 'manmetavar.metavar'
coef(object, ...)

## S3 method for class 'manmetavar.metavar'
vcov(object, robust = NULL, ...)

## S3 method for class 'manmetavar.metavar'
print(x, alpha = NULL, robust = NULL, digits = 4, ...)

## S3 method for class 'manmetavar.metavar'
summary(object, alpha = NULL, robust = NULL, digits = 4, ...)

## S3 method for class 'manmetavar.metavar'
confint(object, parm = NULL, level = 0.95, robust = NULL, ...)

## S3 method for class 'manmetavar.naive'
coef(object, ...)

## S3 method for class 'manmetavar.naive'
vcov(object, ...)

## S3 method for class 'manmetavar.naive'
```

```
print(x, ...)

## S3 method for class 'manmetavar.naive'
summary(object, alpha = 0.05, digits = 4, ...)
```

Arguments

object	Object of class <code>manmetavar.naive</code> .
...	additional arguments.
robust	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix. If NULL, the function will check object if robust standard errors are available.
x	Object of class <code>manmetavar.naive</code> .
alpha	Numeric vector. Significance level α .
digits	Integer indicating the number of decimal places to display.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.

Author(s)

Ivan Jacob Agaloos Pesigan

manmetavar-mplus-methods

Methods for Objects of Class `manmetavar.mplus`

Description

This page documents the available methods for objects of class `manmetavar.mplus`.

Usage

```
## S3 method for class 'manmetavar.mplus'
coef(object, median = TRUE, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
vcov(object, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
summary(object, alpha = 0.05, median = TRUE, digits = 4, burnin = NULL, ...)

## S3 method for class 'manmetavar.mplus'
confint(object, parm = NULL, level = 0.95, burnin = NULL, ...)
```

```
## S3 method for class 'manmetavar.mplus'
plot(
  x,
  what = "posterior",
  parm = NULL,
  level = 0.95,
  burnin = NULL,
  legend_loc = "topright",
  ...
)
```

Arguments

object	Object of class <code>manmetavar.mplus</code> .
median	Logical. If <code>median = TRUE</code> , return median of the posterior. If <code>median = FALSE</code> , return mean of the posterior.
burnin	Integer indicating initial samples to discard. If <code>burnin = NULL</code> , use the burn-in stored in <code>object\$burnin</code> .
...	additional arguments.
alpha	Numeric vector. Significance level α .
digits	Integer indicating the number of decimal places to display.
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
x	Object of class <code>manmetavar.mplus</code> .
what	Character string. If <code>what = "posterior"</code> , return posterior distribution plots. If <code>what = "trace"</code> , return trace plots. If <code>what = "rhat"</code> , <code>"ess"</code> , or <code>"mcse"</code> , return the corresponding Bayesian diagnostic plot from <code>FitMplusDiagnostics()</code> .
legend_loc	Character string. Legend location.

Author(s)

Ivan Jacob Agaloos Pesigan

model	<i>Model Parameters</i>
-------	-------------------------

Description

Model Parameters

Usage

```
data(model)
```

Format

A list with 15 elements:

k Number of variables.

mu_mu Mean of the set-point vector μ .

mu_sigma Covariance matrix of the parameter μ .

mu_sigma_l Cholesky factor of the covariance matrix of the parameter μ .

beta_mu Mean of lagged coefficients matrix β .

beta_sigma Covariance matrix of the parameter $\text{vec}(\beta)$.

beta_sigma_l Cholesky factor of the covariance matrix of the parameter $\text{vec}(\beta)$.

psi Process noise covariance matrix Ψ .

psi_l Cholesky factor of the process noise covariance matrix Ψ .

psi_d_ldl uc_d of the LDL' decomposition of the process noise covariance matrix Ψ . See [fitVARMxID::LDL\(\)](#).

psi_l_ldl s_l of the LDL' decomposition of the process noise covariance matrix Ψ . See [fitVARMxID::LDL\(\)](#).

ma_fixed Vector of fixed effects $\theta = [\mu, \text{vec}(\beta)]'$

ma_random Matrix of random effects $\theta = [\mu, \text{vec}(\beta)]'$

ma_random_d_ldl uc_d of the LDL' decomposition of the random-effects covariance. See [fitVARMxID::LDL\(\)](#).

ma_random_l_ldl s_l of the LDL' decomposition of the random-effects covariance. See [fitVARMxID::LDL\(\)](#).

Author(s)

Ivan Jacob Agaloos Pesigan

MplusInput

Create Mplus Input File

Description

The function creates an Mplus input file.

Usage

```
MplusInput(  
  fn_data,  
  fn_posterior,  
  fn_factorscores,  
  chains,  
  iter,  
  fscores,  
  plot,  
  default_priors = TRUE,  
  ncores = NULL,  
  seed = NULL  
)
```

Arguments

fn_data	Character string. Filename for data file.
fn_posterior	Character string. Filename for posterior output.
fn_factorscores	Character string. Filename for factor scores output.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.
default_priors	Logical. If default_priors = TRUE, use Mplus default priors.
ncores	Positive integer. Number of cores to use.
seed	Integer. Random seed.

See Also

Other Model Fitting Functions: [FitDTVAR\(\)](#), [FitMetaVAR\(\)](#), [FitMplus\(\)](#), [FitMplusDiagnostics\(\)](#), [FitNaive\(\)](#)

Examples

```
cat(  
  MplusInput(  
    fn_data = "data.dat",  
    fn_posterior = "posterior.dat",  
    fn_factorscores = "factorscores.dat",  
    chains = 2L,  
    iter = 40000L,  
    fscores = 1000L,  
    plot = TRUE,  
    default_priors = TRUE,  
    ncores = NULL,  
    seed = 42
```

```
)  
)
```

params	<i>Simulation Parameters</i>
--------	------------------------------

Description

Simulation Parameters

Usage

```
data(params)
```

Format

A dataframe with 12 rows and 3 columns:

- taskid** Simulation Task ID.
- n** Sample size.
- time** Number of measurement occasions. If NA, measurement occasions vary across IDs.
- heterogeneity** Transition-parameter heterogeneity multiplier: 0, 1, or 2.

Author(s)

Ivan Jacob Agaloos Pesigan

population	<i>Calibrated Population Parameters</i>
------------	---

Description

Population moments implied by the stationary transition-matrix generator. The moments of the set points are analytical. The moments of the transition matrices are calculated by Monte Carlo integration over the stationary region for each nonzero heterogeneity condition.

Usage

```
data(population)
```

Format

A list with two elements:

conditions Named list indexed by heterogeneity. Each element contains the calibrated means and covariance matrices, a named population parameter vector, and Monte Carlo calibration information.

calibration Metadata describing the generator, package version, random seed, population size, batch size, stationarity margin, and generation time.

Author(s)

Ivan Jacob Agaloos Pesigan

results

Simulation Results

Description

Simulation Results

Usage

`data(results)`

Format

A data frame with one row per design condition, method, interval type, and parameter:

taskid Simulation task ID.

replications Number of replications.

replications_used Number of admissible replications contributing to the summary.

success_rate Proportion of requested replications that were admissible and contributed to the summary.

parnames Parameter name.

parameter Calibrated population parameter value. For transition parameters under stability rejection, this is the realized truncated population value rather than the nominal untruncated value.

method Estimation method: MetaVAR, BMLVAR with default priors, BMLVAR with user-defined priors, or the uncertainty-uncorrected method.

n Number of persons.

time Number of measurement occasions; NA denotes the unbalanced condition.

heterogeneity Transition-parameter heterogeneity multiplier: 0, 1, or 2.

ci Confidence or credible interval method.

est Mean parameter estimate.

se Mean standard error or posterior standard deviation.

z Mean test statistic when available.

p Mean p-value when available.

ll Mean lower interval limit.

ul Mean upper interval limit.

sig Proportion statistically significant when available.

zero_hit Proportion of intervals containing zero.

theta_hit Proportion of intervals containing the calibrated population value.

sq_error Mean squared error.

bias Mean estimate minus the calibrated population value.

rel_bias Relative bias for nonzero population values and NA when the population value is zero.

rmse Root mean squared error.

n_bias Number of finite replication-level bias values used to calculate the Monte Carlo standard error of bias.

n_rmse Number of finite replication-level squared errors used to calculate the Monte Carlo standard error of RMSE.

n_coverage Number of finite coverage indicators used to calculate the Monte Carlo standard error of coverage.

n_rejection Number of finite rejection indicators used to calculate the Monte Carlo standard error of the rejection rate.

mcse_bias Monte Carlo standard error of bias.

mcse_rmse Delta-method Monte Carlo standard error of RMSE, obtained from the Monte Carlo standard error of mean squared error.

coverage Coverage probability.

mcse_coverage Binomial Monte Carlo standard error of coverage.

rejection_rate Proportion of intervals excluding zero.

mcse_rejection_rate Binomial Monte Carlo standard error of the rejection rate.

power Rejection rate for nonzero population values and NA for zero population values.

mcse_power Monte Carlo standard error of power for nonzero population values and NA for zero population values.

type1_error Rejection rate for zero population values and NA for nonzero population values.

mcse_type1_error Monte Carlo standard error of the Type I error rate for zero population values and NA for nonzero population values.

par_idx Parameter display index.

Author(s)

Ivan Jacob Agaloos Pesigan

Sim	<i>Simulation Replication</i>
-----	-------------------------------

Description

Simulation Replication

Usage

```
Sim(
  taskid,
  repid,
  output_folder,
  overwrite,
  integrity,
  seed,
  data,
  naive,
  metavar,
  mplus,
  chains,
  iter,
  fscores,
  plot
)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
seed	Integer. Random seed.
data	Logical. Simulate data.
naive	Logical. If naive = TRUE, fit the naive approach.
metavar	Logical. If metavar = TRUE, fit the model using the metaDyn package.
mplus	Logical. If mplus = TRUE, fit the model using DSEM in Mplus.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitDTVAR

Simulation Replication - FitDTVAR

Description

Simulation Replication - FitDTVAR

Usage

```
SimFitDTVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Simulation file suffix returned by .SimSuffix().
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMetaVAR	<i>Simulation Replication - FitMetaVAR</i>
---------------	--

Description

Simulation Replication - FitMetaVAR

Usage

SimFitMetaVAR(taskid, repid, output_folder, seed, suffix, overwrite, integrity)

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Simulation file suffix returned by .SimSuffix().
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMplus

Simulation Replication - FitMplus

Description

Simulation Replication - FitMplus

Usage

```
SimFitMplus(
  taskid,
  repid,
  output_folder,
  seed,
  suffix,
  overwrite,
  integrity,
  chains,
  iter,
  fscores,
  plot
)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Simulation file suffix returned by .SimSuffix().
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMplusDiagnostics

Simulation Replication - FitMplus Diagnostics

Description

Simulation Replication - FitMplus Diagnostics

Usage

```
SimFitMplusDiagnostics(  
  taskid,  
  repid,  
  output_folder,  
  seed,  
  suffix,  
  overwrite,  
  integrity  
)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Simulation file suffix returned by <code>.SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMplusPriors	<i>Simulation Replication - FitMplus (User Defined Priors)</i>
-------------------	--

Description

Simulation Replication - FitMplus (User Defined Priors)

Usage

```
SimFitMplusPriors(
  taskid,
  repid,
  output_folder,
  seed,
  suffix,
  overwrite,
  integrity,
  chains,
  iter,
  fscores,
  plot
)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Simulation file suffix returned by .SimSuffix().
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
chains	Integer. Number of chains.
iter	Integer. Number of iterations.
fscores	Integer. Number of iterations for factor scores.
plot	Logical. If plot = TRUE, add PLOT: TYPE = PLOT3; to Mplus input file.

Details

This function is executed via the Sim function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitMplusPriorsDiagnostics

Simulation Replication - FitMplus Diagnostics (User Defined Priors)

Description

Simulation Replication - FitMplus Diagnostics (User Defined Priors)

Usage

```
SimFitMplusPriorsDiagnostics(  
  taskid,  
  repid,  
  output_folder,  
  seed,  
  suffix,  
  overwrite,  
  integrity  
)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Simulation file suffix returned by <code>.SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFitNaive	<i>Simulation Replication - FitNaive</i>
-------------	--

Description

Simulation Replication - FitNaive

Usage

```
SimFitNaive(taskid, repid, output_folder, seed, suffix, overwrite, integrity)
```

Arguments

taskid	Positive integer. Task ID.
repid	Positive integer. Replication ID.
output_folder	Character string. Output folder.
seed	Integer. Random seed.
suffix	Character string. Simulation file suffix returned by <code>.SimSuffix()</code> .
overwrite	Logical. Overwrite existing output in <code>output_folder</code> .
integrity	Logical. If <code>integrity = TRUE</code> , check for the output file integrity when <code>overwrite = FALSE</code> .

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

SimFN	<i>Simulation File Name</i>
-------	-----------------------------

Description

Simulation File Name

Usage

SimFN(output_type, output_folder, suffix)

Arguments

- output_type Character string. Output type. Valid values include "data", "fit-dt-var-mx", "fit-meta-var-mx", "fit-mplus", and "fit-naive".
- output_folder Character string. Output folder.
- suffix Character string. Simulation file suffix returned by .SimSuffix().

Value

Returns a character string file name with the output_folder in the OS-specific format.

SimGenData	<i>Simulation Replication - GenData</i>
------------	---

Description

Simulation Replication - GenData

Usage

SimGenData(taskid, repid, output_folder, seed, suffix, overwrite, integrity)

Arguments

- taskid Positive integer. Task ID.
- repid Positive integer. Replication ID.
- output_folder Character string. Output folder.
- seed Integer. Random seed.
- suffix Character string. Simulation file suffix returned by .SimSuffix().
- overwrite Logical. Overwrite existing output in output_folder.
- integrity Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.

Details

This function is executed via the `Sim` function.

Value

The output is saved as an external file in `output_folder`.

Author(s)

Ivan Jacob Agaloos Pesigan

<code>SimProj</code>	<i>Simulation Project Name</i>
----------------------	--------------------------------

Description

Simulation Project Name

Usage

```
SimProj()
```

Value

Returns the project name as a character string.

Author(s)

Ivan Jacob Agaloos Pesigan

<code>simulation_diagnostics</code>	<i>Simulation Diagnostics</i>
-------------------------------------	-------------------------------

Description

Simulation diagnostics generated from the machine-readable replication status manifests. The objects contain convergence/admissibility counts, boundary or near-zero heterogeneity diagnostics, and runtime summaries.

Usage

```
data(simulation_diagnostics)
```

Format

A list with components thresholds, status, status_summary, boundary_parameter_replications, boundary_parameter_summary, boundary_replication_diagnostics, boundary_replication_summary, runtime_replications, and runtime_summary.

Sum	<i>Summary</i>
-----	----------------

Description

Summary

Usage

```
Sum(  
  taskid,  
  reps,  
  output_folder,  
  overwrite,  
  integrity,  
  naive,  
  metavar_normal,  
  metavar_robust,  
  mplus,  
  ncores  
)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
naive	Logical. If naive = TRUE, summarize naive estimates.
metavar_normal	Logical. If metavar_normal = TRUE, summarize metaVAR model using normal confidence intervals.
metavar_robust	Logical. If metavar_robust = TRUE, summarize metaVAR model using robust (sandwich) confidence intervals.
mplus	Logical. If mplus = TRUE, summarize the DSEM model.
ncores	Positive integer. Number of cores to use.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumDiagnostics

Summarize Simulation Diagnostics

Description

Summarizes the machine-readable status manifests, boundary or near-zero heterogeneity diagnostics, and runtime for a simulation task.

Usage

```
SumDiagnostics(
  taskid,
  reps,
  output_folder,
  overwrite,
  integrity,
  naive,
  metavar,
  mplus,
  variance_tol = 1e-06,
  eigen_tol = 1e-08
)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
naive	Logical. If naive = TRUE, fit the naive approach.
metavar	Logical. If metavar = TRUE, fit the model using the metaDyn package.
mplus	Logical. If mplus = TRUE, fit the model using DSEM in Mplus.
variance_tol	Numeric scalar. Variance estimates no greater than this value are classified as boundary estimates for ML-based methods and as near-zero estimates for Bayesian DSEM.
eigen_tol	Numeric scalar. Estimated heterogeneity covariance matrices with minimum eigenvalues no greater than this value are classified as near singular.

Value

The output is saved as an external file in output_folder and is returned invisibly.

SumFitMetaVARNormal	Summary: Normal Theory (FitMetaVAR)
---------------------	-------------------------------------

Description

Summary: Normal Theory (FitMetaVAR)

Usage

SumFitMetaVARNormal(taskid, reps, output_folder, overwrite, integrity, ncores)

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMetaVARRobust	<i>Summary: Robust (FitMetaVAR)</i>
---------------------	-------------------------------------

Description

Summary: Robust (FitMetaVAR)

Usage

```
SumFitMetaVARRobust(taskid, reps, output_folder, overwrite, integrity, ncores)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMplus	<i>Summary (FitMplus)</i>
-------------	---------------------------

Description

Summary (FitMplus)

Usage

```
SumFitMplus(taskid, reps, output_folder, overwrite, integrity, ncores)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMplusDiagnostics

Summary (FitMplus Diagnostics)

Description

Summary (FitMplus Diagnostics)

Usage

```
SumFitMplusDiagnostics(  
  taskid,  
  reps,  
  output_folder,  
  overwrite,  
  integrity,  
  ncores  
)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMplusPriors	<i>Summary (FitMplus (User Defined Priors))</i>
-------------------	---

Description

Summary (FitMplus (User Defined Priors))

Usage

```
SumFitMplusPriors(taskid, reps, output_folder, overwrite, integrity, ncores)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitMplusPriorsDiagnostics

Summary (FitMplus Diagnostics with User Defined Priors)

Description

Summary (FitMplus Diagnostics with User Defined Priors)

Usage

```
SumFitMplusPriorsDiagnostics(  
  taskid,  
  reps,  
  output_folder,  
  overwrite,  
  integrity,  
  ncores  
)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

SumFitNaive

Summary: Naive

Description

Summary: Naive

Usage

```
SumFitNaive(taskid, reps, output_folder, overwrite, integrity, ncores)
```

Arguments

taskid	Positive integer. Task ID.
reps	Positive integer. Number of replications.
output_folder	Character string. Output folder.
overwrite	Logical. Overwrite existing output in output_folder.
integrity	Logical. If integrity = TRUE, check for the output file integrity when overwrite = FALSE.
ncores	Positive integer. Number of cores to use.

Details

This function is executed via the Sum function.

Value

The output is saved as an external file in output_folder.

Author(s)

Ivan Jacob Agaloos Pesigan

TabMplusDiagSensitivity

Bayesian Diagnostic Failure-Rate Sensitivity Table

Description

Create a simulation-case-level table of Bayesian Mplus diagnostic failure rates. Unlike the overview figure, the function retains one row for every simulation task ID and does not average across simulation cases.

Usage

```

TabMplusDiagSensitivity(
  diagnostics,
  comparison = "difference",
  diagnostic = "Any diagnostic",
  unit = "replication",
  taskid = NULL,
  target = NULL,
  rhat_threshold = 1.01,
  ess_threshold = 400,
  mcse_threshold = 0.05,
  relative_mcse = TRUE,
  output = "data.frame",
  scale = "percent",
  digits = 0L
)

```

Arguments

diagnostics	An all-task diagnostics object containing a parameter's data frame, or the parameter-level data frame itself.
comparison	Character string. "difference" returns paired user-prior minus default-prior failure-rate differences. "levels" returns the two prior-specific failure rates. "all" returns the default rate, user-prior rate, and paired difference.
diagnostic	One or more diagnostic panels. Available values are "Any diagnostic", "R-hat", "Bulk ESS", "Tail ESS", and "Relative MCSE" when relative_mcse = TRUE.
unit	Character string controlling the unit classified as failed. "replication" classifies a replication as failed when any parameter in the selected block fails. "parameter" averages failures over parameter-replication pairs.
taskid	Optional positive integer task IDs to include.
target	Optional parameter blocks to include. Available values are "Innovation", "FE", and "RE".
rhat_threshold	Numeric R-hat threshold.
ess_threshold	Numeric bulk and tail effective sample size threshold.
mcse_threshold	Numeric Monte Carlo standard error threshold.
relative_mcse	Logical. If TRUE, Monte Carlo standard errors are divided by the posterior standard deviation before classifying failures.
output	Character string. "data.frame" returns a wide data frame with simulation-design columns, "matrix" returns only the numeric case-by-summary matrix, and "long" returns one row per task, block, diagnostic, and prior comparison.
scale	Character string. "proportion" returns values on the 0-to-1 scale. "percent" multiplies prior-specific failure rates by 100 and expresses differences in percentage points.
digits	Nonnegative integer used to round the returned values.

Details

Failure rates are computed separately within each task ID. For comparison = "difference", replications are paired before calculating the user-prior minus default-prior difference. Negative differences favor the user-specified priors.

The default unit = "replication" answers the question: within a given simulation case, what percentage of replications had at least one failed parameter in the selected parameter block?

Value

A data frame or numeric matrix. For output = "matrix", simulation design information is stored in the "case_data" attribute.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
## Not run:
data(diagnostics, package = "manMetaVAR")

# Compact sensitivity matrix: one row per simulation case
TabMplusDiagSensitivity(
  diagnostics = diagnostics,
  comparison = "difference",
  output = "matrix"
)

# Default, user-prior, and difference columns
TabMplusDiagSensitivity(
  diagnostics = diagnostics,
  comparison = "all",
  output = "data.frame"
)

# Diagnostic-specific table
TabMplusDiagSensitivity(
  diagnostics = diagnostics,
  comparison = "difference",
  diagnostic = c("R-hat", "Bulk ESS", "Tail ESS", "Relative MCSE")
)

## End(Not run)
```

Index

- * **Compression Functions**
 - Compress, [7](#)
- * **Data Generation Functions**
 - GenData, [18](#)
- * **Figure Functions**
 - FigMetricHeatmap, [8](#)
 - FigMplusDiagnosticsHeatmap, [9](#)
 - FigMplusDiagnosticsOverview, [11](#)
 - FigOverview, [13](#)
- * **Model Fitting Functions**
 - FitDTVAR, [14](#)
 - FitMetaVAR, [15](#)
 - FitMplus, [15](#)
 - FitMplusDiagnostics, [17](#)
 - FitNaive, [18](#)
 - MplusInput, [26](#)
- * **check**
 - Check, [3](#)
 - CheckFitDTVAR, [3](#)
 - CheckFitMetaVAR, [4](#)
 - CheckFitMplus, [5](#)
 - CheckFitMplusPriors, [5](#)
 - CheckFitNaive, [6](#)
- * **compress**
 - Compress, [7](#)
- * **data**
 - diagnostics, [7](#)
 - LoadMplusDiagnostics, [19](#)
 - model, [25](#)
 - params, [27](#)
 - population, [28](#)
 - results, [28](#)
 - simulation_diagnostics, [39](#)
- * **diagnostics**
 - diagnostics, [7](#)
 - FigMplusDiagnosticsHeatmap, [9](#)
 - FigMplusDiagnosticsOverview, [11](#)
 - FitMplusDiagnostics, [17](#)
 - LoadMplusDiagnostics, [19](#)
 - SimFitMplusDiagnostics, [34](#)
 - SimFitMplusPriorsDiagnostics, [36](#)
 - simulation_diagnostics, [39](#)
 - SumDiagnostics, [41](#)
 - SumFitMplusDiagnostics, [44](#)
 - SumFitMplusPriorsDiagnostics, [46](#)
 - TabMplusDiagSensitivity, [47](#)
- * **figure**
 - FigMetricHeatmap, [8](#)
 - FigMplusDiagnosticsHeatmap, [9](#)
 - FigMplusDiagnosticsOverview, [11](#)
 - FigOverview, [13](#)
- * **fit**
 - FitDTVAR, [14](#)
 - FitMplus, [15](#)
 - FitMplusDiagnostics, [17](#)
 - MplusInput, [26](#)
 - SimFitDTVAR, [31](#)
 - SimFitMetaVAR, [32](#)
 - SimFitMplus, [33](#)
 - SimFitMplusDiagnostics, [34](#)
 - SimFitMplusPriors, [35](#)
 - SimFitMplusPriorsDiagnostics, [36](#)
 - SimFitNaive, [37](#)
- * **gendata**
 - GenData, [18](#)
 - SimGenData, [38](#)
- * **manMetaVAR**
 - Check, [3](#)
 - CheckFitDTVAR, [3](#)
 - CheckFitMetaVAR, [4](#)
 - CheckFitMplus, [5](#)
 - CheckFitMplusPriors, [5](#)
 - CheckFitNaive, [6](#)
 - Compress, [7](#)
 - FigMetricHeatmap, [8](#)
 - FigMplusDiagnosticsHeatmap, [9](#)
 - FigMplusDiagnosticsOverview, [11](#)
 - FigOverview, [13](#)

- FitDTVAR, 14
- FitMetaVAR, 15
- FitMplus, 15
- FitMplusDiagnostics, 17
- FitNaive, 18
- GenData, 18
- MplusInput, 26
- Sim, 30
- SimFitDTVAR, 31
- SimFitMetaVAR, 32
- SimFitMplus, 33
- SimFitMplusDiagnostics, 34
- SimFitMplusPriors, 35
- SimFitMplusPriorsDiagnostics, 36
- SimFitNaive, 37
- SimFN, 38
- SimGenData, 38
- SimProj, 39
- Sum, 40
- SumDiagnostics, 41
- SumFitMetaVARNormal, 42
- SumFitMetaVARRobust, 43
- SumFitMplus, 43
- SumFitMplusDiagnostics, 44
- SumFitMplusPriors, 45
- SumFitMplusPriorsDiagnostics, 46
- SumFitNaive, 47
- TabMplusDiagSensitivity, 47
- * meta**
 - FitMetaVAR, 15
 - FitNaive, 18
- * methods**
 - manmetavar-data-methods, 20
 - manmetavar-dtvar-methods, 20
 - manmetavar-metavar-methods, 22
 - manmetavar-mplus-methods, 24
- * parameters**
 - model, 25
 - params, 27
 - population, 28
- * results**
 - results, 28
- * sensitivity**
 - FigMplusDiagnosticsHeatmap, 9
 - FigMplusDiagnosticsOverview, 11
 - TabMplusDiagSensitivity, 47
- * simulation**
 - Check, 3
 - CheckFitDTVAR, 3
 - CheckFitMetaVAR, 4
 - CheckFitMplus, 5
 - CheckFitMplusPriors, 5
 - diagnostics, 7
 - FigMplusDiagnosticsHeatmap, 9
 - FigMplusDiagnosticsOverview, 11
 - LoadMplusDiagnostics, 19
 - Sim, 30
 - SimFitDTVAR, 31
 - SimFitMetaVAR, 32
 - SimFitMplus, 33
 - SimFitMplusDiagnostics, 34
 - SimFitMplusPriors, 35
 - SimFitMplusPriorsDiagnostics, 36
 - SimFitNaive, 37
 - SimFN, 38
 - SimGenData, 38
 - SimProj, 39
 - simulation_diagnostics, 39
 - Sum, 40
 - SumDiagnostics, 41
 - SumFitMetaVARNormal, 42
 - SumFitMetaVARRobust, 43
 - SumFitMplus, 43
 - SumFitMplusDiagnostics, 44
 - SumFitMplusPriors, 45
 - SumFitMplusPriorsDiagnostics, 46
 - SumFitNaive, 47
 - TabMplusDiagSensitivity, 47
- * summary**
 - Sum, 40
 - SumDiagnostics, 41
 - SumFitMetaVARNormal, 42
 - SumFitMetaVARRobust, 43
 - SumFitMplus, 43
 - SumFitMplusDiagnostics, 44
 - SumFitMplusPriors, 45
 - SumFitMplusPriorsDiagnostics, 46
 - SumFitNaive, 47
- * table**
 - TabMplusDiagSensitivity, 47
- Check, 3
- CheckFitDTVAR, 3
- CheckFitMetaVAR, 4
- CheckFitMplus, 5
- CheckFitMplusPriors, 5

CheckFitNaive, 6
 coef.manmetavar.dtvvar
 (manmetavar-dtvvar-methods), 20
 coef.manmetavar.metavar
 (manmetavar-metavar-methods),
 22
 coef.manmetavar.mplus
 (manmetavar-mplus-methods), 24
 coef.manmetavar.naive
 (manmetavar-metavar-methods),
 22
 Compress, 7
 confint.manmetavar.metavar
 (manmetavar-metavar-methods),
 22
 confint.manmetavar.mplus
 (manmetavar-mplus-methods), 24

 diagnostics, 7
 diagnostics_default(diagnostics), 7
 diagnostics_priors(diagnostics), 7

 FigMetricHeatmap, 8
 FigMetricHeatmap(), 9, 11, 13, 14
 FigMplusDiagnosticsHeatmap, 9
 FigMplusDiagnosticsHeatmap(), 9, 11, 13,
 14
 FigMplusDiagnosticsOverview, 11
 FigMplusDiagnosticsOverview(), 9, 11, 14
 FigOverview, 13
 FigOverview(), 9, 11, 13
 FitDTVAR, 14
 FitDTVAR(), 15–18, 26
 FitMetaVAR, 15
 FitMetaVAR(), 14, 16–18, 26
 FitMplus, 15
 FitMplus(), 14, 15, 17, 18, 26
 FitMplusDiagnostics, 17
 FitMplusDiagnostics(), 14–16, 18, 25, 26
 FitNaive, 18
 FitNaive(), 14–17, 26
 fitVARMxID, 14
 fitVARMxID::LDL(), 25

 GenData, 18
 GenData(), 14, 16

 LoadMplusDiagnostics, 19
 LoadMplusDiagnostics(), 8

 manmetavar-data-methods, 20
 manmetavar-dtvvar-methods, 20
 manmetavar-metavar-methods, 22
 manmetavar-mplus-methods, 24
 metaDyn, 15
 model, 25
 MplusInput, 26
 MplusInput(), 14–18

 params, 27
 plot.manmetavar.data
 (manmetavar-data-methods), 20
 plot.manmetavar.mplus
 (manmetavar-mplus-methods), 24
 population, 28
 print.manmetavar.data
 (manmetavar-data-methods), 20
 print.manmetavar.dtvvar
 (manmetavar-dtvvar-methods), 20
 print.manmetavar.metavar
 (manmetavar-metavar-methods),
 22
 print.manmetavar.naive
 (manmetavar-metavar-methods),
 22

 results, 28

 Sim, 30
 SimFitDTVAR, 31
 SimFitMetaVAR, 32
 SimFitMplus, 33
 SimFitMplusDiagnostics, 34
 SimFitMplusPriors, 35
 SimFitMplusPriorsDiagnostics, 36
 SimFitNaive, 37
 SimFN, 38
 SimGenData, 38
 SimProj, 39
 simStateSpace::SimSSMIVary(), 18
 simulation_diagnostics, 39
 Sum, 40
 SumDiagnostics, 41
 SumFitMetaVARNormal, 42
 SumFitMetaVARRobust, 43
 SumFitMplus, 43
 SumFitMplusDiagnostics, 44
 SumFitMplusDiagnostics(), 8
 SumFitMplusPriors, 45

SumFitMplusPriorsDiagnostics, [46](#)
SumFitMplusPriorsDiagnostics(), [8](#)
SumFitNaive, [47](#)
summary.manmetavar.data
 (manmetavar-data-methods), [20](#)
summary.manmetavar.dtvvar
 (manmetavar-dtvvar-methods), [20](#)
summary.manmetavar.metavar
 (manmetavar-metavar-methods),
 [22](#)
summary.manmetavar.mplus
 (manmetavar-mplus-methods), [24](#)
summary.manmetavar.naive
 (manmetavar-metavar-methods),
 [22](#)

TabMplusDiagSensitivity, [47](#)

vcov.manmetavar.dtvvar
 (manmetavar-dtvvar-methods), [20](#)
vcov.manmetavar.metavar
 (manmetavar-metavar-methods),
 [22](#)
vcov.manmetavar.mplus
 (manmetavar-mplus-methods), [24](#)
vcov.manmetavar.naive
 (manmetavar-metavar-methods),
 [22](#)