

# Package ‘metaDyn’

April 16, 2026

**Title** Multivariate Meta-Analysis of Dynamic Model Estimates

**Version** 1.0.2

**Description** Fits fixed-, random-, or mixed-effects multivariate meta-analysis models using dynamic model estimates from each individual building on and extending Lee and Gates (2023) <[doi:10.1080/00273171.2023.2229310](https://doi.org/10.1080/00273171.2023.2229310)>.

**URL** <https://github.com/jeksterslab/metaDyn>,  
<https://jeksterslab.github.io/metaDyn/>

**BugReports** <https://github.com/jeksterslab/metaDyn/issues>

**License** MIT + file LICENSE

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**Depends** R (>= 4.1.0), OpenMx (>= 2.22.10)

**Imports** Matrix, fitVARMxID (>= 1.0.2)

**Suggests** knitr, rmarkdown, testthat, simStateSpace, MASS, metaSEM,  
expm

**Config/roxygen2/version** 7.3.3.9000

**NeedsCompilation** no

**Author** Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:  
<<https://orcid.org/0000-0003-4818-8420>>)

**Maintainer** Ivan Jacob Agaloos Pesigan <[r.jeksterslab@gmail.com](mailto:r.jeksterslab@gmail.com)>

## Contents

|                               |    |
|-------------------------------|----|
| coef.metadynmeta . . . . .    | 2  |
| confint.metadynmeta . . . . . | 2  |
| extract . . . . .             | 3  |
| extract.metadynmeta . . . . . | 3  |
| Meta . . . . .                | 4  |
| MetaVARMx . . . . .           | 9  |
| print.metadynmeta . . . . .   | 15 |
| summary.metadynmeta . . . . . | 16 |
| vcov.metadynmeta . . . . .    | 16 |

**Index****18**


---

|                  |                                                                      |
|------------------|----------------------------------------------------------------------|
| coef.metadynmeta | <i>Estimated Parameter Method for an Object of Class metadynmeta</i> |
|------------------|----------------------------------------------------------------------|

---

**Description**

Estimated Parameter Method for an Object of Class metadynmeta

**Usage**

```
## S3 method for class 'metadynmeta'
coef(object, ...)
```

**Arguments**

|        |                                 |
|--------|---------------------------------|
| object | an object of class metadynmeta. |
| ...    | further arguments.              |

**Value**

Returns a vector of estimated parameters.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|                     |                                                         |
|---------------------|---------------------------------------------------------|
| confint.metadynmeta | <i>Confidence Intervals for the Parameter Estimates</i> |
|---------------------|---------------------------------------------------------|

---

**Description**

Confidence Intervals for the Parameter Estimates

**Usage**

```
## S3 method for class 'metadynmeta'
confint(object, parm = NULL, level = 0.95, robust = NULL, ...)
```

**Arguments**

|        |                                                                                                                                                                                                                                |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object | an object of class metadynmeta.                                                                                                                                                                                                |
| parm   | a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.                                                          |
| level  | the confidence level required.                                                                                                                                                                                                 |
| robust | Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix. If NULL, the function will check object if robust standard errors are available. |
| ...    | further arguments.                                                                                                                                                                                                             |

**Value**

Returns a matrix of confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

extract

*Extract Generic Function*

---

**Description**

A generic function for extracting elements from objects.

**Usage**

```
extract(object, what)
```

**Arguments**

|        |                   |
|--------|-------------------|
| object | An object.        |
| what   | Character string. |

**Value**

A value determined by the specific method for the object's class.

---

|                                  |                                                          |
|----------------------------------|----------------------------------------------------------|
| <code>extract.metadynmeta</code> | <i>Extract Method for an Object of Class metadynmeta</i> |
|----------------------------------|----------------------------------------------------------|

---

### Description

Extract Method for an Object of Class metadynmeta

### Usage

```
## S3 method for class 'metadynmeta'
extract(object, what = NULL)
```

### Arguments

|                     |                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------|
| <code>object</code> | an object of class metadynmeta.                                                                                  |
| <code>what</code>   | Character string. What specific matrix to extract. If <code>what = NULL</code> , extract all available matrices. |

### Value

Returns a list of estimates.

### Author(s)

Ivan Jacob Agaloos Pesigan

---

|      |                                       |
|------|---------------------------------------|
| Meta | <i>Fit Multivariate Meta-Analysis</i> |
|------|---------------------------------------|

---

### Description

This function estimates fixed-, random-, or mixed-effects meta-analytic parameters using per-individual coefficient estimates and their sampling variance-covariance matrices. Optionally, it fits distal-outcome models in which between-person outcomes are regressed on between-person covariates and the meta-analyzed parameters/effect sizes.

### Usage

```
Meta(
  y,
  v,
  x = NULL,
  z = NULL,
  random = TRUE,
  alpha_free = NULL,
```

```
alpha_values = NULL,
alpha_lbound = NULL,
alpha_ubound = NULL,
tau_sqr_diag = FALSE,
tau_sqr_d_free = NULL,
tau_sqr_d_values = NULL,
tau_sqr_d_lbound = NULL,
tau_sqr_d_ubound = NULL,
tau_sqr_l_free = NULL,
tau_sqr_l_values = NULL,
tau_sqr_l_lbound = NULL,
tau_sqr_l_ubound = NULL,
gamma_free = NULL,
gamma_values = NULL,
gamma_lbound = NULL,
gamma_ubound = NULL,
kappa_free = NULL,
kappa_values = NULL,
kappa_lbound = NULL,
kappa_ubound = NULL,
phi_free = NULL,
phi_values = NULL,
phi_lbound = NULL,
phi_ubound = NULL,
omega_free = NULL,
omega_values = NULL,
omega_lbound = NULL,
omega_ubound = NULL,
psi_diag = FALSE,
psi_d_free = NULL,
psi_d_values = NULL,
psi_d_lbound = NULL,
psi_d_ubound = NULL,
psi_l_free = NULL,
psi_l_values = NULL,
psi_l_lbound = NULL,
psi_l_ubound = NULL,
check_estimates = TRUE,
robust = FALSE,
alpha = 0.05,
seed = NULL,
tries_explore = 100,
tries_local = 100,
max_attempts = 10,
silent = FALSE,
ncores = NULL
)
```

**Arguments**

|                               |                                                                                                                                                                              |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>y</code>                | A list. Each element of the list is a numeric vector of estimated coefficients.                                                                                              |
| <code>v</code>                | A list. Each element of the list is a sampling variance-covariance matrix of <code>y</code> .                                                                                |
| <code>x</code>                | An optional list. Each element of the list is a numeric vector of covariates.                                                                                                |
| <code>z</code>                | An optional list. Each element of the list is a numeric vector of distal outcomes.                                                                                           |
| <code>random</code>           | Logical. If <code>random = TRUE</code> , estimates random effects. If <code>random = FALSE</code> , <code>tau_sqr</code> is a null matrix.                                   |
| <code>alpha_free</code>       | Logical vector. Optional vector of free (TRUE) parameters for <code>alpha</code> .                                                                                           |
| <code>alpha_values</code>     | Numeric vector. Optional vector of starting values for <code>alpha</code> .                                                                                                  |
| <code>alpha_lbound</code>     | Numeric vector. Optional vector of lower bound values for <code>alpha</code> .                                                                                               |
| <code>alpha_ubound</code>     | Numeric vector. Optional vector of upper bound values for <code>alpha</code> .                                                                                               |
| <code>tau_sqr_diag</code>     | Logical. If <code>tau_sqr_diag = TRUE</code> , <code>tau_sqr</code> is a diagonal matrix. If <code>tau_sqr_diag = FALSE</code> , <code>tau_sqr</code> is a symmetric matrix. |
| <code>tau_sqr_d_free</code>   | Logical vector indicating free/fixed status of the elements of <code>tau_sqr_d</code> . If NULL, all element of <code>tau_sqr_d</code> are free.                             |
| <code>tau_sqr_d_values</code> | Numeric vector with starting values for <code>tau_sqr_d</code> . If NULL, defaults to a vector of ones.                                                                      |
| <code>tau_sqr_d_lbound</code> | Numeric vector with lower bounds for <code>tau_sqr_d</code> . If NULL, no lower bounds are set.                                                                              |
| <code>tau_sqr_d_ubound</code> | Numeric vector with upper bounds for <code>tau_sqr_d</code> . If NULL, no upper bounds are set.                                                                              |
| <code>tau_sqr_l_free</code>   | Logical matrix indicating which strictly-lower-triangular elements of <code>tau_sqr_l</code> are free. Ignored if <code>tau_sqr_diag = TRUE</code> .                         |
| <code>tau_sqr_l_values</code> | Numeric matrix of starting values for the strictly-lower-triangular elements of <code>tau_sqr_l</code> . If NULL, defaults to a null matrix.                                 |
| <code>tau_sqr_l_lbound</code> | Numeric matrix with lower bounds for <code>tau_sqr_l</code> . If NULL, no lower bounds are set.                                                                              |
| <code>tau_sqr_l_ubound</code> | Numeric matrix with upper bounds for <code>tau_sqr_l</code> . If NULL, no upper bounds are set.                                                                              |
| <code>gamma_free</code>       | Logical matrix. Optional matrix of free (TRUE) parameters for <code>gamma</code> .                                                                                           |
| <code>gamma_values</code>     | Numeric matrix. Optional matrix of starting values for <code>gamma</code> .                                                                                                  |
| <code>gamma_lbound</code>     | Numeric matrix. Optional matrix of lower bound values for <code>gamma</code> .                                                                                               |
| <code>gamma_ubound</code>     | Numeric matrix. Optional matrix of upper bound values for <code>gamma</code> .                                                                                               |
| <code>kappa_free</code>       | Logical vector. Optional vector of free (TRUE) parameters for <code>kappa</code> .                                                                                           |
| <code>kappa_values</code>     | Numeric vector. Optional vector of starting values for <code>kappa</code> .                                                                                                  |
| <code>kappa_lbound</code>     | Numeric vector. Optional vector of lower bound values for <code>kappa</code> .                                                                                               |

|                 |                                                                                                                                                                                                    |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| kappa_ubound    | Numeric vector. Optional vector of upper bound values for kappa.                                                                                                                                   |
| phi_free        | Logical matrix. Optional matrix of free (TRUE) parameters for phi.                                                                                                                                 |
| phi_values      | Numeric matrix. Optional matrix of starting values for phi.                                                                                                                                        |
| phi_lbound      | Numeric matrix. Optional matrix of lower bound values for phi.                                                                                                                                     |
| phi_ubound      | Numeric matrix. Optional matrix of upper bound values for phi.                                                                                                                                     |
| omega_free      | Logical matrix. Optional matrix of free (TRUE) parameters for omega.                                                                                                                               |
| omega_values    | Numeric matrix. Optional matrix of starting values for omega.                                                                                                                                      |
| omega_lbound    | Numeric matrix. Optional matrix of lower bound values for omega.                                                                                                                                   |
| omega_ubound    | Numeric matrix. Optional matrix of upper bound values for omega.                                                                                                                                   |
| psi_diag        | Logical. If psi_diag = TRUE, psi is a diagonal matrix. If psi_diag = FALSE, psi is a symmetric matrix.                                                                                             |
| psi_d_free      | Logical vector indicating free/fixed status of the elements of psi_d. If NULL, all element of psi_d are free.                                                                                      |
| psi_d_values    | Numeric vector with starting values for psi_d. If NULL, defaults to a vector of ones.                                                                                                              |
| psi_d_lbound    | Numeric vector with lower bounds for psi_d. If NULL, no lower bounds are set.                                                                                                                      |
| psi_d_ubound    | Numeric vector with upper bounds for psi_d. If NULL, no upper bounds are set.                                                                                                                      |
| psi_l_free      | Logical matrix indicating which strictly-lower-triangular elements of psi_l are free. Ignored if psi_diag = TRUE.                                                                                  |
| psi_l_values    | Numeric matrix of starting values for the strictly-lower-triangular elements of psi_l. If NULL, defaults to a null matrix.                                                                         |
| psi_l_lbound    | Numeric matrix with lower bounds for psi_l. If NULL, no lower bounds are set.                                                                                                                      |
| psi_l_ubound    | Numeric matrix with upper bounds for psi_l. If NULL, no upper bounds are set.                                                                                                                      |
| check_estimates | Logical. Check elements of v for positive definiteness. If the test fails, the function generates a near positive definite matrix to replace the original using <a href="#">Matrix::nearPD()</a> . |
| robust          | Logical. If TRUE, calculate robust (sandwich) sampling variance-covariance matrix in stage 2.                                                                                                      |
| alpha           | Numeric. Alpha for test of significance and confidence intervals.                                                                                                                                  |
| seed            | Random seed for reproducibility.                                                                                                                                                                   |
| tries_explore   | Integer. Number of extra tries for the wide exploration phase.                                                                                                                                     |
| tries_local     | Integer. Number of extra tries for local polishing.                                                                                                                                                |
| max_attempts    | Integer. Maximum number of remediation attempts after the first Hessian computation fails the criteria.                                                                                            |
| silent          | Logical. If TRUE, suppresses messages during the model fitting stage.                                                                                                                              |
| ncores          | Positive integer. Number of cores to use.                                                                                                                                                          |

**Value**

Returns an object of class `metadynmeta` which is a list with the following elements:

**call** Function call.

**args** List of function arguments.

**fun** Function used ("Meta").

**output** A fitted OpenMx model.

**robust** Output from `OpenMx::mxRobustSE()` with argument `details = TRUE` if `robust = TRUE`.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**References**

Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Wiley. doi:10.1002/9781118957813

Neale, M. C., Hunter, M. D., Pritikin, J. N., Zahery, M., Brick, T. R., Kirkpatrick, R. M., Estabrook, R., Bates, T. C., Maes, H. H., & Boker, S. M. (2015). OpenMx 2.0: Extended structural equation and statistical modeling. *Psychometrika*, 81(2), 535–549. doi:10.1007/s1133601494358

**See Also**

Other Meta-Analysis of VAR Functions: `MetaVARmx()`

**Examples**

```
if (requireNamespace("simStateSpace")) {
  # Generate data using the simStateSpace package-----
  library(simStateSpace)
  set.seed(42)
  n <- 5
  time <- 100
  p <- 2
  alpha <- rep(x = 0, times = p)
  beta <- 0.50 * diag(p)
  psi <- 0.001 * diag(p)
  psi_l <- t(chol(psi))
  mu0 <- SSMMeanEta(
    beta = beta,
    alpha = alpha
  )
  sigma0 <- SSMCovEta(
    beta = beta,
    psi = psi
  )
  sigma0_l <- t(chol(sigma0))
  sim <- SimSSMVARFixed(
    n = n,
    time = time,
```

```

    mu0 = mu0,
    sigma0_l = sigma0_l,
    alpha = alpha,
    beta = beta,
    psi_l = psi_l
  )
  data <- as.data.frame(sim)

  # Stage 1-----
  library(fitVARMxID)
  stage1 <- FitVARMxID(
    data = data,
    observed = paste0("y", seq_len(p)),
    id = "id",
    center = TRUE
  )
  summary(stage1)
  # Stage 2-----
  # Meta-analyze set point vector and matrix of lagged-effects
  y <- coef(
    object = stage1,
    mu = TRUE,
    beta = TRUE,
    alpha = FALSE,
    nu = FALSE,
    psi = FALSE,
    theta = FALSE
  )
  v <- vcov(
    object = stage1,
    mu = TRUE,
    beta = TRUE,
    alpha = FALSE,
    nu = FALSE,
    psi = FALSE,
    theta = FALSE
  )
  library(metaDyn)
  stage2 <- Meta(y = y, v = v, random = FALSE)
  # Methods for the output of the Meta() function
  print(stage2)
  summary(stage2)
  coef(stage2)
  vcov(stage2)
  confint(stage2)
  extract(stage2, what = "alpha")
}

```

## Description

This function estimates fixed-, random-, or mixed-effects meta-analytic parameters using per-individual coefficient estimates and their sampling variance-covariance matrices. Optionally, it fits distal-outcome models in which between-person outcomes are regressed on between-person covariates and the meta-analyzed parameters/effect sizes. This function uses the estimated coefficients and sampling variance-covariance matrix from each individual fitted using the [fitVARMxID\(\):FitVARMxID\(\)](#) function.

## Usage

```
MetaVARMx(
  object,
  x = NULL,
  z = NULL,
  random = TRUE,
  alpha_free = NULL,
  alpha_values = NULL,
  alpha_lbound = NULL,
  alpha_ubound = NULL,
  tau_sqr_diag = FALSE,
  tau_sqr_d_free = NULL,
  tau_sqr_d_values = NULL,
  tau_sqr_d_lbound = NULL,
  tau_sqr_d_ubound = NULL,
  tau_sqr_l_free = NULL,
  tau_sqr_l_values = NULL,
  tau_sqr_l_lbound = NULL,
  tau_sqr_l_ubound = NULL,
  gamma_free = NULL,
  gamma_values = NULL,
  gamma_lbound = NULL,
  gamma_ubound = NULL,
  kappa_free = NULL,
  kappa_values = NULL,
  kappa_lbound = NULL,
  kappa_ubound = NULL,
  phi_free = NULL,
  phi_values = NULL,
  phi_lbound = NULL,
  phi_ubound = NULL,
  omega_free = NULL,
  omega_values = NULL,
  omega_lbound = NULL,
  omega_ubound = NULL,
  psi_diag = FALSE,
  psi_d_free = NULL,
  psi_d_values = NULL,
  psi_d_lbound = NULL,
```

```

psi_d_ubound = NULL,
psi_l_free = NULL,
psi_l_values = NULL,
psi_l_lbound = NULL,
psi_l_ubound = NULL,
check_estimates = TRUE,
effects = TRUE,
set_point = TRUE,
int_meas = TRUE,
int_dyn = TRUE,
cov_meas = TRUE,
cov_dyn = TRUE,
robust_v = FALSE,
robust = FALSE,
alpha = 0.05,
seed = NULL,
tries_explore = 100,
tries_local = 100,
max_attempts = 10,
silent = FALSE,
ncores = NULL
)

```

### Arguments

|                  |                                                                                                                        |
|------------------|------------------------------------------------------------------------------------------------------------------------|
| object           | Output of the <code>fitVARMxID::FitVARMxID()</code> function.                                                          |
| x                | An optional list. Each element of the list is a numeric vector of covariates.                                          |
| z                | An optional list. Each element of the list is a numeric vector of distal outcomes.                                     |
| random           | Logical. If random = TRUE, estimates random effects. If random = FALSE, tau_sqr is a null matrix.                      |
| alpha_free       | Logical vector. Optional vector of free (TRUE) parameters for alpha.                                                   |
| alpha_values     | Numeric vector. Optional vector of starting values for alpha.                                                          |
| alpha_lbound     | Numeric vector. Optional vector of lower bound values for alpha.                                                       |
| alpha_ubound     | Numeric vector. Optional vector of upper bound values for alpha.                                                       |
| tau_sqr_diag     | Logical. If tau_sqr_diag = TRUE, tau_sqr is a diagonal matrix. If tau_sqr_diag = FALSE, tau_sqr is a symmetric matrix. |
| tau_sqr_d_free   | Logical vector indicating free/fixed status of the elements of tau_sqr_d. If NULL, all element of tau_sqr_d are free.  |
| tau_sqr_d_values | Numeric vector with starting values for tau_sqr_d. If NULL, defaults to a vector of ones.                              |
| tau_sqr_d_lbound | Numeric vector with lower bounds for tau_sqr_d. If NULL, no lower bounds are set.                                      |
| tau_sqr_d_ubound | Numeric vector with upper bounds for tau_sqr_d. If NULL, no upper bounds are set.                                      |

|                               |                                                                                                                                                              |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>tau_sqr_1_free</code>   | Logical matrix indicating which strictly-lower-triangular elements of <code>tau_sqr_1</code> are free. Ignored if <code>tau_sqr_diag = TRUE</code> .         |
| <code>tau_sqr_1_values</code> | Numeric matrix of starting values for the strictly-lower-triangular elements of <code>tau_sqr_1</code> . If NULL, defaults to a null matrix.                 |
| <code>tau_sqr_1_lbound</code> | Numeric matrix with lower bounds for <code>tau_sqr_1</code> . If NULL, no lower bounds are set.                                                              |
| <code>tau_sqr_1_ubound</code> | Numeric matrix with upper bounds for <code>tau_sqr_1</code> . If NULL, no upper bounds are set.                                                              |
| <code>gamma_free</code>       | Logical matrix. Optional matrix of free (TRUE) parameters for <code>gamma</code> .                                                                           |
| <code>gamma_values</code>     | Numeric matrix. Optional matrix of starting values for <code>gamma</code> .                                                                                  |
| <code>gamma_lbound</code>     | Numeric matrix. Optional matrix of lower bound values for <code>gamma</code> .                                                                               |
| <code>gamma_ubound</code>     | Numeric matrix. Optional matrix of upper bound values for <code>gamma</code> .                                                                               |
| <code>kappa_free</code>       | Logical vector. Optional vector of free (TRUE) parameters for <code>kappa</code> .                                                                           |
| <code>kappa_values</code>     | Numeric vector. Optional vector of starting values for <code>kappa</code> .                                                                                  |
| <code>kappa_lbound</code>     | Numeric vector. Optional vector of lower bound values for <code>kappa</code> .                                                                               |
| <code>kappa_ubound</code>     | Numeric vector. Optional vector of upper bound values for <code>kappa</code> .                                                                               |
| <code>phi_free</code>         | Logical matrix. Optional matrix of free (TRUE) parameters for <code>phi</code> .                                                                             |
| <code>phi_values</code>       | Numeric matrix. Optional matrix of starting values for <code>phi</code> .                                                                                    |
| <code>phi_lbound</code>       | Numeric matrix. Optional matrix of lower bound values for <code>phi</code> .                                                                                 |
| <code>phi_ubound</code>       | Numeric matrix. Optional matrix of upper bound values for <code>phi</code> .                                                                                 |
| <code>omega_free</code>       | Logical matrix. Optional matrix of free (TRUE) parameters for <code>omega</code> .                                                                           |
| <code>omega_values</code>     | Numeric matrix. Optional matrix of starting values for <code>omega</code> .                                                                                  |
| <code>omega_lbound</code>     | Numeric matrix. Optional matrix of lower bound values for <code>omega</code> .                                                                               |
| <code>omega_ubound</code>     | Numeric matrix. Optional matrix of upper bound values for <code>omega</code> .                                                                               |
| <code>psi_diag</code>         | Logical. If <code>psi_diag = TRUE</code> , <code>psi</code> is a diagonal matrix. If <code>psi_diag = FALSE</code> , <code>psi</code> is a symmetric matrix. |
| <code>psi_d_free</code>       | Logical vector indicating free/fixed status of the elements of <code>psi_d</code> . If NULL, all element of <code>psi_d</code> are free.                     |
| <code>psi_d_values</code>     | Numeric vector with starting values for <code>psi_d</code> . If NULL, defaults to a vector of ones.                                                          |
| <code>psi_d_lbound</code>     | Numeric vector with lower bounds for <code>psi_d</code> . If NULL, no lower bounds are set.                                                                  |
| <code>psi_d_ubound</code>     | Numeric vector with upper bounds for <code>psi_d</code> . If NULL, no upper bounds are set.                                                                  |
| <code>psi_1_free</code>       | Logical matrix indicating which strictly-lower-triangular elements of <code>psi_1</code> are free. Ignored if <code>psi_diag = TRUE</code> .                 |
| <code>psi_1_values</code>     | Numeric matrix of starting values for the strictly-lower-triangular elements of <code>psi_1</code> . If NULL, defaults to a null matrix.                     |
| <code>psi_1_lbound</code>     | Numeric matrix with lower bounds for <code>psi_1</code> . If NULL, no lower bounds are set.                                                                  |

|                 |                                                                                                                                                                                                 |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| psi_1_ubound    | Numeric matrix with upper bounds for psi_1. If NULL, no upper bounds are set.                                                                                                                   |
| check_estimates | Logical. Check elements of v for positive definiteness. If the test fails, the function generates a near positive definite matrix to replace the original using <code>Matrix::nearPD()</code> . |
| effects         | Logical. If effects = TRUE, include estimates of the dynamic effects matrix, if available. If effects = FALSE, exclude estimates of the dynamic effects matrix.                                 |
| set_point       | Logical. If set_point = TRUE, include estimates of the set-point vector, if available. If set_point = FALSE, exclude estimates of the set-point vector.                                         |
| int_meas        | Logical. If int_meas = TRUE, include estimates of the measurement intercept vector, if available. If int_meas = FALSE, exclude estimates of the measurement intercept vector.                   |
| int_dyn         | Logical. If int_dyn = TRUE, include estimates of the dynamic process intercept vector, if available. If int_dyn = FALSE, exclude estimates of the dynamic process intercept vector.             |
| cov_meas        | Logical. If cov_meas = TRUE, include estimates of the measurement error covariance matrix, if available. If cov_meas = FALSE, exclude estimates of the measurement error covariance matrix.     |
| cov_dyn         | Logical. If cov_dyn = TRUE, include estimates of the process noise covariance matrix, if available. If cov_dyn = FALSE, exclude estimates of the process noise covariance matrix.               |
| robust_v        | Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix in stage 1. If FALSE, use normal theory sampling variance-covariance matrix in stage 1.                             |
| robust          | Logical. If TRUE, calculate robust (sandwich) sampling variance-covariance matrix in stage 2.                                                                                                   |
| alpha           | NUmeric. Alpha for test of significance and confidence intervals.                                                                                                                               |
| seed            | Random seed for reproducibility.                                                                                                                                                                |
| tries_explore   | Integer. Number of extra tries for the wide exploration phase.                                                                                                                                  |
| tries_local     | Integer. Number of extra tries for local polishing.                                                                                                                                             |
| max_attempts    | Integer. Maximum number of remediation attempts after the first Hessian computation fails the criteria.                                                                                         |
| silent          | Logical. If TRUE, suppresses messages during the model fitting stage.                                                                                                                           |
| ncores          | Positive integer. Number of cores to use.                                                                                                                                                       |

### Value

Returns an object of class `metadynmeta` which is a list with the following elements:

**call** Function call.

**args** List of function arguments.

**fun** Function used ("Meta").

**output** A fitted OpenMx model.

**robust** Output from `OpenMx::mxRobustSE()` with argument `details = TRUE` if `robust = TRUE`.

**Author(s)**

Ivan Jacob Agaloos Pesigan

**References**

Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Wiley. doi:[10.1002/9781118957813](https://doi.org/10.1002/9781118957813)

Neale, M. C., Hunter, M. D., Pritikin, J. N., Zahery, M., Brick, T. R., Kirkpatrick, R. M., Estabrook, R., Bates, T. C., Maes, H. H., & Boker, S. M. (2015). OpenMx 2.0: Extended structural equation and statistical modeling. *Psychometrika*, 81(2), 535–549. doi:[10.1007/s1133601494358](https://doi.org/10.1007/s1133601494358)

**See Also**

Other Meta-Analysis of VAR Functions: [Meta\(\)](#)

**Examples**

```
if (requireNamespace("simStateSpace")) {
  # Generate data using the simStateSpace package-----
  library(simStateSpace)
  set.seed(42)
  n <- 5
  time <- 100
  p <- 2
  alpha <- rep(x = 0, times = p)
  beta <- 0.50 * diag(p)
  psi <- 0.001 * diag(p)
  psi_l <- t(chol(psi))
  mu0 <- SSMMeanEta(
    beta = beta,
    alpha = alpha
  )
  sigma0 <- SSMCovEta(
    beta = beta,
    psi = psi
  )
  sigma0_l <- t(chol(sigma0))
  sim <- SimSSMVARFixed(
    n = n,
    time = time,
    mu0 = mu0,
    sigma0_l = sigma0_l,
    alpha = alpha,
    beta = beta,
    psi_l = psi_l
  )
  data <- as.data.frame(sim)

  # Stage 1-----
  library(fitVARMxID)
  stage1 <- FitVARMxID(
```

```

    data = data,
    observed = paste0("y", seq_len(p)),
    id = "id",
    center = TRUE
  )
  summary(stage1)
  # Stage 2-----
  # Meta-analyze set point vector and matrix of lagged-effects
  library(metaDyn)
  stage2 <- MetaVARmX(
    object = stage1,
    random = FALSE,
    effects = TRUE,
    set_point = TRUE,
    int_meas = FALSE,
    int_dyn = FALSE,
    cov_meas = FALSE,
    cov_dyn = FALSE
  )
  # Methods for the output of the MetaVARmX() function
  print(stage2)
  summary(stage2)
  coef(stage2)
  vcov(stage2)
  confint(stage2)
  extract(stage2, what = "alpha")
}

```

---

|                   |                                                     |
|-------------------|-----------------------------------------------------|
| print.metadynmeta | <i>Print Method for Object of Class metadynmeta</i> |
|-------------------|-----------------------------------------------------|

---

## Description

Print Method for Object of Class metadynmeta

## Usage

```

## S3 method for class 'metadynmeta'
print(x, alpha = NULL, robust = NULL, digits = 4, ...)

```

## Arguments

|        |                                                                                                                                                                                                                                |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x      | an object of class metadynmeta.                                                                                                                                                                                                |
| alpha  | Numeric vector. Significance level $\alpha$ . If NULL, the function will check object for alpha used in model fitting.                                                                                                         |
| robust | Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix. If NULL, the function will check object if robust standard errors are available. |

digits            Integer indicating the number of decimal places to display.  
...               further arguments.

**Value**

Returns a matrix of estimates, standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|                     |                                                       |
|---------------------|-------------------------------------------------------|
| summary.metadynmeta | <i>Summary Method for Object of Class metadynmeta</i> |
|---------------------|-------------------------------------------------------|

---

**Description**

Summary Method for Object of Class metadynmeta

**Usage**

```
## S3 method for class 'metadynmeta'  
summary(object, alpha = NULL, robust = NULL, digits = 4, ...)
```

**Arguments**

object            an object of class metadynmeta.  
alpha             Numeric vector. Significance level  $\alpha$ . If NULL, the function will check object for alpha used in model fitting.  
robust            Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix. If NULL, the function will check object if robust standard errors are available.  
digits            Integer indicating the number of decimal places to display.  
...               further arguments.

**Value**

Returns a matrix of estimates, standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

|                  |                                                                             |
|------------------|-----------------------------------------------------------------------------|
| vcov.metadynmeta | <i>Variance-Covariance Matrix Method for an Object of Class metadynmeta</i> |
|------------------|-----------------------------------------------------------------------------|

---

**Description**

Variance-Covariance Matrix Method for an Object of Class metadynmeta

**Usage**

```
## S3 method for class 'metadynmeta'  
vcov(object, robust = NULL, ...)
```

**Arguments**

|        |                                                                                                                                                                                                                                |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object | an object of class metadynmeta.                                                                                                                                                                                                |
| robust | Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix. If NULL, the function will check object if robust standard errors are available. |
| ...    | further arguments.                                                                                                                                                                                                             |

**Value**

Returns the sampling variance-covariance matrix of the estimated parameters.

**Author(s)**

Ivan Jacob Agaloos Pesigan

# Index

## \* Meta-Analysis of VAR Functions

Meta, [4](#)

MetaVARmX, [9](#)

## \* metaDyn

Meta, [4](#)

MetaVARmX, [9](#)

## \* meta

Meta, [4](#)

MetaVARmX, [9](#)

## \* methods

coef.metadynmeta, [2](#)

confint.metadynmeta, [2](#)

extract, [3](#)

extract.metadynmeta, [3](#)

print.metadynmeta, [15](#)

summary.metadynmeta, [16](#)

vcov.metadynmeta, [16](#)

coef.metadynmeta, [2](#)

confint.metadynmeta, [2](#)

extract, [3](#)

extract.metadynmeta, [3](#)

fitVARmXID::FitVARmXID(), [9](#), [11](#)

Matrix::nearPD(), [7](#), [12](#)

Meta, [4](#)

Meta(), [14](#)

MetaVARmX, [9](#)

MetaVARmX(), [8](#)

OpenMx::imxRobustSE(), [7](#), [13](#)

print.metadynmeta, [15](#)

summary.metadynmeta, [16](#)

vcov.metadynmeta, [16](#)