

Package ‘metaDyn’

February 1, 2026

Title Multivariate Meta-Analysis of Dynamic Model Estimates

Version 0.0.0.9004

Description Fits fixed-, random-, or mixed-effects multivariate meta-analysis models using dynamic model estimates from each individual.

URL <https://github.com/jeksterslab/metaDyn>,
<https://jeksterslab.github.io/metaDyn/>

BugReports <https://github.com/jeksterslab/metaDyn/issues>

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

Depends R (>= 4.5.0), OpenMx (>= 2.22.10)

Imports Matrix, fitDTVARMxID

Remotes jeksterslab/fitDTVARMxID

Suggests knitr, rmarkdown, testthat, simStateSpace, MASS, metaSEM

RoxygenNote 7.3.3.9000

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0003-4818-8420>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

Contents

coef.metadynmeta	2
confint.metadynmeta	2
extract	3
extract.metadynmeta	4
Meta	4
MetaVARMx	9
print.metadynmeta	14
summary.metadynmeta	14
vcov.metadynmeta	15

Index**16**

coef.metadynmeta	<i>Estimated Parameter Method for an Object of Class metadynmeta</i>
------------------	--

Description

Estimated Parameter Method for an Object of Class metadynmeta

Usage

```
## S3 method for class 'metadynmeta'
coef(object, ...)
```

Arguments

object	an object of class metadynmeta.
...	further arguments.

Value

Returns a vector of estimated parameters.

Author(s)

Ivan Jacob Agaloos Pesigan

confint.metadynmeta	<i>Confidence Intervals for the Parameter Estimates</i>
---------------------	---

Description

Confidence Intervals for the Parameter Estimates

Usage

```
## S3 method for class 'metadynmeta'
confint(object, parm = NULL, level = 0.95, lb = TRUE, robust = FALSE, ...)
```

Arguments

object	an object of class <code>metadynmeta</code> .
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.
lb	Logical. If TRUE, returns profile likelihood-based confidence intervals. If FALSE, returns Wald confidence intervals.
robust	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix.
...	further arguments.

Value

Returns a matrix of confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

extract	<i>Extract Generic Function</i>
---------	---------------------------------

Description

A generic function for extracting elements from objects.

Usage

```
extract(object, what)
```

Arguments

object	An object.
what	Character string.

Value

A value determined by the specific method for the object's class.

<code>extract.metadynmeta</code>	<i>Extract Method for an Object of Class metadynmeta</i>
----------------------------------	--

Description

Extract Method for an Object of Class metadynmeta

Usage

```
## S3 method for class 'metadynmeta'
extract(object, what = NULL)
```

Arguments

<code>object</code>	an object of class metadynmeta.
<code>what</code>	Character string. What specific matrix to extract. If <code>what = NULL</code> , extract all available matrices.

Value

Returns a list of estimates.

Author(s)

Ivan Jacob Agaloos Pesigan

Meta	<i>Fit Multivariate Meta-Analysis</i>
------	---------------------------------------

Description

This function estimates fixed-, random-, or mixed-effects meta-analytic parameters using per-individual coefficient estimates and their sampling variance-covariance matrices. Optionally, it fits distal-outcome models in which between-person outcomes are regressed on between-person covariates and the meta-analyzed parameters/effect sizes.

Usage

```
Meta(
  y,
  v,
  x = NULL,
  z = NULL,
  random = TRUE,
  alpha_free = NULL,
```

```
alpha_values = NULL,
alpha_lbound = NULL,
alpha_ubound = NULL,
tau_sqr_diag = FALSE,
tau_sqr_d_free = NULL,
tau_sqr_d_values = NULL,
tau_sqr_d_lbound = NULL,
tau_sqr_d_ubound = NULL,
tau_sqr_l_free = NULL,
tau_sqr_l_values = NULL,
tau_sqr_l_lbound = NULL,
tau_sqr_l_ubound = NULL,
i_sqr_univariate = FALSE,
gamma_free = NULL,
gamma_values = NULL,
gamma_lbound = NULL,
gamma_ubound = NULL,
kappa_free = NULL,
kappa_values = NULL,
kappa_lbound = NULL,
kappa_ubound = NULL,
phi_values = NULL,
phi_free = NULL,
phi_lbound = NULL,
phi_ubound = NULL,
omega_values = NULL,
omega_free = NULL,
omega_lbound = NULL,
omega_ubound = NULL,
psi_diag = TRUE,
psi_d_free = NULL,
psi_d_values = NULL,
psi_d_lbound = NULL,
psi_d_ubound = NULL,
psi_l_free = NULL,
psi_l_values = NULL,
psi_l_lbound = NULL,
psi_l_ubound = NULL,
check_estimates = TRUE,
robust = FALSE,
tries_explore = 100,
tries_local = 100,
max_attempts = 10,
grad_tol = 0.01,
hess_tol = 1e-08,
eps = 1e-06,
factor = 10,
abs_bnd_tol = 1e-06,
```

```

    rel_bnd_tol = 1e-04,
    silent = FALSE,
    seed = NULL,
    ncores = NULL
)

```

Arguments

<code>y</code>	A list. Each element of the list is a numeric vector of estimated coefficients.
<code>v</code>	A list. Each element of the list is a sampling variance-covariance matrix of <code>y</code> .
<code>x</code>	An optional list. Each element of the list is a numeric vector of covariates.
<code>z</code>	An optional list. Each element of the list is a numeric vector of distal outcomes.
<code>random</code>	Logical. If <code>random = TRUE</code> , estimates random effects. If <code>random = FALSE</code> , <code>tau_sqr</code> is a null matrix.
<code>alpha_free</code>	Logical vector. Optional vector of free (TRUE) parameters for alpha.
<code>alpha_values</code>	Numeric vector. Optional vector of starting values for alpha.
<code>alpha_lbound</code>	Numeric vector. Optional vector of lower bound values for alpha.
<code>alpha_ubound</code>	Numeric vector. Optional vector of upper bound values for alpha.
<code>tau_sqr_diag</code>	Logical. If <code>tau_sqr_diag = TRUE</code> , <code>tau_sqr</code> is a diagonal matrix. If <code>tau_sqr_diag = FALSE</code> , <code>tau_sqr</code> is a symmetric matrix.
<code>tau_sqr_d_free</code>	Logical vector indicating free/fixed status of the elements of <code>tau_sqr_d</code> . If NULL, all element of <code>tau_sqr_d</code> are free.
<code>tau_sqr_d_values</code>	Numeric vector with starting values for <code>tau_sqr_d</code> . If NULL, defaults to a vector of ones.
<code>tau_sqr_d_lbound</code>	Numeric vector with lower bounds for <code>tau_sqr_d</code> . If NULL, no lower bounds are set.
<code>tau_sqr_d_ubound</code>	Numeric vector with upper bounds for <code>tau_sqr_d</code> . If NULL, no upper bounds are set.
<code>tau_sqr_l_free</code>	Logical matrix indicating which strictly-lower-triangular elements of <code>tau_sqr_l</code> are free. Ignored if <code>tau_sqr_diag = TRUE</code> .
<code>tau_sqr_l_values</code>	Numeric matrix of starting values for the strictly-lower-triangular elements of <code>tau_sqr_l</code> . If NULL, defaults to a null matrix.
<code>tau_sqr_l_lbound</code>	Numeric matrix with lower bounds for <code>tau_sqr_l</code> . If NULL, no lower bounds are set.
<code>tau_sqr_l_ubound</code>	Numeric matrix with upper bounds for <code>tau_sqr_l</code> . If NULL, no upper bounds are set.
<code>i_sqr_univariate</code>	Logical. If <code>i_sqr_univariate = TRUE</code> , use the univariate formula for I^2 . If <code>i_sqr_univariate = FALSE</code> , use the multivariate formula for I^2 .

<code>gamma_free</code>	Logical matrix. Optional matrix of free (TRUE) parameters for gamma.
<code>gamma_values</code>	Numeric matrix. Optional matrix of starting values for gamma.
<code>gamma_lbound</code>	Numeric matrix. Optional matrix of lower bound values for gamma.
<code>gamma_ubound</code>	Numeric matrix. Optional matrix of upper bound values for gamma.
<code>kappa_free</code>	Logical vector. Optional vector of free (TRUE) parameters for kappa.
<code>kappa_values</code>	Numeric vector. Optional vector of starting values for kappa.
<code>kappa_lbound</code>	Numeric vector. Optional vector of lower bound values for kappa.
<code>kappa_ubound</code>	Numeric vector. Optional vector of upper bound values for kappa.
<code>phi_values</code>	Numeric matrix. Optional matrix of starting values for phi.
<code>phi_free</code>	Logical matrix. Optional matrix of free (TRUE) parameters for phi.
<code>phi_lbound</code>	Numeric matrix. Optional matrix of lower bound values for phi.
<code>phi_ubound</code>	Numeric matrix. Optional matrix of upper bound values for phi.
<code>omega_values</code>	Numeric matrix. Optional matrix of starting values for omega.
<code>omega_free</code>	Logical matrix. Optional matrix of free (TRUE) parameters for omega.
<code>omega_lbound</code>	Numeric matrix. Optional matrix of lower bound values for omega.
<code>omega_ubound</code>	Numeric matrix. Optional matrix of upper bound values for omega.
<code>psi_diag</code>	Logical. If <code>psi_diag = TRUE</code> , <code>psi</code> is a diagonal matrix. If <code>psi_diag = FALSE</code> , <code>psi</code> is a symmetric matrix.
<code>psi_d_free</code>	Logical vector indicating free/fixed status of the elements of <code>psi_d</code> . If NULL, all element of <code>psi_d</code> are free.
<code>psi_d_values</code>	Numeric vector with starting values for <code>psi_d</code> . If NULL, defaults to a vector of ones.
<code>psi_d_lbound</code>	Numeric vector with lower bounds for <code>psi_d</code> . If NULL, no lower bounds are set.
<code>psi_d_ubound</code>	Numeric vector with upper bounds for <code>psi_d</code> . If NULL, no upper bounds are set.
<code>psi_l_free</code>	Logical matrix indicating which strictly-lower-triangular elements of <code>psi_l</code> are free. Ignored if <code>psi_diag = TRUE</code> .
<code>psi_l_values</code>	Numeric matrix of starting values for the strictly-lower-triangular elements of <code>psi_l</code> . If NULL, defaults to a null matrix.
<code>psi_l_lbound</code>	Numeric matrix with lower bounds for <code>psi_l</code> . If NULL, no lower bounds are set.
<code>psi_l_ubound</code>	Numeric matrix with upper bounds for <code>psi_l</code> . If NULL, no upper bounds are set.
<code>check_estimates</code>	Logical. Check elements of <code>v</code> for positive definiteness. If the test fails, the function generates a near positive definite matrix to replace the original using <code>Matrix::nearPD()</code> .
<code>robust</code>	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix in stage 2. If FALSE, use normal theory sampling variance-covariance matrix in stage 2.
<code>tries_explore</code>	Integer. Number of extra tries for the wide exploration phase using <code>OpenMx::mxTryHardWideSearch()</code> with <code>checkHess = FALSE</code> .

<code>tries_local</code>	Integer. Number of extra tries for local polishing via <code>OpenMx::mxTryHard()</code> when gradients remain above tolerance.
<code>max_attempts</code>	Integer. Maximum number of remediation attempts after the first Hessian computation fails the criteria. Each attempt may nudge off bounds, refit locally without the Hessian, and, on the last attempt, relax bounds.
<code>grad_tol</code>	Numeric. Tolerance for the maximum absolute gradient. Smaller values are stricter.
<code>hess_tol</code>	Numeric. Minimum allowable Hessian eigenvalue. Smaller values are less strict.
<code>eps</code>	Numeric. Proximity threshold to detect parameters on their bounds and to nudge them inward by $10 * \text{eps}$.
<code>factor</code>	Numeric. Multiplicative factor to relax parameter bounds on the final remediation attempt. Lower bounds are divided by factor and upper bounds are multiplied by factor.
<code>abs_bnd_tol</code>	Numeric scalar. Absolute tolerance used when comparing parameter values to bounds.
<code>rel_bnd_tol</code>	Numeric scalar. Relative tolerance multiplier.
<code>silent</code>	Logical. If TRUE, suppresses messages during the model fitting stage.
<code>seed</code>	Random seed for reproducibility.
<code>ncores</code>	Positive integer. Number of cores to use.

Value

Returns an object of class `metadynmeta` which is a list with the following elements:

call Function call.

args List of function arguments.

fun Function used ("Meta").

output A fitted OpenMx model.

robust Output from `OpenMx::mxRobustSE()` with argument `details = TRUE`.

Author(s)

Ivan Jacob Agaloos Pesigan

References

- Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Wiley. doi:10.1002/9781118957813
- Neale, M. C., Hunter, M. D., Pritikin, J. N., Zahery, M., Brick, T. R., Kirkpatrick, R. M., Estabrook, R., Bates, T. C., Maes, H. H., & Boker, S. M. (2015). OpenMx 2.0: Extended structural equation and statistical modeling. *Psychometrika*, 81(2), 535–549. doi:10.1007/s1133601494358

See Also

Other Meta-Analysis of VAR Functions: `MetaVARMx()`

Description

This function estimates fixed-, random-, or mixed-effects meta-analytic parameters using per-individual coefficient estimates and their sampling variance-covariance matrices. Optionally, it fits distal-outcome models in which between-person outcomes are regressed on between-person covariates and the meta-analyzed parameters/effect sizes. This function uses the estimated coefficients and sampling variance-covariance matrix from each individual fitted using the [fitDTVARMxID::FitDTVARMxID\(\)](#) function.

Usage

```
MetaVARMx(
  object,
  x = NULL,
  z = NULL,
  random = TRUE,
  alpha_free = NULL,
  alpha_values = NULL,
  alpha_lbound = NULL,
  alpha_ubound = NULL,
  tau_sqr_diag = FALSE,
  tau_sqr_d_free = NULL,
  tau_sqr_d_values = NULL,
  tau_sqr_d_lbound = NULL,
  tau_sqr_d_ubound = NULL,
  tau_sqr_l_free = NULL,
  tau_sqr_l_values = NULL,
  tau_sqr_l_lbound = NULL,
  tau_sqr_l_ubound = NULL,
  i_sqr_univariate = FALSE,
  gamma_free = NULL,
  gamma_values = NULL,
  gamma_lbound = NULL,
  gamma_ubound = NULL,
  kappa_free = NULL,
  kappa_values = NULL,
  kappa_lbound = NULL,
  kappa_ubound = NULL,
  phi_values = NULL,
  phi_free = NULL,
  phi_lbound = NULL,
  phi_ubound = NULL,
  omega_values = NULL,
  omega_free = NULL,
```

```

omega_lbound = NULL,
omega_ubound = NULL,
psi_diag = TRUE,
psi_d_free = NULL,
psi_d_values = NULL,
psi_d_lbound = NULL,
psi_d_ubound = NULL,
psi_l_free = NULL,
psi_l_values = NULL,
psi_l_lbound = NULL,
psi_l_ubound = NULL,
check_estimates = TRUE,
effects = TRUE,
set_point = FALSE,
int_meas = FALSE,
int_dyn = FALSE,
cov_meas = FALSE,
cov_dyn = FALSE,
converged = TRUE,
vanishing_theta = TRUE,
theta_tol = 0.001,
robust_v = FALSE,
robust = FALSE,
tries_explore = 100,
tries_local = 100,
max_attempts = 10,
grad_tol = 0.01,
hess_tol = 1e-08,
eps = 1e-06,
factor = 10,
abs_bnd_tol = 1e-06,
rel_bnd_tol = 1e-04,
silent = FALSE,
seed = NULL,
ncores = NULL
)

```

Arguments

object	Output of the <code>fitDTVARMxID::FitDTVARMxID()</code> function.
x	An optional list. Each element of the list is a numeric vector of covariates.
z	An optional list. Each element of the list is a numeric vector of distal outcomes.
random	Logical. If <code>random = TRUE</code> , estimates random effects. If <code>random = FALSE</code> , <code>tau_sqr</code> is a null matrix.
alpha_free	Logical vector. Optional vector of free (TRUE) parameters for alpha.
alpha_values	Numeric vector. Optional vector of starting values for alpha.
alpha_lbound	Numeric vector. Optional vector of lower bound values for alpha.

alpha_ubound	Numeric vector. Optional vector of upper bound values for alpha.
tau_sqr_diag	Logical. If tau_sqr_diag = TRUE, tau_sqr is a diagonal matrix. If tau_sqr_diag = FALSE, tau_sqr is a symmetric matrix.
tau_sqr_d_free	Logical vector indicating free/fixed status of the elements of tau_sqr_d. If NULL, all element of tau_sqr_d are free.
tau_sqr_d_values	Numeric vector with starting values for tau_sqr_d. If NULL, defaults to a vector of ones.
tau_sqr_d_lbound	Numeric vector with lower bounds for tau_sqr_d. If NULL, no lower bounds are set.
tau_sqr_d_ubound	Numeric vector with upper bounds for tau_sqr_d. If NULL, no upper bounds are set.
tau_sqr_l_free	Logical matrix indicating which strictly-lower-triangular elements of tau_sqr_l are free. Ignored if tau_sqr_diag = TRUE.
tau_sqr_l_values	Numeric matrix of starting values for the strictly-lower-triangular elements of tau_sqr_l. If NULL, defaults to a null matrix.
tau_sqr_l_lbound	Numeric matrix with lower bounds for tau_sqr_l. If NULL, no lower bounds are set.
tau_sqr_l_ubound	Numeric matrix with upper bounds for tau_sqr_l. If NULL, no upper bounds are set.
i_sqr_univariate	Logical. If i_sqr_univariate = TRUE, use the univariate formula for I^2 . If i_sqr_univariate = FALSE, use the multivariate formula for I^2 .
gamma_free	Logical matrix. Optional matrix of free (TRUE) parameters for gamma.
gamma_values	Numeric matrix. Optional matrix of starting values for gamma.
gamma_lbound	Numeric matrix. Optional matrix of lower bound values for gamma.
gamma_ubound	Numeric matrix. Optional matrix of upper bound values for gamma.
kappa_free	Logical vector. Optional vector of free (TRUE) parameters for kappa.
kappa_values	Numeric vector. Optional vector of starting values for kappa.
kappa_lbound	Numeric vector. Optional vector of lower bound values for kappa.
kappa_ubound	Numeric vector. Optional vector of upper bound values for kappa.
phi_values	Numeric matrix. Optional matrix of starting values for phi.
phi_free	Logical matrix. Optional matrix of free (TRUE) parameters for phi.
phi_lbound	Numeric matrix. Optional matrix of lower bound values for phi.
phi_ubound	Numeric matrix. Optional matrix of upper bound values for phi.
omega_values	Numeric matrix. Optional matrix of starting values for omega.
omega_free	Logical matrix. Optional matrix of free (TRUE) parameters for omega.

omega_lbound	Numeric matrix. Optional matrix of lower bound values for omega.
omega_ubound	Numeric matrix. Optional matrix of upper bound values for omega.
psi_diag	Logical. If psi_diag = TRUE, psi is a diagonal matrix. If psi_diag = FALSE, psi is a symmetric matrix.
psi_d_free	Logical vector indicating free/fixed status of the elements of psi_d. If NULL, all element of psi_d are free.
psi_d_values	Numeric vector with starting values for psi_d. If NULL, defaults to a vector of ones.
psi_d_lbound	Numeric vector with lower bounds for psi_d. If NULL, no lower bounds are set.
psi_d_ubound	Numeric vector with upper bounds for psi_d. If NULL, no upper bounds are set.
psi_l_free	Logical matrix indicating which strictly-lower-triangular elements of psi_l are free. Ignored if psi_diag = TRUE.
psi_l_values	Numeric matrix of starting values for the strictly-lower-triangular elements of psi_l. If NULL, defaults to a null matrix.
psi_l_lbound	Numeric matrix with lower bounds for psi_l. If NULL, no lower bounds are set.
psi_l_ubound	Numeric matrix with upper bounds for psi_l. If NULL, no upper bounds are set.
check_estimates	Logical. Check elements of v for positive definiteness. If the test fails, the function generates a near positive definite matrix to replace the original using <code>Matrix::nearPD()</code> .
effects	Logical. If effects = TRUE, include estimates of the dynamic effects matrix, if available. If effects = FALSE, exclude estimates of the dynamic effects matrix.
set_point	Logical. If set_point = TRUE, include estimates of the set-point vector, if available. If set_point = FALSE, exclude estimates of the set-point vector.
int_meas	Logical. If int_meas = TRUE, include estimates of the measurement intercept vector, if available. If int_meas = FALSE, exclude estimates of the measurement intercept vector.
int_dyn	Logical. If int_dyn = TRUE, include estimates of the dynamic process intercept vector, if available. If int_dyn = FALSE, exclude estimates of the dynamic process intercept vector.
cov_meas	Logical. If cov_meas = TRUE, include estimates of the measurement error covariance matrix, if available. If cov_meas = FALSE, exclude estimates of the measurement error covariance matrix.
cov_dyn	Logical. If cov_dyn = TRUE, include estimates of the process noise covariance matrix, if available. If cov_dyn = FALSE, exclude estimates of the process noise covariance matrix.
converged	Logical. Only include converged cases.
vanishing_theta	Logical. Test for measurement error variance going to zero if converged = TRUE.
theta_tol	Numeric. Tolerance for vanishing theta test if converged and theta_tol are TRUE.

robust_v	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix in stage 1. If FALSE, use normal theory sampling variance-covariance matrix in stage 1.
robust	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix in stage 2. If FALSE, use normal theory sampling variance-covariance matrix in stage 2.
tries_explore	Integer. Number of extra tries for the wide exploration phase using <code>OpenMx::mxTryHardWideSearch()</code> with <code>checkHess = FALSE</code> .
tries_local	Integer. Number of extra tries for local polishing via <code>OpenMx::mxTryHard()</code> when gradients remain above tolerance.
max_attempts	Integer. Maximum number of remediation attempts after the first Hessian computation fails the criteria. Each attempt may nudge off bounds, refit locally without the Hessian, and, on the last attempt, relax bounds.
grad_tol	Numeric. Tolerance for the maximum absolute gradient. Smaller values are stricter.
hess_tol	Numeric. Minimum allowable Hessian eigenvalue. Smaller values are less strict.
eps	Numeric. Proximity threshold to detect parameters on their bounds and to nudge them inward by $10 * \text{eps}$.
factor	Numeric. Multiplicative factor to relax parameter bounds on the final remediation attempt. Lower bounds are divided by factor and upper bounds are multiplied by factor.
abs_bnd_tol	Numeric scalar. Absolute tolerance used when comparing parameter values to bounds.
rel_bnd_tol	Numeric scalar. Relative tolerance multiplier.
silent	Logical. If TRUE, suppresses messages during the model fitting stage.
seed	Random seed for reproducibility.
ncores	Positive integer. Number of cores to use.

Author(s)

Ivan Jacob Agaloos Pesigan

References

- Cheung, M. W.-L. (2015). *Meta-analysis: A structural equation modeling approach*. Wiley. doi:10.1002/9781118957813
- Neale, M. C., Hunter, M. D., Pritikin, J. N., Zahery, M., Brick, T. R., Kirkpatrick, R. M., Estabrook, R., Bates, T. C., Maes, H. H., & Boker, S. M. (2015). OpenMx 2.0: Extended structural equation and statistical modeling. *Psychometrika*, 81(2), 535–549. doi:10.1007/s1133601494358

See Also

Other Meta-Analysis of VAR Functions: [Meta\(\)](#)

print.metadynmeta	<i>Print Method for Object of Class metadynmeta</i>
-------------------	---

Description

Print Method for Object of Class metadynmeta

Usage

```
## S3 method for class 'metadynmeta'
print(x, alpha = 0.05, lb = FALSE, robust = FALSE, digits = 4, ...)
```

Arguments

x	an object of class metadynmeta.
alpha	Numeric vector. Significance level α .
lb	Logical. If TRUE, returns profile likelihood-based confidence intervals. If FALSE, returns Wald confidence intervals.
robust	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix.
digits	Integer indicating the number of decimal places to display.
...	further arguments.

Value

Returns a matrix of estimates, standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

summary.metadynmeta	<i>Summary Method for Object of Class metadynmeta</i>
---------------------	---

Description

Summary Method for Object of Class metadynmeta

Usage

```
## S3 method for class 'metadynmeta'
summary(object, alpha = 0.05, lb = FALSE, robust = FALSE, digits = 4, ...)
```

Arguments

object	an object of class metadynmeta.
alpha	Numeric vector. Significance level α .
lb	Logical. If TRUE, returns profile likelihood-based confidence intervals. If FALSE, returns Wald confidence intervals.
robust	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix.
digits	Integer indicating the number of decimal places to display.
...	further arguments.

Value

Returns a matrix of estimates, standard errors, test statistics, degrees of freedom, p-values, and confidence intervals.

Author(s)

Ivan Jacob Agaloos Pesigan

vcov.metadynmeta	<i>Variance-Covariance Matrix Method for an Object of Class metadynmeta</i>
------------------	---

Description

Variance-Covariance Matrix Method for an Object of Class metadynmeta

Usage

```
## S3 method for class 'metadynmeta'
vcov(object, robust = FALSE, ...)
```

Arguments

object	an object of class metadynmeta.
robust	Logical. If TRUE, use robust (sandwich) sampling variance-covariance matrix. If FALSE, use normal theory sampling variance-covariance matrix.
...	further arguments.

Value

Returns the sampling variance-covariance matrix of the estimated parameters.

Author(s)

Ivan Jacob Agaloos Pesigan

Index

* Meta-Analysis of VAR Functions

Meta, [4](#)

MetaVARMx, [9](#)

* metaDyn

Meta, [4](#)

MetaVARMx, [9](#)

* meta

Meta, [4](#)

MetaVARMx, [9](#)

* methods

coef.metadynmeta, [2](#)

confint.metadynmeta, [2](#)

extract, [3](#)

extract.metadynmeta, [4](#)

print.metadynmeta, [14](#)

summary.metadynmeta, [14](#)

vcov.metadynmeta, [15](#)

coef.metadynmeta, [2](#)

confint.metadynmeta, [2](#)

extract, [3](#)

extract.metadynmeta, [4](#)

fitDTVARMxID::FitDTVARMxID(), [9](#), [10](#)

Matrix::nearPD(), [7](#), [12](#)

Meta, [4](#), [13](#)

MetaVARMx, [8](#), [9](#)

OpenMx::imxRobustSE(), [8](#)

print.metadynmeta, [14](#)

summary.metadynmeta, [14](#)

vcov.metadynmeta, [15](#)