

# Package ‘metaVAR’

July 4, 2024

**Title** Multivariate Meta-Analysis of Vector Autoregressive Model Coefficients  
**Version** 0.9.1  
**Description** Estimates the mean vector and covariance matrix of the multivariate meta-analysis of vector autoregressive model coefficients.  
**URL** <https://github.com/jeksterslab/metaVAR>,  
<https://jeksterslab.github.io/metaVAR/>  
**BugReports** <https://github.com/jeksterslab/metaVAR/issues>  
**License** MIT + file LICENSE  
**Encoding** UTF-8  
**Roxygen** list(markdown = TRUE)  
**Depends** R (>= 3.5.0), OpenMx  
**Imports** numDeriv, Matrix  
**Suggests** knitr, rmarkdown, testthat, simStateSpace  
**RoxygenNote** 7.3.2  
**NeedsCompilation** no  
**Author** Ivan Jacob Agaloos Pesigan [aut, cre, cph]  
(<https://orcid.org/0000-0003-4818-8420>)  
**Maintainer** Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com>

## Contents

coef.metavarmeta . . . . .	2
Meta . . . . .	2
print.metavarmeta . . . . .	3
summary.metavarmeta . . . . .	4
vcov.metavarmeta . . . . .	4
<b>Index</b>	<b>6</b>

---

 coef.metavarmeta

*Estimated Parameter Method for an Object of Class metavarmeta*


---

### Description

Estimated Parameter Method for an Object of Class metavarmeta

### Usage

```
## S3 method for class 'metavarmeta'
coef(object, ...)
```

### Arguments

object            an object of class metavarmeta.  
...               further arguments.

### Value

Returns a vector of the mean estimated parameters.

### Author(s)

Ivan Jacob Agaloos Pesigan

---

 Meta

*Fit Multivariate Meta-Analysis*


---

### Description

This function estimates the mean and covariance matrix of a vector of coefficients using the estimated coefficients and sampling variance-covariance matrix from each individual.

### Usage

```
Meta(
  y,
  v,
  mu_start = NULL,
  mu_lbound = NULL,
  mu_ubound = NULL,
  sigma_l_start = NULL,
  sigma_l_lbound = NULL,
  sigma_l_ubound = NULL,
  try = 1000,
  ncores = NULL
)
```

**Arguments**

y	A list. Each element of the list is a numeric vector of estimated coefficients.
v	A list. Each element of the list is a sampling variance-covariance matrix of y.
mu_start	Numeric vector. Optional vector of starting values for mu.
mu_lbound	Numeric vector. Optional vector of lower bound values for mu.
mu_ubound	Numeric vector. Optional vector of upper bound values for mu.
sigma_l_start	Numeric matrix. Optional matrix of starting values for t(chol(sigma)).
sigma_l_lbound	Numeric matrix. Optional matrix of lower bound values for t(chol(sigma)).
sigma_l_ubound	Numeric matrix. Optional matrix of upper bound values for t(chol(sigma)).
try	Positive integer. Number of extra tries for <code>OpenMx::mxTryHard()</code> .
ncores	Positive integer. Number of cores to use.

**Details**

For  $i = \{1, \dots, n\}$ , the objective function used to estimate the mean  $\mu$  and covariance matrix  $\Sigma$  of the random coefficients  $y_i$  is given by

$$\ell(\mu, \Sigma \mid y_i, \mathbb{V}(y_i)) = -\frac{1}{2} \left[ q \log(2\pi) + \log(|\mathbb{V}(y_i) - \Sigma|) + (y_i - \mu)' (\mathbb{V}(y_i) - \Sigma)^{-1} (y_i - \mu) \right]$$

where  $q$  is the number of unique elements in  $\mu$  and  $\Sigma$ , and  $\mathbb{V}(y_i)$  is the sampling variance-covariance matrix of  $y_i$ .

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

print.metavarmeta      *Print Method for Object of Class metavarmeta*

---

**Description**

Print Method for Object of Class metavarmeta

**Usage**

```
## S3 method for class 'metavarmeta'
print(x, alpha = 0.05, digits = 4, ...)
```

**Arguments**

x	an object of class metavarmeta.
alpha	Numeric vector. Significance level $\alpha$ .
digits	Integer indicating the number of decimal places to display.
...	further arguments.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

summary.metavarmeta	<i>Summary Method for Object of Class metavarmeta</i>
---------------------	---

---

**Description**

Summary Method for Object of Class metavarmeta

**Usage**

```
## S3 method for class 'metavarmeta'  
summary(object, alpha = 0.05, digits = 4, ...)
```

**Arguments**

object	an object of class metavarmeta.
alpha	Numeric vector. Significance level $\alpha$ .
digits	Integer indicating the number of decimal places to display.
...	further arguments.

**Author(s)**

Ivan Jacob Agaloos Pesigan

---

vcov.metavarmeta	<i>Variance-Covariance Matrix Method for an Object of Class metavarmeta</i>
------------------	---

---

**Description**

Variance-Covariance Matrix Method for an Object of Class metavarmeta

**Usage**

```
## S3 method for class 'metavarmeta'  
vcov(object, ...)
```

**Arguments**

object	an object of class metavarmeta.
...	further arguments.

**Value**

Returns the variance-covariance matrix of the estimated parameters.

**Author(s)**

Ivan Jacob Agaloos Pesigan

# Index

- \* **Meta-Analysis of VAR Functions**

- Meta, [2](#)

- \* **metaVAR**

- Meta, [2](#)

- \* **meta**

- Meta, [2](#)

- \* **methods**

- coef.metavarmeta, [2](#)

- print.metavarmeta, [3](#)

- summary.metavarmeta, [4](#)

- vcov.metavarmeta, [4](#)

coef.metavarmeta, [2](#)

Meta, [2](#)

OpenMx::mxTryHard(), [3](#)

print.metavarmeta, [3](#)

summary.metavarmeta, [4](#)

vcov.metavarmeta, [4](#)