```java
// A1.java

public class A1 {
	private A1 a1;
	static{
		System.out.println("A1-S");
	}
	static{
		System.out.println("A1-S2");
	}
	{
		System.out.println("A1-N");
	}
	public A1() {
		System.out.println("A1");
	}
	public A1(A1 a1){
		System.out.println("A1(A1)");
		this.a1 = a1;
	}
	void metoda(){
		System.out.println("metoda A1");
	}
	public static void main(String[] args) {
		A4 a4 = new A4();
		a4.metoda();
		a4.metoda2();
		new A2(a4);
	}
}

class A2 extends A1 {
	A1 a1;
	public A2() {
		this(new A1());
		System.out.println("A2");
	}
	public A2(A1 a1){
		this.a1 = a1;
		System.out.println("A2(A1)");
	}
	public void metoda(){
		System.out.println("metoda A2");
	}
	private void metoda2(){
		System.out.println("metoda2 A2");
	}
}

class A3 extends A2 implements Serializable {
	public A3() {
		System.out.println("A3");
	}
	public A3(A2 a2) {
		this();
		System.out.println("A3(A2)");
	}
	public A3(A2 a2, A1 a1) {
		this(a2);
		System.out.println("A3(A2, A1)");
	}
	protected void metoda(){
		System.out.println("metoda A3");
	}
	public void metoda2(){
		System.out.println("metoda2 A3");
	}
}
```

```
class A4 extends A3 {
	private A1 a = new A2();
	private A2 a2 = new A2(new A1(new A1()));
	Serializable a3 = new A3(a2, a1);
	public A4() {
		a2.metoda();
		System.out.println("A4");
		a.metoda();
		((A1) a3).metoda();
	}
	protected void metoda(){
		System.out.println("metoda A4");
	}
}
```

```
// C1.java

public class C1 {
	C1() {
		System.out.println("C1");
	}

	public static void main(String[] args) throws CE1, Exception {
		C1 c1 = new C1();
		C2 c2 = new C2();
		try {
			System.out.println(c2.metoda(c2));
		} catch (CE2 e) {
			System.out.println("main 2: " + e);
		} catch (CE1 e) {
			System.out.println("main 3: " + e);
		} catch (Error e) {
			System.out.println("main 4: " + e);
		} catch (Throwable e) {
			System.out.println("main 5: " + e);
		} finally {
			System.out.println("finally");
		}
		System.out.println(c1.metoda(c2));
		new C1().metoda(new C1());
		c2.close();
	}

	private boolean t = false;

	Object metoda(C1 c) throws CE1 {
		if(t)
			t = false;
		else
			t = true;
		if (c instanceof C1 && (t)) {
			System.out.println("method");
		} else {
			throw new CE2();
		}
		return 1;
	}
}

class C2 extends C1 implements AutoCloseable {
	C2() {
		System.out.println("C2");
	}
	Object metoda(C1 c) throws CE1 {
		System.out.println("method C2");
		if (errorCheck() && c instanceof C2)
			throw new CE2("Error 2");
		else if (c instanceof C2)
			throw new CE1();
		else
			return new String("abc");
	}

	boolean errorCheck() throws CE1 {
		return metoda(null)!=null;
	}
	@Override
	public void close() throws Exception {
		System.out.println("C2: close()");
	}
}
```

```
class CE1 extends Throwable {
	public CE1() {
		System.out.println("CE1 - 1");
	}
	public CE1(String s) {
		super(s);
		System.out.println("CE1 - 2");
	}
}

class CE2 extends RuntimeException {
	public CE2() {
		System.out.println("CE2 - 1");
	}
	public CE2(String s) {
		this();
		System.out.println("CE2 - 2");
	}
}


// D1.java

public class D1 {

	public static void main(String[] args) {
		String test = "FEE Banjaluka!";
		String res = method(t -> {
			String result = "";
			for (int i = t.length() - 1; i >= 0; i--) {
				result += t.charAt(--i);
			}
			return result;
		}, test);
		System.out.println(res);
		res = method(new D2()::method2, test);
		System.out.println(res);
		res = new DI() {
			public String exec(String s) {
				return s.toLowerCase();
			}
		}.exec(test, 4);
		System.out.println(res);
	}

	static String method(DI sf, String s) {
		return sf.exec(s);
	}
}

class D2 {
	public String method2(String s) {
		String result = "";
		for (int i = s.length() - 1; i >= 0; i--) {
			result += s.charAt(i);
		}
		return result;
	}
}

interface DI {
	public String exec(String s);
	default String exec(String s, int i) {
		return s.substring(i);
	}
}
```

```java
// E1.java

public class E1 extends Thread {
	String name;
	public E1(String name) {
		setDaemon(true);
		this.name = name;
	}
	public void run() {
		new Thread(new Runnable() {
			public void run() {
				for(int i=0; i<3; i++){
					System.out.println(name + "1: " + i);
				}
			}
		}).start();
		new Thread(){
			public void run(){
				for (int i = 0; i < 3; i++){
					System.out.println(name + "2: " + i);
				}
			}
		}.run();
		new Thread() {
			void Thread(){
				start();
			}
			public void run() {
				try {
					System.out.println(name + "3: --------");
					this.join();
				} catch (InterruptedException e) {
					e.printStackTrace();
				}
				for (int i = 0; i < 3; i++) {
					System.out.println(name + "3: " + i);
				}
			}
		}.start();
		System.out.println(name);
	}

	public static void main(String args[]){
		System.out.println("START");
		E1 a = new E1("A");
		E2 b = new E2("B");
		E3 c = new E3("C", a);
		E3 d = new E3("D", a);
		a.start();
		b.start();
		try {
			a.join();
			b.join();
		} catch (InterruptedException e) {
			e.printStackTrace();
		}
		System.out.println("END");
	}
}

class E2 extends E1 implements Runnable{

	public E2(String name) {
		super(name);
	}

}
```

```
class E3 extends E2{
	Thread t;
	public E3(String name, Thread t) {
		super(name);
		this.t = t;
		start();
	}
	public void run(){
		try {
			t.join();
		} catch (InterruptedException e) {
			e.printStackTrace();
		}
		for(int i=0; i<3; i++){
			System.out.println(name + "1: " + i);
		}
	}
}
```

```
package org.unibl.etf.assignment01;

public class A {
	B b1 = new B();
	B b2 = new B();
	static {
		System.out.println("static A");
	}
	{
		System.out.println("non-static A");
	}
	public A() {
		System.out.println("Constructor A");
	}
	public static void main(String[] args) {
		new A();
		new B();
	}
}

class B {
	static {
		System.out.println("static B");
	}
	{
		System.out.println("non-static B");
	}
	public B() {
		System.out.println("Constructor B");
	}
}
```

redoslijed korištenja instanci
klasa određuje redoslijed
poziva statičkih blokova

1

A ✓

```
static A
static B
non-static B
Constructor B
non-static B
Constructor B
non-static A
Constructor A
non-static B
Constructor B
```

B

```
static A
non-static A
Constructor A
static B
non-static B
Constructor B
non-static B
Constructor B
non-static B
Constructor B
```

C

```
static A
static B
non-static A
Constructor A
non-static B
Constructor B
non-static B
Constructor B
non-static B
Constructor B
```

D

```
static A
Constructor A
non-static A
static B
Constructor B
non-static B
Constructor B
non-static B
Constructor B
non-static B
```

```
package org.unibl.etf.assignment02;

public class A {
	static {
		int x = 5;
	}

	static int x, y;

	public static void main(String args[]) {
		x--;
		System.out.println(x);
		System.out.println(y);
		metoda();
		System.out.println(x);
		System.out.println(y);
		System.out.println(++x + x++);		// B
		System.out.println(++A.x);		// C
	}

	public static void metoda() {
		y = ++x;
	}
```

2

A

4
0
5
5
12
8

B

Greška pri kompajliranju u liniji koda označenoj oznakom B

C

Greška pri kompajliranju u liniji koda označenoj oznakom C

D

-1
0
0
0
2
3

```
package org.unibl.etf.assignment03;

public class A {

	static double i = 1;
	static int j = 2;
	int x = 3;
	static int y = 6;

	public static void main(String args[]){
		metoda();
		System.out.println(i + j);
		System.out.println(x + i);		// B
		metoda2();
		System.out.println(i + y);
		System.out.println(i + j);
	}

	public static int metoda(){
		return (int)i + --y + (j++);
	}

	public static double metoda2(){
		return  j++ - --i;
	}
};
;;
                                        // D
```

promjenljiva x je vezana za instancu, nije statička promjenljiva

3

A

4.0
4.0
5.0
4.0

B

Greška pri kompajliranju u liniji koda označenoj oznakom B

C

4
4
5
4

D

Greška pri kompajliranju u liniji koda označenoj oznakom D

```
package org.unibl.etf.assignment04;

public class A {
	static int x = 3;                          // C
	public static void main(String[] args) {
		new A();
	}

	A() {
		A(2);                                  // D
	}

	A(int x) {
		System.out.println(x);
	}
}
```

this(2) ✓

4

A	B
2	3
C	**D**
Greška pri kompajliranju u liniji koda označenoj oznakom C	Greška pri kompajliranju u liniji koda označenoj oznakom D

```java
package org.unibl.etf.assignment05.a;

public class A {

	private void methodA() {
	}

	void methodB() {
	}

	protected void methodC() {
	}

	public void methodD() {
	}
}
```

package-private

unutar klase, podklasa čak i van paketa i unutar istog paketa

```java
package org.unibl.etf.assignment05.b;

import org.unibl.etf.assignment05.a.A;

public class Main {

	public static void main(String[] args) {
		A a = new A();
		a.methodA();		// A
		a.methodB();		// B
		a.methodC();		// C
		a.methodD();		// D
	}

}
```

5

A Greška pri kompajliranju u liniji koda označenoj oznakom A	**B** Greška pri kompajliranju u linijama koda označenim oznakama A i B
C Greška pri kompajliranju u linijama koda označenim oznakama A, B i C	**D** Greška pri kompajliranju u linijama koda označenim oznakama A, B, C i D

```
package org.unibl.etf.assignment07;

public class A {
	int 1abc;
	int abc_1;
	int oneAbc;
	int final;
	int $while;
}
```

while$ takođe validan

6

A

Svi identifikatori su validni

B

Svi identifikatori, osim $while, su validni

C

Validni identifikatori su: abc_1, oneAbc, $while

D

Validni identifikatori su: abc_1, oneAbc

E

Validan je samo identifikator oneAbc

F

Nema validnih identifikatora

```java
package org.unibl.etf.assignment07;

public class B {
	public static void main(String[] args) {
		int i = 1;
		int n = ++i % 5;
		System.out.print(n);
		n = i-- % 4;
		System.out.print(n);
		n = i++ % 2;
		System.out.print(n);
	}
}
```

7

A ✓ 221	**B** 110
C 121	**D** 220
E Izuzetak pri izvršavanju	**F** Greška pri kompajliranju

```java
package org.unibl.etf.assignment07;

public class C {
	public static void main(String arg[]) {
		int i = 4;
		for (; i <= 12; i+=3) {
			i = i++;
			i -= 1;
			i++;
			i += 1;
			i = i++;
		}
		System.out.println(--i);
	}
}
```

8

A ✓ 15	**B** 18
C 17	**D** 13
E 16	**F** 14

```java
package org.unibl.etf.assignment07;


public class D {
	String outerProperty = "1";

	void method() {
		N nestedClass = new N();
		nestedClass.method();
	}

	public class N{
		String innerProperty = "2";
		void method() {
			System.out.print(outerProperty + innerProperty);
		}
	}

	public static void main(String[] args) {
		D outerClass = new D();
		outerClass.method();
		D.N nested = outerClass.new N();
		nested.method();
	}
}
```

9

A

Ispis 1212

B

Ispis 12, pa izuzetak pri izvršavanju

C

Greška pri kompajliranju

D

Izuzetak pri izvršavanju

```java
package org.unibl.etf.assignment08;


class MyError extends Error {
}

public class A {
	public static void main(String args[]) {
		try {
			test();
		} catch (Error ie) {
			System.out.println("Error caught");
		}
	}

	static void test() throws Error {
		throw new MyError();
	}
}
```

10

A Izuzetak pri izvršavanju: metoda test ne može baciti MyError	**B** Greška pri kompajliranju: metoda test ne može baciti MyError
C Greška pri kompajliranju: nije moguće naslijediti klasu Error	**D** Error caught
E Nema ispisa	**F** Ništa od navedenog

```java
package org.unibl.etf.rt_rk.first;

import java.io.IOException;

public class B {
	public static void main(String args[]) {
		try {
			throw new java.io.IOException();
		}
	}
}
```

11

A

Greška pri kompajliranju: nedostaje finally blok

B

Greška pri kompajliranju: nedostaje catch blok

C

Ispisuje se stack trace koji sadrzi informacije o izuzetku

D

Ništa od navedenog

```java
package org.unibl.etf.assignment08;

public class C {
	public static void main(String[] args) {
		Integer i1 = 2;
		Integer i2 = 3;
		Integer i3 = 1;
		Integer i4 = 6;
		Integer i5= i1 & i2 | i3 ^ i4;
		System.out.println(i5);
	}
}
```

^ → XOR

1 0 1
0 1 1
0 0 0
1 1 0

1 0
1 1
---
0 1 0

0 0 1
1 1 0
---
1 1 1

1 0
1 1 1
---
1 1 1 1 = 7

12	
A 6	B 8
C 7	D 1
E 5	F 9

```java
/*
 * Maksimalna veličina heap-a je 1500 MB
 * Pretpostaviti da će garbage collector biti pokrenut u trenutku kada na heap-u nema dovoljno prostora za smještanje novih objekata
 */

package org.unibl.etf.assignment08;


public class D {
	static int counter = 0;
	int intArray[];
	double doubleArray[] = new double[25_000_000];

	public D() {
		intArray = new int[25_000_000];
		byte byteMemory[] = new byte[500_000_000];
		System.out.print(++counter + " ");
	}

	public static void main(String[] args) {
		D array[] = new D[100_000];
		for(int i=0; i<array.length; i++) {
			array[i] = new D();
		}
	}
}
```

~~13~~

A

1 OutOfMemoryError

B

1 2 3
OutOfMemoryError

C

1 2 3 4 5 6 7 8 9
10 11 12 13 14 15
16 17 18 19 20 21
22 23 …
StackOverflowError

D

1 2 3 4 5
OutOfMemoryError

```
package org.unibl.etf.assignment06;

public class A {
	public static void main(String[] args) {
		A a = new A();
		try {
			a.metoda();
		}catch (Exception t) {
			System.out.println("catch");
		}finally{
			System.out.println("finally");
		}
		a.metoda2();                                    // A
	}
	void metoda() throws CE1 {
		throw new CE2("Error 2");
	}
	void metoda2() throws CE3 {
		throw new CE3();                                // B
	}
}
class CE1 extends Exception {
	public CE1() {
		System.out.println("CE1 - 1");
	}
	public CE1(String s) {
		System.out.println(s);
	}
}
class CE2 extends CE1 {
	public CE2(String s) {                              // C
		System.out.println("CE2 - 2");
	}
}
class CE3 extends RuntimeException {
	public CE3() {
		System.out.println("CE3 - 1");
	}
}
```

jer RunTimeException nije uhvaćen i obrađen nigdje

14

A

CE1 - 1
CE2 - 2
catch
finally
CE3 - 1
Propagiran izuzetak u liniji koda označenoj oznakom A

B

CE1 - 2
CE2 - 2
catch
finally

C

Greška pri kompajliranju u liniji koda označenoj oznakom C

D

Greška pri kompajliranju u liniji koda označenoj oznakom B

```java
package org.unibl.etf.assignment09;

public class A {
	public static void main(String[] args) {
		try (AException aEx = new AException()) {
			System.out.println("try block");
			aEx.test();
		} catch (Exception e) {
			System.out.println("catch block");
		} finally {
			System.out.println("finally block");
		}
	}

}

class AException implements AutoCloseable {
	@Override
	public void close() throws Exception {
		System.out.println("close()");
		throw new Exception();
	}
	public void test() {
		System.out.println("test()");
	}
}
```

OBAVEZNO

15

A

Greška pri kompajliranju - catch i finally blokovi su suvišni, jer se koristi try-with-resources konstrukcija

B

try block
test()
catch block
finally block
close()

C

try block
test()
catch block
close()
finally block

D ✓

try block
test()
close()
catch block
finally block

```
package org.unibl.etf.assignment10;

interface A {
	void main(String[] args);
}

interface B {
	public void main(String[] args);
}

interface C {
	public static void main(String[] args);
}

interface D {
	protected void main(String[] args);
}

interface E {
	private void main(String[] args);
}
```

* static i private metode u interfejsu moraju imati implementaciju

* protected zabranjen pristup u interfejsima

16

A

Validne su deklaracije interfejsa A, B i C

B

Validne su deklaracije interfejsa C i E

C

Validne su deklaracije interfejsa A i B

D

Validne su deklaracije interfejsa A, C i D

E

Validne su deklaracije svih interfejsa

F

Nema validnih deklaracija interfejsa

```
package org.unibl.etf.assignment11;


interface I1 { }

interface I2 { }

class B2 implements I1 { }

class B3 extends B2 implements I2 { }

public class B {
	public static void main(String args[]) {
		B2[] base = { new B2() };		// A
		B3 dev[] = { new B3() };		// B
		Object obj = dev;			// C
		B2 b = obj;				// D
	}
}
```

neophodno kastovanje u B2

B2 b = (B2) obj;

17

A Greška pri kompajliranju u liniji označenoj oznakom A	**B** Greška pri kompajliranju u liniji označenoj oznakom B
C Greška pri kompajliranju u liniji označenoj oznakom C	**D** Greška pri kompajliranju u liniji označenoj oznakom D
E Izuzetak pri izvršavanju	**F** Nema izuzetka, nema ispisa

```
package org.unibl.etf.assignment11;


interface I {
	void method();
}

class C implements I {
	static C r = new C();                                  // A
	public static void main(String[] args) {
		C r = new C();                                 // B
		r.method();
	}
	void method() {                                        // C
		System.out.println("abcdef");
	}
}
```

package-private po default-u

OBAVEZNO public

ne smije se smanjiti vidljivost

18

A

Greška pri kompajliranju u liniji označenoj oznakom A

B

Greška pri kompajliranju u liniji označenoj oznakom B

C

Greška pri kompajliranju u liniji označenoj oznakom C

D

abcdef

```
package org.unibl.etf.assignment11;

public enum D1 {
	A (1),
	B (2),
	C (3),
	D (4),
	E (5);
	private D1(int a){
		System.out.print("D1");
	}
	public static void main(String[] args) {
		for(D1 q2: D1.values()){
			System.out.print(q2);
		}
	}
}
```

.values() vraća niz [A, B, C, D, E]

19

A D1D1D1D1D1ABCDE	**B** D1D1D1D1D112345
C 12345	**D** ABCDE
E Izuzetak pri izvršavanju	**F** Greška pri kompajliranju

```java
package org.unibl.etf.assignment11;

public class E {
	private G g = new G();
	public E() {
		System.out.println("E");
	}
	void method() {
		System.out.println("method from E");
	}

	public static void main(String[] args) {
		G g = new G();
		g.method();
	}
}

class F extends E {
	public F() {
		System.out.println("F");
	}
	void method() {
		System.out.println("method from F");
	}
}

class G extends F {
	public G() {
		System.out.println("G");
	}
	void method() {
		super.method();
		System.out.println("method from G");
	}
}
```

problematična linija koda

pokreće rekurzivni lanac

poziva metodu SAMO iz neposredne nadklase (u ovom slučaju klase F)

// A

20

A

```
E
F
G
method from F
method from G
```

B

```
E
F
G
method from E
method from F
method from G
```

C

```
E
G
F
G
method from F
method from G
```

D

```
E
F
G
E
F
G
method from F
method from G
```

E

Izuzetak pri izvršavanju - StackOverflowError

F

Greška pri kompajliranju u liniji označenoj oznakom A