

```

// Klasa0.java
public class Klasa0 {
    static {
        int x = 5;
    }

    static int x, y;

    public static void main(String args[]) {
        x--;
        System.out.println(x + " " + y);
        metoda();
        System.out.println(x + " " + y);
        System.out.println(++x + x++);
        System.out.println(++Klasa0.x);
    }

    public static void metoda() {
        y = ++x;
    }
}
// Klasa1.java

public class Klasa1 {
    int i = 0;

    public static void main(String argv[]) {
    }

    Klasa1() {
        top: while (i < 2) {
            System.out.println(i);
            i++;
            continue top;
        }
    }
}
// Klasa2.java

class Klasa2{

    static double i = 1;
    static int j = 2;
    int x = 3;
    static int y = 6;

    public static void main(String args[]){
        metoda();
        System.out.println(i + j);
        System.out.println(x + i);
        metoda2();
        System.out.println(i + y);
        System.out.println(x + j);
    }

    public static int metoda(){
        return (int)i + --y + (j++);
    }

    public static double metoda2(){
        return j++ - --i;
    }
};
;;

// Klasa4.java
public class Klasa4 {
    int j = 1;

    public static void main(String args[]){
        metoda();
    }
}

```

```

        Klasa4 a = new Klasa4();
        a.metoda();
    }
    public static void metoda(){
        char digit = 'a';
        for (int i = 0; i < 10; i++){
            switch (digit){
                case 'x':
                {
                    int j = 0;
                    System.out.println(j);
                }
                default:
                {
                    int j = 100;
                    System.out.println(j);
                }
            }
        }
        int i = j;
        System.out.println(i);
    }
}

```

```

// Klasa5.java
public class Klasa5 {
    int x = 0, y = 0;
    Klasa5(int a, int b){
        x = a;
        y = b;
    }
    protected int zbir(){
        return x + y;
    }
    protected int razlika(){
        return x - y;
    }
    public static void main(String s[]){
        Klasa5 b = new Klasa5(1,2);
        Klasa6 c = new Klasa6();
        System.out.println(b.razlika());
        System.out.println(c.razlika());
    }
}

```

```

class Klasa6 extends Klasa5{
    public int zbir(){
        return y+x;
    }
    public int razlika(){
        return y-x;
    }
}

```

```

// Klasa3.java
public class Klasa3{
    static int x = 3;

    public static void main(String[] args) {
        new Klasa3();
    }

    Klasa3() {
        Klasa3(2);
    }

    Klasa3(int x) {

```

```

        System.out.println(x);
    }
}

// Klasa7.java
public class Klasa7 {
    public static void main(String[] args) {
        Klasa7 e = new Klasa7();
        Klasa8 f = new Klasa8();
        try {
            f.metoda();
            e.metoda();
        } catch (Exception t) {
            System.out.println("catch 1");
        } finally {
            System.out.println("finally");
        }
    }
    void metoda() throws CE1 {
        throw new CE2("Error 2");
    }
}

class Klasa8 extends Klasa7 {
    void metoda() {
        try {
            throw new CE1();
        } catch (CE1 e) {
            System.out.println("catch 2");
        }
    }
}

class CE1 extends Exception {
    public CE1() {
        System.out.println("CE1 - 1");
    }
    public CE1(String s) {
        System.out.println(s);
    }
}

class CE2 extends CE1 {
    public CE2() {
        System.out.println("CE2 - 1");
    }
    public CE2(String s) {
        System.out.println("CE2 - 2");
    }
}

//Tablet.java
interface Gadget {
    void doStuff();
}
abstract class Electronic {
    void getPower() { System.out.print("plug in "); }
}
public class Tablet extends Electronic implements Gadget {
    void doStuff() { System.out.print("show book "); }
    public static void main(String[] args) {
        new Tablet().getPower();
        new Tablet().doStuff();
    }
}

//Bottom2.java

class Top {
    public Top(String s) { System.out.print("B"); }
}
public class Bottom2 extends Top {

```

```

public Bottom2(String s) { System.out.print("D"); }
public static void main(String [] args) {
    new Bottom2("C");
    System.out.println(" ");
}
}

//Clidlet.java
class Clidder {
    private final void flipper() \{ System.out.println("Clidder"); }
}
public class Clidlet extends Clidder {
    public final void flipper(){ System.out.println("Clidlet"); }
    public static void main(String [] args) {
        new Clidlet().flipper();
    }
}

//Frodo.java
    public class Frodo extends Hobbit
    public static void main(String[] args) {
        int myGold = 7;
        System.out.println(countGold(myGold, 6));
    }
    class Hobbit {
        int countGold(int x, int y) { return x + y; }
    }

//Hawk.java
class Bird {
    \{ System.out.print("b1 "); }
    public Bird() { System.out.print("b2 "); }
}
class Raptor extends Bird {
    static { System.out.print("r1 "); }
    public Raptor() { System.out.print("r2 "); }
    { System.out.print("r3 "); }
    static { System.out.print("r4 "); }
}
class Hawk extends Raptor {
    public static void main(String[] args) {
        System.out.print("pre ");
        new Hawk();
        System.out.println("hawk ");
    }
}

//DogShow.java
class Dog {
    public void bark() \{ System.out.print("woof "); }
}
class Hound extends Dog {
    public void sniff() { System.out.print("sniff "); }
    public void bark() { System.out.print("howl "); }
}
public class DogShow {
    public static void main(String[] args) { new DogShow().go(); }
    void go() {
        new Hound().bark();
        ((Dog) new Hound()).bark();
        ((Dog) new Hound()).sniff();
    }
}

// dodati naziv fajla === _____
class Building {
    Building() { System.out.print("b "); }
    Building(String name) {
        this(); System.out.print("bn " + name);
    }
}
public class House extends Building {

```

```

House() { System.out.print("h "); }
House(String name) {
    this(); System.out.print("hn " + name);
}
public static void main(String[] args) { new House("x "); }
}

//dodati naziv fajla === _____
class Mixer {
    Mixer() {
    }

    Mixer(Mixer m) {
        m1 = m;
    }

    Mixer m1;
    public static void main(String[] args) {
        Mixer m2 = new Mixer();
        Mixer m3 = new Mixer(m2); m3.go();
        Mixer m4 = m3.m1; m4.go();
        Mixer m5 = m2.m1; m5.go();
    }
    void go() {
        System.out.print("hi ");
    }
}

class Fizz {
    int x = 5;\par
    public static void main(String[] args) {
        final Fizz f1 = new Fizz();
        Fizz f2 = new Fizz();
        Fizz f3 = FizzSwitch(f1,f2);
        System.out.println((f1 == f3) + " " + (f1.x == f3.x));\par
    }

    static Fizz FizzSwitch(Fizz x, Fizz y) {
        final Fizz z = x;
        z.x = 6;
        return z;
    }
}

    public class Wind{
        int id;
        Wind(int i){
            id = i;
        }
        public static void main(String[] args){
            new Wind(3).go();
        }
        void go() {\par
            Wind w1 = new Wind(1);\par
            Wind w2 = new Wind(2);\par
            System.out.println(w1.id + " " + w2.id);\par
        }
    }

public class Ouch {
    static int ouch = 7;
    public static void main(String[] args){
        new Ouch().go(ouch);
        System.out.print(" " + ouch);
    }
}

```

```

        void go(int ouch) {
            ouch++;
            for(int ouch = 3; ouch < 6; ouch++);
            System.out.print(" " + ouch);
        }
    }
}

```

```

public class Happy {
    int id;\par
    Happy(int i) {
        id = i;
    }

    public static void main(String[] args){
        Happy h1 = new Happy(1);
        Happy h2 = h1.go(h1);
        System.out.println(h2.id);
    }
    Happy go(Happy h) {
        Happy h3 = h;
        h3.id = 2;
        h1.id = 3;
        return h1;
    }
}

```

```

class Beta {
}

    class Alpha {
        static Beta b1;
        Beta b2;
    }
    public class Tester {
        public static void main(String[] args){
            Beta b1 = new Beta(); Beta b2 = new Beta();
            Alpha a1 = new Alpha(); Alpha a2 = new Alpha();
            a1.b1 = b1;
            a1.b2 = b1;
            a2.b2 = b2;
            a1 = null;
        }
    }
    b1 = null;
    b2 = null;--- nacrtati heap i odrediti koliko objekata ce biti pocisceno
}
}

```

```

public class Telescope {
    static int magnify = 2;
    public static void main(String[] args) {
        go();
    }
    static void go() {
        int magnify = 3 ;
        zoomIn();
    }
    static void zoomIn() {
        magnify *= 5;
        zoomMore(magnify);
        System.out.println(magnify);
    }
    static void zoomMore(int magnify) {
        magnify *= 7; } }

    public class Dark {
        int x = 3;
        public static void main(String[] args) {
            new Dark().gol();
        }
        void gol() {

```

```

int x;
    go2(++x);
}
void go2(int y) {
int x = ++y;
    System.out.println(x);
}
}

```

```

    class Hexy {
public static void main(String[] args) {
int i = 42;
String s = (i<40)?"life":(i>50)?"universe":"everything";
System.out.println(s);
}
}

```

```

public class Main{
public static void main(String[] args){
Thread.sleep(500);
}
}

```

```

public class Dog {
String name;
Dog(String s) { name = s; }
public static void main(String[] args) {
Dog d1 = new Dog("Boi");
Dog d2 = new Dog("Tyri");
System.out.print((d1 == d2) + " ");
Dog d3 = new Dog("Boi");
d2 = d1;
System.out.print((d1 == d2) + " ");
System.out.print((d1 == d3) + " ");
}
}

```

```

class Feline {
public static void main(String[] args) {
long x = 42L;
long y = 44L;
System.out.print(" " + 7 + 2 + " ");
System.out.print(foo() + x + 5 + " ");
System.out.println(x + y + foo());
}
static String foo() { return "foo"; }
}

```

```

public class SpecialOps {
public static void main(String[] args) {
String s = "";
boolean b1 = true;
boolean b2 = false;
if((b2 = false) | (21%5) > 2) s += "x";
if(b1 || (b2 == true)) s += "y";
if(b2 == true) s += "z";
System.out.println(s);
}
}

```

```

interface Vessel { }
interface Toy { }
class Boat implements Vessel { }
class Speedboat extends Boat implements Toy { }
public class Tree {

```

```

public static void main(String[] args) {
    String s = "0";
    Boat b = new Boat();
    Boat b2 = new Speedboat();
    Speedboat s2 = new Speedboat();
    if((b instanceof Vessel) && (b2 instanceof Toy)) s += "1";
    if((s2 instanceof Vessel) && (s2 instanceof Toy)) s += "2";
    System.out.println(s);
}
}

```

```

public class Mutant {
    public static void main(String[] args) {
        StringBuilder sb = new StringBuilder("abc");
        String s = "abc";
        sb.reverse().append("d");
        s.toUpperCase().concat("d");
        System.out.println("." + sb + ". ." + s + ".");
    }
}

```

```

import java.util.*;
public class Sequence {
    public static void main(String[] args) {
        ArrayList<String> myList = new ArrayList<String>();
        myList.add("apple");
        myList.add("carrot");
        myList.add("banana");
        myList.add(1, "plum");
        System.out.print(myList);
    }
}

```

```

public class Tailor {
    public static void main(String[] args) {
        byte[][] ba = {{1,2,3,4}, {1,2,3}};
        System.out.println(ba[1].length + " " + ba.length);
    }
}

```

```

class Dozens {
    int[] dz = {1,2,3,4,5,6,7,8,9,10,11,12};
}

public class Eggs {
    public static void main(String[] args) {
        Dozens [] da = new Dozens[3];
        da[0] = new Dozens();
        Dozens d = new Dozens();
        da[1] = d;
        d = null;
        da[1] = null;
        // do stuff
    }
}

```

```

public class Hedges {
    public static void main(String[] args) {
        String s = "JAVA";
        s = s + "rocks";
        s = s.substring(4,8);
        s.toUpperCase();
        System.out.println(s);
    }
}

class Plane {
    static String s = "-";
    public static void main(String[] args) {
        new Plane().s1();
    }
}

```



```

System.out.println(s);
}
void s1() {
try { s2(); }
catch (Exception e) { s += "c"; }
}
void s2() throws Exception {
s3(); s += "2";
s3(); s += "2b";
}
void s3() throws Exception {
throw new Exception();
}
}

```

```

class Emu {
static String s = "-";
public static void main(String[] args) {
try {
throw new Exception();
} catch (Exception e) {
try {
try { throw new Exception();
} catch (Exception ex) { s += "ic "; }
throw new Exception(); }
catch (Exception x) { s += "mc "; }
finally { s += "mf "; }
} finally { s += "of "; }
System.out.println(s);
} }

```

```

public class Ebb {
static int x = 7;
public static void main(String[] args) {
String s = "";
for(int y = 0; y < 3; y++) {
x++;
switch(x) {
case 8: s += "8 ";
case 9: s += "9 ";
case 10: { s+= "10 "; break; }
default: s += "d ";
case 13: s+= "13 ";
}
}
System.out.println(s);
}
static { x++; }
}

```

```

public class Circles {
public static void main(String[] args) {
int[] ia = {1,3,5,7,9};
for(int x : ia) {
for(int j = 0; j < 3; j++) {
if(x > 4 && x < 8) continue;
System.out.print(" " + x);
if(j == 1) break;
continue;
}
continue;
}
}
}

```

```

public class OverAndOver {
static String s = "";
public static void main(String[] args) {
try {
s += "1";
throw new Exception();
} catch (Exception e) { s += "2";
} finally { s += "3"; doStuff(); s += "4";
}
System.out.println(s);
}
static void doStuff() { int x = 0; int y = 7/x; }
}

public class Wind {
public static void main(String[] args) {
foreach:
for(int j=0; j<5; j++) {
for(int k=0; k< 3; k++) {
System.out.print(" " + j);
if(j==3 && k==1) break foreach;
if(j==0 || j==2) break;
}
}
}
}

public class Kico {
public static void main(String... args){
Integer i = 15 ;
int j = i ;
while(i -- > 0 ) ;
System.out.println("i = " + i + " j = " + j );
}
}

class MyThread extends Thread {
public static void main(String [] args) throws Exception{
MyThread t = new MyThread();
Thread x = new Thread(t);
Thread y = new Thread(t) ;
y.start() ;
y.join() ;
x.start();
}
public void run() {
for(int i=0;i<3;++i) {
System.out.print(i + "..");
}
}
}

class MyThread extends Thread {
MyThread() {
System.out.print("MyThread ");
}
public void run() {
System.out.print("bar ");
}
public void run(String s) {
System.out.print("baz ");
}
}

public class TestThreads {
public static void main (String [] args) {
Thread t = new MyThread() {
public void run() {
System.out.print("foo ");
}
};
};

```

```

t.start();
} } -- crtati niti

public class ThreadDemo {
    synchronized void a() { actBusy(); }
    static synchronized void b() { actBusy(); }
    static void actBusy() {
        try {
            Thread.sleep(1000);
        } catch (InterruptedException e) {}
    }
    public static void main(String[] args) {
        final ThreadDemo x = new ThreadDemo();
        final ThreadDemo y = new ThreadDemo();
        Runnable runnable = new Runnable() {
            public void run() {
                int option = (int) (Math.random() * 4);
                switch (option) {
                    case 0: x.a(); break;
                    case 1: x.b(); break;
                    case 2: y.a(); break;
                    case 3: y.b(); break;
                }
            }
        };
        Thread thread1 = new Thread(runnable);
        Thread thread2 = new Thread(runnable);
        thread1.start();
        thread2.start();
    }
}

```

```

public class TwoThreads {
    static Thread laurel, hardy;
    public static void main(String[] args) {
        laurel = new Thread() {
            public void run() {
                System.out.println("A");
                try {
                    hardy.sleep(1000);
                } catch (Exception e) {}
                System.out.println("B");
            }
        };
        System.out.println("C");
    };
    hardy = new Thread() {
        public void run() {
            System.out.println("D");
            try {
                laurel.wait();
            } catch (Exception e) {}
            System.out.println("E");
        }
    };
    System.out.println("F");
    laurel.start();
    hardy.start();
}

```

```

public class Leader implements Runnable {
    public static void main(String[] args) {
        Thread t = new Thread(new Leader());
        t.start();
        System.out.print("m1 ");
        t.join();
        System.out.print("m2 ");
    }
    public void run() {
        System.out.print("r1 ");
    }
}

```

```

        System.out.print("r2 ");
    }
}

import java.io.*;
class Player {
    Player() { System.out.print("p"); }
}
class CardPlayer extends Player implements Serializable {
    CardPlayer() { System.out.print("c"); }
    public static void main(String[] args) {
        CardPlayer c1 = new CardPlayer();
        try {
            FileOutputStream fos = new FileOutputStream("play.txt");
            ObjectOutputStream os = new ObjectOutputStream(fos);
            os.writeObject(c1);
            os.close();
            FileInputStream fis = new FileInputStream("play.txt");
            ObjectInputStream is = new ObjectInputStream(fis);
            CardPlayer c2 = (CardPlayer) is.readObject();
            is.close();
        } catch (Exception x) { }
    }
}

import java.io.*;
class Keyboard { }
public class Computer implements Serializable {
    private Keyboard k = new Keyboard();
    public static void main(String[] args) {
        Computer c = new Computer();
        c.storeIt(c);
    }
    void storeIt(Computer c) {
        try {
            ObjectOutputStream os = new ObjectOutputStream(
                new FileOutputStream("myFile"));
            os.writeObject(c);
            os.close();
            System.out.println("done");
        } catch (Exception x) {System.out.println("exc"); }
    }
}

import java.io.*;
public class TestSer {
    public static void main(String[] args) {
        SpecialSerial s = new SpecialSerial();
        try {
            ObjectOutputStream os = new ObjectOutputStream(
                new FileOutputStream("myFile"));
            os.writeObject(s); os.close();
            System.out.print(++s.z + " ");
            ObjectInputStream is = new ObjectInputStream(
                new FileInputStream("myFile"));
            SpecialSerial s2 = (SpecialSerial)is.readObject();
            is.close();
            System.out.println(s2.y + " " + s2.z);
        } catch (Exception x) {System.out.println("exc"); }
    }
}
class SpecialSerial implements Serializable {
    transient int y = 7;
    static int z = 9;
}

}

public class Mainy{

    int id;

    double[] doubles = new double[10000000];

```

```

long[] longs = new long[6000000];

Mainy[] mys = new Mainy[3];

Mainy m;

Dumb d;

public Mainy(Main m){

    this.m = m;

    if(m!=null)
        id = m.id + 1;

}

public static void main(String[] args){

    Mainy m0 = new Mainy(null);

    Mainy m1 = new Mainy(m0);

    Mainy m2 = new Mainy(m1);

    Mainy m3 = new Mainy(m2);

    Mainy m4 = m3;

    Mainy m5 = new Mainy(m0);

    Mainy[] ms = new Mainy[3];

    ms[0] = new Mainy(m2);

    ms[1] = new Mainy(m3);

    ms[2] = new Mainy(m2);

    m1 = m2 = m3 = m5 = null;

    System.gc();    //1                //pozivanje garbage collectora

    ms[0] = new Mainy(ms[0]);

    ms[1] = new Mainy(ms[1]);

    ms[2] = new Mainy(ms[2]);

    ms[2].m = ms[0];

    m3 = new Mainy(ms[0] = null);

    ms[0] = new Mainy(ms[0]);

    System.gc();    //2

}

}

class Dumb {

    float[] flaots = new float[20000000];

    int[] ints = new int[40000000];

```

```
}
```

1.

```
public class ThreadA extends Thread {
    String name;
    public ThreadA(String name) {
        this.name = name;
    }
    public void run() {
        new Thread(){
            public void run(){
                for (int i = 0; i < 10; i++){
                    System.out.println(name + "2: " + i);
                }
            }
        }.start();
        System.out.println(name);
    }

    public static void main(String args[]) throws InterruptedException{
        System.out.println("Pocetak programa");
        ThreadA a = new ThreadA("A");
        ThreadB b = new ThreadB("B");
        ThreadC c = new ThreadC("C", a);
        a.start();
        b.start();
        a.join();
        b.join();
        System.out.println("Kraj programa");
    }
}
```

```
class ThreadB extends ThreadA implements Runnable{
    public ThreadB(String name) {
        super(name);
    }
}
```

```
class ThreadC extends ThreadB{
    Thread t;
    public ThreadC(String name, Thread t) {
        super(name);
        this.t = t;
        start();
    }
    public void run(){
        try {
            t.join();
        } catch (InterruptedException e) {
            e.printStackTrace();
        }
        for(int i=0; i<10; i++){
            System.out.println(name + "1: " + i);
        }
    }
}
```

2.

```
public class ThreadD extends Thread {
    private String name;
    public ThreadD(String name) {
        this.name = name;
    }
    public void run() {
        Runnable r = new Runnable() {
            public void run() {
                for(int i=0; i<10; i++){
                    System.out.println(name + "1: " + i);
                }
            }
        }
    }
}
```

```

        };
        new Thread(r).start();

for(int i=0; i<10; i++){
    System.out.println(name + "2: " + i);

    }
}
public static void main(String args[]){
    ThreadD a = new ThreadD("A");
    ThreadD b = new ThreadD("B");
    a.start();
    b.start();
}
}
3.
public class ThreadE extends Thread {
    private String name;
    public ThreadE(String name) {
        this.name = name;
    }
    public void run() {
        new Runnable() {
            public void run() {
                for(int i=0; i<10; i++){
                    System.out.println(name + "1: " + i);
                }
            }
        }.start();

        for (int i = 0; i < 10; i++){
            System.out.println(name + "2: " + i);
        }
    }
    public static void main(String args[]){
        ThreadE a = new ThreadE("A");
        ThreadE b = new ThreadE("B");
        a.start();
        b.start();
    }
}

```

```

// Peta.java
interface PrviI extends DrugiI, TreciI {
    void metoda();
}
interface DrugiI {
    void metoda();
}
interface TreciI {
    void metodaI3();
}

```

```

class Peta implements PrviI, TreciI {
    public void metoda() {
        System.out.println("metoda");
    }
    public void metodaI3() {
        System.out.println("metoda I3");
    }
}

```

```

class Dvanaesta{
    public static void main(String [] args) {
        Peta e = new Peta();
        PrviI i = new Peta();
        DrugiI i2 = e;
        i.metoda();
        e.metodaI3();
        i.metodaI3();
        i2.metoda();
    }
}

```

```

    }
}

// H.java
package paketA;

interface I {
    void metoda();
}

class H implements I {
    static H h = new H();
    public static void main(String[] args) {
        H h = new H();
        h.metoda();
    }

    void metoda() {
        System.out.println("abcdef");
    }
}

```

```

//A.java
package paketA;

class A {
    static int i;
    A() {
        ++i;
    }

    private int metoda() {
        return ++i;
    }
};

class B extends A {

    B() {
        i++;
    }

    int metoda() {
        return (i + 3);
    }
};

class X extends B {

    public static void main(String ka[]) {
        X x = new X();
        A a = new A();
        a = (A) x;
        System.out.println(a.metoda());
    }
};

// A.java
public class A {
    int j = 1;
}

```



```

public static void main(String args[]){
    metoda();
    A a = new A();
    a.metoda();
}
public static void metoda(){
    char digit = 'a';
    for (int i = 0; i < 10; i++){
        switch (digit){
            case 'x':
            {
                int j = 0;
                System.out.println(j);
            }
            default:
            {
                int j = 100;
                System.out.println(j);
            }
        }
    }
    int i = j;
    System.out.println(i);
}
}

```

```

// B.java
public class B {
    int x = 0, y = 0;
    B(int a, int b){
        x = a;
        y = b;
    }
    protected int zbir(){
        return x + y;
    }
    protected int razlika(){
        return x - y;
    }
    public static void main(String s[]){
        B b = new B(1,2);
        C c = new C();
        System.out.println(b.razlika());
        System.out.println(c.razlika());
    }
}

```

```

class C extends B{
    public int zbir(){
        return y+x;
    }
    public int razlika(){
        return y-x;
    }
}

```

```

// D.java
public class D implements I3{
    public void metoda3() {
        System.out.println(3);
    }
    public void metoda() {
        System.out.println(1);
    }
    public void metoda2() {
        System.out.println(2);
    }
    public static void main(String args[]){
        D d = new D();
        E e = new E();
    }
}

```

```

        d.metoda();
        e.metoda();
    }
}

class E implements I{
    public void metoda() {
        System.out.println(11);
    }
}

interface I{
    void metoda();
}

abstract interface I2{
    abstract void metoda2();
}

interface I3 extends I, I2{
    void metoda3();
}

//F.java
public class F {
    private int i = 0;
    private long y = 0;

    long metoda(){
        return i + y;
    }
    F napravi(){
        return new F();
    }
    public static void main(String args[]){
        F f = new F();
        G g = new G();
        F f1 = f.napravi();
        F f2 = g.napravi();
        System.out.println(f1.metoda());
        System.out.println(f2.metoda());
    }
}

class G extends F{
    int i = 1;
    long z = 1;

    protected long metoda(){
        z = super.metoda();
        return i + z;
    }
    G napravi(){
        return new G();
    }
}

import java.util.*;

public class M1{
    int id;
    M1 m1;
    M2 m2;
    char[] nizChar = new char[10_000_000];
    int[] nizInt = new int[5_000_000];
    M2 mArray[][] = new M2[3][2];

    public M1(int id)
    {
        System.out.println("M1: " + id);
        this.id = id;
    }
}

```

```

}

public M1(M1 m1,int id,M2 m2)
{
    System.out.println("M1: " + id);
    this.m1 = m1;
    this.m2 = m2;
    this.id = id;
}

@Override//kad se pozove gc on pozove finallize
protected void finalize()
{
    System.out.println(id + "finallize");
}

public static void main (String[] args)
{

    M1 m10 = new M1(10);
    M2 m21 = new M2(m10,21);
    M1 m11 = new M1(m10,11,m21);
    M2 m22 = new M2(null,22);
    M1 m12 = new M1(null,12,m22);

    m12.mArray[0][0] = m22;
    m12.mArray[1][1] = new M2(23);
    m12.mArray[2][1] = new M2(24);
    m12.mArray[1] = null;
    System.gc();
    m10.mArray[1][0] = new M2(25);
    m11.m2 = m10.mArray[1][0];
    m11 = null;
    System.gc();
    m10.mArray[2][2] = new M2(new M1(1000),26);
    System.gc();
} //zatvoren main

}

class M2
{
    float[] f = new float[2_500_000];
    M1 m1 = new M1(0);

    private int id2 = 0;

    public M2(M1 m1,int id2)
    {
        System.out.println("M2: " + id2);
        this.m1 = m1;
        this.id2 = id2;
    }

    public M2(int id2)
    {
        System.out.println("M2: " + id2);
        this.id2 = id2;
    }

    @Override//kad se pozove gc on pozove finallize
    protected void finalize()
    {
        System.out.println(id2 + "finallize");
    }

}

```

```

public class VanjskaKlasa
{
    public static String vanjskiString;

    static{
        System.out.println("Staticki blok, VANJSKE klase");
    };

    public class UnutrasnjaKlasa
    {
        public static String o;
        static{
            System.out.println("Staticki blok, UNUTRASNJE klase");
        }

    }

    public static void main(String[] args)
    {
        VanjskaKlasa vanjskaKlasa = new VanjskaKlasa();
        VanjskaKlasa.UnutrasnjaKlasa unutrasnjaKlasa = vanjskaKlasa. new UnutrasnjaKlasa();
    }
}

```

\*testirati serijalizaciju klase kod koje osnovna klasa ne implementira serializable  
(pozivace se podrazumevani konstruktor osnovne klase)