University of Antwerp
Faculty of Business and Economics

Warehouse App refactoring using Normalized System Theory

Pavel Jelínek

DA-SEA

20. 01. 2026

Contents

Executive Summary . . . 3
- Motivation . . . 3
- Approach . . . 3
- Key Results . . . 3
- Conclusion . . . 3

1. Theory . . . 3
   - 1.1. Normalized Systems Theory . . . 3
   - 1.2. Four Core Theorems . . . 4
   - 1.3. Application to Frontend Development . . . 4
2. Current System Analysis . . . 5
   - 2.1. System Architecture . . . 5
   - 2.2. Identified Violations . . . 5
   - 2.3. Metrics Summary . . . 6
3. Refactored System . . . 6
   - 3.1. Test-Driven Approach . . . 6
   - 3.2. Configuration Module (DVT) . . . 7
   - 3.3. Sorting Logic Extraction (SoC) . . . 7
   - 3.4. Export Dialog Extraction (SoC) . . . 7
   - 3.5. Quality Mapping Extraction (SoC) . . . 7
   - 3.6. Chart Decomposition (SoC) . . . 8
   - 3.7. Summary of Changes . . . 8

Conclusion . . . 8
- Achievements . . . 8
- Lessons Learned . . . 9
- Future Work . . . 9
- Final Remarks . . . 9

Bibliography . . . 9

Executive Summary

This report documents the refactoring of the **hranolky-react** warehouse management application according to Normalized Systems (NS) Theory principles. The application, built with React, TypeScript, and Firebase, manages inventory data for a woodworking company.

Motivation

The original codebase exhibited several maintainability issues:

- Large components mixing UI rendering, business logic, and data fetching
- Hardcoded configuration values scattered throughout the codebase
- Limited test coverage making refactoring risky

Approach

Using NS Theory's four core theorems—Separation of Concerns (SoC), Data Version Transparency (DVT), Action Version Transparency (AVT), and Separation of States (SoS)—we systematically identified violations and refactored the codebase.

Key Results

Phase	Extracted Module	Lines Saved
Config (DVT)	`appConfig.ts`	30 lines of hardcoded values
Sorting (SoC)	`slotSorting.ts`	50 lines from `SlotsTable.tsx`
Export (SoC)	`ExportDialog.tsx`	70 lines from `Filters.tsx`
Quality (SoC)	`qualityMapping.ts`	40 lines from `WarehouseSlotClass`
Chart (SoC)	`useChartAnimation.ts`	30 lines from `VolumeInTimeChart`

A comprehensive test suite was established as the foundation:

- **72 automated tests** across 8 test files
- Mock fixtures for Firebase, authentication, and slot data
- Integration tests for complete user workflows

Conclusion

The refactoring successfully improved the codebase's modularity and testability while maintaining full backward compatibility. All existing functionality remains intact, verified through manual testing and the new automated test suite.

1. Theory

This section introduces Normalized Systems (NS) Theory and its four core theorems that guided the refactoring process.

1.1. Normalized Systems Theory

Normalized Systems Theory, developed by Herwig Mannaert at the University of Antwerp, provides a theoretical framework for building evolvable software systems. The theory identifies **combinatorial effects**—situations where a single change propagates to multiple locations in the codebase—as the primary obstacle to software evolvability [1].

NS Theory defines four fundamental theorems that, when followed, eliminate these combinatorial effects and enable linear scalability of maintenance effort.

1.2. Four Core Theorems

1.2.1. Separation of Concerns (SoC)

The SoC theorem states that each software element should address exactly one concern. When a component mixes multiple concerns (e.g., UI rendering and business logic), changes to one concern require modifications to the entire component.

Violation example in hranolky-react:

```
// SlotsTable.tsx - mixing presentation with sorting logic
{warehouseSlots.sort((a, b) => {
  if (sortingBy === SortingBy.quality) {
    return a.quality.localeCompare(b.quality);
  } else if (sortingBy === SortingBy.thickness) {
    return a.thickness - b.thickness;
  }
  // ... 50 lines of sorting logic
}).map(slot => <TableRow />)}
```

1.2.2. Data Version Transparency (DVT)

The DVT theorem requires that data structures can evolve without causing ripple effects. Hardcoded values and tight coupling to specific data shapes violate this principle.

Violation example:

```
// Hardcoded admin emails in component
{['jelinekp6@gmail.com', 'jelinekv007@gmail.com']
  .includes(user.email) && <AdminButton />}
```

1.2.3. Action Version Transparency (AVT)

The AVT theorem ensures that actions (operations, functions) can evolve independently. When business logic is embedded directly in UI components, changes to the logic require modifying presentation code.

1.2.4. Separation of States (SoS)

The SoS theorem requires that state changes are isolated to prevent unintended side effects. Global state mutations that affect multiple unrelated areas violate this principle.

1.3. Application to Frontend Development

While NS Theory was originally developed for enterprise systems, its principles apply directly to React applications:

NS Theorem	React Application
SoC	Separate components for UI, hooks for logic
DVT	Configuration modules, typed interfaces
AVT	Pure utility functions, custom hooks
SoS	Isolated state management, context boundaries

2. Current System Analysis

This section analyzes the original codebase structure and identifies specific NS theory violations.

2.1. System Architecture

The hranolky-react application is a single-page React application with the following architecture:

Layer	Technology
Frontend	React 19, TypeScript, Vite
UI Framework	Tailwind CSS, MUI, Actify
State	React Context, Local State
Data	Firebase Firestore
Charts	Recharts

The application manages warehouse inventory for two product types: **Hranolky** (beams) and **Sparovky** (jointers), allowing filtering, sorting, and exporting of slot data.

2.2. Identified Violations

2.2.1. Filters.tsx (321 lines)

This component exhibited the most severe SoC violation, combining:

- Filter chip UI rendering
- Export dialog modal
- Export progress tracking
- CSV generation coordination

```
// Original: Export dialog embedded in filter component
{showExportDialog && (
  <div className="fixed inset-0 ...">
    <div className="bg-[var(--color-bg-01)] ...">
      <h3>Exportovat historii stavů</h3>
      <button onClick={handleExport}>...</button>
      <button onClick={handleCopyToClipboard}>...</button>
    </div>
  </div>
)}
```

2.2.2. SlotsTable.tsx (179 lines)

Mixed presentation with complex sorting logic:

```
// Original: 50+ lines of inline sorting
{warehouseSlots.sort((a, b) => {
  if (sortingBy === SortingBy.quality) {
    return b.quality.localeCompare(a.quality);
  } else if (sortingBy === SortingBy.thickness) {
    return (a.thickness ?? 0) - (b.thickness ?? 0);
  }
  // ... more sorting cases
}).flatMap(slot => <TableRow />)}
```

2.2.3. WarehouseSlotClass (187 lines)

Data model class mixed with display formatting:

```
// Original: 40-line switch statement in data class
private getFullQualityName(quality: string): string {
  switch (quality) {
    case "DUB-A|A": return "DUB A/A";
    case "DUB-B|B": return "DUB B/B";
    // ... 15+ more cases
  }
}
```

2.2.4. WarehouseScreen.tsx (116 lines)

Hardcoded configuration values (DVT violation):

```
// Original: Hardcoded admin emails
{['jelinekp6@gmail.com', 'jelinekv007@gmail.com']
  .includes(user.email || '') && (
    <button onClick={() => navigate('/admin')}>Admin</button>
)}
```

2.3. Metrics Summary

File	Lines	Violations
`Filters.tsx`	321	SoC: UI + Dialog + Export
`SlotsTable.tsx`	179	SoC: Presentation + Sorting
`VolumeInTimeChart.tsx`	482	SoC: Animation + Data + UI
`WarehouseSlotClass`	187	SoC: Data + Display
`WarehouseScreen.tsx`	116	DVT: Hardcoded config

3. Refactored System

This section documents the changes made to address the identified NS theory violations.

3.1. Test-Driven Approach

Before refactoring, we established a comprehensive test suite as a safety net:

Test Category	Files	Tests
Unit Tests	`SlotFilter.test.ts`, `slotSorting.test.ts`, `qualityMapping.test.ts`	35
Component Tests	`SlotsTable.test.tsx`, `ExportDialog.test.tsx`, `VolumeInTimeChart.test.tsx`	28
Integration Tests	`FilteringFlow.test.tsx`	5
Total	8 files	**72 tests**

3.2. Configuration Module (DVT)

Created `config/appConfig.ts` to centralize hardcoded values:

```
// After: Centralized configuration
export const ADMIN_EMAILS = [
  'jelinekp6@gmail.com',
  'jelinekv007@gmail.com',
] as const

export function isAdminUser(email: string | null): boolean {
  if (!email) return false
  return ADMIN_EMAILS.includes(email)
}

export const COLLECTION_NAMES = {
  [SlotType.Beam]: 'Hranolky',
  [SlotType.Jointer]: 'Sparovky',
} as const
```

Impact: Admin check now requires one-line change to update permissions.

3.3. Sorting Logic Extraction (SoC)

Created `utils/slotSorting.ts` extracting comparison logic:

```
// After: Pure utility function
export function sortSlots(
  slots: WarehouseSlotClass[],
  sortingBy: SortingBy,
  sortingOrder: SortingOrder
): WarehouseSlotClass[] {
  const ascending = sortingOrder === SortingOrder.asc
  const comparator = getComparator(sortingBy, ascending)
  return [...slots].sort(comparator)
}
```

Before: 50 lines inline in component **After:** Single function call: `sortSlots(warehouseSlots, sortingBy, sortingOrder)`

3.4. Export Dialog Extraction (SoC)

Created `components/ExportDialog.tsx` as a standalone component:

```
// After: Dedicated component with clear props
interface ExportDialogProps {
  isOpen: boolean
  onClose: () => void
  onExportCsv: () => void
  onCopyToClipboard: () => void
  isExporting: boolean
  isCopying: boolean
  itemCount: number
}
```

Before: 70 lines embedded in Filters.tsx **After:** 10-line component usage

3.5. Quality Mapping Extraction (SoC)

Created `common/utils/qualityMapping.ts` with data-driven approach:

```
// After: Data structure instead of switch
export const QUALITY_MAPPINGS: Record<string, string> = {
  'DUB-A|A': 'DUB A/A',
  'DUB-B|B': 'DUB B/B',
  'ZIR-ZIR': 'ZIRBE',
  // ... more mappings
}

export function getFullQualityName(code: string | null): string {
  if (!code) return ''
  return QUALITY_MAPPINGS[code] ?? code
}
```

Impact: Adding new quality types requires only adding to the data structure.

3.6. Chart Decomposition (SoC)

Extracted animation and rendering logic from VolumeInTimeChart:

- `hooks/useChartAnimation.ts` - Pulsing/goofy loading animation
- `components/chart/ChartTooltip.tsx` - Tooltip rendering
- `components/chart/ChartXAxisTick.tsx` - Custom X-axis with year grouping

3.7. Summary of Changes

Original File	Extracted To	Lines Moved	Theorem
`WarehouseScreen`	`appConfig.ts`	30	DVT
`SlotsTable`	`slotSorting.ts`	50	SoC
`Filters`	`ExportDialog.tsx`	70	SoC
`WarehouseSlot`	`qualityMapping.ts`	40	SoC
`VolumeInTimeChart`	`useChartAnimation.ts`	30	SoC

Total lines extracted: **220 lines** moved into focused, testable modules.

Conclusion

This project successfully applied Normalized Systems Theory principles to refactor the hranolky-react warehouse management application, improving its modularity, testability, and maintainability.

Achievements

Quantitative Results

Metric	Value
Automated tests added	72
Test files created	8
Utility modules extracted	6
Lines of code reorganized	220

Large components refactored	5

Qualitative Improvements

- **Improved Testability:** Extracted utilities can be unit tested in isolation
- **Better Maintainability:** Changes to sorting logic require only modifying `slotSorting.ts`
- **Centralized Configuration:** Admin permissions managed in one location
- **Reusable Components:** `ExportDialog` can be used in other contexts
- **Data-Driven Design:** Quality mappings stored as data, not code

Lessons Learned

1. **Test First:** Establishing tests before refactoring provides confidence that behavior is preserved.
2. **Incremental Extraction:** Small, focused extractions are safer than large rewrites.
3. **NS Theory Applicability:** The four theorems translate well to React development:
   - SoC maps to component/hook separation
   - DVT maps to configuration modules
   - AVT maps to pure utility functions

Future Work

- Complete extraction of chart subcomponents in `VolumeInTimeChart.tsx`
- Apply NS principles to remaining screens (AdminPanel)
- Consider state management refactoring for SoS compliance
- Expand test coverage to include more integration scenarios

Final Remarks

Normalized Systems Theory provides a principled approach to software design that addresses the root causes of maintenance complexity. By systematically identifying and eliminating combinatorial effects, we created a codebase that is better prepared for future evolution.

The 72-test safety net ensures that future modifications can be made with confidence, while the extracted modules provide clear boundaries for understanding and modifying specific functionality.

Bibliography

[1] H. Mannaert, J. Verelst, and P. De Bruyn, *Normalized Systems Theory: From Foundations for Evolvable Software Toward a General Theory for Evolvable Design*. NSX bvba, 2016.