



Computer Vision

Edge detection

27 August 2008

Copyright © 2001 – 2008 by
Noordelijke Hogeschool Leeuwarden and Van de Loosdrecht Machine Vision
All rights reserved

j.van.de.loosdrecht@tech.nhl.nl, jaap@vdlmv.nl

Edge detection




Overview:

- **First derivative**
 - Gradient difference
 - Template matching (*)
- **Second derivative**
 - Laplacian
 - Laplacian of Gaussian (Mexican Hat)
 - Difference of Gaussians (*)
- **Combination of first and second derivative**
- **Connecting edges**
 - Marr- Hildreth
 - Canny (*)
- **FindEdgeLine**
- **FindEdgeCircle**

28-aug-08

Edge detection

2

First and second derivatives of an edge**Edge profile****First derivative****Second derivative**

28-aug-08

Edge detection

3

Edge detection**First derivative :**

- **Gradient difference**
 - Sobel
 - Prewitt
 - Frei Chen
 - Scharr
 - Roberts (*)
- **Template matching (*)**
 - Kirsch
 - Robinson

28-aug-08


Edge detection

4

Edge detection

Definitions:

- **magnitude:** strength of edge
- **direction:** orientation of edge
- angles are measured in radians ($-\pi .. \pi$]



28-aug-08

Edge detection


5

Edge detection

Definitions (continued):

- edge directions are calculated from low towards high pixel values perpendicular at the edge contour
- example:

White = 0, Black = 10 !!!



28-aug-08


Edge detection

6

Gradient difference

Idea:

- Calculate the edge using convolution in two perpendicular directions d_1 and d_2
- Edge magnitude = $\text{sqrt} (d_1^2 + d_2^2)$
- Edge direction = $\text{arctan} (d_1 / d_2)$



28-aug-08

Edge detection

7

Gradient difference

Examples:

- Sobel (src, magImage, dirImage, gradient, dirScale, minEdge);

gradient: magnitude, direction or both

dirScale: direction in radians * gradScale

minEdge: if gradient is both, all directions with an edge magnitude lower then minEdge are not calculated and set to zero.

Masks:

-1	-2	-1
0	0	0
1	2	1

-1	0	1
-2	0	2
-1	0	1

28-aug-08

Edge detection

8

Demonstration Sobel


- Open image edgetest.jl (do not use sq2.jl)
- Apply Sobel magnitude on image
- Apply Sobel direction with scale = 10000 on image
- Edit images (3x) and explain

28-aug-08

Edge detection

9

Image edgetest.jl



28-aug-08

Edge detection

10

VisionLab V3.24 2-1-2002 (c) Van de Loosdrecht Machine Vision www.vdmv.nl

File Operator Camera Server Options Window User Help

Edit ED... Edit ED...

Edit EDGETEST_IL%1 (Int16Image)

	0	1	2	3	4	5	6	7	8	9	10	11
0	0	0	0	0	0	0	0	0	0	0	0	0
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	0	0	0	0	0	0	0	0	0
3	0	0	0	0	10	10	10	10	0	0	0	0
4	0	0	0	0	10	10	10	10	0	0	0	0
5	0	0	0	0	10	10	10	10	0	0	0	0
6	0	0	0	0	10	10	10	10	0	0	0	0
7	0	0	0	0	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0

☐ stay on top field w

Edit EDGETEST_IL%8 (Int16Image)

	0	1	2	3	4	5	6	7	8	9	10	11
0	0	0	0	0	0	0	0	0	0	0	0	0
1	0	0	0	0	0	0	0	0	0	0	0	0
2	0	0	0	14	32	40	40	32	14	0	0	0
3	0	0	0	32	42	40	40	42	32	0	0	0
4	0	0	0	40	40	0	0	40	40	0	0	0
5	0	0	0	40	40	0	0	40	40	0	0	0
6	0	0	0	32	42	40	40	42	32	0	0	0
7	0	0	0	14	32	40	40	32	14	0	0	0
8	0	0	0	0	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0	0	0	0

Server log

34.950 us

11

The screenshot displays the VisionLab v3.24 software interface. The title bar indicates the user is logged in as 'c) Van de Loosdrecht Machine Vision' and the website 'www.vdmv.nl' is visible. The menu bar includes 'File', 'Operator', 'Camera', 'Server', 'Options', 'Window', 'User', and 'Help'. Below the menu bar, there are three icons for 'ED...' with associated window controls. The main workspace contains two windows. The first window, titled 'Edit EDGETEST_IL%1 (Int16Image)', shows a 12x12 grid of zeros. The second window, titled 'Edit EDGETEST_IL%11 (Int16Image)', shows a 12x12 grid of values. The first row of the second window contains non-zero values: 0, 0, 0, 0, 4, 0, 0, 0, 0, 0, 0, 0. The rest of the grid contains zeros. At the bottom left, there is a checkbox labeled 'stay on top' and a text field for 'field width' set to '40'. The status bar at the bottom left shows '203 us'.

12

Exercise Find strong edges with angle of 90°

**Make a script for image circles.jl that finds strong edges
(> 200) with angle of 90° (p.a.: bottom of dark circle) using
Sobel edge detection**

Answer: strongedges2.jls

28-aug-08

Edge detection

13

Gradient difference**Examples (continued):**• **Prewitt:**

-1	-1	-1	-1	0	1
0	0	0	-1	0	1
1	1	1	-1	0	1

• **Frei Chenn:**

-1	$-\sqrt{2}$	-1	-1	0	1
0	0	0	$-\sqrt{2}$	0	$\sqrt{2}$
1	$\sqrt{2}$	1	-1	0	1

implemented with ints and divisor of 100

• **Sharr:**

-3	-10	-3	-3	0	3
0	0	0	-10	0	10
3	10	3	-3	0	3

theoretical best accuracy, but beware of overflow

28-aug-08

Edge detection

14

Gradient difference (*)

Examples (continued):

- **Roberts:**

-1	0	0	-1
0	-1	1	0

notes:

- mask centre is top left.
- all edges are shifted by one-half of a pixel in x and y direction.
- the two diagonal directions are rotated by $\pi/4$.
- due to smaller masks faster operation

28-aug-08

Edge detection

15

Template matching (*)

Idea:

- Calculate N times the edge using convolution with mask that is rotated $2\pi / N$ after each convolution
- Edge magnitude = $\max(\text{conv}_i : i = 1 \text{ to } N)$
- Edge direction = rotation of $\max(\text{conv}_i : i = 1 \text{ to } N)$

problem: what to do if two or more masks give the highest value

28-aug-08

Edge detection

16

Template matching (*)

Examples:

- **Kirsch: (8 rotations)**

```
-3 -3 5  
-3 0 5  
-3 -3 5
```

- **Robinson: (8 rotations)**

```
-1 0 1  
-2 0 2  
-1 0 1
```

28-aug-08

Edge detection

17

Demonstration Kirsch (*)


- Apply Kirsch on circles.jls for magnitude and direction, note increase of processor time compared with Sobel.

28-aug-08

Edge detection

18

Kirsch on circles.jls for magnitude and direction (*)



28-aug-08

Edge detection

19

Edge detection

Second derivative


- Laplacian
- Laplacian of Gaussian (Mexican Hat)
- Finding edges using zero crossings

28-aug-08


Edge detection

20


First and second derivatives of an edge



Edge profile



First derivative



Second derivative

28-aug-08

Edge detection

21

Laplacian

Examples of convolution masks:

• Laplacian 3x3:

-1	-1	-1
-1	8	-1
-1	-1	-1

• Laplacian 5x5:

0	0	-1	0	0
0	-1	-2	-1	0
-1	-2	16	-2	-1
0	-1	-2	-1	0
0	0	-1	0	0

Usage:

- high pass filter
- edge detection, but sensitive to noise

28-aug-08

Edge detection

22

Demonstration high pass filter


- Open image circles.jl
- Convolution with Laplacian 3x3
- 2x analyse pixels:
 - low frequencies $\rightarrow 0$
 - high frequencies $\rightarrow |\text{pixel value}| \gg 1$

28-aug-08

Edge detection

23


Convolution with Laplacian 3x3



28-aug-08

Edge detection

24



Mexican hat

- Variant of low and high pass filters
- Combination of low and high pass filter
- Mask (7x7):

0	0	-1	-1	-1	0	0
0	-1	-3	-3	-3	-1	0
-1	-3	0	7	0	-3	-1
-1	-3	7	24	7	-3	-1
-1	-3	0	7	0	-3	-1
0	-1	-3	-3	-3	-1	0
0	0	-1	-1	-1	0	0
- Local noise is smoothed out by low pass filter in centre

28-aug-08

Edge detection

26

Laplacian of Gaussian

LoGFilter (image, sigma, size)

This is a generalized implementation of a Mexican hat filter.

Parameter sigma is the standard deviation, typical values are [2/3 .. 3].

Size is the size of the neighbourhood of the operation. If size is 0 the algorithm calculates a size so that pixels at 3*sigma are neglected.

28-aug-08

Edge detection

27

Difference of Gaussians (DoG) filter (*)

DoGFilter (image, sigmaLow, sigmaHigh, size)

An alternative implementation for a generalised Mexican hat filter, using the difference of two Gaussians with substantially different sigmas.

Parameters:

- **sigmaLow and sigmaHigh are the standard deviations for the DoG operator. Typical values are [0 .. 3].**
- **size is the size of the neighbourhood of the operation. If size is 0 the algorithm calculates a size so that pixels at 3*sigma are neglected**

28-aug-08

Edge detection

28


Demonstration Mexican hat (*)

- Open image circles.jl (use LUT stretch)
- Add noise 1 0 50
- Convolution Laplacian 5x5 on noise image
- Convolution Mexican hat on noise image (smooth noise and enhance high frequencies)
- Open image circles.jl
- Convolution Mexican hat on image
- LoGFilter 1.4 7 on Image (same result)

28-aug-08

Edge detection

29


With noise**Mexican hat****Laplacian (*)**

28-aug-08

Edge detection

30

image MexicanHat7x7 LoGFilter 1.4 7 (*)



28-aug-08
Edge detection
31

Combination of first and second derivative

The positions of the edges can not be found exactly using first derivative edge detectors because the maximum value are position dependant.

The zero crossings in the second derivative 'ANDed' with the strong edges in the first derivative give the exact position of the edges.

28-aug-08

Edge detection

32

Zero crossings

- Open image circles.jl
- Convolution Laplacian 3x3
 - Show zero crossings with pixel analysis
- Zero crossings FourConnected on laplacian
- Sobel Magnitude on circles
- Threshold 200 1000 on sobel
- Multiply zero crossing with threshold gives the exact position of the edges

Note:

- With zero crossings the “middle” of the edge will be found and the edge will be approximately one pixel thick
- With Sobel magnitude followed by threshold an edge will be found which is in general more than one pixel thick, its thickness will vary with the intensity of the lighting.

28-aug-08


Edge detection

33

original

Laplacian

Zero crossings




28-aug-08

Edge detection


34

Sobel Threshold 200 10000



28-aug-08 Edge detection 35

Multiply zero crossing with threshold



28-aug-08 Edge detection 36

Marr - Hildreth

MarrHildreth (srcImage, destImage, sigmaG, sigmaLoG, minEdge)

This operator calculates a binary image with the positions of the edges.

Algorithm:

- First the Gaussian smoothing is performed (to 'connect' the edges)
- ZeroCrossings of the 2nd derivative (LoG) are multiplied with the high edges of the first derivative

Parameters:

- **sigmaG**: standard deviation for Gaussian smoothing
- **sigmaLoG**: standard deviation for the LoG operator
- **minEdge**: the minimal level for the first derivative

28-aug-08

Edge detection

37

Marr - Hildreth


- Open image circles.jl
- MarrHildreth 0 1 200

28-aug-08

Edge detection

38

MarrHildreth 0 1 200



Canny (*)

Canny (srcImage, destImage, sigma, low, high, connected)

This operator calculates a binary image with the positions of the edges.

Algorithm and parameters:

- Gaussian smoothing with *sigma*
- Sobel edge detection
- Maxima of the edges magnitudes are searched for and linked. All pixels with a edge greater than *high* are selected as object pixels. These object pixels are used as seeds. All connected neighbours of the seeds with a edge greater than *low* are added to the object pixels. This growing process is repeated until no pixels are added.

Demonstration Canny (*)

Try to find the signature and 'big circle'


- Open image circels.jl
- Sobel GradientMagnitude 10000 0
- Threshold edge 60 1000, -> to much
- Threshold edge 150 1000, -> only 2 disconnected pixels of signature
- Canny image 0 60 150 EightConnected -> position of signature

28-aug-08

Edge detection

41


Sobel GradientMagnitude 10000 0 (*)



28-aug-08

Edge detection


42

Threshold edge 60 1000 (*)

28-aug-08

Edge detection

43


Threshold edge 150 1000 (*)

28-aug-08


Edge detection

44

Canny image 0 60 150 EightConnected (*)



Exercise Segmentation using edge detection



- Use image shading_c.jl in the exercise directory
- Try to find good threshold values in order to separate the cells from the background
This will be unsuccessful due to uneven lightning conditions
- Use Sobel edge detection to find the borders of the cells and then to segment the image
- See shading_c_sobel.jls for answer

28-aug-08

Edge detection

46

Exercise (*)

- Experiment with the the other edge detection operators on image shading_c.jl

28-aug-08

Edge detection

47

FindEdgeLine

FindEdgeLine (image, middlePoint, endLine, endBox, lineDistance, outlierDistance, nrliterations)

This operator finds with subpixel precision a line with the largest edges within the specified rectangle middlePoint, endLine and endBox.

In the specified rectangle scan lines will be tested at the specified lineDistance. The rectangle should have a width of at least 5 pixels.

If outLayerDistance is greater then zero then the regression algorithm is repeated for nrliterations. In each next iterations only pixel with a distance smaller then outlierDistance to the previous found line are used in the calculation of the next line.


The function result is the start and the end coordinate of the line found and the number of pixels found on the line.

28-aug-08

Edge detection

48

Specification of rectangle for scan lines





28-aug-08

Edge detection

49

Finding the line

edge**scan lines****subpixel
precision****regression**

28-aug-08

Edge detection

50


Demonstration FindEdgeLine

- Open image findEdgeLine1.jl
- FindEdgeLine (200,10) (350,60) (80,400) 1 10 1

28-aug-08

Edge detection

51



28-aug-08

Edge detection

52

Demonstration FindEdgeLine


Increase speed by setting lineDistance to 10, decrease of accuracy (see number of points found)

- FindEdgeLine (200,10) (350,60) (80,400) 10 10 1

28-aug-08

Edge detection


53



28-aug-08

Edge detection

54

Example scan lines not perpendicular at edge

28-aug-08

Edge detection

55


Demonstration scan lines not perpendicular to edge

- Open image findEdgeLine1.jl
- FindEdgeLine (20,10) (350,10) (20,400) 1 10 1

28-aug-08

Edge detection

56



Demonstration FindEdgeLine with outliers


- Open image findedgeline2.jl
- FindEdgeLine (50,1) (200,1) (50,250) 1 0 1

28-aug-08

Edge detection

58

Demonstration FindEdgeLine with outliers no iterations



28-aug-08

Edge detection

59

Demonstration FindEdgeLine with outliers


- **FindEdgeLine (50,1) (200,1) (50,250) 1 10 4**

28-aug-08

Edge detection

60

Demonstration FindEdgeLine with outliers 4 iterations



28-aug-08

Edge detection

61

FindEdgeCircle

FindEdgeCircle (image, middlePoint, nrSamples, minR, maxR, outlierDistance, nrIterations)

This operator finds with subpixel precision a circle within the specified disk shape specified by middlePoint, minR and maxR. In the specified disk shape nrSamples scan lines tested starting from a distance minR from the middlepoint and ending at a distance maxR from the middlepoint. The probe lines will be equally divided in the space bounded by middlePoint, minR and maxR.

Note: the number of probe lines will be nrSamples rounded up to the next multiple of 4. maxR must be > minR + 5.

If outlierDistance is greater than zero then the regression algorithm is repeated for nrIterations. In each next iterations only pixel with a distance smaller than outlierDistance to the previous found line are used in the calculation of the next line.


The function result is the center coordinate, the radius and the number of pixels found on the circle.

28-aug-08

Edge detection

62

Specification of disk shape for scanlines



middlePoint

minR

maxR

Scan lines

28-aug-08

Edge detection

63

Demonstration FindEdgeCircle


- Open image circles.jl
- FindEdgeCircle (118,65) 200 20 65 1 1
- FindEdgeCircle (118,65) 50 20 65 1 1 (faster)

28-aug-08

Edge detection

64

FindEdgeCircle (118,65) 200 20 65 1 1




center, radius, nr pixels

28-aug-08

Edge detection

65

FindEdgeCircle (118,65) 50 20 65 1 1



28-aug-08

Edge detection

66

Alternative for finding lines and circles

Alternative operators to find lines and circles are based on the Hough transform, see the chapter about Hough transforms

Edge based:

- Fast
- Search area must contain only edges to find
- Can find only 1 line or circle
- Outliers cause problems

Hough based:

- Slower
- Search area can be whole image
- Can find more than 1 lines or circles
- Less problems with outliers

28-aug-08

Edge detection

67