



Computer Vision

Classification with Neural Networks part II

script commands and examples

27 August 2008

Copyright © 2001 – 2008 by
Noordelijke Hogeschool Leeuwarden and Van de Loosdrecht Machine Vision
All rights reserved

j.van.de.loosdrecht@tech.nhl.nl, jaap@vdlmv.nl

Classification with Neural Networks part II

Overview script commands and examples :

- **Script commands**
 - Class Image Set (CIS)
 - Class Feature Set (CFS)
 - Back Propagation Network (BPN)
- **Examples**
 - Learning sinus function
 - Generate CIS
 - Create CIS and BPN, Train BPN with CIS, Classify image using BPN and Evaluate BPN using CIS
 - Create CFS and BPN, Train BPN with CFS, Classify image using BPN and Evaluate BPN using CFS

28-Aug-08

Classification with Neural
Networks part II

2

Class Image Set commands

Introduction:

A CIS is a collection of images with their associated classes. All images in a CIS must have the same image type and size. The image type and size are defined when the CIS is created. The info field gives a text description of the CIS. This info field is defined when the CIS is created and the text should be between quotes">" and "<" if the text field contains spaces.

**A CIS has a class table and for each class an image table.
Each image in an image table has its unique image index number.**

28-Aug-08

Classification with Neural Networks part II

3

Class Image Set commands

Overview:

- CIS_AddClass <cisName> <className>
- CIS_AddImage <cisName> <imageName> <className>
- CIS_ClassId <cisName> <className>
- CIS_ClassName <cisName> <classId>
- CIS_Create <cisName> <imageType> <info> <height> <width>
- CIS_Delete <cisName>
- CIS_GetClassTab <cisName>
- CIS_GetInfo <cisName>
- CIS_GetImage <cisName> <imageName> <className>
 <imageIndex>
- CIS_GetImageHeight <cisName>
- CIS_GetImageWidth <cisName>

28-Aug-08

Classification with Neural Networks part II

4

Class Image Set commands

Overview:

- CIS_GetMaxPixel <cisName>
- CIS_GetMinPixel <cisName>
- CIS_MaxClassId <cisName>
- CIS_NrOfImages <cisName> <className>
- CIS_ReadFromFile <cisName> <filename>
- CIS_RemoveClass <cisName> <className>
- CIS_RemoveImage <cisName> <className> <imageIndex>
- CIS_Rename <old cisName> <new cisName>
- CIS_WriteToFile <cisName> <filename>

28-Aug-08

Classification with Neural
Networks part II

5

Class Image Set commands

CIS_AddClass <cisName> <className>

Add class to cis.

Function result is string with classId.

CIS_AddImage <cisName> <imageName> <className>

Add image to cis.

Function result is string with imageId.

CIS_ClassId <cisName> <className>

Function result is string with classId.

CIS_ClassName <cisName> <classId>

Function result is string with class name.

CIS_Create <cisName> <imageType> <info> <height> <width>

Create an cis for specified image type with images of height x width.

28-Aug-08

Classification with Neural
Networks part II

6

Class Image Set commands**CIS_Delete <cisName>**

Delete specified cis.

CIS_GetClassTab <cisName>

Function result is string with class table.

CIS_GetInfo <cisName>

Function result is string with info field.

CIS_GetImage <cisName> <imageName> <className> <imageIndex>

Specified image in cis is copied to image with image name.

CIS_GetImageHeight <cisName>

Function result is string with height of images in cis.

CIS_GetImageWidth <cisName>

Function result is string with width of images in cis.

28-Aug-08

Classification with Neural
Networks part II

7

Class Image Set commands**CIS_GetMaxPixel <cisName>**

Function result is string with max pixel value of all images in cis.

CIS_GetMinPixel <cisName>

Function result is string with min pixel value of all images in cis.

CIS_MaxClassId <cisName>

Function result is a string the largest classId in cis.

CIS_NrOfImages <cisName> <className>

Function result is a string the nr of images in cis.

CIS_ReadFromFile <cisName> <filename>

Read cis from file.

CIS_RemoveClass <cisName> <className>

Remove class from cis.

28-Aug-08

Classification with Neural
Networks part II

8

Class Image Set commands

CIS_RemoveImage <cisName> <className> <imageIndex>
Remove specified image from cis.

CIS_Rename <old cisName> <new cisName>
Rename cis from old name to new name.

CIS_WriteToFile <cisName> <filename>
Write cis to file.

28-Aug-08

Classification with Neural
Networks part II

9

Class Feature Set commands

Introduction:

A CFS is a collection of images with their associated classes.

**A CFS has a class table and for each class an image table.
Each image in an image table has its unique image index number.**

28-Aug-08

Classification with Neural
Networks part II

10

Class Feature Set commands

Overview:

- CFS_AddClass <cfsName> <className>
- CFS_AddFeature <cfsName> <featureName>
- CFS_AddImage <cfsName> <imageName> <className>
- CFS_CalcFeatures <cfsName> <internalScriptName>
- CFS_ClassId <cfsName> <className>
- CFS_ClassName <cfsName> <classId>
- CFS_Create <cfsName> <imageType> <info>
- CFS_Delete <cfsName>
- CFS_GetFeatureNameTab <cfsName>
- CFS_GetInfo <cfsName>
- CFS_GetImage <cfsName> <imageName> <className> <imageIndex>
- CFS_GetMinMaxTab <cfsName>
- CFS_GetNrFeatures <cfsName>
- CFS_GetNrSelectedFeatures <cfsName>
- CFS_GetFeaturesImage <cfsName> <className> <imageIndex>
- CFS_GetScriptName <cfsName>

28-Aug-08

Classification with Neural
Networks part II

11

Class Feature Set commands

Overview:

- CFS_GetSelectedFeaturesImage <cfsName> <className> <imageIndex>
- CFS_GetSelectTab <cfsName>
- CFS_GetClassTab <cfsName>
- CFS_MaxClassId <cfsName>
- CFS_NrOfImages <cfsName> <className>
- CFS_ReadFromFile <cfsName> <filename>
- CFS_RemoveClass <cfsName> <className>
- CFS_RemoveFeature <cfsName> <featureName>
- CFS_RemoveImage <cfsName> <className> <imageIndex>
- CFS_Rename <old cfsName> <new cfsName>
- CFS_SelectFeature <cfsName> <featureName> <0|1>
- CFS_SetMinMaxTab <cfsName> <minmaxinputtab>
- CFS_SetFeaturesImage <cfsName> <className> <imageIndex> <features>
- CFS_SetScriptName <cfsName> <scriptname>
- CFS_SetSelectTab <cfsName> <selected>
- CFS_WriteToFile <cfsName> <filename>

28-Aug-08

Classification with Neural
Networks part II

12

Class Feature Set commands

CFS_AddClass <cfsName> <className>

Add class to cfs.

Function result is string with classId.

CFS_AddFeature <cfsName> <featureName>

Add feature to cfs.

Function result is string with featureId.

CFS_AddImage <cfsName> <imageName> <className>

Add image with imageName to cfs for class className.

CFS_CalcFeatures <cfsName> <internalScriptName>

Execute internal script with internalScriptName to calculate all features for all images in cfs.

CFS_ClassId <cfsName> <className>

Function result is string with classId for class with className in cfs.

28-Aug-08

Classification with Neural
Networks part II

13

Class Feature Set commands

CFS_ClassName <cfsName> <classId>

Function result is string with class name for classId in cfs.

CFS_Create <cfsName> <imageType> <info>

Create a cfs for specified image type and add text in info parameter to info field of cfs.

CFS_Delete <cfsName>

Delete specified cfs.

CFS_GetFeatureNameTab <cfsName>

Function result is string with all feature names.

CFS_GetInfo <cfsName>

Function result is info field of cfs.

CFS_GetImage <cfsName> <imageName> <className> <imageIndex>

Specified image in cfs is copied to image with image name.

28-Aug-08

Classification with Neural
Networks part II

14

Class Feature Set commands

CFS_GetMinMaxTab <cfsName>

Function result is string with MinMaxTable of cfs.

CFS_GetNrFeatures <cfsName>

Function result is string with nr of features in cfs.

CFS_GetNrSelectedFeatures <cfsName>

Function result is string with nr of selected features of cfs.

CFS_GetFeaturesImage <cfsName> <className> <imageIndex>

Function result is string with all features of selected image in cfs.

CFS_GetScriptName <cfsName>

Function result is string with internal script name of cfs used to calculate the features.

CFS_GetSelectedFeaturesImage <cfsName> <className> <imageIndex>

Function result is string with the selected features of selected image in cfs.

28-Aug-08

Classification with Neural
Networks part II

15

Class Feature Set commands

CFS_GetSelectTab <cfsName>

Function result is a string with represents the selected features.

The string consists of '0' and '1' separated by spaces.

'0' means feature not selected, '1' means feature is selected.

The '0' and '1' are in the order of increasing classId.

CFS_GetClassTab <cfsName>

Function result is a string with the class table.

CFS_MaxClassId <cfsName>

Function result is a string the largest classId in cfs.

CFS_NrOfImages <cfsName> <className>

Function result is a string with the number of images of className in cfs.

CFS_ReadFromFile <cfsName> <filename>

Read cfs from file.

28-Aug-08

Classification with Neural
Networks part II

16

Class Feature Set commands

CFS_RemoveClass <cfsName> <className>

Remove class className from cfs, all images for className are deleted from cfs.

CFS_RemoveFeature <cfsName> <featureName>

Remove feature with featureName from cfs.

CFS_RemoveImage <cfsName> <className> <imageIndex>

Remove specified image from cfs.

CFS_Rename <old cfsName> <new cfsName>

Rename cfs from old name to new name.

CFS_SelectFeature <cfsName> <featureName> <0|1>

Include ('1') or remove ('0') specified feature to selected set of features of cfs.

28-Aug-08

Classification with Neural
Networks part II

17

Class Feature Set commands

CFS_SetMinMaxTab <cfsName> <minmaxinputtab>

Set minMaxTab of cfs.

**CFS_SetFeaturesImage <cfsName> <className> <imageIndex>
<features>**

Set features of specified image in cfs.

CFS_SetScriptName <cfsName> <scriptname>

Set name of internal script used to calculate the features for all images in cfs.

CFS_SetSelectTab <cfsName> <selected>

Set selected features of cfs.

The selected string consists of '0' and '1' seperated by spaces.

'0' means feature not selected, '1' means feature is selected.

The '0' and '1' are in the order of increasing classId.

28-Aug-08

Classification with Neural
Networks part II

18

Class Feature Set commands

CFS_WriteToFile <cfsName> <filename>
Write cfs to file.

28-Aug-08

Classification with Neural
Networks part II

19

Back Propagation Network commands

Overview:

- **BPN_Classify** <bpnName> <inputs>
- **BPN_ClassifyFeatures** <bpnName> <image> <iscript>
- **BPN_ClassifyImage** <bpnName> <image>
- **BPN_Create** <bpnName> <func> <bias> <\$minMaxInputTab> <minOutput>
<maxOutput> <\$layerdescrtab>
- **BPN_CreateClassifier** <bpnName> <hiddens1> <hiddens2> <nrClasses>
<bias> <\$minMaxInputTab>
- **BPN_CreateFeatureClassifier** <bpnName> <cfsName> <nrHiddens1>
<nrHiddens2> <bias>
- **BPN_CreateImageClassifier** <bpnName> <imageType> <nrPixels>
<hiddens1> <hiddens2> <nrClasses> <bias> <\$minMaxInputTab>
- **BPN_Delete** "<bpnName>
- **BPN_EvaluateClass** <bpnName> <input> <classExp>
- **BPN_EvaluateCIS** <bpnName> <cisName> <minConfidence> <NoDetails |
LowDetails | HighDetails>
- **BPN_EvaluateImage** <bpnName> <imageName> <classExp>
- **BPN_EvaluateImageSet** <bpnName> <minConfidence> <NoDetails |
LowDetails | HighDetails> <\$images> <\$classes>

28-Aug-08

Classification with Neural
Networks part II

20

Back Propagation Network commands

Overview:

- BPN_EvaluateClassSet <bpnName> <minConfidence> <NoDetails | LowDetails | HighDetails> <inputs> <classes>
- BPN_EvaluateSet <bpnName> <\$inputs> <\$targets>
- BPN_GetLearnError <bpnName>
- BPN_GetMomentum <bpnName>
- BPN_GetNameLearnSet <bpnName>
- BPN_GetSizeLayer <bpnName> <layerNr>
- BPN_Produce <bpnName> <inputs>
- BPN_ReadFromFile <bpnName> <filename>
- BPN_Rename <old bpnName> <new bpnName>
- BPN_Reset <bpnName> <minRand> <maxRandW>
- BPN_SetNameLearnSet <bpnName> <name learn set>
- BPN_Train <bpnName> <learnRate> <momentum> <\$input> <\$target>
- BPN_TrainSet <bpnName> <nrOfEpochs> <learnRate> <momentum> <\$inputs> <\$targets>
- BPN_TrainClass <bpnName> <learnRate> <momentum> <\$input> <class>

28-Aug-08

Classification with Neural
Networks part II

21

Back Propagation Network commands

Overview:

- BPN_TrainClassSet <bpnName> <nrOfEpochs> <learnRate> <momentum> <setsize> <\$input class> <\$classes>
- BPN_TrainImage <bpnName> <learnRate> <momentum> <image> <class>
- BPN_TrainImageSet <bpnName> <nrOfEpochs> <learnRate> <momentum> <setsize> <\$images> <\$classes>
- BPN_TrainCIS <bpnName> <cisName> <nrOfEpochs> <learnRate> <momentum>
- BPN_WriteToFile <bpnName> <filename>

28-Aug-08

Classification with Neural
Networks part II

22

Back Propagation Network commands

BPN_Classify <bpnName> <inputs>

Classify with specified inputs, function result is string with classId and confidence separated with a space.

bpnName: name of bpn variable.

inputs: string with all inputs separated by space.

BPN_ClassifyFeatures <bpnName> <image> <iscript>

Classify image with feature classifier.

Features are calculated with internal script, %p1 is image.

Function result is string with classId and confidence separated with a space.

bpnName: name of bpn variable.

image: name of image to classify

iscript: name of internal script.

28-Aug-08

Classification with Neural
Networks part II

23

Back Propagation Network commands

BPN_ClassifyImage <bpnName> <image>

Classify image with image classifier.

Function result is string with classId and confidence separated with a space.

bpnName: name of bpn variable.

image: name of image to classify

BPN_Create <bpnName> <func> <bias> <\$minMaxInputTab> <minOutput>
<maxOutput> <\$layerdescrtab>

Create a bpn.

bpnName: name of bpn variable.

func: activation function, values: Hyperbolic, Linear or Sigmoid.

bias: use of BiasNodes, values: Bias NoBias

minMaxInputTab: string with min and max value for all inputs, separated by spaces

minOutPut: minimum value for output neuron

maxOutput: maximum value for output neuron

layerdescrtab: string with: nrLayers followed by nr of neurons for each layer

28-Aug-08

Classification with Neural
Networks part II

24

Back Propagation Network commands

BPN_CreateClassifier <bpnName> <hiddens1> <hiddens2> <nrClasses>
<bias> <\$minMaxInputTab>

Create a classifier.

bpnName: name of bpn variable.

hiddens1: size of hidden layer 1

hiddens2: size of hidden layer 2

nrClasses: nr of classes

bias: use of BiasNodes, values: Bias NoBias

minMaxInputTab: string with min and max value for all inputs, separated by spaces

BPN_CreateFeatureClassifier <bpnName> <cfsName> <nrHiddens1>
<nrHiddens2> <bias>

Create a feature classifier.

bpnName: name of bpn variable.

cfsName: name of cfs variable.

hiddens1: size of hidden layer 1

hiddens2: size of hidden layer 2

bias: use of BiasNodes, values: Bias NoBias

28-Aug-08

Classification with Neural
Networks part II

25

Back Propagation Network commands

BPN_CreateImageClassifier <bpnName> <imageType> <nrPixels>
<hiddens1> <hiddens2> <nrClasses> <bias> <\$minMaxInputTab>

Create an image classifier.

bpnName: name of bpn variable.

imageType: type of image, like ByteImage or RGB888Image.

nrPixels: nr of pixels in image

hiddens1: size of hidden layer 1

hiddens2: size of hidden layer 2

nrClasses: nr of classes.

bias: use of BiasNodes, values: Bias NoBias

minMaxInputTab: string with min and max value for all inputs, separated by spaces

BPN_Delete "<bpnName>

Delete a BPN.

bpnName: name of bpn variable.

28-Aug-08

Classification with Neural
Networks part II

26

Back Propagation Network commands

BPN_Evaluate <bpnName> <input> <target>

Evaluate BPN by producing outputs with input and comparing with target.

Function result is the mean error in the output layer.

bpnName: name of bpn variable.

input: string with all input values separated with spaces.

target: string with all expected target values separated with spaces.

BPN_EvaluateClass <bpnName> <input> <classExp>

Evaluate feature classifier.

Function result is string with classId and confidence.

bpnName: name of bpn variable.

input: string with all input values separated with spaces.

classExp: expected classId.

28-Aug-08

Classification with Neural
Networks part II

27

Back Propagation Network commands

BPN_EvaluateCIS <bpnName> <cisName> <minConfidence> <NoDetails | LowDetails | HighDetails>

Evaluate a CIS.

Function result is a string with:

maxError, meanError, nr of missclassifications and nr of low confidences

If not NoDetails is specified the result string is expanded for all miss classifications by:

expected classId, result, classId, confidence, imageIndex and if high details all values for all output neurons.

If not NoDetails is specified the result string is expanded for all low confidences by:

expected classId, result, classId, confidence, imageIndex and if high details all values for all output neurons.

bpnName: name of bpn variable.

cisName: name of cis variable.

minConfidence: the minimum value for the confidence wanted.

details: NoDetails, LowDetails or HighDetails.

28-Aug-08

Classification with Neural
Networks part II

28

Back Propagation Network commands

BPN_EvaluateImage <bpnName> <imageName> <classExp>

Evaluate an Image.

Function result is string with classId and confidence.

bpnName: name of bpn variable.

input: string with all input values separated with spaces.

classExp: expected classId.

28-Aug-08

Classification with Neural
Networks part II

29

Back Propagation Network commands

BPN_EvaluateImageSet <bpnName> <minConfidence> <NoDetails |
LowDetails | HighDetails> <\$images> <\$classes>

Evaluate an image set.

Function result is a string with:

maxError, meanError, nr of missclassifications and nr of low confidences

If not NoDetails is specified the result string is expanded for all miss
classifications by:

expected classId, result, classId, confidence, imageIndex and if high
details all values for all output neurons.

If not NoDetails is specified the result string is expanded for all low
confidences by:

expected classId, result, classId, confidence, imageIndex and if high
details all values for all output neurons.

bpnName: name of bpn variable.

minConfidence: the minimum value for the confidence wanted.

details: NoDetails, LowDetails or HighDetails.

images: string with all image names.

classes: string with all classIds.

28-Aug-08

Classification with Neural
Networks part II

30

Back Propagation Network commands

BPN_EvaluateClassSet <bpnName> <minConfidence> <NoDetails | LowDetails | HighDetails> <inputs> <classes>
 Evaluate a class set.
 Function result is a string with:
 maxError, meanError, nr of missclassifications and nr of low confidences
 If not NoDetails is specified the result string is expanded for all missclassifications by:
 expected classId, result, classId, confidence, imageIndex and if high details all values for all output neurons.
 If not NoDetails is specified the result string is expanded for all low confidences by:
 expected classId, result, classId, confidence, imageIndex and if high details all values for all output neurons.
 bpnName: name of bpn variable.
 minConfidence: the minimum value for the confidence wanted.
 details: NoDetails, LowDetails or HighDetails.
 inputs: string with setsize followed by all inputs.
 classes: string with setsize followed by all classIds.

28-Aug-08

Classification with Neural
Networks part II

31

Back Propagation Network commands

BPN_EvaluateSet <bpnName> <\$inputs> <\$targets>
 Evaluate a set of inputs.
 Function result is string with max error and mean error.
 bpnName: name of bpn variable.
 inputs: string with setsize followed by all inputs.
 targets: string with setsize followed by all targets.

BPN_GetLearnError <bpnName>
 Function result is learn error of specified bpn.

BPN_GetLearnRate <bpnName>
 Function result is learn rate of specified bpn.

BPN_GetMomentum <bpnName>
 Function result is momentum of specified bpn.

BPN_GetNameLearnSet <bpnName>
 Function result is name of learnset of specified bpn.

28-Aug-08

Classification with Neural
Networks part II

32

Back Propagation Network commands

BPN_GetSizeLayer <bpnName> <layerNr>

Function result is size of layer with layernr of specified bpn.

BPN_Produce <bpnName> <inputs>

Function result is the values of the output layers.

bpnName: name of bpn variable.

inputs: string with the input values.

BPN_ReadFromFile <bpnName> <filename>

Read bpn from file.

bpnName: name of bpn variable.

filename: file to read bpn from.

BPN_Rename <old bpnName> <new bpnName>

Rename bpn with old bpnName to new bpnName.

BPN_Reset <bpnName> <minRand> <maxRandW>

Reset all weights of bpn to random values.

28-Aug-08

Classification with Neural
Networks part II

33

Back Propagation Network commands

BPN_SetNameLearnSet <bpnName> <name learn set>

Set name of learn set of bpn to specified value.

BPN_Train <bpnName> <learnRate> <momentum> <\$input> <\$target>

Train bpn with one example.

Function result is learn error.

bpnName: name of bpn variable.

learnRate: learn rate.

momentum: momentum.

input: string with input values

target: string with target values

28-Aug-08

Classification with Neural
Networks part II

34

Back Propagation Network commands

BPN_TrainSet <bpnName> <nrOfEpochs> <learnRate> <momentum>
<\$inputs> <\$targets>

Train bpn with a set of examples.

Function result is learn error.

bpnName: name of bpn variable.

nrOfEpochs: number of times training process is repeated.

learnRate: learn rate.

momentum: momentum.

inputs: string with input values.

targets: string with target values.

BPN_TrainClass <bpnName> <learnRate> <momentum> <\$input> <class>

Train a classifier with one examples.

Function result is learn error.

bpnName: name of bpn variable.

learnRate: learn rate.

momentum: momentum.

input: string with input values.

class: string with targetId.

28-Aug-08

Classification with Neural
Networks part II

35

Back Propagation Network commands

BPN_TrainClassSet <bpnName> <nrOfEpochs> <learnRate> <momentum>
<setsize> <\$input class> <\$classes>

Train classifier with a set of examples.

Function result is the max error and mean error.

bpnName: name of bpn variable.

nrOfEpochs: number of times training process is repeated.

learnRate: learn rate.

momentum: momentum.

setsize: nr of examples.

inputs: string with input values.

classes: string with classIds.

28-Aug-08

Classification with Neural
Networks part II

36

Back Propagation Network commands

BPN_TrainImage <bpnName> <learnRate> <momentum> <image> <class>

Train a classifier with one image.

Function result is learn error.

bpnName: name of bpn variable.

learnRate: learn rate.

momentum: momentum.

image: string with name of image.

class: string with targetId.

28-Aug-08

Classification with Neural
Networks part II

37

Back Propagation Network commands

BPN_TrainImageSet <bpnName> <nrOfEpochs> <learnRate> <momentum>
<setsize> <\$images> <\$classes>

Train a classifier with set of images.

Function result is the max error and mean error.

bpnName: name of bpn variable.

nrOfEpochs: number of times training process is repeated.

learnRate: learn rate.

momentum: momentum.

setsize: nr of examples.

images: string with name of images.

classes: string with targetIds.

28-Aug-08

Classification with Neural
Networks part II

38

Back Propagation Network commands

BPN_TrainCIS <bpnName> <cisName> <nrOfEpochs> <learnRate>
<momentum>

Train a classifier with set of images.

Function result is the max error and mean error.

bpnName: name of bpn variable.

cisName: name of the cis variable.

nrOfEpochs: number of times training process is repeated.

learnRate: learn rate.

momentum: momentum.

BPN_WriteToFile <bpnName> <filename>

Write bpn to file.

bpnName: name of bpn variable.

filename: name of file to write bpn.

28-Aug-08

Classification with Neural
Networks part II

39

Examples

- Learning sinus function
- Generate Class Image Set
- Create CIS and BPN, Train BPN with CIS, Classify image using BPN and Evaluate BPN using CIS
- Create CFS and BPN, Train BPN with CFS, Classify image using BPN and Evaluate BPN using CFS

28-Aug-08

Classification with Neural
Networks part II

40

Example: learning sinus function


- Create BPN with
 - Input layer of 1 neuron
 - One hidden layer of 100 neurons
 - Output layer of 1 neuron
- Train the BPN with 100 random examples: $x, \sin(x)$
 - $\$in = \text{random } -1 \ 1$
 - $\$out = \sin \in
 - Note the behaviour of the training error ($\$t_err$)
- Test the BPN with 5 random values
 - $\$in = \text{random } -1 \ 1$
 - $\$res = \text{sinus of } \$in \text{ learned by BPN}$
 - $\$exp = \sin \in
 - $\$error = \text{error in result}$
- use script `bpn_sinus.jls`

28-Aug-08

Classification with Neural
Networks part II

41

Example: learning sinus function



28-Aug-08

Classification with Neural
Networks part II

42

Example: generate class image set

- Create cis
- Threshold image
- Remove big blobs
- Label image
- BlobAnalyse SortDown TopLeft UseX Height TopLeft Width
- for \$group = 0 to 1 do
 - for \$num = 0 to 9 do
 - for \$i = 0 to 9 do
 - Roi \$t \$l \$h \$w
 - Contraststretch
 - Zoom NearestPixelInterpolation
 - Add normalized image to cis

28-Aug-08

Classification with Neural
Networks part II

43

script: gen_ocr1_cis.jls (1)

```

$path = lpwd
$oldpath = pwd
cwd $path

$imagename = ocr1.jl
$cisname = ocr1.cis
$h_norm = 23
$w_norm = 17
$size = $h_norm * $w_norm
cis_create cis ByteImage "big number test" $h_norm $w_norm
cis_addclass cis zero
cis_addclass cis one
cis_addclass cis two
cis_addclass cis three
cis_addclass cis four
cis_addclass cis five
cis_addclass cis six
cis_addclass cis seven
cis_addclass cis eight
cis_addclass cis nine

```

Save old file path server

File path server = file path client

Create CIS and add 10 classes

28-Aug-08

Classification with Neural
Networks part II

44

script: gen_ocr1_cis.jls (2)

```

lread org $imasename
display org
copy org bin
thresholdisodata bin DarkObject
removeblobs bin EightConnected Area 300 10000 UseX
labelblobs bin EightConnected
$ana = blobanalysis bin SortDown TopLeft UseX Height TopLeft Width
for $group = 0 to 1 do
  for $num = 0 to 9 do
    $classname = cis_classname cis :
    for $i = 0 to 9 do
      removefirstword &$ana
      $h = removefirstword &$ana
      $tl = removefirstword &$ana
      $t = getnthfromvector 1 $tl
      $l = getnthfromvector 2 $tl
      $w = removefirstword &$ana

```

Remove 2 big horizontal lines

Find the image position of all digits

Note: blobs are sorted on x coordinate of top left

So there are first 10 zero's followed by 10 ones etc

There are two groups of 10 * 10 digits

28-Aug-08

Classification with Neural
Networks part II

45

script: gen_ocr1_cis.jls (3)

```

$t = $t - 1
$l = $l - 1
$h = $h + 2
$w = $w + 2
roi org roi $t $l $h $w
convert roi contrast ByteImage
contraststretch contrast 0 255
zoom contrast new $h_norm $w_norm NearestPixelInterpolation
cis_addimage cis new $classname
display new
syncvars
endfor $i
endfor $num
endfor $group
cis_writetofile cis $cisname
cld $oldpath

```

Cut out digits with a margin of 1 pixel

Convert to ByteImage

Normalize contrast and size

Add image with digit to CIS

Write CIS to file

Set file path server to original path

28-Aug-08

Classification with Neural
Networks part II

46

Example script bpn_cis_digits.jls

Steps:

- Create CIS
- Create BPN
- Train BPN with CIS
- Classify image using BPN
- Evaluate BPN using CIS

Notes

- This example creates only a tiny CIS with only one image for each class. See example gen_ocr1_cis.jls for generating a bigger more realistic CIS.
- Set \$debug to true to enable "debugging" script and examine the \$variables with Examine Variables in Server menu

28-Aug-08

Classification with Neural
Networks part II

47

Script bpn_cis_digits.jls (1)

```
initrandomgen 0
$debug = true
$path = lpwd
$oldpath = pwd
cwd $path
```

Save old file path server

File path server = file path client

```
$cisName = small.cis
$h_norm = 24
$w_norm = 16
$size = $h_norm * $w_norm
$base = number
cis_create $cisName ByteImage info $h_norm $w_norm
for $learn = 0 to 9 do
  $name = $base . $learn
  $classid = cis_addclass $cisName $name
endfor $learn
```

Create CIS and add classes

```
$classtab = cis_getclasstab $cisName
```

Get class table from cis

28-Aug-08

Classification with Neural
Networks part II

48

Script bpn_cis_digits.jls (2)

```

lread org numbers.jl
copy org thres
threshold thres 0 250
removeblobs thres EightConnected Area 300 10000 UseX
labelblobs thres EightConnected
$ana = blobanalysis thres SortDown TopLeft UseX Height TopLeft Width
$base = number

```

Find the image position of the digits

Note: blobs are sorted on x coordinate of top left

28-Aug-08

Classification with Neural
Networks part II

49

Script bpn_cis_digits.jls (3)

```

for $label = 0 to 9 do
  removefirstword &$ana
  $h = removefirstword &$ana
  $tl = removefirstword &$ana
  $t = getnthfromvector 1 $tl
  $l = getnthfromvector 2 $tl
  $w = removefirstword &$ana
  roi org tmp $t $l $h $w
  contraststretch tmp 0 255
  $class = $label
  $name = $base . $class
  zoom tmp $name $h_norm $w_norm NearestPixelInterpolation
  if $debug then
    display $name
  endif
  cis_addimage $cisName $name $name
endfor $label

```

Cut out digits with a margin of 1 pixel

Convert to ByteImage

Normalize contrast and size

Add image with digit to CIS

28-Aug-08

Classification with Neural
Networks part II

50

Script bpn_cis_digits.jls (4)

```

cis_writetofile $cisName $cisName      Save CIS to file
cis_delete $cisName                    Delete CIS

cis_readfromfile cis_small small.cis    Read CIS from file

$h = cis_getimageheight cis_small      Retrieve height/width info from CIS
$w = cis_getimagewidth cis_small
$size = $h * $w

                                     Create BPN
$hidden = 20
bpn_createimageclassifier bpn_small Bytelmage $size $hidden 0 10 NoBias 0 255
$base = number
$nrOfEpochs = 10
for $epoch = 1 to 10 do               Train BPN using CIS
    $a_err = bpn_traincis bpn_small cis_small $nrOfEpochs 0.001 0.0001
    if $debug then
        syncvars
    endif
endfor $epoch

```

28-Aug-08

Classification with Neural
Networks part II

51

Script bpn_cis_digits.jls (5)

```

for $t = 0 to 9 do
    $name = $base . $a_class_test
    $a_out = bpn_classifyimage bpn_small $name
    $a_class_res = getfirstword $a_out
    $a_class_id = cis_classname cis_small $a_class_res
    $a_class_confidence = getnthword 2 $a_out
    if $debug then
        syncvars
        break
    endif
endfor $t

                                     Classify image using BPN, result is classId and
                                     confidence

                                     Use CIS to convert classId to className

$res = bpn_evaluatecis bpn_small cis_small 1.0 HighDetails

                                     Evaluate BPN using CIS
                                     Note: in this example evaluation CIS
                                     and train CIS are the same

```

28-Aug-08

Classification with Neural
Networks part II

52

Script bpn_cis_digits.jls (6)

```
bpn_writetofile bpn_small small.bpn  Write BPN to file
bpn_delete bpn_small                Delete BPN and CIS from memory
cis_delete cis_small

cwd $oldpath                        Set file path server to original path
```

28-Aug-08

Classification with Neural
Networks part II

53

Example script test_feat_cfs.jls**Steps:**

- Create CFS
- Create BPN
- Train BPN with CFS
- Classify image using BPN
- Evaluate BPN using CFS

Notes

- Set \$debug to true to enable “debugging” script and examine the \$variables with Examine Variables in Server menu

28-Aug-08

Classification with Neural
Networks part II

54

script test_feat_cfs.jls (1)

```

$display = true
$path = lpwd
$oldpath = pwd
cwd $path

$х_norm = 23
$w_norm = 17

cfs_create cfs Int16Image info
cfs_addclass cfs zero
cfs_addclass cfs one
cfs_addclass cfs two
cfs_addclass cfs three
cfs_addclass cfs four
cfs_addclass cfs five
cfs_addclass cfs six
cfs_addclass cfs seven
cfs_addclass cfs eight
cfs_addclass cfs nine
$classtab = cfs_getclasstab cfs

```

Save old file path server
File path server = file path client

Create CFS and add classes

Get class table from CFS

28-Aug-08

Classification with Neural
Networks part II

55

script test_feat_cfs.jls (2)

```

cfs_addfeature cfs Area
cfs_addfeature cfs AreaHoles
cfs_addfeature cfs Breadth
cfs_addfeature cfs CentreOfGravity_x
cfs_addfeature cfs CentreOfGravity_y
cfs_addfeature cfs MomentsScale_xy
cfs_addfeature cfs NOfHoles
cfs_addfeature cfs Perimeter
$name_base = SumRow
for $h = 1 to $h_norm do
    $fname = $name_base . $h
    cfs_addfeature cfs $fname
endfor $h
$name_base = sumCol
for $c = 1 to $w_norm do
    $fname = $name_base . $c
    cfs_addfeature cfs $fname
endfor $h
$featurenametab = cfs_getfeaturenametab cfs

```

Add features to CFS

Get feature table from CFS

28-Aug-08

Classification with Neural
Networks part II

56

script test_feat_cfs.jls (3)

```

lread org ocr1.jl
if $display then
  display org
endif
copy org bin
thresholdisodata bin DarkObject
removeblobs bin EightConnected Area 300 10000 UseX
fillspecificholes bin FourConnected Area 0 10 UseX
labelblobs bin EightConnected
$ana = blobanalysis bin SortDown TopLeft UseX Height TopLeft Width
for $group = 0 to 1 do
  for $num = 0 to 9 do
    for $i = 0 to 9 do
      removefirstword &$ana
      $h = removefirstword &$ana
      $tl = removefirstword &$ana
      $t = getnthfromvector 1 $tl
      $l = getnthfromvector 2 $tl
      $w = removefirstword &$ana

```

Find the image position of the digits**Note: blobs are sorted on x coordinate of top left**

28-Aug-08

Classification with Neural
Networks part II

57

script test_feat_cfs.jls (4)

```

$t = $t - 1
$l = $l - 1
$h = $h + 2
$w = $w + 2
roi org roi $t $l $h $w
$class_name = cfs_classname cfs $num
contraststretch roi 0 255
zoom roi new $h_norm $w_norm NearestPixelInterpolation
cfs_addimage cfs new $class_name
if $display then
  display roi
  syncvars
endif
endfor $i
endfor $num
endfor $group
break

```

Cut out digits with a margin of 1 pixel**Convert to ByteImage****Normalize contrast and size****Add image with digit to CFS**

28-Aug-08

Classification with Neural
Networks part II

58

script test_feat_cfs.jls (5)

```

cfs_setscriptname cfs test_calc_feat.jls Set script name of CFS
laddscript ocr_feat test_calc_feat.jls Calculate all features for all image in CFS
cfs_calcfeatures cfs ocr_feat Save and read CFS
cfs_writetofile cfs test.cfs
cfs_readfromfile cfs test.cfs
break
$nr_epochs = 40
$learnrate = 0.005
$momentum = 0.01 Create BPN
$nr_hidden = 200
bpn_createfeatureclassifier bpn_feature_test cfs $nr_hidden 0 Bias
BPN_SetNameLearnSet bpn_feature_test test.cfs
for $epoch = 1 to $nr_epochs do Train BPN using CFS
    $a_err = bpn_traincfs bpn_feature_test cfs 1 $learnrate $momentum
    if $display then
        syncvars
    endif
endfor $epoch Save BPN
bpn_writetofile bpn_feature_test feature_test.bpn
break

```

28-Aug-08

Classification with Neural
Networks part II

59

script test_feat_cfs.jls (6)

```

$a_eval = bpn_evaluatecfs bpn_feature_test cfs 0.7 LowDetails
break Evaluate BPN using CFS

$s = ""
for $f = 1 to 48 do Create string with selected features
    $s = $s . 1
endfor $f
lread roi eight.jl Classify image with selected features

$a_class = bpn_classifyselectedfeatures bpn_feature_test roi ocr_feat $s
break
$a_class = bpn_classifyfeatures bpn_feature_test roi ocr_feat
break Classify image

cfs_delete cfs Delete CFS from memory
delete org
delete bin
delete roi

cwd $oldpath Set file path server to original path

```

28-Aug-08

Classification with Neural
Networks part II

60