

Clock Conditioning

10 MHz In J1 SMA TH RA TP4 1nF C1 50V NP0 TP5 10MHz_3v3 R7 10k 0.1% GND R2 10k 0.1% D1 PESD5V0H1BSF GND

USB

USB_C_Receptacle_USB2.0 J9 +5V VBUS A4 CC1 A5 CC2 B5 D- A7 B7 D+ A6 B6 USB_DM USB_DP USBLC6-2SC6 U3 R10 5.1k R11 5.1k GND

Power

+5V TP6 10uF 16V C6 SMF5V0A D9 LP5907MFX-3.3 U2 IN EN OUT 5 +3V3 C5 10uF 16V C7 2.2uF 10V C4 2.2uF 10V TP7 Green LED Power D7 R8 680

Programming

+3V3 J7 1 2 SWDIO 3 4 SWCLK 5 6 SWO 7 8 RESET 9 10 Prog J8 Ground

SW1 Reset RESET 10MHz_3v3 PG10 PF0 PF1 PD2 PC0 PC1 PC2 PC3 PC4 PC5 PC6 PC7 PC8 PC9 PC10 PC11 PC12 PC13 PC14 PC15 VREF+ VBAT VDD VDD VDD VDD VDDA PA0 PA1 PA2 PA3 PA4 PA5 PA6 PA7 PA8 PA9 PA10 PA11 PA12 PA13 PA14 PA15 PB0 PB1 PB2 PB3 PB4 PB5 PB6 PB7 PB8 PB9 PB10 PB11 PB12 PB13 PB14 PB15 J5 1 2 Chan 2 SMA TH RA J6 Debug TX RX boot0 R3 680 D3 Green LED Chan 0 J3 1 2 Chan 1 J2 1 2 Chan 0 R4 680 D4 Green LED Chan 1 R5 680 D5 Green LED Chan 2 R6 680 D6 Green LED Chan 3 R9 680 D8 Green LED USB R1 680 D2 Green LED 10 MHz In

Sheet: /
File: PulseGen.kicad_sch

Title:

Size: A4 Date: Rev: B
KiCad E.D.A. 10.0.3 Id: 1/1

[illegible][illegible]