

## Follow the leader on OLO problems



- Getting to know online linear optimization (OLO) problems
- See that FTL might fail for these problems
- Understanding the root cause for FTL's flaw



# FTL FOR ONLINE LINEAR OPTIMIZATION

- Another popular instantiation of the online learning problem is the online linear optimization problem, which is characterized by a linear loss function  $(a, z) = a^\top z$ .



# FTL FOR ONLINE LINEAR OPTIMIZATION


- Another popular instantiation of the online learning problem is the online linear optimization problem, which is characterized by a linear loss function  $(a, z) = a^\top z$ .

- Let  $\mathcal{A} = [-1, 1]$  and suppose that  $z_t = \begin{cases} -\frac{1}{2}, & t = 1, \\ 1, & t \text{ is even,} \\ -1, & t \text{ is odd.} \end{cases}$



# FTL FOR ONLINE LINEAR OPTIMIZATION

- Another popular instantiation of the online learning problem is the online linear optimization problem, which is characterized by a linear loss function  $(a, z) = a^\top z$ .
- Let  $\mathcal{A} = [-1, 1]$  and suppose that  $z_t = \begin{cases} -\frac{1}{2}, & t = 1, \\ 1, & t \text{ is even,} \\ -1, & t \text{ is odd.} \end{cases}$
- No matter how we choose the first action  $a_1^{\text{FTL}}$ , it will hold that FTL has a cumulative loss greater than (or equal)  $T - 3/2$ , while the best action in hindsight has a cumulative loss of  $-1/2$ .
- Thus, FTL's cumulative regret is at least  $T - 1$ , which is linearly growing in  $T$ .



# FTL FOR ONLINE LINEAR OPTIMIZATION

- Indeed, note that

$$\begin{aligned} a_{t+1}^{\text{FTL}} &= \arg \min_{a \in \mathcal{A}} \sum_{s=1}^t (a, z_s) = \arg \min_{a \in [-1, 1]} a \sum_{s=1}^t z_s \\ &= \begin{cases} -1, & \text{if } \sum_{s=1}^t z_s > 0, \\ 1, & \text{if } \sum_{s=1}^t z_s < 0, \\ \text{arbitrary}, & \text{if } \sum_{s=1}^t z_s = 0. \end{cases} \end{aligned}$$



# FTL FOR ONLINE LINEAR OPTIMIZATION

- Indeed, note that

$$\begin{aligned} a_{t+1}^{\text{FTL}} &= \arg \min_{a \in \mathcal{A}} \sum_{s=1}^t (a, z_s) = \arg \min_{a \in [-1, 1]} a \sum_{s=1}^t z_s \\ &= \begin{cases} -1, & \text{if } \sum_{s=1}^t z_s > 0, \\ 1, & \text{if } \sum_{s=1}^t z_s < 0, \\ \text{arbitrary}, & \text{if } \sum_{s=1}^t z_s = 0. \end{cases} \end{aligned}$$

$t$	$a_t^{\text{FTL}}$	$z_t$	$(a_t^{\text{FTL}}, z_t)$	$\sum_{s=1}^t (a_s^{\text{FTL}}, z_s)$	$\sum_{s=1}^t z_s$
1	1	-1/2	-1/2	-1/2	-1/2




# FTL FOR ONLINE LINEAR OPTIMIZATION

- Indeed, note that

$$\begin{aligned} a_{t+1}^{\text{FTL}} &= \arg \min_{a \in \mathcal{A}} \sum_{s=1}^t (a, z_s) = \arg \min_{a \in [-1, 1]} a \sum_{s=1}^t z_s \\ &= \begin{cases} -1, & \text{if } \sum_{s=1}^t z_s > 0, \\ 1, & \text{if } \sum_{s=1}^t z_s < 0, \\ \text{arbitrary}, & \text{if } \sum_{s=1}^t z_s = 0. \end{cases} \end{aligned}$$

$t$	$a_t^{\text{FTL}}$	$z_t$	$(a_t^{\text{FTL}}, z_t)$	$\sum_{s=1}^t (a_s^{\text{FTL}}, z_s)$	$\sum_{s=1}^t z_s$
1	1	-1/2	-1/2	-1/2	-1/2
2	1	1	1	1 - 1/2	1/2



# FTL FOR ONLINE LINEAR OPTIMIZATION

- Indeed, note that

$$\begin{aligned} a_{t+1}^{\text{FTL}} &= \arg \min_{a \in \mathcal{A}} \sum_{s=1}^t (a, z_s) = \arg \min_{a \in [-1, 1]} a \sum_{s=1}^t z_s \\ &= \begin{cases} -1, & \text{if } \sum_{s=1}^t z_s > 0, \\ 1, & \text{if } \sum_{s=1}^t z_s < 0, \\ \text{arbitrary}, & \text{if } \sum_{s=1}^t z_s = 0. \end{cases} \end{aligned}$$

$t$	$a_t^{\text{FTL}}$	$z_t$	$(a_t^{\text{FTL}}, z_t)$	$\sum_{s=1}^t (a_s^{\text{FTL}}, z_s)$	$\sum_{s=1}^t z_s$
1	1	-1/2	-1/2	-1/2	-1/2
2	1	1	1	1 - 1/2	1/2
3	-1	-1	1	2 - 1/2	-1/2





# FTL FOR ONLINE LINEAR OPTIMIZATION

- Indeed, note that

$$\begin{aligned} a_{t+1}^{\text{FTL}} &= \arg \min_{a \in \mathcal{A}} \sum_{s=1}^t (a, z_s) = \arg \min_{a \in [-1, 1]} a \sum_{s=1}^t z_s \\ &= \begin{cases} -1, & \text{if } \sum_{s=1}^t z_s > 0, \\ 1, & \text{if } \sum_{s=1}^t z_s < 0, \\ \text{arbitrary}, & \text{if } \sum_{s=1}^t z_s = 0. \end{cases} \end{aligned}$$


$t$	$a_t^{\text{FTL}}$	$z_t$	$(a_t^{\text{FTL}}, z_t)$	$\sum_{s=1}^t (a_s^{\text{FTL}}, z_s)$	$\sum_{s=1}^t z_s$
1	1	-1/2	-1/2	-1/2	-1/2
2	1	1	1	1 - 1/2	1/2
3	-1	-1	1	2 - 1/2	-1/2
$\vdots$	$\vdots$	$\vdots$	$\vdots$	$\vdots$	$\vdots$
$T$	$(-1)^T$	$(-1)^T$	1	$T - 1 - 1/2$	$(-1/2)^T$



# FTL FOR ONLINE LINEAR OPTIMIZATION

- Indeed, note that

$$\begin{aligned}
 a_{t+1}^{\text{FTL}} &= \arg \min_{a \in \mathcal{A}} \sum_{s=1}^t (a, z_s) = \arg \min_{a \in [-1, 1]} a \sum_{s=1}^t z_s \\
 &= \begin{cases} -1, & \text{if } \sum_{s=1}^t z_s > 0, \\ 1, & \text{if } \sum_{s=1}^t z_s < 0, \\ \text{arbitrary}, & \text{if } \sum_{s=1}^t z_s = 0. \end{cases}
 \end{aligned}$$



$t$	$a_t^{\text{FTL}}$	$z_t$	$(a_t^{\text{FTL}}, z_t)$	$\sum_{s=1}^t (a_s^{\text{FTL}}, z_s)$	$\sum_{s=1}^t z_s$
1	1	$-1/2$	$-1/2$	$-1/2$	$-1/2$
2	1	1	1	$1 - 1/2$	$1/2$
3	-1	-1	1	$2 - 1/2$	$-1/2$
$\vdots$	$\vdots$	$\vdots$	$\vdots$	$\vdots$	$\vdots$
$T$	$(-1)^T$	$(-1)^T$	1	$T - 1 - 1/2$	$(-1/2)^T$

- The best action has cumulative loss

$$\inf_{a \in \mathcal{A}} \sum_{s=1}^T (a, z_s) = \inf_{a \in [-1, 1]} a \underbrace{\sum_{s=1}^T z_s}_{=(-1/2)^T} = -1/2.$$

# FTL FOR ONLINE LINEAR OPTIMIZATION

- Thus, we see: FTL can fail for **online linear optimization problems**, although it is well suited for **online quadratic optimization problems**!
- The reason is that the action selection of FTL is not stable enough (caused by the loss function), which is fine for **the latter problem**, but problematic for **the former**.
- One has to note that the online linear optimization problem example above, where FTL fails, is in fact an adversarial learning setting: The environmental data is generated in such a way that the FTL learner is fooled in each time step.

