



DECISION TREES - EXAMPLE

- Fit decision tree with tree depth of 3 on bike data
- E.g., mean prediction for the first 105 days since 2011 is 1798
~> Applies to $\hat{=}$ 15% of the data (leftmost branch)
- days_since_2011**: highest feature importance (explains most of variance)



Feature	Importance
days_since_2011	79.53
temp	17.55
hum	2.92



UNBIASED RECURSIVE PARTITIONING

► Hothorn et al. (2006)

► Zeileis et al. (2008)


► Strobl et al. (2007)

Problems with CART (Classification and Regression Trees):

- ❶ Selection bias towards high-cardinal/continuous features
- ❷ Does not consider significant improvements when splitting (\rightsquigarrow overfitting)

Unbiased recursive partitioning via conditional inference trees (**ctree**) or
model-based recursive partitioning (**mb**):

- ❶ Separate selection of **feature used for splitting** and **split point**
- ❷ Hypothesis test as stopping criteria




UNBIASED RECURSIVE PARTITIONING

► Hothorn et al. (2006)

► Zeileis et al. (2008)

► Strobl et al. (2007)



Problems with CART (Classification and Regression Trees):

- 1 Selection bias towards high-cardinal/continuous features
- 2 Does not consider significant improvements when splitting (\leadsto overfitting)

Unbiased recursive partitioning via conditional inference trees (cforest) or
model-based recursive partitioning (mmb):


- 1 Separate selection of **feature used for splitting** and **split point**
- 2 Hypothesis test as stopping criteria

Example (selection bias):

Simulate data ($n = 200$) with $Y \sim N(0, 1)$
and 3 features of different cardinality
independent from Y (repeat 500 times):

- $X_1 \sim \text{Binom}(n, \frac{1}{2})$
- $X_2 \sim M(n, (\frac{1}{4}, \frac{1}{4}, \frac{1}{4}, \frac{1}{4}))$
- $X_3 \sim M(n, (\frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}, \frac{1}{8}))$


Which feature is selected in the first split?




UNBIASED RECURSIVE PARTITIONING

Differences to CART:

- Two-step approach (1. find most significant split feature, 2. find best split point)
- Parametric model (e.g. LM) instead of constant can be fitted in leave nodes
- Significance of split (p-value) given in each node
- `ctree` and `mda` differ in hypothesis test used for selecting the split feature (independence test vs. fluctuation test) and how to find the best split point



UNBIASED RECURSIVE PARTITIONING




Differences to CART:

- Two-step approach (1. find most significant split feature, 2. find best split point)
- Parametric model (e.g. LM instead of constant) can be fitted in leave nodes
- Significance of split (p-value) given in each node
- ctree and mob differ in hypothesis test used for selecting the split feature (independence test vs. fluctuation test) and how to find the best split point

Example (ctree): Bike data (constant model in final nodes)

Example (ctree): Bike data (constant model in final nodes)




Train error (MSE):
758,844.0 (ctree)
742,244.4 (mob)

UNBIASED RECURSIVE PARTITIONING


Differences to CART:

- Two-step approach (1. find most significant split feature, 2. find best split point)
- Parametric model (e.g. LM instead of constant) can be fitted in leaf nodes
- Significance of split (p-value) given in each node
- ctree and mob differ in hypothesis test used for selecting the split feature (independence test vs. fluctuation test) and how to find the best split point



Example (mob): Bike data (linear model with temp in final nodes)

Example (mob): Bike data (linear model with temp in final nodes)



Train error (MSE):
758,844.0 (ctree)
742,244.4 (mob)

Train error (MSE): 758,844.0 (ctree), 742,244.4 (mob)

OTHER RULE-BASED MODELS

Decision Rules ► Holte 1993

- (Chaining of) simple “if – then” statements
~> very intuitive and easy-to-interpret
- Most methods work only for classification and categorical features

RuleFit ► Friedman and Popescu 2008

- Combination of LM and decision trees
- Allows for feature interactions and non-linearities

IF size=small THEN value=low
IF size=medium THEN value=medium
IF size=big THEN value=high

