

Feature-Weighted Elastic Net for Competing Risk Outcomes

Lukas Burk

Context

The elastic net objective function is given as:

$$J(\beta_0, \beta) = \frac{1}{2} \|\mathbf{y} - \beta_0 \mathbf{1} - \mathbf{X}\beta\|_2^2 + \lambda \sum_{j=1}^p \left(\alpha |\beta_j| + \frac{1-\alpha}{2} \beta_j^2 \right)$$

- $\lambda \in \mathbb{R}$ controls overall sparsity

(Zou and Hastie 2005)

Context

The elastic net objective function is given as:

$$J(\beta_0, \beta) = \frac{1}{2} \|\mathbf{y} - \beta_0 \mathbf{1} - \mathbf{X}\beta\|_2^2 + \lambda \sum_{j=1}^p \left(\alpha |\beta_j| + \frac{1-\alpha}{2} \beta_j^2 \right)$$

- ▶ $\lambda \in \mathbb{R}$ controls overall sparsity
- ▶ Higher \Rightarrow larger penalty on all β_j , *equally*

(Zou and Hastie 2005)

Context

The elastic net objective function is given as:

$$J(\beta_0, \beta) = \frac{1}{2} \|\mathbf{y} - \beta_0 \mathbf{1} - \mathbf{X}\beta\|_2^2 + \lambda \sum_{j=1}^p \left(\alpha |\beta_j| + \frac{1-\alpha}{2} \beta_j^2 \right)$$

- ▶ $\lambda \in \mathbb{R}$ controls overall sparsity
- ▶ Higher \Rightarrow larger penalty on all β_j , *equally*
- ▶ $\alpha \in [0, 1]$ is the mixing parameter

(Zou and Hastie 2005)

Context

The elastic net objective function is given as:

$$J(\beta_0, \beta) = \frac{1}{2} \|\mathbf{y} - \beta_0 \mathbf{1} - \mathbf{X}\beta\|_2^2 + \lambda \sum_{j=1}^p \left(\alpha |\beta_j| + \frac{1-\alpha}{2} \beta_j^2 \right)$$

- ▶ $\lambda \in \mathbb{R}$ controls overall sparsity
- ▶ Higher \Rightarrow larger penalty on all β_j , *equally*
- ▶ $\alpha \in [0, 1]$ is the mixing parameter
- ▶ $1 \Rightarrow$ only ℓ^1 penalty (LASSO)

(Zou and Hastie 2005)

Context

The elastic net objective function is given as:

$$J(\beta_0, \beta) = \frac{1}{2} \|\mathbf{y} - \beta_0 \mathbf{1} - \mathbf{X}\beta\|_2^2 + \lambda \sum_{j=1}^p \left(\alpha |\beta_j| + \frac{1-\alpha}{2} \beta_j^2 \right)$$

- ▶ $\lambda \in \mathbb{R}$ controls overall sparsity
- ▶ Higher \Rightarrow larger penalty on all β_j , *equally*
- ▶ $\alpha \in [0, 1]$ is the mixing parameter
- ▶ $1 \Rightarrow$ only ℓ^1 penalty (LASSO)
- ▶ $0 \Rightarrow$ only ℓ^2 penalty

(Zou and Hastie 2005)

Feature-Weighted Elastic Net (fwe1net)

- ▶ Introduced by Tay et al. (2020)

Feature-Weighted Elastic Net (fwe1net)

- ▶ Introduced by Tay et al. (2020)
- ▶ Multiple applications: External information & feature-grouping

Feature-Weighted Elastic Net (fwe1net)

- ▶ Introduced by Tay et al. (2020)
- ▶ Multiple applications: External information & feature-grouping
- ▶ Sometimes it's desirable to adjust penalization weights on individual or groups of coefficients

Feature-Weighted Elastic Net (fwelnet)

- ▶ Introduced by Tay et al. (2020)
- ▶ Multiple applications: External information & feature-grouping
- ▶ Sometimes it's desirable to adjust penalization weights on individual or groups of coefficients
- ▶ Assign groups via matrix $\mathbf{Z} \in \mathbb{R}^{p \times K}$

Feature Weighting: Groups

$$\mathbf{Z} = \begin{pmatrix} 1 & 0 \\ 1 & 0 \\ 0 & 1 \\ 0 & 1 \end{pmatrix}$$

► Features 1, 2 group 1

Feature Weighting: Groups

$$\mathbf{Z} = \begin{pmatrix} 1 & 0 \\ 1 & 0 \\ 0 & 1 \\ 0 & 1 \end{pmatrix}$$

- ▶ Features 1, 2 group 1
- ▶ Features 3, 4 group 2

Feature Weighting: Groups

$$\mathbf{Z} = \begin{pmatrix} 1 & 0 \\ 1 & 0 \\ 0 & 1 \\ 0 & 1 \end{pmatrix}$$

- ▶ Features 1, 2 group 1
- ▶ Features 3, 4 group 2

Feature Weighting: Groups

$$\mathbf{Z} = \begin{pmatrix} 1 & 0 \\ 1 & 0 \\ 0 & 1 \\ 0 & 1 \end{pmatrix}$$

► Features 1, 2 group 1

► Features 3, 4 group 2

Now imagine this, but with $p \gg 1000$ and e.g. genetic data.

Feature-Weighting

$$J(\beta_0, \beta) = \frac{1}{2} \|\mathbf{y} - \beta_0 \mathbf{1} - \mathbf{X}\beta\|_2^2 + \lambda \sum_{j=1}^p w_j(\theta) \left(\alpha |\beta_j| + \frac{1-\alpha}{2} \beta_j^2 \right)$$

where

Feature-Weighting

$$J(\beta_0, \beta) = \frac{1}{2} \|\mathbf{y} - \beta_0 \mathbf{1} - \mathbf{X}\beta\|_2^2 + \lambda \sum_{j=1}^p w_j(\theta) \left(\alpha |\beta_j| + \frac{1-\alpha}{2} \beta_j^2 \right)$$

where

$$w_j(\theta) = \frac{\sum_{l=1}^p \exp(\mathbf{z}_l^T \theta)}{p \exp(\mathbf{z}_j^T \theta)}$$

Defines the **penalization weight** of coefficient j based on its corresponding value in \mathbf{Z} and additionally hyper-parameter θ

Penalization Weights

- ▶ $w_j(\theta)$ is chosen heuristically, suggested by the authors for desirable properties

Penalization Weights

- ▶ $w_j(\theta)$ is chosen heuristically, suggested by the authors for desirable properties
- ▶ $\mathbf{z}_j^T \theta$ functions as a *score*

Penalization Weights

- ▶ $w_j(\theta)$ is chosen heuristically, suggested by the authors for desirable properties
- ▶ $\mathbf{z}_j^T \theta$ functions as a *score*
 - ▶ $= 0$, reduces to original elastic net

Penalization Weights

- ▶ $w_j(\theta)$ is chosen heuristically, suggested by the authors for desirable properties
- ▶ $\mathbf{z}_j^T \theta$ functions as a *score*
 - ▶ $= 0$, reduces to original elastic net
 - ▶ Higher score \rightarrow lower penalization weight, feature is “more important”

Penalization Weights

- ▶ $w_j(\theta)$ is chosen heuristically, suggested by the authors for desirable properties
- ▶ $\mathbf{z}_j^T \theta$ functions as a *score*
 - ▶ $= 0$, reduces to original elastic net
 - ▶ Higher score \rightarrow lower penalization weight, feature is “more important”

Penalization Weights

- ▶ $w_j(\theta)$ is chosen heuristically, suggested by the authors for desirable properties
- ▶ $\mathbf{z}_j^T \theta$ functions as a *score*
 - ▶ $= 0$, reduces to original elastic net
 - ▶ Higher score \rightarrow lower penalization weight, feature is “more important”
- ▶ In the “feature grouping” setting, this just allows group-specific penalization weights.

Penalization Weights

- ▶ $w_j(\theta)$ is chosen heuristically, suggested by the authors for desirable properties
- ▶ $\mathbf{z}_j^T \theta$ functions as a *score*
 - ▶ $= 0$, reduces to original elastic net
 - ▶ Higher score \rightarrow lower penalization weight, feature is “more important”
- ▶ In the “feature grouping” setting, this just allows group-specific penalization weights.
- ▶ Related to the “group lasso” (Jacob, Obozinski, and Vert 2009)

Feature-Weighting: Single Group

- ▶ \mathbf{Z} can also be $p \times 1$: No groups, just weights

Feature-Weighting: Single Group

- ▶ \mathbf{Z} can also be $p \times 1$: No groups, just weights
- ▶ Example from paper: \mathbf{Z} set to noisy version of true $|\beta|$ in simulation study

Feature-Weighting: Single Group

- ▶ \mathbf{Z} can also be $p \times 1$: No groups, just weights
- ▶ Example from paper: \mathbf{Z} set to noisy version of true $|\beta|$ in simulation study

Feature-Weighting: Single Group

- ▶ \mathbf{Z} can also be $p \times 1$: No groups, just weights
- ▶ Example from paper: \mathbf{Z} set to noisy version of true $|\beta|$ in simulation study
- ▶ Higher $|\beta_j| \Rightarrow$ lower penalization for $\hat{\beta}_j$

Feature-Weighting: Single Group

- ▶ \mathbf{Z} can also be $p \times 1$: No groups, just weights
- ▶ Example from paper: \mathbf{Z} set to noisy version of true $|\beta|$ in simulation study
- ▶ Higher $|\beta_j| \Rightarrow$ lower penalization for $\hat{\beta}_j$
- ▶ $|\beta_j| \approx 0 \Rightarrow$ higher penalization for $\hat{\beta}_j$

Application for Multi-Task Learning

- ▶ Authors suggest multi-task learning algorithm, outline:

Application for Multi-Task Learning

► Authors suggest multi-task learning algorithm, outline:

1. $\beta_1^{(0)}, \beta_2^{(0)}$: `glmnet` solution for $(\mathbf{X}, \mathbf{y}_1), (\mathbf{X}, \mathbf{y}_2)$ respectively

Application for Multi-Task Learning

► Authors suggest multi-task learning algorithm, outline:

1. $\beta_1^{(0)}, \beta_2^{(0)}$: `glmnet` solution for $(\mathbf{X}, \mathbf{y}_1), (\mathbf{X}, \mathbf{y}_2)$ respectively
2. For $k = 0, 1, \dots$:

Application for Multi-Task Learning

► Authors suggest multi-task learning algorithm, outline:

1. $\beta_1^{(0)}, \beta_2^{(0)}$: `glmnet` solution for $(\mathbf{X}, \mathbf{y}_1), (\mathbf{X}, \mathbf{y}_2)$ respectively
2. For $k = 0, 1, \dots$:
 - a) $\mathbf{Z}_2 = |\beta_1^{(k)}|$. Fit `fwelnet` with $(\mathbf{X}, \mathbf{y}_2, \mathbf{Z}_2)$

Application for Multi-Task Learning

► Authors suggest multi-task learning algorithm, outline:

1. $\beta_1^{(0)}, \beta_2^{(0)}$: `glmnet` solution for $(\mathbf{X}, \mathbf{y}_1), (\mathbf{X}, \mathbf{y}_2)$ respectively
2. For $k = 0, 1, \dots$:
 - a) $\mathbf{Z}_2 = |\beta_1^{(k)}|$. Fit `fwelnet` with $(\mathbf{X}, \mathbf{y}_2, \mathbf{Z}_2)$
 - Set $|\beta_2^{(k+1)}|$ to solution with optimal `lambda`

Application for Multi-Task Learning

► Authors suggest multi-task learning algorithm, outline:

1. $\beta_1^{(0)}, \beta_2^{(0)}$: `glmnet` solution for $(\mathbf{X}, \mathbf{y}_1), (\mathbf{X}, \mathbf{y}_2)$ respectively
2. For $k = 0, 1, \dots$:
 - a) $\mathbf{Z}_2 = |\beta_1^{(k)}|$. Fit `fwelnet` with $(\mathbf{X}, \mathbf{y}_2, \mathbf{Z}_2)$
 - Set $|\beta_2^{(k+1)}|$ to solution with optimal `lambda`
 - b) $\mathbf{Z}_1 = |\beta_2^{(k+1)}|$. Fit `fwelnet` with $(\mathbf{X}, \mathbf{y}_1, \mathbf{Z}_1)$

Application for Multi-Task Learning

► Authors suggest multi-task learning algorithm, outline:

1. $\beta_1^{(0)}, \beta_2^{(0)}$: `glmnet` solution for $(\mathbf{X}, \mathbf{y}_1), (\mathbf{X}, \mathbf{y}_2)$ respectively
2. For $k = 0, 1, \dots$:
 - a) $\mathbf{Z}_2 = |\beta_1^{(k)}|$. Fit `fwelnet` with $(\mathbf{X}, \mathbf{y}_2, \mathbf{Z}_2)$
 - Set $|\beta_2^{(k+1)}|$ to solution with optimal `lambda`
 - b) $\mathbf{Z}_1 = |\beta_2^{(k+1)}|$. Fit `fwelnet` with $(\mathbf{X}, \mathbf{y}_1, \mathbf{Z}_1)$
 - Set $|\beta_1^{(k+1)}|$ to solution with optimal `lambda`

Transfer to Competing Risks

- ▶ Setting with two causes: $\mathbf{y}_1, \mathbf{y}_2 \in \{0, 1\}$

Transfer to Competing Risks

- ▶ Setting with two causes: $\mathbf{y}_1, \mathbf{y}_2 \in \{0, 1\}$
- ▶ Assumption: Shared information for both causes:

Transfer to Competing Risks

- ▶ Setting with two causes: $y_1, y_2 \in \{0, 1\}$
- ▶ Assumption: Shared information for both causes:
 - ▶ If x_j is important for y_1 , also for y_2 ?

Transfer to Competing Risks

- ▶ Setting with two causes: $y_1, y_2 \in \{0, 1\}$
- ▶ Assumption: Shared information for both causes:
 - ▶ If x_j is important for y_1 , also for y_2 ?
 - ▶ \Rightarrow Avoid shrinking it to 0 in cause-specific models

Transfer to Competing Risks

- ▶ Setting with two causes: $y_1, y_2 \in \{0, 1\}$
- ▶ Assumption: Shared information for both causes:
 - ▶ If x_j is important for y_1 , also for y_2 ?
 - ▶ \Rightarrow Avoid shrinking it to 0 in cause-specific models
- ▶ Basic idea: Adapt previous algorithm to Cox regression

Transfer to Competing Risks

- ▶ Setting with two causes: $y_1, y_2 \in \{0, 1\}$
- ▶ Assumption: Shared information for both causes:
 - ▶ If x_j is important for y_1 , also for y_2 ?
 - ▶ \Rightarrow Avoid shrinking it to 0 in cause-specific models
- ▶ Basic idea: Adapt previous algorithm to Cox regression
- ▶ Multi-task \Rightarrow “Multi-cause”

What We Have

- ▶ 1: Adapt `fwelnet` for Coxnet/Surv endpoint via `glmnet`

What We Have

- ▶ 1: Adapt `fwelnet` for Coxnet/Surv endpoint via `glmnet`
- ▶ 2: Implement algorithm for Cox/CR setting

What We Have

- ▶ 1: Adapt `fwelnet` for Coxnet/Surv endpoint via `glmnet`
- ▶ 2: Implement algorithm for Cox/CR setting
- ▶ 3: Apply algorithm to some “easy” simulated data settings:

What We Have

- ▶ 1: Adapt `fwelnet` for Coxnet/Surv endpoint via `glmnet`
- ▶ 2: Implement algorithm for Cox/CR setting
- ▶ 3: Apply algorithm to some “easy” simulated data settings:
 - ▶ Large effects ($\beta_j = 1$ or 0.25 for “small effect”)

What We Have

- ▶ 1: Adapt `fwelnet` for Coxnet/Surv endpoint via `glmnet`
- ▶ 2: Implement algorithm for Cox/CR setting
- ▶ 3: Apply algorithm to some “easy” simulated data settings:
 - ▶ Large effects ($\beta_j = 1$ or 0.25 for “small effect”)
 - ▶ $N = 1000$

What We Have

- ▶ 1: Adapt `fwelnet` for Coxnet/Surv endpoint via `glmnet`
- ▶ 2: Implement algorithm for Cox/CR setting
- ▶ 3: Apply algorithm to some “easy” simulated data settings:
 - ▶ Large effects ($\beta_j = 1$ or 0.25 for “small effect”)
 - ▶ $N = 1000$
 - ▶ 11-14 noise variables

What We Have

- ▶ 1: Adapt `fwelnet` for Coxnet/Surv endpoint via `glmnet`
- ▶ 2: Implement algorithm for Cox/CR setting
- ▶ 3: Apply algorithm to some “easy” simulated data settings:
 - ▶ Large effects ($\beta_j = 1$ or 0.25 for “small effect”)
 - ▶ $N = 1000$
 - ▶ 11-14 noise variables

What We Have

- ▶ 1: Adapt `fwelnet` for Coxnet/Surv endpoint via `glmnet`
- ▶ 2: Implement algorithm for Cox/CR setting
- ▶ 3: Apply algorithm to some “easy” simulated data settings:
 - ▶ Large effects ($\beta_j = 1$ or 0.25 for “small effect”)
 - ▶ $N = 1000$
 - ▶ 11-14 noise variables

First goal: See if we find some improvement over cause-specific `glmnet`

What Comes Next

- ▶ Wider set of simulation cases

What Comes Next

- ▶ Wider set of simulation cases
- ▶ Evaluate predictive performance (non-trivial in CR/censored setting)

References

- Jacob, Laurent, Guillaume Obozinski, and Jean-Philippe Vert. 2009. "Group Lasso with Overlap and Graph Lasso." In *Proceedings of the 26th Annual International Conference on Machine Learning - ICML '09*, 1–8. ACM Press.
<https://doi.org/10.1145/1553374.1553431>.
- Tay, J. Kenneth, Nima Aghaeepour, Trevor Hastie, and Robert Tibshirani. 2020. "Feature-Weighted Elastic Net: Using 'Features of Features' for Better Prediction." *arXiv:2006.01395 [Cs, Stat]*, June. <http://arxiv.org/abs/2006.01395>.
- Zou, Hui, and Trevor Hastie. 2005. "Regularization and Variable Selection via the Elastic Net." *Journal of the Royal Statistical Society. Series B (Statistical Methodology)* 67 (2): 301–20.
<https://www.jstor.org/stable/3647580>.