

A Large-Scale Neutral Comparison Study of Survival Models

Burk, L.^{1,2,3,4} Zobolas, J.⁵ Bischl, B.^{2,4} Bender, A.^{2,4} Wright, M. N.^{1,3} Lang, M.⁶ Sonabend, R.^{7,8}

¹Leibniz Institute for Prevention Research and Epidemiology – BIPS

²LMU Munich ³University of Bremen

⁴Munich Center for Machine Learning (MCML)

⁵University of Oslo ⁶TU Dortmund

⁷OSPO Now ⁸Imperial College, London

Biometric Colloquium — March 1st, 2024

Introduction



1

- There are many survival learners (“models”) to choose from

Introduction



1

- There are many survival learners (“models”) to choose from
- Advantages and Disadvantages often unclear, specific to setting

Introduction



1

- There are many survival learners (“models”) to choose from
- Advantages and Disadvantages often unclear, specific to setting
- Various comparisons exist in literature

Introduction



1

- There are many survival learners (“models”) to choose from
- Advantages and Disadvantages often unclear, specific to setting
- Various comparisons exist in literature
- Limited scope (learners, tasks, evaluation measures)

Introduction



1

- There are many survival learners (“models”) to choose from
- Advantages and Disadvantages often unclear, specific to setting
- Various comparisons exist in literature
- Limited scope (learners, tasks, evaluation measures)
- Focus on individual / new method \Rightarrow no neutral comparison

Introduction



1

- There are many survival learners (“models”) to choose from
- Advantages and Disadvantages often unclear, specific to setting
- Various comparisons exist in literature
- Limited scope (learners, tasks, evaluation measures)
- Focus on individual / new method \Rightarrow no neutral comparison
- No (or limited) quantitative comparison

Introduction



1

- There are many survival learners (“models”) to choose from
- Advantages and Disadvantages often unclear, specific to setting
- Various comparisons exist in literature
- Limited scope (learners, tasks, evaluation measures)
- Focus on individual / new method \Rightarrow no neutral comparison
- No (or limited) quantitative comparison

Introduction



1

- There are many survival learners (“models”) to choose from
- Advantages and Disadvantages often unclear, specific to setting
- Various comparisons exist in literature
- Limited scope (learners, tasks, evaluation measures)
- Focus on individual / new method \Rightarrow no neutral comparison
- No (or limited) quantitative comparison

\Rightarrow Needs **comprehensive comparison!**

Quick Summary



- 32 tasks
- 18 learners
- 2 tuning measures
- 9 evaluation measures

Quick Summary



2

- 32 tasks
- 18 learners
- 2 tuning measures
- 9 evaluation measures

- **Large-scale** \Rightarrow Generalizability
- **Neutral** \Rightarrow Fair comparison

Quick Summary



2

- 32 tasks
- 18 learners
- 2 tuning measures
- 9 evaluation measures

- **Large-scale** \Rightarrow Generalizability
- **Neutral** \Rightarrow Fair comparison

\Rightarrow The **largest survival benchmark** to date as far as we know

The “Standard Setting”:

- Single-event outcome: $\delta_i \in \{0, 1\}$
- Low-dimensional: $2 \leq p < n$
- No time-varying covariates
- Right-censoring only
- At least 100 observed events

Tasks



4

32 tasks collected from R packages on CRAN

	Minimum	q25%	Median	q75%	Maximum
N	137	446	820	2378	52410
p	2	4	5	7	25
Observed Events	101	194	323	699	5616
Cens. %	6	32	48	74	95

Learners



5

18 learners implemented in R and available via the `mlr3`¹ framework

- **Baseline:** Kaplan-Meier & Nelson-Aalen

¹Lang et al. (2019)

Learners



5

18 learners implemented in R and available via the `mlr3`¹ framework

- **Baseline:** Kaplan-Meier & Nelson-Aalen
- **Classical:** Cox, penalized, parametric

¹Lang et al. (2019)

Learners



5

18 learners implemented in R and available via the `mlr3`¹ framework

- **Baseline:** Kaplan-Meier & Nelson-Aalen
- **Classical:** Cox, penalized, parametric
- **Trees:** Individual and ensembles thereof

¹Lang et al. (2019)

Learners



5

18 learners implemented in R and available via the `mlr3`¹ framework

- **Baseline:** Kaplan-Meier & Nelson-Aalen
- **Classical:** Cox, penalized, parametric
- **Trees:** Individual and ensembles thereof
- **Boosting:** Gradient- and likelihood-based

¹Lang et al. (2019)

Learners



5

18 learners implemented in R and available via the `mlr3`¹ framework

- **Baseline:** Kaplan-Meier & Nelson-Aalen
- **Classical:** Cox, penalized, parametric
- **Trees:** Individual and ensembles thereof
- **Boosting:** Gradient- and likelihood-based
- **Other:** Akritas, SVM

¹Lang et al. (2019)

List of Learners (Baseline, Classical)



6

Name	Abbreviation	Package
Kaplan-Meier	KM	survival
Nelson-Aalen	NA	survival
Cox Regression	CPH	survival
Penalized Cox Regression (L1, L2)	GLM	glmnet
Penalized Cox Regression (L1, L2)	Pen	penalized
Parametric (AFT)	Par	survival
Flexible Parametric Splines	Flex	flexsurv
Akritis	AK	survivalmodels
Survival SVM	SSVM	survivalsvm

List of Learners (Trees, Boosting)



7

Name	Abbreviation	Package
Decison Tree	RRT	rpart
Random Survival Forest	RFSRC	randomForestSRC
Random Survival Forest	RAN	ranger
Conditional Inference Forest	CIF	partykit
Oblique RSF	ORSF	aorsf
Model-Based Boosting	MBO	mboost
Likelihood-Based Boosting	CoxB	CoxBoost
Gradient Boosting (Cox objective)	XGB Cox	xgboost
Gradient Boosting (AFT objective)	XGB AFT	xgboost

Tuning



8

- Tuning spaces discussed with learner authors

Tuning



8

- Tuning spaces discussed with learner authors
- **Resampling:** Nested cross-validation (5-fold outer, 3-fold inner)

Tuning



8

- Tuning spaces discussed with learner authors
- **Resampling:** Nested cross-validation (5-fold outer, 3-fold inner)
- **Strategy:** Random Search

Tuning



8

- Tuning spaces discussed with learner authors
- **Resampling:** Nested cross-validation (5-fold outer, 3-fold inner)
- **Strategy:** Random Search
- **Budget:** Tuning stopped if **either** is reached

Tuning



8

- Tuning spaces discussed with learner authors
- **Resampling:** Nested cross-validation (5-fold outer, 3-fold inner)
- **Strategy:** Random Search
- **Budget:** Tuning stopped if **either** is reached
 1. Number of evaluations: $n_{\text{evals}} = n_{\text{parameters}} \times 50$

Tuning



8

- Tuning spaces discussed with learner authors
- **Resampling:** Nested cross-validation (5-fold outer, 3-fold inner)
- **Strategy:** Random Search
- **Budget:** Tuning stopped if **either** is reached
 1. Number of evaluations: $n_{\text{evals}} = n_{\text{parameters}} \times 50$
 2. Tuning time of 150 hours ($6\frac{1}{4}$ days)

Evaluation



9

- Main Results:

Evaluation



9

- Main Results:
 - Friedman rank sum tests

Evaluation



9

- Main Results:
 - Friedman rank sum tests
 - Critical difference plots² based on Bonferroni-Dunn tests

²Demšar (2006)

Evaluation



9

- Main Results:
 - Friedman rank sum tests
 - Critical difference plots² based on Bonferroni-Dunn tests
- 3 types of metrics: Discrimination, Calibration, [Scoring Rules](#)

²Demšar (2006)

Evaluation



9

- Main Results:
 - Friedman rank sum tests
 - Critical difference plots² based on Bonferroni-Dunn tests
- 3 types of metrics: Discrimination, Calibration, [Scoring Rules](#)
- Tuned on 2 different measures

²Demšar (2006)

Evaluation



9


- Main Results:
 - Friedman rank sum tests
 - Critical difference plots² based on Bonferroni-Dunn tests
- 3 types of metrics: Discrimination, Calibration, [Scoring Rules](#)
- Tuned on 2 different measures
 - Harrell's C (Discrimination)

²Demšar (2006)

- Main Results:
 - Friedman rank sum tests
 - Critical difference plots² based on Bonferroni-Dunn tests
- 3 types of metrics: Discrimination, Calibration, [Scoring Rules](#)
- Tuned on 2 different measures
 - Harrell's C (Discrimination)
 - Right-Censored Log Loss (Scoring Rule)

²Demšar (2006)


Boxplot (Harrel's C, higher is better)




Boxplot (IBS, lower is better)




11




Boxplot (IBS, truncated)



Critical Difference: Bonferroni-Dunn (Harrell's C)



Critical Difference: Bonferroni-Dunn (IBS/RCLL)



Closing Remarks



15

- Only computationally feasible due to resources of ARCC³

³Advanced Research Computing Center, Beartooth Computing Environment, University of Wyoming.

Closing Remarks



15

- Only computationally feasible due to resources of ARCC³
 - Sequential runtime: ≈ 18 years

³Advanced Research Computing Center, Beartooth Computing Environment, University of Wyoming.

Closing Remarks



15

- Only computationally feasible due to resources of ARCC³
 - Sequential runtime: ≈ 18 years
 - Effective runtime: 32 days

³Advanced Research Computing Center, Beartooth Computing Environment, University of Wyoming.

Closing Remarks



15

- Only computationally feasible due to resources of ARCC³
 - Sequential runtime: \approx 18 years
 - Effective runtime: 32 days
- Experimental design is not perfect, but it was **possible** to conduct

³Advanced Research Computing Center, Beartooth Computing Environment, University of Wyoming.

Closing Remarks



15

- Only computationally feasible due to resources of ARCC³
 - Sequential runtime: \approx 18 years
 - Effective runtime: 32 days
- Experimental design is not perfect, but it was possible to conduct
- Results still need processing, checking, ...

³Advanced Research Computing Center, Beartooth Computing Environment, University of Wyoming.

Closing Remarks



15

- Only computationally feasible due to resources of ARCC³
 - Sequential runtime: \approx 18 years
 - Effective runtime: 32 days
- Experimental design is not perfect, but it was **possible** to conduct
- Results still need processing, checking, ...
- **Preliminary conclusion:** Cox regression — hard to beat since 1972!

³Advanced Research Computing Center, Beartooth Computing Environment, University of Wyoming.

Closing Remarks



15

- Only computationally feasible due to resources of ARCC³
 - Sequential runtime: \approx 18 years
 - Effective runtime: 32 days
- Experimental design is not perfect, but it was **possible** to conduct
- Results still need processing, checking, ...
- **Preliminary conclusion:** Cox regression — hard to beat since 1972!
- The “standard setting” \approx the “do you need ML?”-setting

³Advanced Research Computing Center, Beartooth Computing Environment, University of Wyoming.

Thank you for your attention!



www.leibniz-bips.de/en

Contact

Lukas Burk

Leibniz Institute for Prevention Research
and Epidemiology – BIPS

Achterstraße 30
D-28359 Bremen



burk@leibniz-bips.de



References I



17

-  Demšar, Janez (2006). “Statistical comparisons of classifiers over multiple data sets”. In: [Journal of Machine learning research 7.1](#), pp. 1–30.
-  Lang, Michel et al. (2019). “mlr3: A modern object-oriented machine learning framework in R”. In: [Journal of Open Source Software 4.44](#), p. 1903. DOI: [10.21105/joss.01903](#).