

Insert here your thesis' task.



**FACULTY
OF INFORMATION
TECHNOLOGY
CTU IN PRAGUE**

Bachelor's thesis

Probabilistic algorithms for computing the LTS estimate

Martin Jenč

Department of Applied Mathematics
Supervisor: Ing. Karel Klouda, Ph.D.

March 7, 2019

Acknowledgements

THANKS to everybody

Declaration

I hereby declare that the presented thesis is my own work and that I have cited all sources of information in accordance with the Guideline for adhering to ethical principles when elaborating an academic final thesis.

I acknowledge that my thesis is subject to the rights and obligations stipulated by the Act No. 121/2000 Coll., the Copyright Act, as amended, in particular that the Czech Technical University in Prague has the right to conclude a license agreement on the utilization of this thesis as school work under the provisions of Article 60(1) of the Act.

In Prague on March 7, 2019

.....

Czech Technical University in Prague

Faculty of Information Technology

© 2019 Martin Jenč. All rights reserved.

This thesis is school work as defined by Copyright Act of the Czech Republic. It has been submitted at Czech Technical University in Prague, Faculty of Information Technology. The thesis is protected by the Copyright Act and its usage without author's permission is prohibited (with exceptions defined by the Copyright Act).

Citation of this thesis

Jenč, Martin. *Probabilistic algorithms for computing the LTS estimate*. Bachelor's thesis. Czech Technical University in Prague, Faculty of Information Technology, 2019.

Abstrakt

V několika větách shrňte obsah a přínos této práce v českém jazyce.

Klíčová slova LTS odhad, lineární regrese, optimalizace, nejmenších čtverců, usekané čtverce, metoda nejmenších čtverců, outliers

Abstract

The least trimmed squares (LTS) method is a robust version of the classical method of least squares used to find an estimate of coefficients in the linear regression model. Computing the LTS estimate is known to be NP-hard, and hence suboptimal probabilistic algorithms are used in practice.

Keywords LTS, linear regression, robust estimator, least trimmed squares, ordinary least squares, outliers, outliers detection

Contents

| | |
|------------------------------------|-----------|
| Introduction | 1 |
| 1 Linear Regression | 3 |
| 1.1 Description | 3 |
| 1.2 Computation | 3 |
| 1.3 Downfalls | 3 |
| 2 The Least trimmed squares | 5 |
| 3 Algorithms | 7 |
| 3.1 FAST-LTS | 7 |
| 3.2 Exact algorithm | 10 |
| 3.3 Feasible solution | 10 |
| 3.4 MMEA | 10 |
| 3.5 Branch and bound | 10 |
| 3.6 Adding row | 10 |
| 4 Experiments | 11 |
| 4.1 Data | 11 |
| 4.2 Results | 11 |
| 4.3 Outlier detection | 11 |
| Conclusion | 13 |
| Bibliography | 15 |
| A Datasets | 17 |
| B Contents of enclosed CD | 19 |

List of Figures

Introduction

Linear Regression

- 1.1 Description
- 1.2 Computation
- 1.3 Downfalls

The Least trimmed squares

2.0.1 Objective function

2.0.1.1 Problems

Algorithms

3.1 FAST-LTS

In this section we will introduce FAST-LTS algorithm[1]. It is, as well as in other cases, iterative algorithm. We will discuss all main components of the algorithm starting with its core idea called concentration step which authors simply call C-step.

3.1.1 C-step

We will show that from existing LTS estimate $\hat{\mathbf{w}}_{old}$ we can construct new LTS estimate $\hat{\mathbf{w}}_{new}$ which objective function is less or equal to the old one. Based on this property we will be able to create sequence of LTS estimates which will lead to better results.

Theorem 1. Consider dataset consisting of $\mathbf{x}_1, \mathbf{x}_2 \dots, \mathbf{x}_n$ explanatory variables where $\mathbf{x}_i \in \mathbb{R}^p, \forall \mathbf{x}_i = (x_1^i, x_2^i, \dots, x_p^i)$ where $x_1^i = 1$ and its corresponding y_1, y_2, \dots, y_n response variables. Let's also have $\hat{\mathbf{w}}_0 \in \mathbb{R}^p$ any p-dimensional vector and $H_0 = \{h_i; h_i \in \mathbb{Z}, 1 \leq h_i \leq n\}, |H_0| = h$. Let's now mark $RSS(\hat{\mathbf{w}}_0) = \sum_{i \in H_0} (r_0(i))^2$ where $r_0(i) = y_i - (w_1^0 x_1^i + w_2^0 x_2^i + \dots + w_p^0 x_p^i)$. Let's take $\hat{n} = \{1, 2, \dots, n\}$ and mark $\pi : \hat{n} \rightarrow \hat{n}$ permutation of \hat{n} such that $|r_0(\pi(1))| \leq |r_0(\pi(2))| \leq \dots \leq |r_0(\pi(n))|$ and mark $H_1 = \{\pi(1), \pi(2), \dots, \pi(h)\}$ set of h indexes corresponding to h smallest absolute residuals $r_0(i)$. Finally take $\hat{\mathbf{w}}_1^{OLS(H_1)}$ ordinary least squares fit on H_1 subset of observations and its corresponding $RSS(\hat{\mathbf{w}}_1) = \sum_{i \in H_1} (r_1(i))^2$ sum of least squares. Then

$$RSS(\hat{\mathbf{w}}_1) \leq RSS(\hat{\mathbf{w}}_0) \quad (3.1)$$

Proof. Because we take h observations with smallest absolute residuals r_0 , then for sure $\sum_{i \in H_1} (r_0(i))^2 \leq \sum_{i \in H_0} (r_0(i))^2 = RSS(\hat{\mathbf{w}}_0)$. When we take into account that Ordinary least squares fit OLS_{H_1} minimize objective function of H_1 subset of observations, then for sure $RSS(\hat{\mathbf{w}}_1) = \sum_{i \in H_1} (r_1(i))^2 \leq$

3. ALGORITHMS

$\sum_{i \in H_1} (r_0(i))^2$. Together we get

$$RSS(\hat{\mathbf{w}}_1) = \sum_{i \in H_1} (r_1(i))^2 \leq \sum_{i \in H_1} (r_0(i))^2 \leq \sum_{i \in H_0} (r_0(i))^2 = RSS(\hat{\mathbf{w}}_0)$$

□

Corollary 2. Based on previous theorem, using some $\hat{\mathbf{w}}^{OLS(H_{old})}$ on H_{old} subset of observations we can construct H_{new} subset with corresponding $\hat{\mathbf{w}}^{OLS(H_{new})}$ such that $RSS(\hat{\mathbf{w}}^{OLS(H_{new})}) \leq RSS(\hat{\mathbf{w}}^{OLS(H_{old})})$. With this we can apply above theorem again on $\hat{\mathbf{w}}^{OLS(H_{new})}$ with H_{new} . This will lead to the iterative sequence of $RSS(\hat{\mathbf{w}}_{old}) \leq RSS(\hat{\mathbf{w}}_{new}) \leq \dots$. One step of this process is described by following pseudocode. Note that for C-step we actually need only $\hat{\mathbf{w}}$ without need of passing H .

Algorithm 1: C-step

Input: dataset consisting of $\mathbf{X} \in \mathbb{R}^{n \times p}$ and $\mathbf{y} \in \mathbb{R}^{n \times 1}$, $\hat{\mathbf{w}}_{old} \in \mathbb{R}^{p \times 1}$

Output: $\hat{\mathbf{w}}_{new}$, H_{new}

```

1  $R \leftarrow \emptyset$ ;
2 for  $i \leftarrow 1$  to  $n$  do
3    $R \leftarrow R \cup \{|y_i - \hat{\mathbf{w}}_{old} \mathbf{x}_i^T|\}$ ;
4 end
5  $H_{new} \leftarrow$  select set of  $h$  smallest absolute residuals from  $R$ ;
6  $\hat{\mathbf{w}}_{new} \leftarrow OLS(H_{new})$ ;
7 return  $\hat{\mathbf{w}}_{new}$ ,  $H_{new}$ ;

```

Observation 3. Time complexity of algorithm C-step 1 is same as time complexity as OLS. Thus $O(p^2n)$ **TODO**

Proof. In C-step we must compute n absolute residuals. Computation of one absolute residual consist of matrix multiplication of shapes $\times p$ and $pt \times 1$ that give us $\mathcal{O}(p)$. Rest is in constant time. So time of computation n residuals is $\mathcal{O}(np)$. Next we must select set of h smallest residuals which can be done in $\mathcal{O}(n)$ using modification of algorithm QuickSelect. reference: **TODO** Finally we must compute $\hat{\mathbf{w}}$ OLS estimate on h subset of data. Because h is linearly dependent on n , time complexity can be stated as follows. $\mathbf{A} = \mathbf{X}^T \mathbf{X} \sim \mathcal{O}(p^2n)$ and $\mathbf{B} = \mathbf{X}^T \mathbf{Y} \sim \mathcal{O}(pn)$ and $\mathbf{A}^{-1} \mathbf{B} \sim \mathcal{O}(p^3 + p^2)$. That give us $\mathcal{O}(p^2n + pn + p^3 + p^2n)$ which asymptotically dominates previous steps which time complexity is $\mathcal{O}(np + n)$.

TODO neni tedý casove narocnejši vynosobeni $\mathbf{X}^T \mathbf{X}$ nez inverze, kdyz bereme v uvahu $n \gg p$??? □

Observation 4.

Algorithm 8 is a greedy change-making algorithm (Slide 19 in Class Slides).

Algorithm 14 and Algorithm 13 will find the first duplicate element in a sequence of integers.

Input: A finite set $A = \{a_1, a_2, \dots, a_n\}$ of integers

Output: The largest element in the set

```
1  $max \leftarrow a_1$ 
2 for  $i \leftarrow 2$  to  $n$  do
3   if  $a_i > max$  then
4      $max \leftarrow a_i$ 
5   end
6 end
7 return  $max$ 
```

Input: A set $C = \{c_1, c_2, \dots, c_r\}$ of denominations of coins, where
 $c_i > c_2 > \dots > c_r$ and a positive number n

Output: A list of coins d_1, d_2, \dots, d_k , such that $\sum_{i=1}^k d_i = n$ and k is
minimized

```
1  $C \leftarrow \emptyset$ 
2 for  $i \leftarrow 1$  to  $r$  do
3   while  $n \geq c_i$  do
4      $C \leftarrow C \cup \{c_i\}$ 
5      $n \leftarrow n - c_i$ 
6   end
7 end
8 return  $C$ 
```

Input: A sequence of integers $\langle a_1, a_2, \dots, a_n \rangle$

Output: The index of first location with the same value as in a
previous location in the sequence

```
1  $location \leftarrow 0$ 
2  $i \leftarrow 2$ 
3 while  $i \leq n$  and  $location = 0$  do
4    $j \leftarrow 1$ 
5   while  $j < i$  and  $location = 0$  do
6     if  $a_i = a_j$  then
7        $location \leftarrow i$ 
8     else
9        $j \leftarrow j + 1$ 
10    end
11  end
12   $i \leftarrow i + 1$ 
13 end
14 return  $location$ 
```

3. ALGORITHMS

Input: A sequence of integers $\langle a_1, a_2, \dots, a_n \rangle$
Output: The index of first location with the same value as in a previous location in the sequence

```
1 location  $\leftarrow$  0
2 i  $\leftarrow$  2
3 while  $i \leq n \wedge \textit{location} = 0$  do
4   j  $\leftarrow$  1
5   while  $j < i \wedge \textit{location} = 0$  do
6     if  $a_i = a_j$  then location  $\leftarrow$  i
7   else j  $\leftarrow$  j + 1
8   end
9   i  $\leftarrow$  i + 1
10 end
11 return location
```

In this section we will describe FAST-LTS algorithm and its main properties. The main idea of this algorithm is based on the fact that from one approximation of the algorithm we can compute another which can have lower objective function. TA DAAAAAAAAAAAAAAAAAAAAA Theorem 1: [2] Let w_0 ... w_p be the LTS estimate. for each data sample we can compute $\|y - wx\|$

3.2 Exact algorithm

3.3 Feasible solution

3.4 MMEA

3.5 Branch and bound

3.6 Adding row

Experiments

- 4.1 Data
- 4.2 Results
- 4.3 Outlier detection

Conclusion

Bibliography

- [1] Rousseeuw, P. J.; Driessen, K. V. An Algorithm for Positive-Breakdown Regression Based on Concentration Steps. In *Data Analysis: Scientific Modeling and Practical Application*, edited by M. S. W. Gaul, O. Opitz, Springer-Verlag Berlin Heidelberg, 2000, pp. 335–346.
- [2] Rybicka, J. *LaTeX pro začátečníky*. Brno: Konvoj, third edition, ISBN 80-7302-049-1.

Datasets

GUI Graphical user interface

XML Extensible markup language

Contents of enclosed CD

| | | |
|--|------------------|---|
| | readme.txt | the file with CD contents description |
| | exe | the directory with executables |
| | src | the directory of source codes |
| | wbdcm | implementation sources |
| | thesis | the directory of \LaTeX source codes of the thesis |
| | text | the thesis text directory |
| | thesis.pdf | the thesis text in PDF format |
| | thesis.ps | the thesis text in PS format |