

Insert here your thesis' task.





**FACULTY  
OF INFORMATION  
TECHNOLOGY  
CTU IN PRAGUE**

Bachelor's thesis

# **Probabilistic algorithms for computing the LTS estimate**

***Martin Jenč***

Department of Applied Mathematics  
Supervisor: Ing. Karel Klouda, Ph.D.

March 5, 2019



---

# Acknowledgements

THANKS to everybody



---

## Declaration

I hereby declare that the presented thesis is my own work and that I have cited all sources of information in accordance with the Guideline for adhering to ethical principles when elaborating an academic final thesis.

I acknowledge that my thesis is subject to the rights and obligations stipulated by the Act No. 121/2000 Coll., the Copyright Act, as amended, in particular that the Czech Technical University in Prague has the right to conclude a license agreement on the utilization of this thesis as school work under the provisions of Article 60(1) of the Act.

In Prague on March 5, 2019

.....

Czech Technical University in Prague

Faculty of Information Technology

© 2019 Martin Jenč. All rights reserved.

*This thesis is school work as defined by Copyright Act of the Czech Republic. It has been submitted at Czech Technical University in Prague, Faculty of Information Technology. The thesis is protected by the Copyright Act and its usage without author's permission is prohibited (with exceptions defined by the Copyright Act).*

### **Citation of this thesis**

Jenč, Martin. *Probabilistic algorithms for computing the LTS estimate*. Bachelor's thesis. Czech Technical University in Prague, Faculty of Information Technology, 2019.



---

## Abstrakt

V několika větách shrňte obsah a přínos této práce v českém jazyce.

**Klíčová slova** LTS odhad, lineární regrese, optimalizace, nejmenších čtverců, usekané čtverce, metoda nejmenších čtverců, outliers

---

## Abstract

The least trimmed squares (LTS) method is a robust version of the classical method of least squares used to find an estimate of coefficients in the linear regression model. Computing the LTS estimate is known to be NP-hard, and hence suboptimal probabilistic algorithms are used in practice.

**Keywords** LTS, linear regression, robust estimator, least trimmed squares, ordinary least squares, outliers, outliers detection



---

# Contents

<b>Introduction</b>	<b>1</b>
<b>1 Linear Regression</b>	<b>3</b>
1.1 Description . . . . .	3
1.2 Computation . . . . .	3
1.3 Downfalls . . . . .	3
<b>2 The Least trimmed squares</b>	<b>5</b>
<b>3 Algorithms</b>	<b>7</b>
3.1 FAST-LTS . . . . .	7
3.2 Exact algorithm . . . . .	9
3.3 Feasible solution . . . . .	9
3.4 MMEA . . . . .	9
3.5 Branch and bound . . . . .	9
3.6 Adding row . . . . .	9
<b>4 Experiments</b>	<b>11</b>
4.1 Data . . . . .	11
4.2 Results . . . . .	11
4.3 Outlier detection . . . . .	11
<b>Conclusion</b>	<b>13</b>
<b>Bibliography</b>	<b>15</b>
<b>A Datasets</b>	<b>17</b>
<b>B Contents of enclosed CD</b>	<b>19</b>



---

## List of Figures



---

# Introduction





# Linear Regression

- 1.1 Description
- 1.2 Computation
- 1.3 Downfalls



# **The Least trimmed squares**

## **2.0.1 Objective function**

### **2.0.1.1 Problems**



# Algorithms

## 3.1 FAST-LTS

In this section we'll introduce FAST-LTS algorithm[1]. It's, as well as in other cases, iterative algorithm. We'll discuss all main components of the algorithm starting with its core idea called concentration step which authors simply calls C-step.

### 3.1.1 C-step

We'll show that from existing LTS estimate  $\hat{\mathbf{w}}_{old}$  we can construct new LTS estimate  $\hat{\mathbf{w}}_{new}$  which objective function is less or equal to old one. Based on this property we'll be able to create sequence of LTS estimates which will lead to better results.

**Theorem 1:** Let's have dataset consisting of  $x_1, x_2 \dots x_n$  explanatory variables and its corresponding  $y_1, y_2 \dots y_n$  response variables where  $x_i$

**Theorem 2:** Buď  $f$  funkce, která má [1] po  $\mathbb{R}$  spojitou derivaci na intervalu  $\langle -T, T \rangle$ . Potom Fourierova řada funkce  $f$  na intervalu  $(-T, T)$  konverguje na celém množině  $\mathbb{R}$ . Označme  $F$  její součtovou funkci, tzn.

$$F(x) := \frac{a_0}{2} + \sum_{k=1}^{\infty} a_k \cos \frac{k\pi x}{T} + b_k \sin \frac{k\pi x}{T}, \quad \forall x \in \mathbb{R},$$

kde posloupnosti  $(a_n)_{n=0}^{\infty}$  a  $(b_n)_{n=1}^{\infty}$  jsou určeny vztahy . Potom platí:

- (i)  $F$  je periodická funkce s periodou  $2T$ .
- (ii)  $F(x) = \frac{f(x+) + f(x-)}{2}$  pro každé  $x \in (-T, T)$ .
- (iii)  $F(T) = F(-T) = \frac{f(-T+) + f(T-)}{2}$ .

*Proof.* NeuvĚdĚme. □

**Data:** this text

**Result:** how to write algorithm with L<sup>A</sup>T<sub>E</sub>X2<sub>ε</sub>

```
1 initialization;
2 while not at end of this document do
3   read current;
4   if understand then
5     go to next section;
6     current section becomes this one;
7   else
8     go back to the beginning of current section;
9   end
10 end
```

In this section we'll describe FAST-LTS algorithm and it's main properties. The main idea of this algorithm is based on the fact that from one approximation of the algorithm we can compute another which can have lower objective function. TA DAAAAAAAAAAAAAAAAAAAA Thorem 1: [2] Let  $w_0 \dots w_p$  be the LTS estimate. for each data sample we can compute  $\|y - wx\|$

Hlavní myšlenka tohoto algoritmu spočívá ve faktu,

V ĚdeskĚ variantĚ naleznete Ěablony v souborech pojmenovanĚ · ch ve formĚtu prĚce.kĚsdovĚnĚj.tex. Typ prĚce mĚřĚ"e bĚ · t:

**BP** bakalĚĚskĚ prĚce,

**DP** diplomovĚ (magisterskĚ) prĚce.

**UTF-8** kĚsdovĚnĚj Unicode,

**ISO-8859-2** latin2,

**Windows-1250** znakovĚ sada 1250 Windows.

V pĚĚĚpadĚ nejistoty ohlednĚ kĚsdovĚnĚj doporuĚDujeme nĚsle-  
dujĚncĚj postup:

1. V opaĚDnĚm pĚĚĚpadĚ postupujte dĚle podle toho, jakĚ · op-  
eraĚDnĚj systĚm pouĚ"ĚvĚte:
  - v pĚĚĚpadĚ Windows pouĚ"ijte Ěablonu pro kĚsdovĚnĚj  
Windows-1250,
  - jinak zkuste pouĚ"Ět Ěablonu pro kĚsdovĚnĚj ISO-8859-2.

V anglickĚ variantĚ jsou Ěablony pojmenovanĚ podle typu prĚce,  
moĚnosti jsou:

**bachelors** bakalĚĚskĚ prĚce,

**masters** diplomovĚ (magisterskĚ) prĚce.

**3.2 Exact algorithm**

**3.3 Feasible solution**

**3.4 MMEA**

**3.5 Branch and bound**

**3.6 Adding row**





# Experiments

4.1 Data

4.2 Results

4.3 Outlier detection



---

## Conclusion



---

## Bibliography

- [1] Rousseeuw, P. J.; Driessen, K. V. An Algorithm for Positive-Breakdown Regression Based on Concentration Steps. In *Data Analysis: Scientific Modeling and Practical Application*, edited by M. S. W. Gaul, O. Opitz, Springer-Verlag Berlin Heidelberg, 2000, pp. 335–346.
- [2] Rybicka, J. *LaTeX pro začátečníky*. Brno: Konvoj, third edition, ISBN 80-7302-049-1.



## Datasets

**GUI** Graphical user interface

**XML** Extensible markup language





## Contents of enclosed CD

	readme.txt .....	the file with CD contents description
	exe .....	the directory with executables
	src .....	the directory of source codes
	wbdcm .....	implementation sources
	thesis .....	the directory of $\text{\LaTeX}$ source codes of the thesis
	text .....	the thesis text directory
	thesis.pdf .....	the thesis text in PDF format
	thesis.ps .....	the thesis text in PS format