

# Package ‘diaQTL’

December 2, 2025

**Title** QTL Analysis in Diallel Populations

**Version** 1.11

**Author** Jeffrey B. Endelman and Rodrigo R. Amadeu

**Maintainer** Jeffrey Endelman <endelman@wisc.edu>

**Description** QTL analysis of diploid and autotetraploid diallel populations. Phenotypes are regressed on genotype probabilities, and the regression coefficients are random effects.

**Depends** R (>= 4.0)

**License** GPL-3 + file LICENSE

**LazyData** true

**RoxygenNote** 7.3.2

**Roxygen** list(markdown = TRUE)

**Encoding** UTF-8

**Imports** BGLR, ggplot2, methods, coda, Matrix, scam, parallel, arrangements, tidyr, ggfittext, ggden-  
dro, labeling, rlang, reshape2, plyr

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

## Contents

BayesCI . . . . .	2
convert_mappoly . . . . .	3
convert_onemap . . . . .	3
convert_polyorigin . . . . .	4
convert_rabbit . . . . .	5
diallel_geno-class . . . . .	5
diallel_geno_pheno-class . . . . .	6
DIC_thresh . . . . .	6
diplo_freq . . . . .	7
diplo_get . . . . .	8
F1codes . . . . .	8
fine_map . . . . .	9
fitQTL . . . . .	10
get_map . . . . .	12
haplo_cluster . . . . .	13
haplo_freq . . . . .	13

haplo_get . . . . .	14
haplo_match . . . . .	15
haplo_plot . . . . .	15
IBDmat . . . . .	16
phased_parents . . . . .	17
read_data . . . . .	18
S1codes . . . . .	19
scan1 . . . . .	20
scan1_permute . . . . .	21
scan1_summary . . . . .	22
set_params . . . . .	23
<b>Index</b>	<b>25</b>

---

BayesCI	<i>Bayesian Credible Interval for QTL position</i>
---------	--

---

**Description**

Bayesian Credible Interval for QTL position

**Usage**

BayesCI(scan1\_data, data, chrom, CI.prob = 0.9)

**Arguments**

scan1_data	data frame output from scan1
data	variable of class diallel_geno_pheno
chrom	chromosome
CI.prob	probability for the credible interval

**Details**

Parameter CI.prob sets the probability for the Bayesian credible interval (e.g., 0.90, 0.95) using the profile likelihood (posterior mean).

**Value**

first and last marker in the CI

**Examples**

```
## Not run:
  BayesCI(scan1_example, diallel_example, chrom="10", CI.prob=0.9)

## End(Not run)
```

---

convert_mappoly	<i>Generate diaQTL input files from MAPpoly</i>
-----------------	---

---

### Description

Generates diaQTL input files from the output of calc\_genoprob or calc\_genoprob\_error in the MAPpoly package. The argument data is a list containing the results for each linkage group. Map distances are rounded to 0.01 cM, and genotype probabilities are rounded to three decimal places.

### Usage

```
convert_mappoly(data, ploidy, outstem = "")
```

### Arguments

data	list of variables of class mappoly.genoprob (one for each linkage group)
ploidy	Either 2 or 4
outstem	prefix for the pedigree and genotype files for diaQTL

### Examples

```
## Not run:
# see MAPpoly tutorial for details on its functions
MAP <- list(lg1, lg2, lg3) #list of linkage groups
genoprob <- vector("list", 3) #if 3 linkage groups
for(i in 1:length(genoprob))
  genoprob[[i]] <- mappoly::calc_genoprob_error(input.map = MAP[[i]], error = 0.05)
convert_mappoly(genoprob, ploidy=4)

## End(Not run)
```

---

convert_onemap	<i>Generate diaQTL input files from OneMap</i>
----------------	--

---

### Description

Generate diaQTL input files from 'onemap\_progeny\_haplotypes' object class of OneMap R package (version >2.2.0)

### Usage

```
convert_onemap(data, digits = 4, outstem = "")
```

### Arguments

data	onemap_progeny_haplotypes object class
digits	how many rounding digits for the probabilities output (default=4)
outstem	prefix for the pedigree and genotype files for diaQTL

## Examples

```
## Not run:
map <- list(LG1_final, LG2_final)
progeny_haplot <- onemap::progeny_haplotypes(map,
                                             most_likely = FALSE,
                                             ind = "all")

convert_onemap(progeny_haplot)

## End(Not run)
```

---

convert_polyorigin	Create diaQTL input files from PolyOrigin output
--------------------	--

---

## Description

Create diaQTL input files from PolyOrigin output

## Usage

```
convert_polyorigin(
  filename,
  mapfile = NULL,
  remove.outliers = TRUE,
  outstem = ""
)
```

## Arguments

filename	Name of polyancestry file
mapfile	Optional name of CSV file containing the physical map (marker, chrom, bp)
remove.outliers	Should offspring flagged as outliers be removed (default is TRUE)
outstem	prefix for output filenames

## Details

Creates the pedigree (diaQTL\_pedfile.csv) and genotype (diaQTL\_genofile.csv) input files needed for [read\\_data](#) from the polyancestry output file generated by the PolyOrigin software. PolyOrigin outputs a genetic map in cM. To add a physical map in bp, use the option mapfile. The input file needed for [phased\\_parents](#) (diaQTL\_parents.csv) is also created.

---

convert_rabbit	<i>Generate diaQTL input files from RABBIT MagicReconstruct</i>
----------------	---

---

### Description

Generate diaQTL input files from RABBIT MagicReconstruct

### Usage

```
convert_rabbit(rabbit.outfile, ped.file, outstem)
```

### Arguments

rabbit.outfile	name of RABBIT output file
ped.file	name of RABBIT pedigree file
outstem	prefix for the pedigree and genotype files for diaQTL

---

diallel geno-class	<i>S4 class with genotype data</i>
--------------------	------------------------------------

---

### Description

S4 class with genotype data

### Slots

ploidy Either 2 or 4

input matrix of character strings from the genotype input file, one row per bin

Xa list of matrices (one for each offspring) with the expected haplotype dosage (rows) for each parental origin genotype (columns)

dominance Maximum dosage stored in slot geno. Integer 1-4 indicating 1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance.

X.GCA Incidence matrix for GCA effects

map data frame with marker,chrom, position (cM and/or bp) and bin

geno list of length equal to the number of marker bins. Each element is a list of length dominance. The elements in the nested list are sparse matrices with dimensions (id x effects), containing the dosage for each effect.

A list with the additive relationship matrix for each chromosome

---

diallel\_geno\_pheno-class

*S4 class with genotype and phenotype data*


---

### Description

S4 class with genotype and phenotype data

### Slots

ploidy Either 2 or 4

input matrix of character strings from the genotype input file

Xa list of matrices with the expected haplotype dosage (rows) for each parental origin genotype (columns)

dominance Maximum dosage stored in slot geno. Integer 1-4 indicating 1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance.

X.GCA Incidence matrix for GCA effects

map data frame with marker,chrom, position (cM and/or bp) and bin

geno list of length equal to the number of marker bins. Each element is a list of length dominance. The elements in the nested list are sparse matrices with dimensions (id x effects), containing the dosage for each effect.

A list with the additive relationship matrix for each chromosome

pheno data frame of phenotypes

X incidence matrix for fixed effects

Z incidence matrix for individuals

---

DIC\_thresh

*delta DIC thresholds for scan1*


---

### Description

delta DIC thresholds for scan1

### Usage

```
DIC_thresh(genome.size, num.parents, ploidy, alpha = 0.05, dominance = 1)
```

### Arguments

genome.size Genome size in Morgans (not centiMorgans)

num.parents Number of parents (2 to 10)

ploidy 2 or 4

alpha significance level (0.01, 0.05, 0.10, or 0.20)

dominance 1 (additive) or 2 (digenic dominance)

**Details**

Thresholds to control the genome-wide false positive rate at alpha were determined for half-diallel mating designs with up to 10 parents.

**Value**

-deltaDIC threshold

**Examples**

```
## Not run:
  DIC_thresh(genome.size=10,
             num.parents=4,
             ploidy=4,
             dominance=1,
             alpha=0.05)

## End(Not run)
```

---

diplo_freq	<i>Diplotype frequencies</i>
------------	------------------------------

---

**Description**

Plot the frequency of individuals with diplotype dosage above a threshold

**Usage**

```
diplo_freq(data, diplotypes, dosage, position, chrom = NULL)
```

**Arguments**

data	Variable inheriting from class <code>diallel_geno</code>
diplotypes	Names of diplotypes
dosage	Dosage threshold
position	Either "cM" or "bp" for plotting
chrom	Names of chromosomes (default is all)

**Details**

Useful for visualizing selection in selfed populations.

**Value**

List containing

**result** Data frame with the map and frequency

**plot** ggplot object

---

diplo_get	<i>Dosage of parental diplotypes</i>
-----------	--------------------------------------

---

### Description

Dosage of parental diplotypes

### Usage

```
diplo_get(data, marker = NULL, id = NULL)
```

### Arguments

data	Variable inheriting from class <code>diallel_geno</code>
marker	Name of marker
id	Name of individual

### Details

Function can be used to get parental diplotype dosage estimates at a single marker for all individuals (in which case `id` should be `NULL`) or for a single individual for all markers (in which case `marker` should be `NULL`)

### Value

Matrix of (id or markers) x parental diplotypes

### Examples

```
## Not run:
diplo_example = diplo_get(data = diallel_example,
                          marker = "solcap_snp_c2_25522")
diplo_example = diplo_get(data = diallel_example,
                          id = "W15263-8R")

## End(Not run)
```

---

F1codes	<i>Genotype codes for F1 populations</i>
---------	--

---

### Description

Character vector with the 100 possible tetraploid genotypes for a F1 population. Maternal haplotypes are denoted 1,2,3,4 and paternal haplotypes 5,6,7,8.

### Usage

```
data(F1codes)
```

**Format**

character vector

---

fine_map	<i>Visualize haplotype switches for fine mapping</i>
----------	--

---

**Description**

Visualize haplotype switches for fine mapping

**Usage**

```
fine_map(data, haplotype, interval, trait = NULL, marker = NULL)
```

**Arguments**

data	Variable inheriting from class <code>diallel_geno</code>
haplotype	Name of parental haplotype
interval	2-vector with marker names
trait	Name of trait to plot (optional)
marker	Optional, marker to indicate with dashed line

**Details**

Function returns graphic for all individuals with a haplotype switch (defined as change in dosage from 0 to  $\geq 1$  or vice versa) for haplotype within interval. If trait is included, the trait values for each individual are displayed on the right side. The function requires map positions in bp to be included in data.

**Value**

ggplot2 variable

**Examples**

```
## Not run:
fine_map(data = diallel_example,
  haplotype = "W6511-1R.2",
  interval = c("solcap_snp_c2_40766", "solcap_snp_c1_15225"))

fine_map(data = diallel_example,
  haplotype = "W6511-1R.2",
  interval = c("solcap_snp_c2_40766", "solcap_snp_c1_15225"),
  marker = "solcap_snp_c2_25522")

## End(Not run)
```

fitQTL

*Fit multiple QTL model***Description**

Fit multiple QTL model

**Usage**

```
fitQTL(
  data,
  trait,
  qtl,
  epistasis = NULL,
  polygenic = FALSE,
  params = list(burnIn = 100, nIter = 5000),
  CI.prob = 0.9
)
```

**Arguments**

<code>data</code>	variable of class <code>diallel_geno_pheno</code>
<code>trait</code>	name of trait
<code>qtl</code>	data frame, see Details
<code>epistasis</code>	optional data frame, see Details
<code>polygenic</code>	TRUE/FALSE whether to include additive polygenic effect
<code>params</code>	list containing the number of burn-in ( <code>burnIn</code> ) and total iterations ( <code>nIter</code> )
<code>CI.prob</code>	probability for Bayesian credible interval

**Details**

Argument `qtl` is a data frame with columns `marker` and `dominance` to specify the marker name and highest order effect (1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance). All effects up to the value in `dominance` are included. Optional argument `epistasis` is a data frame with columns `marker1` and `marker2`, where each row specifies an additive x additive epistatic interaction. The number of burn-in and total iterations in `params` can be estimated using [set\\_params](#). Parameter `CI.prob` sets the probability (e.g., 0.90, 0.95) for the Bayesian credible interval for the estimated effects (to disable plotting of the CI, use `CI.prob=NULL`).

**Value**

List containing

**deltaDIC** DIC relative to model with GCA but no QTL effects**resid** residuals**var** matrix with proportion of variance for the effects**effects** list with two matrices, additive and digenic, with markers on the rows and effects on the columns**plots** list of ggplot objects, one for each marker, containing elements additive and digenic. The digenic plot has digenic effects above the diagonal and the sum of additive and digenic effects below the diagonal.

## Examples

```
## Not run:
## getting minimum burnIn and nIter for one qtl
set_params(data = diallel_example,
            trait = "tuber_shape",
            q = 0.05,
            r = 0.025,
            qtl = data.frame(marker="solcap_snp_c2_25522", dominance=2),
            polygenic = TRUE)

## additive effects
fit1 <- fitQTL(data = diallel_example,
               trait = "tuber_shape",
               params = list(burnIn=100, nIter=5000),
               qtl = data.frame(marker="solcap_snp_c2_25522", dominance=1),
               CI.prob = 0.9)

## additive + digenic dominance effects
fit2 <- fitQTL(data = diallel_example,
               trait = "tuber_shape",
               params = list(burnIn=100, nIter=5000),
               qtl = data.frame(marker="solcap_snp_c2_25522", dominance=2),
               CI.prob=0.9)

## getting minimum burnIn and nIter for two qtl with epistasis
set_params(data = diallel_example,
            trait = "tuber_shape",
            q = 0.05,
            r = 0.025,
            qtl = data.frame(marker=c("PotVar0099535", "solcap_snp_c2_25522"),
                             dominance=c(2,1)),
            epistasis = data.frame(marker1="solcap_snp_c2_25522", marker2="PotVar0099535"),
            polygenic = TRUE)

## additive + digenic dominance effects for both QTL
fit3 <- fitQTL(data = diallel_example, trait = "tuber_shape",
               params = list(burnIn=100, nIter=5000),
               qtl = data.frame(marker=c("PotVar0099535", "solcap_snp_c2_25522"),
                             dominance=c(2,2)),
               polygenic = TRUE, CI.prob = 0.9)

## additive + digenic dominance effects for both QTL + their epistatic effects
fit4 <- fitQTL(data = diallel_example, trait = "tuber_shape",
               params = list(burnIn=100, nIter=5000),
               qtl = data.frame(marker=c("PotVar0099535", "solcap_snp_c2_25522"),
                             dominance=c(2,2)),
               epistasis = data.frame(marker1="solcap_snp_c2_25522", marker2="PotVar0099535"),
               polygenic = TRUE, CI.prob = 0.9)

## additive + digenic dominance effects for three QTL + all their epistatic effects
fit5 <- fitQTL(data = diallel_example, trait = "tuber_shape",
               params = list(burnIn=100, nIter=5000),
               qtl = data.frame(marker=c("PotVar0099535",
                                         "solcap_snp_c1_6427",
                                         "solcap_snp_c2_25522"),
                             dominance=c(2,2,2)),
```

```

epistasis = data.frame(marker1=c("solcap_snp_c2_25522",
                                "solcap_snp_c2_25522",
                                "PotVar0099535"),
                        marker2=c("PotVar0099535",
                                "solcap_snp_c1_6427",
                                "solcap_snp_c1_6427")),
polygenic = TRUE, CI.prob = 0.9)

## End(Not run)

```

get\_map

*Get map summary from diallel\_geno object***Description**

Get map summary from diallel\_geno object

**Usage**

```
get_map(data, summary = TRUE)
```

**Arguments**

data	Variable inheriting from class <code>diallel_geno</code>
summary	logical, if TRUE (default) returns total sizes per chromosome, if FALSE returns the map

**Value**

data frame with map summary or the map

**Examples**

```

## Not run:
  get_map(diallel_example)

## End(Not run)

```

---

haplo_cluster	<i>Cluster parental haplotypes</i>
---------------	------------------------------------

---

**Description**

Cluster parental haplotypes

**Usage**

```
haplo_cluster(filename, marker, haplotypes = NULL)
```

**Arguments**

filename	Name of diaQTL_parents input file
marker	Either target marker or marker interval (see Details).
haplotypes	Vector of haplotype names (default is all)

**Details**

The argument marker can be either a single marker or vector of two markers. If a single marker, the function finds the smallest interval containing that marker such that the phased SNP haplotypes are all unique. If two markers are provided, that interval is used. Clustering utilizes hclust(method="average"). See also [phased\\_parents](#) for an additional visualization tool.

**Value**

List containing

**haplo** Data frame of haplotypes

**dendro** Dendrogram

---

haplo_freq	<i>Haplotype frequencies</i>
------------	------------------------------

---

**Description**

Plots the frequency of individuals with haplotype dosage above a threshold

**Usage**

```
haplo_freq(
  data,
  haplotypes,
  dosage,
  id = NULL,
  position = "cM",
  chrom = NULL,
  markers = NULL
)
```

**Arguments**

data	Variable inheriting from class <code>diallel_geno</code>
haplotypes	Names of haplotypes
dosage	Dosage threshold
id	Vector of id names (default is entire population)
position	Either "cM" (default) or "bp" for plotting
chrom	Names of chromosomes (default is all)
markers	Optional, markers to indicate with dashed line. Only available when plotting a single chromosome.

**Details**

Useful for visualizing selection in selfed populations. For multiple chromosomes, each haplotype is shown in its own panel using `facet_wrap`. For one chromosome, the haplotypes are shown on the same set of axes.

**Value**

List containing

- result** Data frame with the map and frequency
- plot** ggplot object

---

haplo_get	<i>Dosage of parental haplotypes</i>
-----------	--------------------------------------

---

**Description**

Dosage of parental haplotypes

**Usage**

```
haplo_get(data, marker = NULL, id = NULL)
```

**Arguments**

data	Variable inheriting from class <code>diallel_geno</code>
marker	Name of marker
id	Name of individual

**Details**

Function can be used to get parental haplotype dosage estimates at a single marker for all individuals (in which case `id` should be `NULL`) or for a single individual for all markers (in which case `marker` should be `NULL`)

**Value**

Matrix of (id or markers) x parental haplotypes

**Examples**

```
## Not run:
haplo_example = haplo_get(data = diallel_example,
                          marker = "solcap_snp_c2_25522")
haplo_example = haplo_get(data = diallel_example,
                          id = "W15263-8R")

## End(Not run)
```

---

haplo_match	<i>Match up parental haplotypes</i>
-------------	-------------------------------------

---

**Description**

Match up parental haplotypes

**Usage**

```
haplo_match(file1, file2, chrom)
```

**Arguments**

file1	name of CSV phased parent file
file2	name of CSV phased parent file
chrom	chromosome

**Details**

Designed to match up parental haplotypes between two phased parent files based on genetic distance. In the plots, the haplotypes in file1 are numbered 1-4, and those in file2 are numbered 5-8.

**Value**

Data frame with results

---

haplo_plot	<i>Plot parental haplotype dosage</i>
------------	---------------------------------------

---

**Description**

Plot parental haplotype dosages across the chromosome for one individual

**Usage**

```
haplo_plot(data, id, chrom, position = "cM", markers = NULL)
```

**Arguments**

data	Variable inheriting from class <code>diallel_geno</code>
id	Name of individual
chrom	Name of chromosome
position	Either "cM" (default) or "bp"
markers	Optional, markers to indicate with dashed line

**Details**

For "cM" plotting, only one marker per bin is displayed. For "bp" plotting, all markers are included.

**Value**

ggplot object

**Examples**

```
## Not run:
haplo_plot(data = diallel_example,
            id = "W15263-8R",
            chrom = 10)

haplo_plot(data = diallel_example,
            id = "W15263-8R",
            chrom = 10,
            marker = "solcap_snp_c2_25522")

## End(Not run)
```

---

IBDmat

*Realized IBD relationship*


---

**Description**

Calculates realized relationship matrices from founder genotype probabilities

**Usage**

```
IBDmat(
  data,
  dominance = 1,
  epistasis = FALSE,
  spacing = 1,
  chrom = NULL,
  n.core = 1
)
```

**Arguments**

data	Variable inheriting from class <code>diallel_geno</code>
dominance	One of 1,2,3,4
epistasis	TRUE/FALSE
spacing	spacing between marker bins, in cM
chrom	Optional, vector of chromosome names to include
n.core	number of cores for parallel execution

**Details**

Parameter dominance refers to 1 = additive, 2 = digenic, 3 = trigenic, 4 = quadrigenic. Can specify to use only a subset of the chromosomes (by default, all chromosomes are used). If epistasis is TRUE, then dominance must be 1 (additive x additive epistasis). Only pairs of markers on different chromosomes are used for epistasis.

**Value**

Relationship matrix

**Examples**

```
## Not run:
IBD_example = IBDmat(data = diallel_example, dominance=1) #additive
IBD_example = IBDmat(data = diallel_example, dominance=2) #digenic dominance
IBD_example = IBDmat(data = diallel_example, epistasis=TRUE) #additive x additive epistasis

## End(Not run)
```

---

phased\_parents

*Visualize phased SNPs of parents*


---

**Description**

Visualize phased SNPs of parents

**Usage**

```
phased_parents(filename, interval, markers, parents)
```

**Arguments**

filename	Name of CSV input file
interval	Vector of length 2 with the first and last marker names
markers	Vector of marker names to plot
parents	Vector of parent names to plot

Details

The solid circles in the figure represent the allele counted by dosage.

Value

ggplot2 object

---

read_data	<i>Read data files</i>
-----------	------------------------

---

Description

Reads genotype, pedigree, and phenotype data files

Usage

```
read_data(  
  genofile,  
  ploidy = 4,  
  pedfile,  
  phenofile = NULL,  
  fixed = NULL,  
  bin.markers = TRUE,  
  dominance = NULL,  
  n.core = 1  
)
```

Arguments

genofile	File with map and genotype probabilities
ploidy	Either 2 or 4
pedfile	File with pedigree data (id,parent1,parent2)
phenofile	File with phenotype data (optional)
fixed	If there are fixed effects, this is a character vector of "factor" or "numeric"
bin.markers	TRUE/FALSE whether to bin markers with the same cM position
dominance	Maximum value of dominance that will be used for analysis. Default = ploidy.
n.core	Number of cores for parallel execution

Details

The first 3 columns of the genotype file should be the genetic map (labeled marker, chrom, cM), and a fourth column for a reference genome position (labeled bp) can also be included. The map is followed by the members of the population. The genotype data for each marker x individual combination is a string with the format "state|state|state...=>prob|prob|prob...", where "state" refers to the genotype state and "prob" is the genotype probability in decimal format. Only states with nonzero probabilities need to be listed. The encoding for the states in tetraploids is described in the documentation for the F1codes and S1codes datasets that come with the package. For diploids, there are 4 F1 genotype codes, 1,2,3,4, which correspond to haplotype combinations 1-3,1-4,2-3,2-4, respectively; the S1 genotype codes 1,2,3 correspond to 1-1,1-2,2-2, respectively.

For the phenotype file, first column is id, followed by traits, and then any fixed effects. Pass a character vector for the function argument "fixed" to specify whether each effect is a factor or numeric covariate. The number of traits is deduced based on the number of columns. Binary traits must be coded N/Y and are converted to 0/1 internally for analysis by probit regression. Missing data in the phenotype file should be coded as NA.

The parameter dominance specifies the maximum value of dominance that can be used in subsequent analysis: 1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance. The default is dominance = ploidy, which allows the full range of dominance models in functions such as [scan1](#) and [fitQTL](#), but this requires the most RAM. Output files from the BGLR package are stored in a folder named 'tmp' in the current directory.

### Value

Variable of class [diallel\\_geno](#) if phenofile is NULL, otherwise [diallel\\_geno\\_pheno](#)

### Examples

```
## Not run:
## Get the location of raw csv files examples
genocsv = system.file( "vignette_data", "potato_geno.csv", package = "diaQTL" )
pedcsv = system.file( "vignette_data", "potato_ped.csv", package = "diaQTL" )
phenocsv = system.file( "vignette_data", "potato_pheno.csv", package = "diaQTL" )

## Check their location in the system
print(genocsv)
print(pedcsv)
print(phenocsv)

## Load them in R
diallel_example <- read_data(genofile = genocsv,
                             ploidy = 4,
                             pedfile = pedcsv,
                             phenofile = phenocsv)

## End(Not run)
```

---

S1codes

*Genotype codes for S1 populations*

---

### Description

Character vector with the 35 possible tetraploid genotypes for a S1 population. Haplotypes are denoted 1,2,3,4.

### Usage

```
data(S1codes)
```

### Format

character vector

---

scan1	<i>Single QTL scan</i>
-------	------------------------

---

## Description

Performs a linear regression for each position in the map.

## Usage

```
scan1(
  data,
  trait,
  params = list(burnIn = 100, nIter = 1000),
  dominance = 1,
  covariate = NULL,
  chrom = NULL,
  n.core = 1
)
```

## Arguments

data	variable of class <a href="#">diallel_geno_pheno</a>
trait	name of trait
params	list containing burnIn and nIter
dominance	maximum dominance for the scan, see Details
covariate	optional, to include markers as covariates. See Details
chrom	names of chromosomes to scan (default is all)
n.core	number of cores for parallel execution

## Details

Parameter dominance has possible values of 1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance. MCMC params can be estimated using [set\\_params](#). Optional argument covariate is used to include other markers in the model during the scan, which can improve statistical power with multiple QTL. It is a data frame with three columns: marker = name of the marker, dominance = 1 to 4, and epistasis = TRUE/FALSE. Function returns deltaDIC = DIC for the QTL model relative to null model with only GCA effects for the parents, as well as LL = posterior mean of the log-likelihood, which is used by [BayesCI](#).

## Value

Data frame containing the map, LL, and deltaDIC.

## Examples

```
## Not run:
## getting minimum burnIn and nIter
set_params(data = diallel_example,
           trait = "tuber_shape")
```

```

scan1_example <- scan1(data = diallel_example,
                      chrom = "10",
                      trait = "tuber_shape",
                      params = list(burnIn=60,nIter=600))

## End(Not run)

```

---

scan1_permute	<i>Permutation test for scan1</i>
---------------	-----------------------------------

---

## Description

Permutation test for scan1

## Usage

```

scan1_permute(
  data,
  trait,
  params,
  n.permute = 1000,
  chrom = NULL,
  dominance = 1,
  covariate = NULL,
  n.core = 1
)

```

## Arguments

data	Variable of class <a href="#">diallel_geno_pheno</a>
trait	Name of trait
params	List containing burnIn and nIter
n.permute	Number of permutations
chrom	Names of chromosomes to scan (default is all)
dominance	Dominance degree (1-4)
covariate	optional, to include markers as covariates. See Details.
n.core	Number of cores for parallel execution

## Value

Data frame with maximum LOD and minimum deltaDIC for each iteration

## Examples

```

## Not run:
set_params(data = diallel_example,
           trait = "tuber_shape")

ans1_permut <- scan1_permute(data = diallel_example,

```

```

chrom = 10,
trait = "tuber_shape",
params = list(burnIn=60,nIter=600),
n.permute = 100)

## computing permutation threshold for alpha=0.05
quantile(ans1_permut$min_deltaDIC, 0.05)

## End(Not run)

```

---

scan1_summary	<i>Summary of scan1 result</i>
---------------	--------------------------------

---

## Description

Summary of scan1 result

## Usage

```
scan1_summary(scan1_data, thresh = NULL, chrom = NULL, position = "cM")
```

## Arguments

scan1_data	output from scan1
thresh	optional -deltaDIC threshold for plotting
chrom	optional, subset of chromosomes to plot
position	Either "cM" (default) or "bp"

## Details

Plots the "score" (-deltaDIC) for each marker vs. genome position. The thresh argument should be a positive number.

## Value

List containing

**peaks** data frame of markers with the highest score on each chromosome

**plot** ggplot object

## Examples

```

## Not run:
scan1_summary( scan1_example )
scan1_summary( scan1_example, chrom = "10" )
scan1_summary( scan1_example, chrom = c( "10", "12" ) )
scan1_summary( scan1_example, chrom = "10", thresh = 20)

## End(Not run)

```

set\_params

*Determine number of iterations for MCMC***Description**

Determine number of iterations for MCMC

**Usage**

```
set_params(
  data,
  trait,
  qtl = NULL,
  epistasis = NULL,
  polygenic = FALSE,
  q = 0.5,
  r = 0.1,
  nIter = 2000
)
```

**Arguments**

data	variable of class <a href="#">diallel_geno_pheno</a>
trait	name of trait
qtl	optional data frame, see Examples
epistasis	optional data frame, see Example
polygenic	TRUE/FALSE whether to include additive polygenic effect
q	quantile to estimate
r	tolerance for quantile
nIter	number of iterations

**Details**

Determines the burn-in and total number of iterations using the Raftery and Lewis diagnostic from R package coda, based on a 95% probability that the estimate for quantile  $q$  of the additive genetic variance is within the interval  $(q-r, q+r)$ . If marker=NULL (default), the first marker of each chromosome is analyzed, and the largest value across this set is returned. Parameter dominance specifies which genetic model (1 = additive, 2 = digenic dominance, 3 = trigenic dominance, 4 = quadrigenic dominance) to use when determining the number of iterations, but this parameter must still be specified when calling functions such as [scan1](#) or [fitQTL](#). The default values of  $q=0.5$  and  $r=0.1$  are recommended for [scan1](#) based on the idea of estimating the posterior mean. For estimating the 90% Bayesian CI with [fitQTL](#), suggested values are  $q=0.05$ ,  $r=0.025$ . Parameter nIter sets the number of iterations used to apply the Raftery and Lewis diagnostic; the default value is 2000, and if a larger number is needed, an error will be generated with this information.

**Value**

matrix showing the number of burn-in and total iterations for the genetic variances in the model

**Examples**

```

## Not run:
# Parameters for scan1
par1 <- set_params(data = diallel_example,
                  trait = "tuber_shape",
                  q=0.5,
                  r=0.1)

# Parameters for fitQTL (specify the position)
set_params(data = diallel_example,
          trait = "tuber_shape",
          q=0.05,
          r=0.025,
          qtl=data.frame(marker="solcap_snp_c2_25522",dominance=2))

# Parameters for fitQTL (specify the position) with polygenic effects
set_params(data = diallel_example,
          trait = "tuber_shape",
          q=0.05,
          r=0.025,
          qtl=data.frame(marker="solcap_snp_c2_25522",dominance=2),
          polygenic=TRUE)

# Parameters for fitQTL with 2 QTLs
set_params(data = diallel_example,
          trait = "tuber_shape",
          q=0.05,
          r=0.025,
          qtl=data.frame(marker=c("solcap_snp_c2_25522", "solcap_snp_c2_14750"),dominance=c(2,1)))

# Parameters for fitQTL with epistasis
set_params(data = diallel_example,
          trait = "tuber_shape",
          q=0.05,
          r=0.025,
          epistasis = data.frame(marker1="solcap_snp_c2_25522",marker2="solcap_snp_c2_14750"),
          qtl=data.frame(marker=c("solcap_snp_c2_25522", "solcap_snp_c2_14750"),dominance=c(2,1)))

## End(Not run)

```

# Index

## \* datasets

F1codes, [8](#)

S1codes, [19](#)

BayesCI, [2](#), [20](#)

convert\_mappoly, [3](#)

convert\_onemap, [3](#)

convert\_polyorigin, [4](#)

convert\_rabbit, [5](#)

diallel\_genotype, [7–9](#), [12](#), [14](#), [16](#), [17](#), [19](#)

diallel\_genotype (diallel\_genotype-class), [5](#)

diallel\_genotype-class, [5](#)

diallel\_genotype\_phenotype, [2](#), [10](#), [19–21](#), [23](#)

diallel\_genotype\_phenotype  
(diallel\_genotype\_phenotype-class), [6](#)

diallel\_genotype\_phenotype-class, [6](#)

DIC\_thresh, [6](#)

diplo\_freq, [7](#)

diplo\_get, [8](#)

F1codes, [8](#)

fine\_map, [9](#)

fitQTL, [10](#), [19](#), [23](#)

get\_map, [12](#)

haplo\_cluster, [13](#)

haplo\_freq, [13](#)

haplo\_get, [14](#)

haplo\_match, [15](#)

haplo\_plot, [15](#)

IBDmat, [16](#)

phased\_parents, [4](#), [13](#), [17](#)

read\_data, [4](#), [18](#)

S1codes, [19](#)

scan1, [19](#), [20](#), [23](#)

scan1\_permute, [21](#)

scan1\_summary, [22](#)

set\_params, [10](#), [20](#), [23](#)