



CALIFA Electronics & DAQ

Tobias Jenegger

CALIFA WG meeting
18.10.2024

Preamplifier Status

DAQ status – Exp S091/118 in 2024

DAQ Upgrade

Documentation Status

Supported by BMBF 05P15WOFNA and 05P19WOFN1.


The results presented here are based on the experiment s444/s473, which was performed at the beam line/infrastructure Cave C at the GSI Helmholtzzentrum für Schwerionenforschung, Darmstadt (Germany) in the frame of FAIR Phase-0.

TUM Members:

Roman Gernhäuser, Philipp Klenze, Mrunmoy Jena, Gero Bollmann, Tobias Jenegger

CEPA	iPhos	Ring 4	Ring 3	Ring 2	Ring 1	
	DR 48 30/450	SR 30/300	SR 30/300			→ CEPA: 8 x 3/45pC DR Preamplifier
	DR 30/300	SR 30/300	SR 30/300			→ iPhos: mixed configuration: 8 x 3/45pC DR PA 8 x 3/30pC DR PA
	DR 48 30/450	SR 30/300	SR 30/300			→ Barrel – Ring 4&3: 32 x 3/30pC SR PA
	DR 30/300	SR 30/300	SR 30/300			→ Backward Barrel (BB) – Ring 2: Bricolage of 16 PA (SR/DR)
	DR 48 30/450	SR 30/300	SR 30/300			<u>What is still needed?</u>
	DR 30/300	SR 30/300	SR 30/300			32 x SR 3/30pC PA for BB (the current BB are spares for different applications)
	DR 48 30/450	SR 30/300	SR 30/300			Modifications: 12x DR → to low noise input and 3/45pC range 32x SR → lower noise input stage
	DR 30/300	SR 30/300	SR 30/300			


CEPA	iPhos	Ring 4	Ring 3	Ring 2	Ring 1
DR 48 30/450		SR 30/300	SR 30/300		
	DR 30/300	SR 30/300	SR 30/300		
DR 48 30/450		SR 30/300	SR 30/300		
	DR 30/300	SR 30/300	SR 30/300		
DR 48 30/450		SR 30/300	SR 30/300		
	DR 30/300	SR 30/300	SR 30/300		
DR 48 30/450		SR 30/300	SR 30/300		
	DR 30/300	SR 30/300	SR 30/300		



CEPA iPhos Ring 4 Ring 3 Ring 2 Ring 1

DR 48 30/450	SR 30/300	SR 30/300	SR 30/300	SR 30/300
DR 30/300	SR 30/300	SR 30/300	SR 30/300	SR 30/300
DR 48 30/450	SR 30/300	SR 30/300	SR 30/300	SR 30/300
DR 30/300	SR 30/300	SR 30/300	SR 30/300	SR 30/300
DR 48 30/450	SR 30/300	SR 30/300	SR 30/300	SR 30/300
DR 30/300	SR 30/300	SR 30/300	SR 30/300	SR 30/300
DR 48 30/450	SR 30/300	SR 30/300	SR 30/300	SR 30/300
DR 30/300	SR 30/300	SR 30/300	SR 30/300	SR 30/300

Overlord



PC1:
108 (MES)
109 (WIX)

PC0:
75 (MES)
76 (WIX)

Hardware ordered:

- ✓ 5 Exploders (as spares)
- ✓ 16+ FEBEX cards
- ✓ 1 NIM Power Crate

Cables:

- ✓ 48+ SR data cables (BB)
- ✓ 16+ LV power cables (BB)

DAQ Testing:

- ✗ Running sub-system with all three crates was not possible, unstable

This needs to be tested and debugged!

- Info about FAB, FEBEX, PAs, Exploders on google spreadsheet:
<https://docs.google.com/spreadsheets/d/1TqvITK1xVxb5rhWSQISCEBDzf2x7GS8RSkM1WwQoNJM/edit?hl=de&pli=1&gid=1790449867#gid=1790449867>
- Info califa-cabling-slowcontrol:
<https://elog.gsi.de/land/CALIFA/375>
- More (more or less structured) info on our wiki:
<https://wiki.r3b-nustar.de/detectors/califa/overview>

General Questions:

- Do we have an overview what we have documented and what not?
 - Where and how should the documentations be stored?
 - lifetime (how long will google spreadsheets be available (for free) ?)
 - accessibility (read and write permissions?)
- } Maybe open question for R3BWeek-Paris, since all detector groups should be affected