



SURGE SHORE

POWERTECH LLP

PRODUCT CATALOGUE

INDUSTRIAL ELECTRIC MOTORS & AUTOMATION

- 3-Phase & 1-Phase Induction Motors (C.I. & Aluminium Body)
- Flange Mounted Motors (B5 / B14 Gearbox Series)
- Diamond Special High-RPM Polishing Motors
- High Discharge Immersion Coolant Pumps
- Self-Priming Heavy Duty Centrifugal Pumps
- Custom Electrical Panels & Servo Stabilizers

POWERING INDUSTRY

Driving Performance

SURGE SHORE POWERTECH LLP

Rajkot, Gujarat, India | IS 325 / IS 996 / IEC 60034 Certified
www.surgeshorepowertech.com | surgeshorepowertech@gmail.com



SURGE SHORETM

An ISO 9001:2015 certified company

POWERTECH LLP

07+

Years Of Experience

20+

Employees & Engineers

125+

Industrial Clients

CORE PHILOSOPHY

“We believe that Innovation is the driving force behind progress.”

Delivering precision-engineered 1-Phase & 3-Phase motors built for continuous duty cycles.

Since 2020...

A Leading Manufacturer of High-Quality Pumps and Motors

Surge Shore Powertech LLP is a premier engineering concern specializing in the design, tooling, and mass fabrication of high-torque, energy-efficient electric induction motors and industrial pumps.

With a legacy of excellence spanning over 06+ years since 2020, we have established ourselves as a trusted partner in the machinery manufacturing ecosystem across Gujarat and all over India.

Our commitment to continuous innovation, precision CNC engineering, and uncompromising customer satisfaction makes us the preferred OEM vendor for machine tool builders, agricultural equipment fabricators, and turnkey processing plants.

100% Electrolytic Copper

Class F (155°C) thermal insulation margin for 24/7 continuous duty S1

Dynamic Computer Balancing

ISO 1940 Grade G2.5 dual-plane balancing eliminates rotor vibrations.

EN8E High Tensile Shafts

Ground alloy steel shafts precision machined to micrometer tolerance.

High Voltage Breakdown Tested

Every unit passes 2.0 kV dielectric high-pot and locked-rotor tests.

Quality and Certifications

Surge Shore is committed to delivering motors of the highest quality. We adhere to international quality standards and hold IS 325 / IS 996 / IEC 60034 certifications to demonstrate our commitment to excellence.

Vision

We believe that innovation is the driving force behind progress. We are dedicated to pushing the boundaries of what's possible, continually seeking new solutions, and embracing change with open arms.

Mission

Our mission is to design and produce the most efficient & reliable 1-Phase & 3-Phase Induction motors in the industry. We are dedicated to driving technological advancements & sustainability.

Our Product Range

Induction Motors (C.I. Body)	0.25 HP to 10 HP IS 325 Heavy Cast Iron
Induction Motors (Aluminum)	0.25 HP to 3.0 HP High Heat Dissipation
Diamond Special Motors	High RPM (2800 RPM) Low Vibration Run
Coolant Pumps (PCP Series)	0.10 HP to 0.25 HP Immersion Machine Tool
Self Priming Pumps (DELUX)	0.5 HP to 1.0 HP Forged Brass Impeller

Industries We Served

Manufacturing & CNC	Agriculture & Irrigation
HVAC & Air Handling	Water & Wastewater
Oil & Gas Fuel Transfer	Food & Dairy Processing
Renewable Energy Systems	Heat Treatment & Furnaces

INDUCTION MOTORS (C.I. Body)

Heavy-Duty Cast Iron Construction for Maximum Rigidity and Continuous S1 Duty

- 3-Phase
- 1-Phase

DESIGN & CONSTRUCTION HIGHLIGHTS	
Frame Sizes:	71 to 132M (Cast Iron Heavy Housing)
Power Rating:	0.25 HP to 10.0 HP (0.18 kW to 7.5 kW)
Rated Speeds:	2-Pole (2880 RPM) & 4-Pole (1440 RPM)
Winding Quality:	100% Dual Coated Electrolytic Grade Copper Wire
Thermal Insulation:	Class F (155°C) with Class B temperature rise limit
Stator Lamination:	Low-loss CRNO cold-rolled non-oriented electrical steel
Shaft Material:	Ground EN8E high-tensile carbon alloy steel
Bearings:	Deep groove C3 clearance pre-packed shielded ball bearings
Protection Class:	IP55 totally enclosed fan cooled (TEFC) standard
Voltage Supply:	415V ±10% 50Hz 3-Phase 230V ±10% 50Hz 1-Phase

HEAVY CAST IRON HOUSING — ZERO FLUTTER & EXCELLENT HEAT SINK

Cast Iron body motors exhibit superior vibration absorption dampening harmonics on heavy machine tools. Recommended for air compressors, punch presses, stone crushers, flour mills, and continuous pumps.

3-Phase Cast Iron Induction Motors Specification

Kw	Hp	Frame	Full Load RPM	Current (A)	Torque %	Start Cur %	Efficiency %	Power Factor
0.37	0.5	71	1400	1.15	210	320	72.7	0.65
0.55	0.75	80	1410	1.35	205	420	77.1	0.74
0.75	1.0	80	1415	1.90	210	430	79.6	0.73
1.10	1.5	90S	1410	2.50	210	455	81.4	0.81
1.50	2.0	90L	1420	3.20	215	460	82.8	0.82
2.20	3.0	100L	1425	4.70	200	490	84.3	0.79
3.70	5.0	112M	1435	7.50	210	540	86.3	0.81
5.50	7.5	132S	1450	10.8	160	500	83.9	0.85
7.50	10.0	132M	1450	14.3	165	510	85.3	0.86

1-Phase Cast Iron Induction Motors Specification

Kw	Hp	Frame	RPM	Current	Torque %	Start %	Eff %	PF	Run Cap	Start Cap
0.18	0.25	71	1450	2.0	270	475	63.0	0.80	15 uF	-
0.37	0.50	80	1440	3.4	275	500	65.0	0.79	15 uF	80-100 uF
0.37	0.50	90S	1445	5.0	300	500	65.0	0.79	15 uF	80-100 uF
0.75	1.00	90S	1450	6.7	250	475	72.0	0.75	15 uF	100-120 uF
0.75	1.00	100L	1450	7.0	275	475	72.0	0.75	8 uF	120-150 uF
1.10	1.50	90L	1455	7.8	240	525	75.0	0.85	25 uF	150-200 uF
1.10	1.50	100M	1455	8.0	255	530	75.0	0.85	25 uF	150-200 uF
1.50	2.00	100L	1460	9.1	250	500	79.0	0.91	30 uF	200-250 uF
1.50	2.00	112M	1460	9.1	255	500	79.0	0.90	36 uF	200-250 uF
2.20	3.00	112M	1460	12.5	275	550	81.0	0.95	30+30 uF	200-250 uF

FEATURES

- CI Casting body with high vibration damping
- High starting torque for instantaneous full-load start
- CRNO electrical grade stator laminations (low iron losses)
- High quality pre-packed shielded bearings (SKF / NBC equivalent)
- Motor shaft precision ground from EN8E alloy steel
- Electrolytic grade copper winding with thermal Class 'F' insulation

INDUCTION MOTORS (Aluminium Body)

High Thermal Conductivity & Compact Lightweight Construction for Clean-Room & Portable Machinery

Kw	Hp	Frame	Full Load RPM	Current (A)	Torque %	Start %	Eff %	Power Factor
0.18	0.25	63	1365	0.80	220	280	55.7	0.64
0.37	0.50	71	1400	1.15	210	320	72.7	0.65
0.55	0.75	80	1410	1.35	205	420	77.1	0.74
0.75	1.00	80	1415	1.90	210	430	79.6	0.73
1.10	1.50	90S	1410	2.50	210	455	81.4	0.81
1.50	2.00	90L	1420	3.20	215	460	82.8	0.82
2.20	3.00	100L	1425	4.70	200	490	84.3	0.79

KEY ENGINEERING ADVANTAGES

- 40% Lighter Weight:**Facilitates direct mounting on cantilever arms, packaging lines & portable tools.
- Superior Heat Dissipation:**Extruded fin design runs significantly cooler under continuous operations.
- Corrosion-Resistant Housing:**Smooth surface finish ideal for pharmaceutical, food packaging & chemical plants.
- Detachable Feet (Multi-Mount):**Permits easy re-orientation of terminal box to top, left, or right sides.
- IP55 Moisture & Dust Sealed:**Reinforced end-shield oil seals protect windings against airborne contaminants.

DIAMOND SPECIAL MOTORS

Ultra-High Precision Speeds (2800 RPM) for Diamond Cutting, Faceting, Gemstone & Tool Polishing

3-Phase Ratings

Kw	Hp	Frame	Full Load RPM	Current (A)	Torque %	Efficiency %	Power Factor
0.18	0.25	71	2790	0.79	200	60.4	0.49
0.24	0.33	80	2815	0.84	210	64.8	0.54
0.37	0.50	80	2840	0.90	225	73.8	0.84

1-Phase Ratings

Kw	Hp	Frame	Full Load RPM	Current (A)	Torque %	Efficiency %	Power Factor	Cap (uF)
0.18	0.25	71	2790	2.10	200	60.4	0.49	10 uF
0.24	0.33	80	2815	2.60	210	64.8	0.54	12 uF
0.37	0.50	80	2840	3.00	225	73.8	0.84	15 uF

PRECISION ROTOR BALANCING FOR ZERO FACET CHATTER

- Specially extended threaded / tapered nose shafts for gemstone scaife and diamond laps
- Ultra-low axial run-out under 5 microns ensures mirror facet cutting accuracy without scoring
- Custom high-speed bearings pre-loaded with synthetic grease to withstand continuous high RPM heat
- Rigid vibration-damped foot brackets engineered for Surat & Rajkot diamond processing benches

FLANGE MOUNTED MOTORS (B5 / B14)

Concentric Spigot Direct Bolt-On Drive for Gearboxes, Hydraulic Packs & Inline Blowers

DIRECT GEARBOX & PUMP COUPLING WITHOUT BELTS OR PULLEYS

Surge Shore Flange-Mounted (B5 / B14) Motors are engineered with a precision-machined circular front end-shield. This permits immediate direct spigot alignment to industrial worm reduction, helical, and planetary gearboxes, hydraulic powerpack pump bell-housings, and inline air blowers without flexible couplings or belt tensioners.

- B5 Large Flange: Outer through-holes for clearance bolt connection to large industrial machinery.
- B14 Face Flange: Compact inner bolt circle with precision-tapped holes for space-restricted gearboxes (NMRV).
- Zero Runout Guarantee: Eliminates angular misalignment, bearing fatigue, and gearbox seal leakage.
- Integrated Oil Seal Recess: Nitrile rubber rotary shaft oil seals prevent gear oil ingress into motor windings.

FLANGE PCD & SHAFT TOLERANCE (IS 2223 / IEC 60072-1)

Frame	HP Rating	B5 Flange PCD	B14 Face PCD	Shaft Dia (mm)	Keyway
63	0.25 HP	115 mm	75 mm	11 mm (j6)	4 x 4 mm
71	0.50 HP	130 mm	85 mm	14 mm (k6)	5 x 5 mm
80	0.75 - 1.0 HP	165 mm	100 mm	19 mm (j6)	6 x 6 mm
90S/L	1.5 - 2.0 HP	165 mm	115 mm	24 mm (j6)	8 x 7 mm
100L	3.0 HP	215 mm	130 mm	28 mm (j6)	8 x 7 mm
112M	5.0 HP	215 mm	130 mm	28 mm (j6)	8 x 7 mm

Flange Motors Technical Ratings & Electrical Characteristics

3-Phase 415V Flange Motor Series

Kw	Hp	Frame	Full Load RPM	Current	Torque %	Start %	Eff %	PF
0.37	0.5	71	1400	1.15	210	320	72.7	0.65
0.55	0.75	80	1410	1.35	205	420	77.1	0.74
0.75	1.0	80	1415	1.90	210	430	79.6	0.73
1.10	1.5	90S	1410	2.50	210	455	81.4	0.81
1.50	2.0	90L	1420	3.20	215	460	82.8	0.82
2.20	3.0	100L	1425	4.70	200	490	84.3	0.79
3.70	5.0	112M	1435	7.50	210	540	86.3	0.81
5.50	7.5	132S	1450	10.8	160	500	83.9	0.85
7.50	10.0	132M	1450	14.3	165	510	85.3	0.86

1-Phase 230V Flange Motor Series

Kw	Hp	Frame	RPM	Current	Torque %	Start %	Eff %	PF	Run Cap	Start Cap
0.18	0.25	71	1450	2.0	270	475	63.0	0.80	15 uF	-
0.37	0.50	80	1440	3.4	275	500	65.0	0.79	15 uF	80-100 uF
0.75	1.00	90S	1450	6.7	250	475	72.0	0.75	15 uF	100-120 uF
1.10	1.50	90L	1455	7.8	240	525	75.0	0.85	25 uF	150-200 uF
1.50	2.00	100L	1460	9.1	250	500	79.0	0.91	30 uF	200-250 uF
2.20	3.00	112M	1460	12.5	275	550	81.0	0.95	30+30 uF	200-250 uF

COOLANT PUMPS (PCP SERIES)

High-Flow Submerged Centrifugal Pumps for Machine Tool Lubrication & Continuous Chip Flushing

3-Phase Coolant Pump Models

Model Name	Power (kW)	Power (HP)	Head Range (mtr)	Discharge (LPM)	Pipe Size	Stem Lengths
PCP 15	0.10 kW	0.15 HP	4.0 Meters	50 LPM	1/2" BSP	120, 170, 220 mm
PCP 25	0.18 kW	0.25 HP	6.0 Meters	80 LPM	3/4" BSP	120, 170, 270 mm

FLUID COMPATIBILITY & APPLICATIONS

- Fluid Types: Water-soluble coolant emulsion, synthetic grinding fluid, semi-synthetic cutting oil & light lubricants.
- Impeller & Stem: Semi-open thermoplastic & cast bronze non-clogging impeller handles metallic swarf & fine chips.
- Motor Drive: High insulation Class F totally enclosed air-cooled motor positioned safely above tank fluid level.
- Used On: CNC Turning Centers, VMC Milling Centers, Deep Hole Drilling, Surface Grinders, Bandsaws, Lathes.
- Submersion Depths: Available in standardized immersion stem lengths: 120mm, 170mm, 220mm, and 270mm.

SELF PRIMING PUMPS (DELUX SERIES)

Heavy-Duty Monoblock Self-Priming Water Lifting Pumps with Forged Brass Impeller

Performance Specifications (3-Phase / 1-Phase)

Model Name	Power (kW)	Power (HP)	Suction x Delivery	Head Range (m)	Discharge (LPH)	TOP Protected
DELUX 50	0.37 kW	0.50 HP	1/2" x 1/2" (13x13 mm)	30 Meters	725 - 1900 LPH	Yes (Built-in)
DELUX 75	0.55 kW	0.75 HP	1" x 1" (25x25 mm)	40 Meters	700 - 2450 LPH	Yes (Built-in)
DELUX 100	0.75 kW	1.00 HP	1" x 1" (25x25 mm)	50 Meters	575 - 2625 LPH	Yes (Built-in)

FEATURES & CONSTRUCTION DETAILS

- **High Suction Lift Capability:** Rapid self-priming chamber pulls water up to 7.5 meters without manual foot-valve priming.
- **Forged Brass Impeller:** Zero cavitation erosion and corrosion resistance ensures consistent pressure year after year.
- **Thermal Overload Protector (TOP):** Built-in auto-reset thermal protector prevents motor burnout in abnormal voltage shifts.
- **Superior Carbon-Ceramic Mechanical Seal:** Prevents shaft scoring and guarantees zero water leakage into motor housing.
- **Ultra-Wide Operating Voltage:** Operates smoothly under Indian rural & urban supply fluctuations from 180V to 240V AC.



DIRECT MANUFACTURER PRICING & FACTORY DISPATCH

Surge Shore Powertech LLP welcomes OEM inquiries, machinery builder contracts, and authorized dealership applications across all states of India.

FACTORY & CORPORATE OFFICE

Company Name:	SURGE SHORE POWERTECH LLP
Works Address:	Plot No. 1/7, Copper Industrial Area,
Landmark:	Near Korat Chowk,
City & State:	Rajkot, Gujarat - 360022, India
Direct Hotline:	+91 91739 59019
WhatsApp Orders:	+91 91739 59019
Official Email:	surgeshorepowertech@gmail.com
Web Portal:	www.surgeshorepowertech.com
Working Hours:	Thu - Tue: 8:30 AM - 8:00 PM (Wednesday Weekly Off)