

Bootstrap 5.0

Lab 2 – Open Admin Page List

A practical guide to understanding the Bootstrap classes, utilities, icons, and custom CSS used in the supplied Admin Page screenshot/code.

Important: This page is more complex than Lab 1 because it combines Bootstrap with a large amount of custom CSS and Bootstrap Icons. The PDF separates those two so you know exactly what Bootstrap is doing.

Bootstrap reference: [Bootstrap 5.0 Documentation](#)

Icon reference: [Bootstrap Icons](#)

What this guide covers

- Every Bootstrap class actually used in the supplied HTML
- Bootstrap table, card, badge, form, select, spacing, display and alignment classes
- Bootstrap Icons classes used for search, menu, users, actions, stars, filter, etc.
- Which classes are Bootstrap and which are your own custom CSS classes
- How to build the page in a lab instead of blindly copying the final page
- Official Bootstrap 5.0 and Bootstrap Icons documentation links
- Version warning: your code loads Bootstrap 5.3.2, while your preferred study reference is Bootstrap 5.0

1. First understand what libraries this page uses

Your page is not Bootstrap-only. It loads two external CSS libraries and then adds a large custom `<style>` section.

1. Bootstrap CSS

[Bootstrap 5.0 documentation](#)

2. Bootstrap Icons

[Bootstrap Icons documentation](#)

3. Custom CSS

Classes such as **sidebar**, **brand**, **search**, **main**, **topbar**, **content**, **selected-row**, **star-blue**, **star-green**, **action**, **table-footer**, and **page-box** are NOT Bootstrap classes. They are created by your own CSS.

Version mismatch

The supplied code uses:

```
https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css
```

But your study/reference system is Bootstrap 5.0. If this is a college lab where the teacher expects Bootstrap 5.0, use the Bootstrap 5.0 CDN/reference consistently. The concepts and most classes in this page are shared, but you should not casually mix documentation versions.

Bootstrap 5.0 CDN reference: [Getting Started / Download](#)

2. Exact Bootstrap classes used in your code

This is the most important revision table. These are Bootstrap classes present in the supplied HTML; custom CSS classes and Bootstrap Icons are listed separately later.

Class	Type	Use in this page
form-control	Form	Styles the search input as a Bootstrap form control
form-control-sm	Form	Smaller search input
table	Table	Base Bootstrap table styling
table-hover	Table	Highlights rows on hover
mb-0	Spacing	Removes bottom margin from the table
align-middle	Vertical alignment	Vertically centers table cell content
badge	Badge	Creates small tag labels
bg-success	Background	Green tag background
bg-info	Background	Info/cyan tag background
form-check-input	Forms	Bootstrap checkbox styling
form-select	Forms	Bootstrap select/dropdown styling
form-select-sm	Forms	Smaller select control
d-inline	Display utility	Makes the select display inline
w-auto	Sizing utility	Width fits content instead of full width
fs-4	Typography utility	Makes the menu icon larger
text-muted	Text utility	Muted gray appearance for "List"

There are also Bootstrap classes used indirectly in the CSS? No. The custom CSS rules such as **.table th** and **.table td** target the Bootstrap table but are written by you.

3. Form controls: search, checkbox and entries select

Official documentation: [Forms](#) · [Form Controls](#) · [Checks & Radios](#) · [Select](#)

Search input

```
<input type="text"
class="form-control form-control-sm"
placeholder="Search">
```

form-control gives the input Bootstrap form styling. **form-control-sm** changes its size to small.

Checkbox

```
<input class="form-check-input" type="checkbox">
```

form-check-input is Bootstrap's class for the actual checkbox control. Your custom CSS then changes the checked colour to red.

Select

```
<select class="form-select form-select-sm d-inline w-auto">
<option>20</option>
</select>
```

Here four ideas are combined:

Class	Meaning
form-select	Bootstrap select styling
form-select-sm	Small select size
d-inline	Display the select inline
w-auto	Width automatically fits its content

This is a good example of how Bootstrap classes are meant to be combined rather than memorised as one giant class.

4. Table + Card structure

Official documentation: [Tables](#) · [Cards](#)

Your table is wrapped inside a Bootstrap **card**:

```
<div class="card">
<table class="table table-hover mb-0 align-middle">
...
</table>
</div>
```

Bootstrap classes here

Class	Purpose
card	Creates the Bootstrap card container
table	Activates Bootstrap table styling
table-hover	Adds hover highlighting to rows
mb-0	Removes bottom margin from the table
align-middle	Vertically aligns cell content in the middle

Your custom CSS then modifies the table further:

```
.table th{
background:#f8f9fa;
font-size:14px;
padding:14px;
}

.table td{
font-size:14px;
padding:18px;
vertical-align:middle;
}
```

This is important: **table**, **table-hover**, **mb-0**, and **align-middle** are Bootstrap. The rules inside **.table th** and **.table td** are your custom CSS.

5. Badges and contextual colours

Official documentation: [Badges](#) · [Background utilities](#)

```
<span class="badge bg-success">new</span>
<span class="badge bg-info">special</span>
```

Class breakdown

Class	Role
badge	Base Bootstrap badge component
bg-success	Green contextual background
bg-info	Info contextual background

Your code also contains a custom **.badge { font-size:11px; }** rule. Bootstrap supplies the badge component; your CSS changes its font size.

Useful contextual variants to know

```
bg-primary
bg-secondary
bg-success
bg-danger
bg-warning
bg-info
bg-light
bg-dark
```

Do not confuse **bg-*** with **badge**. **badge** creates the component; **bg-success** supplies a background colour.

6. Small Bootstrap utility classes in the page

Official documentation: [Spacing](#) · [Display](#) · [Text](#) · [Sizing](#) · [Vertical alignment](#)

Class	Breakdown	Effect
mb-0	m = margin, b = bottom, 0 = zero	No bottom margin
fs-4	font-size level 4	Larger font size
text-muted	text colour utility	Muted text colour
d-inline	display: inline	Keeps select inline with surrounding text
w-auto	width auto	Fits width to content
align-middle	vertical alignment utility	Middle-aligns content

Spacing notation reminder

Bootstrap's spacing system uses combinations such as **m** for margin, **p** for padding, and directional letters such as **t**, **b**, **s**, **e**, **x**, and **y**. Your Lab 2 code happens to use **mb-0**, which means margin-bottom = 0.

7. Bootstrap Icons – separate from Bootstrap CSS

Official documentation: [Bootstrap Icons](#)

The icons in the screenshot are NOT Bootstrap component classes such as **btn** or **table**. They come from the separate Bootstrap Icons library.

Your HTML loads:

```
<link href="https://cdn.jsdelivr.net/npm/bootstrap-icons/font/bootstrap-icons.css"
rel="stylesheet">
```

Then an icon is created using the **bi** base class plus a specific icon name.

Icon class	Visual purpose in your page
bi bi-search	Search icon in sidebar search box
bi bi-speedometer2	Dashboard icon
bi bi-file-earmark	Pages icon
bi bi-person-badge	Admin icon
bi bi-chevron-right	Right arrow for menu item
bi bi-people	Helpers icon
bi bi-images	Media manager icon
bi bi-gear	Config icon
bi bi-plug	API tester icon
bi bi-layout-text-window	Page Designer icon
bi bi-list	Topbar menu icon
bi bi-person-circle	Administrator account icon
bi bi-funnel	Date filter icon
bi bi-star	Empty star
bi bi-star-fill	Filled star
bi bi-pencil	Edit action
bi bi-eye	View action
bi bi-trash	Delete action
bi bi-flask	Test/action icon

Icon pattern

```
<i class="bi bi-search"></i>
<i class="bi bi-pencil"></i>
<i class="bi bi-trash"></i>
```

Here **bi** identifies the Bootstrap Icons font/icon system and **bi-search**, **bi-pencil**, etc. identify the actual icon.

8. Custom CSS classes – NOT Bootstrap

This is where your supplied code becomes a custom admin template. These classes are defined by you inside the **<style>** block. Bootstrap will not create these automatically.

Custom class	Purpose in page
sidebar	Fixed left navigation panel, width 260px, full viewport height
brand	Open Admin heading inside sidebar
search	Search wrapper positioning
main	Main area offset by sidebar width
topbar	White top header bar
content	Page content padding
selected-row	Yellow background for checked/selected rows
star-blue	Blue star colour
star-green	Green star colour
action	Spacing/cursor for action icons
table-footer	Footer area below table
page-box	Pagination box styling

Also custom:

```
.sidebar a
.sidebar a span
.sidebar a.active
.sidebar a:hover
.sidebar .search i
.sidebar .search input
.action i
.page-box span
.page-box .active
.form-check-input:checked
.form-check-input[type="checkbox"]
```

Some of these selectors target Bootstrap elements. For example, **.form-check-input:checked** changes the Bootstrap checkbox's checked colour. The selector itself is still your custom CSS.

9. Lab 2 – build the page in a logical order

Do not try to memorise the 200+ lines as one block. Build it in layers.

1. Add the HTML5 structure

Create html, head, title, and body.

2. Add Bootstrap CSS

Load Bootstrap before using its classes.

3. Add Bootstrap Icons

Load the icon stylesheet because the page uses bi-* icons.

4. Create the sidebar with custom CSS

The sidebar itself is custom. Use Bootstrap only for elements inside it where appropriate.

5. Add the search input

Use form-control + form-control-sm, then custom CSS for the icon position/background.

6. Add sidebar links

Use normal anchors plus Bootstrap Icons. The .active and hover behaviour in this page is custom CSS.

7. Create main and topbar

These are custom layout classes using fixed width/margins/flexbox.

8. Create the page heading

Use h4 and the Bootstrap text-muted utility for the smaller “List” text.

9. Create the table card

Wrap the table in .card, then use table + table-hover + mb-0 + align-middle.

10. Add checkboxes

Use form-check-input.

11. Add badges

Use badge + bg-success/bg-info.

12. Add icons

Use bi bi-pencil, bi bi-eye, bi bi-trash, bi bi-flask, etc.

13. Add footer controls

Use form-select, form-select-sm, d-inline, w-auto for the entries selector.

14. Add custom pagination styling

The page-box and its spans are custom CSS, not Bootstrap pagination.

15. Compare with screenshot

Only after the structure works should you tune custom CSS for exact spacing, colours, and dimensions.

Why this order is better

If you start by copying the entire final page, you may get the screenshot but learn very little. If you build it in layers, you can identify which part comes from Bootstrap, which part comes from Bootstrap Icons, and which part is your own CSS.

10. Class combinations you should understand

Combination	How to read it
form-control form-control-sm	Base form control + small size
table table-hover mb-0 align-middle	Table component + hover modifier + zero bottom margin + vertical alignment
badge bg-success	Badge component + green contextual background
badge bg-info	Badge component + info background
form-select form-select-sm d-inline w-auto	Select component + small size + inline display + automatic width
bi bi-star-fill star-green	Bootstrap Icon + filled star icon + custom green colour class
bi bi-star star-blue	Bootstrap Icon + outline star icon + custom blue colour class

This is the main skill to take from the page: **component + modifier + utility**. Sometimes a fourth class is your own custom CSS.

11. Official documentation links for Lab 2

Reference	Official page	Use for this lab
Bootstrap 5.0 main documentation	https://getbootstrap.com/docs/5.0/	Main reference
Bootstrap 5.0 Forms overview	https://getbootstrap.com/docs/5.0/forms/overview/	Forms and controls
Form Control	https://getbootstrap.com/docs/5.0/forms/form-control/	Text/search input
Checks & Radios	https://getbootstrap.com/docs/5.0/forms/checks-radios/	Checkboxes
Select	https://getbootstrap.com/docs/5.0/forms/select/	Select dropdown
Tables	https://getbootstrap.com/docs/5.0/content/tables/	Table classes
Cards	https://getbootstrap.com/docs/5.0/components/card/	Card wrapper
Badges	https://getbootstrap.com/docs/5.0/components/badge/	Tag badges
Spacing utilities	https://getbootstrap.com/docs/5.0/utilities/spacing/	mb-0 and spacing pattern
Display utilities	https://getbootstrap.com/docs/5.0/utilities/display/	d-inline
Text utilities	https://getbootstrap.com/docs/5.0/utilities/text/	text-muted
Sizing utilities	https://getbootstrap.com/docs/5.0/utilities/sizing/	w-auto
Vertical alignment	https://getbootstrap.com/docs/5.0/utilities/vertical-align/	align-middle
Background utilities	https://getbootstrap.com/docs/5.0/utilities/background/	bg-success/bg-info
Bootstrap Icons	https://icons.getbootstrap.com/	All bi-* icons used in the page
Bootstrap Icons GitHub / usage reference	https://icons.getbootstrap.com/	Icon search and usage

Note: the exact visual appearance of this screenshot is not produced by Bootstrap alone. A significant portion is custom CSS. Bootstrap gives you the reusable building blocks; the custom CSS creates the particular admin-template design.

12. Final Lab 2 revision checklist

- I know the difference between Bootstrap classes and my custom CSS classes.
- I can explain **form-control form-control-sm**.
- I can explain **table table-hover mb-0 align-middle**.
- I can create a badge using **badge bg-success**.
- I can style a checkbox using **form-check-input**.
- I can create a select using **form-select** and make it small with **form-select-sm**.
- I understand **d-inline** and **w-auto**.
- I know that **bi bi-pencil** comes from Bootstrap Icons, not the Bootstrap component library.
- I can find the correct icon on the Bootstrap Icons website.
- I can recreate the page section-by-section instead of copying the complete source.
- I know that sidebar, topbar, selected-row, star-blue, star-green, action, table-footer, and page-box are custom classes.

Most important exam rule

If your teacher asks “Which Bootstrap classes are used?”, do not list your custom classes as Bootstrap. In this page, **form-control, form-control-sm, table, table-hover, mb-0, align-middle, badge, bg-success, bg-info, form-check-input, form-select, form-select-sm, d-inline, w-auto, fs-4, and text-muted** are the Bootstrap classes. The **bi-*** classes belong to Bootstrap Icons, and the admin-layout classes are your custom CSS.