

K-Nearest Neighbor

Supervised Learning

- Given training data $\{(\mathbf{x}_1, \mathbf{y}_1), \dots, (\mathbf{x}_N, \mathbf{y}_N)\}$

Supervised Learning

- Given training data $\{(\mathbf{x}_1, \mathbf{y}_1), \dots, (\mathbf{x}_N, \mathbf{y}_N)\}$
- N input/output pairs; \mathbf{x}_i - input, \mathbf{y}_i - output/label

Supervised Learning

- Given training data $\{(\mathbf{x}_1, \mathbf{y}_1), \dots, (\mathbf{x}_N, \mathbf{y}_N)\}$
- N input/output pairs; \mathbf{x}_i - input, \mathbf{y}_i - output/label
- \mathbf{x}_i is a **vector** consisting of D **features**
 - Also called **attributes** or **dimensions**
 - Features can be discrete or continuous
 - x_{im} denotes the m -th feature of \mathbf{x}_i

Supervised Learning

- Given training data $\{(\mathbf{x}_1, \mathbf{y}_1), \dots, (\mathbf{x}_N, \mathbf{y}_N)\}$
- N input/output pairs; \mathbf{x}_i - input, \mathbf{y}_i - output/label
- \mathbf{x}_i is a **vector** consisting of D **features**
 - Also called **attributes** or **dimensions**
 - Features can be discrete or continuous
 - x_{im} denotes the m -th feature of \mathbf{x}_i
- Forms of the output:
 - $\mathbf{y}_i \in \{1, \dots, C\}$ for classification; a discrete variable
 - $\mathbf{y}_i \in \mathbb{R}$ for regression; a continuous (real-valued) variable

Supervised Learning


- Given training data $\{(\mathbf{x}_1, \mathbf{y}_1), \dots, (\mathbf{x}_N, \mathbf{y}_N)\}$
- N input/output pairs; \mathbf{x}_i - input, \mathbf{y}_i - output/label
- \mathbf{x}_i is a **vector** consisting of D **features**
 - Also called **attributes** or **dimensions**
 - Features can be discrete or continuous
 - x_{im} denotes the m -th feature of \mathbf{x}_i
- Forms of the output:
 - $\mathbf{y}_i \in \{1, \dots, C\}$ for classification; a discrete variable
 - $\mathbf{y}_i \in \mathbb{R}$ for regression; a continuous (real-valued) variable
- **Goal:** predict the output \mathbf{y} for an **unseen** test example \mathbf{x}

K-Nearest Neighbor

- Given training data $\mathcal{D} = \{(\mathbf{x}_1, \mathbf{y}_1), \dots, (\mathbf{x}_N, \mathbf{y}_N)\}$ and a test point
- Prediction Rule: Look at the K most similar training examples


K-Nearest Neighbor

- Given training data $\mathcal{D} = \{(\mathbf{x}_1, \mathbf{y}_1), \dots, (\mathbf{x}_N, \mathbf{y}_N)\}$ and a test point
- Prediction Rule: Look at the K most similar training examples



K-Nearest Neighbor


- Given training data $\mathcal{D} = \{(\mathbf{x}_1, \mathbf{y}_1), \dots, (\mathbf{x}_N, \mathbf{y}_N)\}$ and a test point
- Prediction Rule: Look at the K most similar training examples



- For classification: assign the majority class label (**majority voting**)
- For regression: assign the **average response**

K-Nearest Neighbor

- Given training data $\mathcal{D} = \{(\mathbf{x}_1, \mathbf{y}_1), \dots, (\mathbf{x}_N, \mathbf{y}_N)\}$ and a test point
- Prediction Rule: Look at the K most similar training examples



- For classification: assign the majority class label (**majority voting**)
- For regression: assign the **average response**
- The algorithm requires:
 - Parameter K : number of nearest neighbors to look for
 - **Distance function**: To compute the similarities between examples

K-Nearest Neighbor Algorithm

- Compute the test point's distance from each training point
- Sort the distances in ascending (or descending) order
- Use the sorted distances to select the K nearest neighbors
- Use **majority rule** (for classification) or **averaging** (for regression)

K-Nearest Neighbor Algorithm

- Compute the test point's distance from each training point
- Sort the distances in ascending (or descending) order
- Use the sorted distances to select the K nearest neighbors
- Use **majority rule** (for classification) or **averaging** (for regression)

Note: K -Nearest Neighbors is called a *non-parametric* method

- Unlike other supervised learning algorithms, K -Nearest Neighbors doesn't learn an explicit mapping f from the training data

K-Nearest Neighbor Algorithm

- Compute the test point's distance from each training point
- Sort the distances in ascending (or descending) order
- Use the sorted distances to select the K nearest neighbors
- Use **majority rule** (for classification) or **averaging** (for regression)

Note: K -Nearest Neighbors is called a *non-parametric* method

- Unlike other supervised learning algorithms, K -Nearest Neighbors doesn't learn an explicit mapping f from the training data
- It simply uses the training data at the test time to make predictions

K-NN: Compute Distance

- The K -NN algorithm requires computing distances of the test example from each of the training examples

K-NN: Compute Distance

- The K -NN algorithm requires computing distances of the test example from each of the training examples
- Several ways to compute distances
- The choice depends on the **type of the features** in the data

K-NN: Compute Distance

- The K -NN algorithm requires computing distances of the test example from each of the training examples
- Several ways to compute distances
- The choice depends on the **type of the features** in the data
- **Real-valued features** ($\mathbf{x}_i \in \mathbb{R}^D$): **Euclidean distance** is commonly used

$$d(\mathbf{x}_i, \mathbf{x}_j) = \sqrt{\sum_{m=1}^D (x_{im} - x_{jm})^2} = \sqrt{\|\mathbf{x}_i\|^2 + \|\mathbf{x}_j\|^2 - 2\mathbf{x}_i^T \mathbf{x}_j}$$

K-NN: Compute Distance

- The K -NN algorithm requires computing distances of the test example from each of the training examples
- Several ways to compute distances
- The choice depends on the **type of the features** in the data
- **Real-valued features** ($\mathbf{x}_i \in \mathbb{R}^D$): **Euclidean distance** is commonly used

$$d(\mathbf{x}_i, \mathbf{x}_j) = \sqrt{\sum_{m=1}^D (x_{im} - x_{jm})^2} = \sqrt{\|\mathbf{x}_i\|^2 + \|\mathbf{x}_j\|^2 - 2\mathbf{x}_i^T \mathbf{x}_j}$$

- Generalization of the distance between points in 2 dimensions

K-NN: Compute Distance

- The K -NN algorithm requires computing distances of the test example from each of the training examples
- Several ways to compute distances
- The choice depends on the **type of the features** in the data
- **Real-valued features** ($\mathbf{x}_i \in \mathbb{R}^D$): **Euclidean distance** is commonly used

$$d(\mathbf{x}_i, \mathbf{x}_j) = \sqrt{\sum_{m=1}^D (x_{im} - x_{jm})^2} = \sqrt{\|\mathbf{x}_i\|^2 + \|\mathbf{x}_j\|^2 - 2\mathbf{x}_i^T \mathbf{x}_j}$$

- Generalization of the distance between points in 2 dimensions
- $\|\mathbf{x}_i\| = \sqrt{\sum_{m=1}^D x_{im}^2}$ is called the **norm** of \mathbf{x}_i
 - Norm of a vector \mathbf{x} is also its **length**

K-NN: Compute Distance

- The K -NN algorithm requires computing distances of the test example from each of the training examples
- Several ways to compute distances
- The choice depends on the **type of the features** in the data
- **Real-valued features** ($\mathbf{x}_i \in \mathbb{R}^D$): **Euclidean distance** is commonly used

$$d(\mathbf{x}_i, \mathbf{x}_j) = \sqrt{\sum_{m=1}^D (x_{im} - x_{jm})^2} = \sqrt{\|\mathbf{x}_i\|^2 + \|\mathbf{x}_j\|^2 - 2\mathbf{x}_i^T \mathbf{x}_j}$$

- Generalization of the distance between points in 2 dimensions
- $\|\mathbf{x}_i\| = \sqrt{\sum_{m=1}^D x_{im}^2}$ is called the **norm** of \mathbf{x}_i
 - Norm of a vector \mathbf{x} is also its **length**

K-NN: Feature Normalization

- Note: Features should be on the same scale
- Example: if one feature has its values in millimeters and another has in centimeters, we would need to normalize

K-NN: Feature Normalization

- Note: Features should be on the same scale
- Example: if one feature has its values in millimeters and another has in centimeters, we would need to normalize
- One way is:
 - Replace x_{im} by $z_{im} = \frac{(x_{im} - \bar{x}_m)}{\sigma_m}$ (make them zero mean, unit variance)

K-NN: Feature Normalization

- Note: Features should be on the same scale
- Example: if one feature has its values in millimeters and another has in centimeters, we would need to normalize
- One way is:
 - Replace x_{im} by $z_{im} = \frac{(x_{im} - \bar{x}_m)}{\sigma_m}$ (make them zero mean, unit variance)
 - $\bar{x}_m = \frac{1}{N} \sum_{i=1}^N x_{im}$: empirical mean of m^{th} feature

K-NN: Feature Normalization

- Note: Features should be on the same scale
- Example: if one feature has its values in millimeters and another has in centimeters, we would need to normalize
- One way is:
 - Replace x_{im} by $z_{im} = \frac{(x_{im} - \bar{x}_m)}{\sigma_m}$ (make them zero mean, unit variance)
 - $\bar{x}_m = \frac{1}{N} \sum_{i=1}^N x_{im}$: empirical mean of m^{th} feature
 - $\sigma_m^2 = \frac{1}{N} \sum_{i=1}^N (x_{im} - \bar{x}_m)^2$: empirical variance of m^{th} feature

K-NN: Other Distance Measure

- Binary-valued features
 - Use Hamming distance: $d(x_i, x_j) = \sum_{m=1}^D \mathbb{I}(x_{im} \neq x_{jm})$
 - Hamming distance counts the number of features where the two examples disagree


K-NN: Other Distance Measure

- Binary-valued features
 - Use Hamming distance: $d(x_i, x_j) = \sum_{m=1}^D \mathbb{I}(x_{im} \neq x_{jm})$
 - Hamming distance counts the number of features where the two examples disagree
- Mixed feature types (some real-valued and some binary-valued)?
 - Can use mixed distance measures
 - E.g., Euclidean for the real part, Hamming for the binary part


K-NN: Other Distance Measure

- Binary-valued features
 - Use Hamming distance: $d(x_i, x_j) = \sum_{m=1}^D \mathbb{I}(x_{im} \neq x_{jm})$
 - Hamming distance counts the number of features where the two examples disagree
- Mixed feature types (some real-valued and some binary-valued)?
 - Can use mixed distance measures
 - E.g., Euclidean for the real part, Hamming for the binary part
- Can also assign **weights** to features: $d(x_i, x_j) = \sum_{m=1}^D w_m d(x_{im}, x_{jm})$

K-NN: Choice of K




K-NN: Choice of K




- Small K
 - Creates many small regions for each class
 - May lead to non-smooth) decision boundaries and overfit

K-NN: Choice of K




- Small K
 - Creates many small regions for each class
 - May lead to non-smooth) decision boundaries and overfit
- Large K
 - Creates fewer larger regions
 - Usually leads to smoother decision boundaries (caution: too smooth decision boundary can underfit)

K-NN: Choice of K



- Small K
 - Creates many small regions for each class
 - May lead to non-smooth decision boundaries and overfit
- Large K
 - Creates fewer larger regions
 - Usually leads to smoother decision boundaries (caution: too smooth decision boundary can underfit)
- Choosing K
 - Often data dependent and heuristic based
 - Or using **cross-validation** (using some **held-out data**)

K-NN: Choice of K



- Small K
 - Creates many small regions for each class
 - May lead to non-smooth) decision boundaries and overfit
- Large K
 - Creates fewer larger regions
 - Usually leads to smoother decision boundaries (caution: too smooth decision boundary can underfit)
- Choosing K
 - Often data dependent and heuristic based
 - Or using **cross-validation** (using some **held-out data**)
 - In general, a K too small or too big is bad!

K-NN: Properties


- What's nice

- Simple and intuitive; easily implementable
- Asymptotically consistent (a theoretical property)
 - With infinite training data and large enough K , K -NN approaches the best possible classifier (Bayes optimal)

- What's not so nice..

- Store all the training data *in memory* even at test time
 - Can be memory intensive for large training datasets
 - An example of non-parametric, or memory/instance-based methods
 - Different from parametric, model-based learning models
- Expensive at test time: $O(ND)$ computations for each test point
 - Have to search through all training data to find nearest neighbors
 - Distance computations with N training points (D features each)
- Sensitive to noisy features
- May perform badly in high dimensions (curse of dimensionality)
 - In high dimensions, distance notions can be counter-intuitive!

K-NN: Example



K-NN: Pseudocode

1. Calculate “ $d(x, x_i)$ ” $i = 1, 2, \dots, n$; where d denotes the Euclidean distance between the points.
2. Arrange the calculated n Euclidean distances in non-decreasing order.
3. Let k be a +ve integer, take the first k distances from this sorted list.
4. Find those k -points corresponding to these k -distances.
5. Let k_i denotes the number of points belonging to the i^{th} class among k points i.e. $k \geq 0$
6. If $k_i > k_j \forall i \neq j$ then put x in class i .

Let (X_i, C_i) where $i = 1, 2, \dots, n$ be data points. X_i denotes feature values & C_i denotes labels for X_i for each i .

Assuming the number of classes as ‘ c ’

$C_i \in \{1, 2, 3, \dots, c\}$ for all values of i

Let x be a point for which label is not known, and we would like to find the label class using k -nearest neighbor algorithms.