

Gene calling with Prodigal

James Thornton Jr

Abstract

This protocol provides the procedure to generate gene calls on your contigs using Prodigal.

Citation: James Thornton Jr Gene calling with Prodigal. **protocols.io**

dx.doi.org/10.17504/protocols.io.kixcufn

Published: 31 Oct 2017

Protocol

Step 1.

Login to the HPC and move into ocelote.

```
cmd COMMAND
$ ssh hpc
$ ocelote
```

Step 2.

Move into your class directory.

```
cmd COMMAND
$ cd /rsgrps/bh_class/username
Use YOUR username to be in the right directory
```

Step 3.

Copy the following into a new script called run-interactive.sh :

```
cmd COMMAND
#!/bin/bash

#PBS -W group_list=bh_class
#PBS -q windfall
#PBS -l select=1:ncpus=2:mem=4gb
#PBS -l walltime=24:00:00
#PBS -l cput=24:00:00
#PBS -M netid@email.arizona.edu
#PBS -m bea
Replace netid
```

Step 4.


Submit run-interactive.sh interactively using qsub:

```
cmd COMMAND
```

```
qsub -I run-interactive.sh
```

The capital " I " indicates this will be an interactive job

📄 EXPECTED RESULTS



```
1. jameshornton@r2i1n1:~ (ssh)
[jamesthornton@service2 jetjr]$ qsub -I run-interactive.sh
qsub: waiting for job 655455.service2 to start
qsub: job 655455.service2 ready

[jamesthornton@r2i1n1 ~]$
```

Step 5.

Once the job is ready move back into your class directory.

```
cmd COMMAND
$ cd /rsgrps/bh_class/username
Use YOUR username
```

Step 6.

Make a directory named prodigal:

```
cmd COMMAND
$ mkdir prodigal
```

Step 7.

Move into your assembly directory which contains your contigs:

```
cmd COMMAND
$ cd /rsgrps/bh_class/username/assembly
```

📌 NOTES

James Thornton Jr 17 Oct 2016

Note: Its possible your contigs are in another directory (megahit-out). Move to the directory where final_contigs.fa are located. Remember final_contigs.fa is the combined assemblies from your partner.

Step 8.

Load prodigal and run it on your final_contigs.fa to generate gene calls.

```
cmd COMMAND
$ prodigal -i final_contigs.fa -o ../prodigal/gene_calls -a ../prodigal/proteins.faa -d ../prodigal/nucleotides.fna
```

IMPORTANT: make sure to run prodigal on the final_contigs.fa file which was generated when combining assemblies with your partner. The output will be placed in the prodigal directory that was created and the file name will be gene_calls in addition to a file containing the protein (proteins.faa) and nucleotide (nucleotide.faa) sequences for the genes.

📌 NOTES

James Thornton Jr 17 Oct 2016

Since final_contigs.fa may be located somewhere other than the assembly directory, you can write out the full paths to make sure the output goes where its suppose to:

```
$ prodigal -i /path/to/final_contigs.fa -o /rsgrps/bh_class/username/prodigal/gene_calls -  
a /rsgrps/bh_class/username/prodigal/proteins.faa -  
d /rsgrps/bh_class/username/prodigal/nucleotides.fna
```

James Thornton Jr 17 Oct 2016

The prodigal command is executed in one line.


Step 9.

Move into your prodigal directory and make sure the gene calls were generated.

cmd **COMMAND**

```
$ cd /rsgrps/bh_class/username/prodigal  
$ head gene_calls
```

📄 **EXPECTED RESULTS**



```
1. james Thornton@r2i1n1:/rsgrps/bh_class/jetjr/prodigal (ssh)  
[jamesthornton@r2i1n1 prodigal]$ head gene_calls  
DEFINITION  seqnum=1;seqlen=3384;seqhdr="1";version=Prodigal.v2.6.2;run_type=Single;model="Ab initio";gc_cont=59.13;transl_table=11;uses_sd=1  
FEATURES             Location/Qualifiers  
     CDS             <1..585  
                     /note="ID=1_1;partial=10;start_type=Edge;rbs_motif=None;rbs_spacer=None;gc_cont=0.694;conf=100.00;score=64.40;cscore=61.18:sscore=3.22;rscore=0.00;uscore=0.00;tscore=3.22;"  
     CDS             complement(611..1393)  
                     /note="ID=1_2;partial=00;start_type=ATG;rbs_motif=GGAG/GAG/AGG;rbs_spacer=5-10bp;gc_cont=0.674;conf=100.00;score=127.23;cscore=121.91:sscore=5.32;rscore=0.27;uscore=0.84;tscore=3.13;"  
     CDS             complement(1412..1933)  
                     /note="ID=1_3;partial=00;start_type=ATG;rbs_motif=GGAG/GAG;G;rbs_spacer=5-10bp;gc_cont=0.600;conf=100.00;score=73.38;cscore=66.09:sscore=7.29;rscore=2.87;uscore=0.31;tscore=3.13;"  
     CDS             complement(1930..>3384)  
                     /note="ID=1_4;partial=01;start_type=Edge;rbs_motif=None;rbs_spacer=None;gc_cont=0.635;conf=99.99;score=218.15;cscore=214.93:sscore=3.22;rscore=0.00;uscore=0.00;tscore=3.22;"  
[jamesthornton@r2i1n1 prodigal]$
```

Step 10.

Use your scripting or unix skills to detect how many genes were detected in your contigs file. Create a table that shows the number of 'ORFs' or open reading frames detected on the contigs.