

# Mapping Metagenomic Reads to Reference Sequences (Cyverse) Version 3

Benjamin Bolduc

## Abstract

Mapping metagenomic reads from [Ocean Sampling Day](#) (OSD) 2014 against NCBI's ViralRefSeq alongside viral sequences identified from the Tara Oceans survey using [VirSorter](#).

**Citation:** Benjamin Bolduc Mapping Metagenomic Reads to Reference Sequences (Cyverse). [protocols.io](#)

dx.doi.org/10.17504/protocols.io.gv2bw8e

**Published:** 31 Dec 2016

## Guidelines

One of the most commonly used procedures for analyzing viral metagenomic data is to map their reads (or reads from another dataset) against a set of references, often those from the read assembly. For example, if one wanted to know how well-represented viruses in NCBI's Viral Reference Sequences (ViralRefSeq) were in ocean viromes, they could map reads from lots of ocean viral metagenomes against ViralRefSeq. This is generally done using [Bowtie2](#) or [BWA](#), by selecting a reference set of sequences, and then providing paired or unpaired reads to Bowtie2/BWA. *Then* the results must be processed/filtered to generate coverage tables. Dealing with setting up multiple reads files (10 paired metagenomes = 10 alignment runs) and the processing those read files can be challenging (not to mention requiring computational resources).

In this protocol, we'll be using reads from [Ocean Sampling Day](#) (OSD) 2014 and map them against ViralRefSeq alongside viral sequences identified from the Tara Oceans survey using [VirSorter](#).

## Before start

To run this protocol, users must first [register](#) for Cyverse account. All data (both inputs and outputs) are available within Cyverse's data store at `/iplant/home/shared/iVirus/ExampleData/`

All source code is available at the Sullivan lab bitbucket repository, [MAVERICLab](#) - either `*-bowtiebatch` or `*-read2refmapper`. `*` denotes either docker or stampede-based repos.


## Protocol

### BowtieBatch

#### Step 1.

# Open BowtieBatch

Open BowtieBatch-1.0.0 from 'Apps'



## BowtieBatch

### Step 2.

## Select Inputs

Select the 'Inputs' tab.

For **Reference file with FASTA-formatted sequences**: this is a FASTA-formatted file with reference sequences to map reads against

- Navigate to *Community Data --> iVirus --> ExampleData --> BowtieBatch --> Inputs*. Select *VirRefSeq\_and\_Virsorted\_Tara\_10kb.fasta*. Alternatively, copy-and-paste the location: `/iplant/home/shared/iVirus/ExampleData/BowtieBatch/Inputs` into the navigation bar and select the fasta file.

For **Directory with reads**: this is a directory containing the reads files that are to be mapped

- Navigate to *Community Data --> iVirus --> ExampleData --> BowtieBatch --> Inputs*. Select the *Reads* folder. Alternatively, copy-and-paste the location: `/iplant/home/shared/iVirus/ExampleData/BowtieBatch/Inputs` into the navigation bar and select the reads folder.

## 🔗 NOTES

**Benjamin Bolduc** 31 Dec 2016

TIP: Reads directory can contain any number of reads files. They can be paired, unpaired, gzipped or uncompressed. They *do* have to have some semblance of ordering, either computer or human-natural sorting.

## BowtieBatch

### Step 3.

## Select Parameters

The default options will be sufficient for this example, however additional options are explain below.

**File extension:** Extension of the reads. GZIP files are automatically recognized.

**Interleaved files:** Are reads interleaved? i.e. Are forward and reverse reads in the same file? These read files contain both pairs, usually Forward1, Reverse1, Forward2, etc... By using this option users can automatically handle interleaved files w/out worrying about having another app handling this conversion.

**Read type:** What type are the reads? *Paired*, *unpaired*, a *mix* of both?

**Levenshtein distance:** "Distance" between the read names. i.e. "CAT" and "BAT" have a distance of 1 because the C/B difference. Generally, read pairs/unpairs differ by 1 and mixed differ by 3. If reads do not group correctly, try changing this value.

**Keep SAM files:** Bowtie2 generates SAM files as a result of mapping reads. However, these take up a lot of space and aren't kept if they're not needed. Users can select if they'd like to keep these files around in case they have other analyses that use SAM files. For this example, they are unnecessary.

**Log file name:** Information about the run's processing will be stored with this file name. This file *can become very large* as it contains trimming information.

**Merge results:** Bowtie2 can create a single SAM file that combines all the individual paired/unpaired alignments. Because the next tool in this pipeline (Read2RefMapper) requires individually separated files, do not select this.

**Merged file name:** Name to use if results are combined.

The remaining options are bowtie specific, please consult [the Bowtie2 documentation](#).

BowtieBatch 1.0.0

Analysis Name: BowtieBatch\_1.0.0\_analysis1

\* Inputs

\* Parameters

\* File extension.:
FASTQ (\*.fastq)

☐ Interleaved files.

\* Read type:
Reads to be aligned are paired.

Levenshtein distance between filenames. See documentation. 1 paired/unpaired only. 3 mixed.:
1

☐ Keep SAM files.

\* Log file name:
bowtie2-read-mapping.log

☐ Merge results

\* Merged file name:
bowtie2-run.sam

\* Local or global alignment:
Entire read must align.

\* End-to-end alignment presets:
sensitive: -D 15 -R 2 -N 0 -L 22 -i S,1,1.15 (default)

\* Local alignment presets:
sensitive-local: -D 15 -R 2 -N 0 -L 20 -i S,1,0.75 (default)

☐ Use non-deterministic method.

Trim 5' bases.:
0

Trim 3' bases.:
0

Minimum fragment length.:
0

Maximum fragment length.:
2000

Launch Analysis

## NOTES

**Benjamin Bolduc** 31 Dec 2016

While the default options will suffice for this example, play around with a few of the options (excluding file extension).

**Benjamin Bolduc** 31 Dec 2016

Reads can be paired, unpaired or a mix of both. In this example there are 2 sets of paired reads. Alternatively, one could set all the reads to be unpaired.

**BowtieBatch 1.0.0**

Analysis Name: BowtieBatch\_1.0.0\_analysis1

**\* Inputs**

**\* Parameters**

\* File extension.: FASTQ (\*.fastq)

☐ Interleaved files.

\* Read type: Reads to be aligned are unpaired.

Levenshtein distance between filenames. See documentation. 1 paired/unpaired only. 3 mixed.: 1

☐ Keep SAM files.

\* Log file name: bowtie2-read-mapping.log

☐ Merge results

\* Merged file name: bowtie2-run.sam

\* Local or global alignment: Entire read must align.

\* End-to-end alignment presets: sensitive: -D 15 -R 2 -N 0 -L 22 -i S,1,1.15 (default)

\* Local alignment presets: sensitive-local: -D 15 -R 2 -N 0 -L 20 -i S,1,0.75 (default)

☐ Use non-deterministic method.

Trim 5' bases.: 0

Trim 3' bases.: 0

Minimum fragment length.: 0

Maximum fragment length.: 2000

**Launch Analysis**

## BowtieBatch

### Step 4.

## Launch Analysis

Run the job!

Depending on the number of files to align and/or the number of sequences in the reference database, the job could take many hours.

















































## BowtieBatch

### Step 5.





































## Results

Expected results can be found from the 'output' directory of BowtieBatch. They'll consist of 3 directories:

- Reads: containing the original files
- bowtie2-db: containing the bowtie2-formatted sequences
- reads: any uncompressed version of the reads (those files actually used by bowtie2) and BAM files. If **Keep Sam files** was selecting, they'll be SAM files there as well.

<input type="checkbox"/>	Name	Last Modified	Size	
<input type="checkbox"/>	  Reads	2016 Dec 30 06:33:52		   
<input type="checkbox"/>	  bowtie2-db	2016 Dec 30 06:30:05		   
<input type="checkbox"/>	  reads	2016 Dec 30 06:31:42		   
<input type="checkbox"/>	  .agave.log	2016 Dec 30 06:29:53	354 bytes	   
<input type="checkbox"/>	  VirRefSeq_and_Virsorted_Tara_10kb.fasta	2016 Dec 30 06:35:01	216.24 MB	   
<input type="checkbox"/>	  agave-6655dac6-fd33-4bd8-b697-7fd533...	2016 Dec 30 06:29:57	0 bytes	   
<input type="checkbox"/>	  agave-6655dac6-fd33-4bd8-b697-7fd533...	2016 Dec 30 06:30:01	396 bytes	   
<input type="checkbox"/>	  bowtie2-read-mapping.log	2016 Dec 30 06:31:38	6.6 KB	   

Content of reads directory:

<input checked="" type="checkbox"/>	 	OSD24_R1_shotgun_workable.bam	2016 Dec 30 06:31:44	949.98 KB	   
<input type="checkbox"/>	 	OSD24_R1_shotgun_workable.fastq	2016 Dec 30 06:31:48	605.05 MB	   
<input type="checkbox"/>	 	OSD24_R2_shotgun_workable.fastq	2016 Dec 30 06:32:32	575.44 MB	   
<input checked="" type="checkbox"/>	 	OSD46_R1_shotgun_workable.bam	2016 Dec 30 06:33:04	1.47 MB	   
<input type="checkbox"/>	 	OSD46_R1_shotgun_workable.fastq	2016 Dec 30 06:33:09	247.96 MB	   
<input type="checkbox"/>	 	OSD46_R2_shotgun_workable.fastq	2016 Dec 30 06:33:32	220.38 MB	   

Additionally, the read mapping log file contains very useful information, such as the overall read mapping statistics:



```

Created reads directory: /work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1
Created bowtie2-db directory: /work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1
Directory content for reads:
[]
Directory contents for bowtie2-db directory:
[]
Workable Files
['Reads/OSD46_R2_shotgun_workable.fastq.gz',
'Reads/OSD46_R1_shotgun_workable.fastq.gz',
'Reads/OSD24_R2_shotgun_workable.fastq.gz',
'Reads/OSD24_R1_shotgun_workable.fastq.gz']
Workable Reads
['Reads/OSD46_R2_shotgun_workable.fastq.gz',
'Reads/OSD46_R1_shotgun_workable.fastq.gz',
'Reads/OSD24_R2_shotgun_workable.fastq.gz',
'Reads/OSD24_R1_shotgun_workable.fastq.gz']
Executing cp VirRefSeq_and_Virsorted_Tara_10kb.fasta /work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1
Executing bowtie2-build -f /work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1
Building a SMALL index
Bowtie2 base db: /work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1
Sorted files:
{0: {'paired': ['Reads/OSD24_R1_shotgun_workable.fastq.gz',
'Reads/OSD24_R2_shotgun_workable.fastq.gz']},
1: {'paired': ['Reads/OSD46_R1_shotgun_workable.fastq.gz',
'Reads/OSD46_R2_shotgun_workable.fastq.gz']}}
Executing zcat Reads/OSD24_R1_shotgun_workable.fastq.gz > /work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1
Executing zcat Reads/OSD46_R1_shotgun_workable.fastq.gz > /work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1
Reads in their appropriate locations?
{0: {'paired': ['/work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1/Reads/OSD24_R1_shotgun_workable.fastq.gz',
'/work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1/Reads/OSD24_R2_shotgun_workable.fastq.gz']},
1: {'paired': ['/work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1/Reads/OSD46_R1_shotgun_workable.fastq.gz',
'/work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1/Reads/OSD46_R2_shotgun_workable.fastq.gz']}}
Executing bowtie2 -q --phred33 --end-to-end --sensitive -p 16 -I 0 -X 2000 --no-unal -x /work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1
perl: warning: Setting locale failed.
perl: warning: Please check that your locale settings:
    LANGUAGE = (unset),
    LC_ALL = "en_US.UTF-8",
    LANG = "en_US.UTF-8"
are supported and installed on your system.
perl: warning: Falling back to the standard locale ("C").
1214226 reads; of these:
  1214226 (100.00%) were paired; of these:
    1211266 (99.76%) aligned concordantly 0 times
    2174 (0.18%) aligned concordantly exactly 1 time
    786 (0.06%) aligned concordantly >1 times
  -----
  1211266 pairs aligned concordantly 0 times; of these:
    42 (0.00%) aligned discordantly 1 time
  -----
  1211224 pairs aligned 0 times concordantly or discordantly; of these:
    2422448 mates make up the pairs; of these:
      2421921 (99.98%) aligned 0 times
      365 (0.02%) aligned exactly 1 time
      162 (0.01%) aligned >1 times
0.27% overall alignment rate

Executing bowtie2 -q --phred33 --end-to-end --sensitive -p 16 -I 0 -X 2000 --no-unal -x /work/03548/bb_t4k0/bbolduc-iplant-2015/job-3903125675091029530-242ac114-0001-007-6655dac6-1
perl: warning: Setting locale failed.
perl: warning: Please check that your locale settings:
    LANGUAGE = (unset),
    LC_ALL = "en_US.UTF-8",
    LANG = "en_US.UTF-8"
are supported and installed on your system.
perl: warning: Falling back to the standard locale ("C").
406075 reads; of these:
  406075 (100.00%) were paired; of these:
    403125 (99.27%) aligned concordantly 0 times
    2513 (0.62%) aligned concordantly exactly 1 time
    437 (0.11%) aligned concordantly >1 times
  -----
  403125 pairs aligned concordantly 0 times; of these:
    103 (0.03%) aligned discordantly 1 time
  -----
  403022 pairs aligned 0 times concordantly or discordantly; of these:
    806044 mates make up the pairs; of these:
      805075 (99.88%) aligned 0 times
      785 (0.10%) aligned exactly 1 time
      184 (0.02%) aligned >1 times
0.87% overall alignment rate

Program Complete


```

Notice the grouping of the paired files, under "Sorted files." It shows 2 groups, 0 and 1, that have OSD24 and OSD46 as read groups.

## 📌 NOTES

















































**Benjamin Bolduc** 31 Dec 2016

A sample output directory is located  
at: /iplant/home/shared/iVirus/ExampleData/BowtieBatch/Outputs



**Benjamin Bolduc** 31 Dec 2016

If the reads were selected to be unpaired, a BAM file would be associated with each input file.

<input checked="" type="checkbox"/>	 	OSD24_R1_shotgun_workable.bam	2016 Dec 30 06:39:58	629.27 KB	   
<input type="checkbox"/>	 	OSD24_R1_shotgun_workable.fastq	2016 Dec 30 06:40:02	605.05 MB	   
<input checked="" type="checkbox"/>	 	OSD24_R2_shotgun_workable.bam	2016 Dec 30 06:40:40	684.36 KB	   
<input type="checkbox"/>	 	OSD24_R2_shotgun_workable.fastq	2016 Dec 30 06:40:44	575.44 MB	   
<input checked="" type="checkbox"/>	 	OSD46_R1_shotgun_workable.bam	2016 Dec 30 06:41:18	825.23 KB	   
<input type="checkbox"/>	 	OSD46_R1_shotgun_workable.fastq	2016 Dec 30 06:41:22	247.96 MB	   
<input checked="" type="checkbox"/>	 	OSD46_R2_shotgun_workable.bam	2016 Dec 30 06:41:39	900.63 KB	   
<input type="checkbox"/>	 	OSD46_R2_shotgun_workable.fastq	2016 Dec 30 06:41:43	220.38 MB	   

And each file would be grouped individually:

```

Created reads directory: /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-
Created bowtie2-db directory: /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-
Directory content for reads:
[]
Directory contents for bowtie2-db directory:
[]
Workable Files
['Reads/OSD46_R2_shotgun_workable.fastq.gz',
'Reads/OSD46_R1_shotgun_workable.fastq.gz',
'Reads/OSD24_R2_shotgun_workable.fastq.gz',
'Reads/OSD24_R1_shotgun_workable.fastq.gz']
Workable Reads
['Reads/OSD46_R2_shotgun_workable.fastq.gz',
'Reads/OSD46_R1_shotgun_workable.fastq.gz',
'Reads/OSD24_R2_shotgun_workable.fastq.gz',
'Reads/OSD24_R1_shotgun_workable.fastq.gz']
Executing cp VirRefSeq_and_Virsorted_Tara_10kb.fasta /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-

Executing bowtie2-build -f /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624
Building a SMALL index

Bowtie2 base db: /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624
Sorted files:
{0: {'unpaired': ['Reads/OSD24_R1_shotgun_workable.fastq.gz']},
1: {'unpaired': ['Reads/OSD24_R2_shotgun_workable.fastq.gz']},
2: {'unpaired': ['Reads/OSD46_R1_shotgun_workable.fastq.gz']},
3: {'unpaired': ['Reads/OSD46_R2_shotgun_workable.fastq.gz']}}
Executing zcat < Reads/OSD24_R1_shotgun_workable.fastq.gz > /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624
Executing zcat < Reads/OSD24_R2_shotgun_workable.fastq.gz > /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624
Executing zcat < Reads/OSD46_R1_shotgun_workable.fastq.gz > /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624
Executing zcat < Reads/OSD46_R2_shotgun_workable.fastq.gz > /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624

Reads in their appropriate locations?
{0: {'unpaired': ['/work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624/Reads/OSD24_R1_shotgun_workable.fastq.gz']},
1: {'unpaired': ['/work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624/Reads/OSD24_R2_shotgun_workable.fastq.gz']},
2: {'unpaired': ['/work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624/Reads/OSD46_R1_shotgun_workable.fastq.gz']},
3: {'unpaired': ['/work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624/Reads/OSD46_R2_shotgun_workable.fastq.gz']}}
Executing bowtie2 -q --phred33 --end-to-end --sensitive -p 16 -I 0 -X 2000 --no-unal -x /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624
perl: warning: Setting locale failed.
perl: warning: Please check that your locale settings:
    LANGUAGE = (unset),
    LC_ALL = "en_US.UTF-8",
    LANG = "en_US.UTF-8"
are supported and installed on your system.
perl: warning: Falling back to the standard locale ("C").
1214226 reads; of these:
    1210931 (99.73%) aligned 0 times
    2432 (0.20%) aligned exactly 1 time
    863 (0.07%) aligned >1 times
0.27% overall alignment rate

Executing bowtie2 -q --phred33 --end-to-end --sensitive -p 16 -I 0 -X 2000 --no-unal -x /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624
perl: warning: Setting locale failed.
perl: warning: Please check that your locale settings:
    LANGUAGE = (unset),
    LC_ALL = "en_US.UTF-8",
    LANG = "en_US.UTF-8"
are supported and installed on your system.
perl: warning: Falling back to the standard locale ("C").
1214226 reads; of these:
    1210806 (99.72%) aligned 0 times
    2511 (0.21%) aligned exactly 1 time
    909 (0.07%) aligned >1 times
0.28% overall alignment rate

Executing bowtie2 -q --phred33 --end-to-end --sensitive -p 16 -I 0 -X 2000 --no-unal -x /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624
perl: warning: Setting locale failed.
perl: warning: Please check that your locale settings:
    LANGUAGE = (unset),
    LC_ALL = "en_US.UTF-8",
    LANG = "en_US.UTF-8"
are supported and installed on your system.
perl: warning: Falling back to the standard locale ("C").
406075 reads; of these:
    402472 (99.11%) aligned 0 times
    3007 (0.74%) aligned exactly 1 time
    596 (0.15%) aligned >1 times
0.89% overall alignment rate

Executing bowtie2 -q --phred33 --end-to-end --sensitive -p 16 -I 0 -X 2000 --no-unal -x /work/03548/bb_t4k0/bbolduc-iplant-2015/job-1500220321997909530-242ac114-0001-007-32577624
perl: warning: Setting locale failed.
perl: warning: Please check that your locale settings:

```

## Read2RefMapper

### Step 6.

# Open Read2RefMapper

Open Read2RefMapper-1.1.0 from 'Apps'

Read2RefMapper 1.1.0

Analysis Name: Read2RefMapper\_1.1.0\_analysis1

Analysis Name:

Read2RefMapper\_1.1.0\_analysis1

Comments:

Select output folder:

/iplant/home/bbolduc-iplant-2015/analyses

Browse

\* Inputs

\* Parameters

Launch Analysis

## Read2RefMapper

### Step 7.

## Select Inputs

Select the 'Inputs' tab.


For **BAM File Directory (optionally including metagenome sizes file)**:

- Navigate to *Community Data --> iVirus --> ExampleData --> Read2ReferenceMapper --> Inputs*. Select the *BAM\_files\_and\_coverages\_file* folder. This will contain BAM files and a coverage file. Alternatively, copy-and-paste the location: `/iplant/home/shared/iVirus/ExampleData/Read2ReferenceMapper/Inputs` into the navigation bar and select the folder.

For **Metagenome Sizes File (CSV-formatted)**:

- Navigate to *Community Data --> iVirus --> ExampleData --> Read2ReferenceMapper --> Inputs*. Select the *BAM\_files\_and\_coverages\_file* folder. Select *metagenome\_bp.csv*. Alternatively, copy-and-paste the location: `/iplant/home/shared/iVirus/ExampleData/Read2ReferenceMapper/Inputs` into the navigation bar and select the *metagenome\_bp.csv* file.





## ⊕ NOTES

**Benjamin Bolduc** 31 Dec 2016

NEW: Prior versions of Read2RefMapper required users to type in the filename for the metagenome sizes file and place it within the same directory. Updates to the core code have eliminated this requirement. This example still uses the old directory structure.

## Read2RefMapper

### Step 8.

## Select Parameters and Outputs

For this example, the defaults are sufficient.

**% Read Coverage:** Percent of the reference sequence that must be covered by reads. For example, if 75% of a reference must be covered by reads to be considered 'present' in that sample.

**Percent ID:** Minimum identity a read must be against the reference sequence. For example, 0.90 is 90% identity between the read and reference.

**Percent Alignment:** What percent of the read length must be aligned to be considered matching. For example, 0.90 is 90% of the *read length* must align to the reference. This allows users to exclude reads where only a small local alignment is present.

**Coverage Mode:** How coverage should be calculated.

**Output resolution for adjusted coverage table heatmap (DPI):** If metagenome sizes file provided, will dictate the resolution of the heatmap for the adjusted coverage.

**Log file:** Filename to store logging information.

**Coverage table:** Name of the coverage table.

**Output format for adjusted coverage table heatmap:** If metagenome sizes file provided, will generate a heatmap for the adjusted coverage.

## Read2RefMapper

### Step 9.

## Launch Analysis

Run the job!

In terms of run time, Read2RefMapper is considerably faster than BatchBowtie (above).







































































## Read2RefMapper

### Step 10.

## Results

Expect results can be found in the associated app's 'output' directory.

There will be several directories, corresponding to each step along the pipeline. Notably are the *coverage\_table.csv*, which will have raw coverages for each contig across all metagenomes, and the *adj\_coverage\_table.csv*. In this example, we specified a metagenome bp file, meaning Read2RefMapper will adjust/normalize the coverage table according to the metagenome sizes. If no metagenome bp file is found, then the adjusted/normalized coverage table will not be generated!

<input type="checkbox"/>	Name	Last Modified	Size	
<input type="checkbox"/>	  1.sources	2016 Dec 30 23:13:50		  
<input type="checkbox"/>	  2.filtered	2016 Dec 30 23:14:37		  
<input type="checkbox"/>	  3.sorted-indexed	2016 Dec 30 23:15:22		  
<input type="checkbox"/>	  4.coverageFiltered	2016 Dec 30 23:16:51		  
<input type="checkbox"/>	  5.reSorted-reFiltered	2016 Dec 30 23:17:37		  
<input type="checkbox"/>	  BAM_files_and_coverages_file	2016 Dec 30 23:19:22		  
<input type="checkbox"/>	  .agave.log	2016 Dec 30 23:13:47	354 bytes	  
<input checked="" type="checkbox"/>	  adj_coverage_table.csv	2016 Dec 30 23:19:06	613 bytes	  
<input checked="" type="checkbox"/>	  adj_coverage_table.png	2016 Dec 30 23:19:10	183.24 KB	  
<input type="checkbox"/>	  agave-7498219b-4213-4f25-a7cc-...	2016 Dec 30 23:19:14	0 bytes	  
<input type="checkbox"/>	  agave-7498219b-4213-4f25-a7cc-...	2016 Dec 30 23:19:18	275 bytes	  
<input type="checkbox"/>	  coverage_table.csv	2016 Dec 30 23:20:42	706.61 KB	  
<input type="checkbox"/>	  metagenome_bp.csv	2016 Dec 30 23:20:46	188 bytes	  
<input type="checkbox"/>	  read2refmapper.log	2016 Dec 30 23:20:51	39.69 KB	  

## EXPECTED RESULTS

The adjusted coverage table.



adj\_coverage\_table.csv



Tabular View: adj\_coverage\_table.csv

Save Refresh + - Line Numbers Skip First N Line(s) 0 First Row Header Editable

0	1	2	3	4	5	6	7
#contig	OSD132	OSD170	OSD171	OSD172	OSD173	OSD21	OSD24
22SUR_7071	0.0	0.0	0.0	0.0	0.0	12.9200211496	0.0
25SUR_7849	0.0	0.0	0.0	0.0	0.0	0.0	5.08353390511
25SUR_26449	0.0	0.0	0.0	0.0	0.0	19.4146784438	0.0
34SUR_108524	8.4838156008	0.0	0.0	0.0	0.0	0.0	0.0
67SUR_52277	0.0	7.16997102321	6.73235754524	0.0	0.0	0.0	0.0
67SUR_52974	0.0	10.6403082552	0.0	0.0	0.0	0.0	0.0
gil331028007 re...	0.0	0.0	0.0	0.0	0.0	0.0	0.0
gil356870794 re...	0.0	0.0	0.0	0.0	0.0	0.0	0.0

The output PNG file:

Population relative abundance in a sample  
(Bp mapped / Kb contig / Mb metagenome)



## 📌 NOTES

**Benjamin Bolduc** 31 Dec 2016

The non-adjusted coverage table results:

coverage_table.csv							
Tabular View: coverage_table.csv							
0	1	2	3	4	5	6	7
#contig	Length	/work/03548/bb...	/work/03548/bb...	/work/03548/bb...	/work/03548/bb...	/work/03548/bb...	/work/03548/
109DCM_97	14114	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_614	16022	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_751	10589	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_1006	15802	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_1161	24128	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_1650	21707	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_1731	12288	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_1847	13361	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_2193	11566	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_2433	17771	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_2878	10902	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_3111	11841	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_3849	15865	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_4160	11481	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_4380	13426	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_4727	18243	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
109DCM_4943	15454	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000