Creation of low-oxygen conditions.

Shengyi Yan[1], [2]

[1]Northeast Forestry University, [2]Northeast Forest University

Sep 14, 2019

1 Works for me

dx.doi.org/10.17504/protocols.io.69mhh46

2019 iGEM NEFU_China

Tech. support email: **shengyiyanwork@gmail.com**

ABSTRACT

We use Na_2SO_3 to create low-oxygen conditions in our experiment.

MATERIALS TEXT

LB medium
Na_2SO_3
IPTG
SMART SENSOR AR8010+ Dissolved Oxygen Meter

1

1 Prepare LB medium with different concentrations of Na_2SO_3.

1.1

Na2SO3(100g/L)	LB medium
0μL	20mL
20μL	20mL
40μL	20mL
100μL	20mL
200μL	20mL
400μL	20mL

2 Use Dissolved Oxygen Meter to measure dissolved oxygen of LB medium with different concentrations of Na_2SO_3 in 0h、1h、2h、5h.

2

3 Add 50ml LB medium and 200ul bacteria solution to conical flask, shake overnight at 37°C.

4 Take 5 ml in 5 50ml centrifuge tubes separately, centrifuge the bacteria at 3000xg at room temperate for 5 min.Discard the supernatant.

5 Prepare LB medium with different concentrations of Na_2SO_3.
dd Na_2SO_3 to LB medium.

Na2SO3(100g/L)	LB medium
0ul	20ml
100ul	20ml
200ul	20ml
400ul	20ml
800ul	20ml

6 Add LB medium with different concentrations of Na_2SO_3 to 5 50ml centrifuge tubes separately.

7 Add 2ul IPTG to 5 50ml centrifuge tubes separately,and reascend. Shake 5h at 37°C.

8 Use to measure ABS with different concentrations of Na_2SO_3 in 0 h、1h、2h、5h.