



Aug 08,
2019

Stranded Transcript Count Table Generation from Long Reads V.7

Forked from [Transcript Coverage Analysis from Long Reads](#)

David Eccles¹

¹Malaghan Institute of Medical Research (NZ)

In Development

[dx.doi.org/10.17504/protocols.io.59zg976](https://doi.org/10.17504/protocols.io.59zg976)



David A. Eccles

Malaghan Institute of Medical Research (NZ)



ABSTRACT

This protocol is for comparing different samples at the transcript level, using long reads that are mapped to transcripts.

Input(s): demultiplexed and oriented fastq files (see protocol [Preparing Reads for Stranded Mapping](#)), transcript reference fasta file, annotation file

Output(s): transcript table, sorted by differential coverage, annotated with gene name / description / location

BEFORE STARTING

Obtain a transcript fasta file, and an annotation file. For the mouse genome, I use the following files:

1. Transcript [CDS] sequences from [Ensembl](#); [this file](#) was the most current when I last checked.
2. Annotation file obtained from [Ensembl BioMart](#) (Ensembl Genes -> Mouse Genes) as a compressed TSV file with the following attribute columns:

- Transcript stable ID
- Gene description
- Gene start (bp)
- Gene end (bp)
- Strand
- Gene name
- Chromosome/scaffold name

Demultiplex Reads

1

Demultiplex and orient reads as per the protocol [Preparing Reads for Stranded Mapping](#). It is expected that these demultiplexed reads will be split up in the current directory, and coupled with a 'barcode_counts.txt' file. If that's the case, the following should work:

```
for bc in $(awk '{print $2}' barcode_counts.txt);  
do ls oriented/${bc}_reads_dirAdjusted.fq.gz;  
done
```

Example expected output:

```
oriented/BC03_reads_dirAdjusted.fastq.gz  
oriented/BC04_reads_dirAdjusted.fastq.gz  
oriented/BC05_reads_dirAdjusted.fastq.gz  
oriented/BC06_reads_dirAdjusted.fastq.gz  
oriented/BC07_reads_dirAdjusted.fastq.gz  
oriented/BC08_reads_dirAdjusted.fastq.gz
```

If the 'barcode_counts.txt' file is not present, this error will appear:

```
awk: fatal: cannot open file `barcode_counts.txt' for reading (No such file or directory)
```

If one or more of the oriented read files is missing, it will look something like this:

```
oriented/BC03_reads_dirAdjusted.fastq.gz
oriented/BC04_reads_dirAdjusted.fastq.gz
ls: cannot access 'oriented/BC05_reads_dirAdjusted.fastq.gz':
  No such file or directory
ls: cannot access 'oriented/BC06_reads_dirAdjusted.fastq.gz':
  No such file or directory
oriented/BC07_reads_dirAdjusted.fastq.gz
oriented/BC08_reads_dirAdjusted.fastq.gz
```

Index Preparation

2 Prepare transcript index (see Guidelines for data sources)

```
lastdb Mus_musculus.GRCm38.cds.all.fa <(zcat Mus_musculus.GRCm38.cds.all.fa.gz)
```

Transcriptome Mapping

3 Reads are mapped to the transcriptome with LAST.

The results of that mapping can be piped through *last-map-probs* to exclude unlikely hits, then through *'maf-convert -n tab'* to convert to a one-line-per-mapping CSV format. This CSV format is further processed to make sure that there is only one mapping per transcript-read pair, and then aggregated to sum up counts per transcript.

```
mkdir -p mapped
for bc in $(awk '{print $2}' barcode_counts.txt);
do echo "*** ${bc} ***";
  lastal -Q 1 -P 10 Mus_musculus.GRCm38.cds.all.fa <(pv oriented/${bc}_reads_dirAdjusted.fq.gz |
  zcat) | \
  last-map-probs | maf-convert -n tab | cut -f 2,7,10 | sort | uniq | \
  awk -F'\t' -v "bc=${bc}" '{print bc,$1,$3}' | sort | uniq -c | \
  gzip > mapped/trnCounts_LAST_${bc}_vs_Mmus_transcriptome.txt.gz;
done
```

Annotation and Result generation

4 count_analysis.r

Transcript counts are merged with ensembl gene annotation, then converted into wide format (one line per transcript) using an R script.

The transcript annotation in this case is from ensembl BioMart (see Guidelines for more details).

```
#!/usr/bin/env Rscript
library(dplyr);
library(tidyr);

## load ensemble transcript metadata (including gene name)
ensembl.df <- as.tbl(read.delim('ensembl_mm10_geneFeatureLocations.txt.gz',
  col.names=c('transcript','Description','Start','End',
    'Strand','Gene','Chr'),
```

```

stringsAsFactors=FALSE));
ensembl.df$Description <- sub(' \\[.*$', '', ensembl.df$Description);
ensembl.df$Description <- sub('^(.{50}).+$', '\\1...', ensembl.df$Description);
ensembl.df[,1:7] <- ensembl.df[,c(1,7,5,3,4,2,6)];
colnames(ensembl.df)[1:7] <- colnames(ensembl.df)[c(1,7,5,3,4,2,6)];
options(scipen=15); ## don't show scientific notation for large positions
## load used barcode identifiers
bcNames <- read.table("barcode_counts.txt", stringsAsFactors=FALSE)[,2];
## load count data into 'narrow' array (one line per count)
trn.counts <- tibble(); for(bc in bcNames){
  trn.counts <-
    bind_rows(trn.counts,
      as.tbl(read.table(
        sprintf('mapped/trnCounts_LAST_%s_vs_Mmus_transcriptome.txt.gz', bc),
        col.names=c('count', 'barcode', 'transcript', 'dir'),
        stringsAsFactors=FALSE)));
}

## remove revision number from transcript names (if present)
trn.counts$transcript <- sub('\\\\.[0-9]+$', '', trn.counts$transcript);
## convert to wide format (one line per transcript)
trn.counts.wide <- spread(trn.counts, barcode, count) %>%
  mutate(dir = c('+='fwd', '-='rev')[dir]);
for(bd in colnames(trn.counts.wide[, -1])){
  trn.counts.wide[[bd]] <- replace_na(trn.counts.wide[[bd]], 0);
}
## merge ensembl metadata with transcript counts
gene.counts.wide <- inner_join(ensembl.df, trn.counts.wide, by='transcript');
gene.counts.wide <- gene.counts.wide[order(-rowSums(gene.counts.wide[, -(1:8)])),];
## write result out to a file
write.csv(gene.counts.wide, file='wide_transcript_counts_LAST.csv',
  row.names=FALSE);

```

Downstream Workflows

- 5 A downstream workflow is still [in development](<https://support.bioconductor.org/p/120764/>). I have had reasonable success doing transcript-level differential expression analysis using [DESeq2](<https://bioconductor.org/packages/release/bioc/html/DESeq2.html>).

I would like to emphasise that batch effects should be considered for nanopore sequencing, given how frequently the technology changes. Make sure that at least the sequencing *library* (i.e. samples prepared in tandem on the same day from the same kit) is added into the statistical model, and try to make sure that sequencing libraries are fairly heterogeneous - replicates from a sample with skewed transcript distributions could influence the outcome of statistical tests.



This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited