



# Gradient of a spatial point process along a linear feature

Miklós Koren<sup>1</sup>

<sup>1</sup>Central European University

[dx.doi.org/10.17504/protocols.io.ubhesj6](https://dx.doi.org/10.17504/protocols.io.ubhesj6)

In devel.

Oct 04, 2018



Miklós Koren

Central European University



## ABSTRACT

How we measure the gradient of the density of 19th century post offices along North American rivers in our paper Armenter, Roc, Miklós Koren and Dávid K Nagy. "Bridges"

Method relies on maximum likelihood formula in Zhao, M., and M. Xie. 1996. "On Maximum Likelihood Estimation for a General Non-Homogeneous Poisson Process." *Scandinavian Journal of Statistics, Theory and Applications* 23 (4): 597–607.

## THIS PROTOCOL ACCOMPANIES THE FOLLOWING PUBLICATION

Armenter, Roc, Miklós Koren and Dávid K Nagy. 2018. "Bridges." Working paper.

## PROTOCOL STATUS

### In development

We are still developing and optimizing this protocol

## Convert all features to a distance-invariant projection

- 1 Most geospatial data are in WGS84, which is not distance-invariant. Convert everything (points, lines) to a distance-invariant projection such as Lambert Conformal Conic. Make sure (x,y) coordinates are in meters.

```
import pyproj
from shapely.ops import transform
from shapely.geometry.base import BaseGeometry
from shapely.geometry import asShape

from shapely.geometry import Point

PROJECTIONS = dict(
    wgs84 = pyproj.Proj("+init=EPSG:4326"),
    lcc = pyproj.Proj(proj="lcc",
    nhgis = pyproj.Proj("+proj=aea +lat_1=29.5 +lat_2=45.5 +lat_0=37.5 +lon_0=-96 +x_0=0 +y_0=0 +ellps=GRS80
+towgs84=0,0,0,0,0,0,0 +units=m +no_defs"),
    epsg3975 = pyproj.Proj("+proj=cea +lon_0=0 +lat_ts=30 +x_0=0 +y_0=0 +ellps=WGS84 +datum=WGS84 +units=m
+no_defs"),
    albers = pyproj.Proj("+proj=aea +lat_1=29.5 +lat_2=45.5 +lat_0=37.5 +lon_0=-96 +x_0=0 +y_0=0 +datum=NAD83
+units=m +no_defs"),
    eov = pyproj.Proj("+proj=somerc +lat_0=47.14439372222222 +lon_0=19.04857177777778 +k_0=0.99993
+x_0=650000 +y_0=200000 +ellps=GRS67 +towgs84=52.17,-71.82,-14.9,0,0,0,0 +units=m +no_defs")
)

def project_geometry(geometry, tfrom, tto):
    return transform(lambda x, y: pyproj.transform(PROJECTIONS[tfrom], PROJECTIONS[tto], x, y), geometry)

class ProjectedFeature(object):
    def __init__(self, geometry, projection):
        """
        Every incoming geometry (point, linestring, polygon) is stored in wgs84.
        """
```

```

if not isinstance(geometry, BaseGeometry):
    # if not shapely geometry, treat as geojson dictionary
    geometry = asShape(geometry)
    self.geometry = project_geometry(geometry, projection, 'wgs84')

def __getattr__(self, projection):
    """
    We can refer to projected features as an attribute, e.g.

    feature.wgs84
    feature.lcc
    """
    if projection in PROJECTIONS:
        return project_geometry(self.geometry, 'wgs84', projection)
    else:
        raise AttributeError

if __name__ == '__main__':
    union_sq = Point((1827011, 574994))
    union_sq_geojson = {
        "type": "Point",
        "coordinates": [1827011, 574994]
    }

    Union_Sq = ProjectedFeature(union_sq, 'nhgis')
    print Union_Sq.wgs84
    print Union_Sq.lcc

    Union_Sq = ProjectedFeature(union_sq_geojson, 'nhgis')
    print Union_Sq.wgs84

```

## Select relevant sample of points close to linear feature

### 2 Create a polygon around your linear feature by extending it a D distance either circularly or by parallel shift

```

from project_geojson import ProjectedFeature
import json
from shapely.geometry.geo import mapping
from shapely.geometry import LineString, Point, Polygon, asShape
import sys

def bank(river, side, width_km=10):
    bank = river.parallel_offset(width_km*1000.0, side)
    river_coords = list(river.coords)
    bank_coords = list(bank.coords)
    if side=='left':
        bank_coords = bank_coords[::-1]
    linestring = river_coords+bank_coords
    return Polygon(linestring)

if __name__ == '__main__':
    which_bank = sys.argv[1]
    width_km = 10

    river_json = json.load(sys.stdin)
    river = ProjectedFeature(river_json['features'][0]['geometry'], 'wgs84').lcc
    bank = ProjectedFeature(bank(river, which_bank, width_km), 'lcc').wgs84.buffer(0)
    meta = river_json['features'][0]['properties']
    meta['bank'] = which_bank
    meta['width_km'] = 10.0

```

```
print json.dumps(dict(type="Feature", geometry=mapping(bank), properties=meta))
```

Select the intersection of this polygon with the points of interest.

### Project points on linear feature and convert to linear coordinates

- 3 Make sure you know where the start and end of your linear feature is. Measure coordinates as distance along the feature to the start.

```
bridge_rivermile = river.project(bridge)
postoffice_rivermile = river.project(postoffice)
```

### For each point, measure distance to nearest crossing point

4

```
def distance_to_nearest_bridge(river_mile, bridges):
    return min([abs(bridge['river_mile']-river_mile) for bridge in bridges])
for postoffice in postoffices:
    postoffice['distance_to_bridge'] = distance_to_nearest_bridge(postoffice['river_mile'], bridges)
```

### Given the distribution of distances, estimate gradient parameters by maximum likelihood

- 5 Given a distance function  $f()$ ,

$$\lambda(z) = e^{a_j - bf(|z-x_j|)}.$$

The log likelihood is then

$$\ln \mathcal{L}(x, y, \theta) = n(T) \ln M(T) - \ln[n(T)!] - 2M(T) + n(T)a_j - b \sum_{i=1}^{N(T)} f(|y_i - x_j|).$$



This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited