


# MetaVelvet : An extension of Velvet assembler to de novo metagenome assembly from short sequence reads

Afiahayati, Sato K, Namiki T, Hachiya T, Tanaka H, Sakakibara Y.

## Abstract

**Motivation:** An important step of "metagenomics" analysis is the assembly of multiple genomes from mixed sequence reads of multiple species in a microbial community. Most conventional pipelines employ a single-genome assembler with carefully optimized parameters and post-process the resulting scaffolds to correct assembly errors. Limitations of the use of a single-genome assembler for *de novo* metagenome assembly are that highly conserved sequences shared between different species often causes chimera contigs, and sequences of highly abundant species are likely mis-identified as repeats in a single genome.

**Methods:** We modified and extended a single-genome and de Bruijn-graph based assembler, [Velvet](#), for *de novo* metagenome assembly. Our fundamental ideas are first decomposing de Bruijn graph constructed from mixed short reads into individual sub-graphs and second building scaffolds based on every decomposed de Bruijn sub-graph as isolate species genome.



**Citation:** Afiahayati, Sato K, Namiki T, Hachiya T, Tanaka H, Sakakibara Y. MetaVelvet : An extension of Velvet assembler to de novo metagenome assembly from short sequence reads. [protocols.io](#)

## Collection



### 1. [Installation and Getting Started](#)

CONTACT: [Bonnie Hurwitz](#)

### 2. [Manual setting of k-mer coverage peaks](#)

CONTACT: [Bonnie Hurwitz](#)

### 3. [Use Bambus2 scaffolding module](#)

CONTACT: [Bonnie Hurwitz](#)

### 4. [How to use paired-end information for graph decomposition](#)

CONTACT: [Bonnie Hurwitz](#)