

2019

Working

# Case - Heavy Water Assays by GC-mass spectrometry

Henri Brunengraber<sup>1</sup>

<sup>1</sup>Case Western Reserve University

dx.doi.org/10.17504/protocols.io.ydsfs6e

Mouse Metabolic Phenotyping Centers Tech. support email: info@mmpc.org



Lili Liang 69

ABSTRACT

### Summary:

Heavy water can be used as a tracer for estimating metabolic rates (in vivo, in vitro) such as total energy expenditure (TEE) and fractional synthesis rates (FSR; eg. protein, lipids, triglycerides). When using both <sup>2</sup>H<sub>2</sub>O and H<sub>2</sub><sup>18</sup>O (DLW), TEE is estimated from the total production of CO<sub>2</sub> as measured by the differences in decay rates of labeled the <sup>18</sup>O and <sup>2</sup>H in body water over time following a single bolus of DLW (1). 2H2O can be used to estimate fractional synthesis rates of metabolic reactions such as those associated with proteins, lipids, triglycerides, and cholesterol (2,4).

#### References:

- 1. Gas chromatography-mass spectrometry assay of the (18) O enrichment of water as trimethyl phosphate. Brunengraber DZ, McCabe BJ, Katanik J, and Previs SF. Anal Biochem 306: 278 - 282 (2002).
- 2. Increased plasma membrane cholesterol in cystic fibrosis cells correlates with CFTR genotype and depends on de novo cholesterol synthesis. Fang D, West RH, Manson ME, Ruddy J, Jiang D, Previs SF, Sonawane ND, Burgess JD, Kelley TJ.Respir Res.; 11:61 (2010).
- 3. Triglyceride synthesis in epididymal adipose tissue: contribution of glucose and non-glucose carbon sources. Bederman IR, Foy S, Chandramouli V, Alexander JC, Previs SF. J Biol Chem.; 284(10):6101-8 (2009).
- 4. Novel application of the "doubly labeled" water method: measuring CO2 production and the tissue-specific dynamics of lipid and protein in vivo. Bederman IR, Dufner DA, Alexander JC, Previs SF. Am J Physiol Endocrinol Metab.; 290(5):E1048-56 (2006).

**EXTERNAL LINK** 

https://mmpc.org/shared/document.aspx?id=275&docType=Protocol

MATERIALS

NAME ~	CATALOG #	VENDOR ~	CAS NUMBER $\vee$ RRID $\vee$
Deuterium oxide 2H2O (99 atom % excess);		Sigma Aldrich	
H2 180 (95% atom excess)		Isotec	

MATERIALS TEXT

## **Reagents and Materials:**

Reagent/Material	Quantity Required	Vendor
Deuterium oxide, <sup>2</sup> H <sub>2</sub> O		Sigma-Aldrich
(99 atom % excess);		46
NaOH	2µL	stock
H <sub>2</sub> <sup>18</sup> O (95% atom	\$ \$\tilde{\chi}\$	Isotec (Miamisburg, OH)
excess)	6.00000	5000 CO
acetone/acetonitrile	4µL	stock
solution	100,40,000	***************************************
Chloroform	200- 500 μL	stock
Dhaanharus		stock
Phosphorus	3 mg	SIUCK
Pentachlorate; TMP*	400-1	-11-
Diethyl ether	120µl	stock

Analysis of  ${}^2\!H_2\!O$  and  ${}^4\!H_2\!O$ :  ${}^2\!H$  labeling of body water is determined by exchange with acetone and the  $^{18}$ O labeling of body water is determined by conversion to trimethyl phosphate \*(TMP; generated by reacting phosphoric acid with diazomethane).

## Note:

Sigma-Aldrich, RRID: SCR\_008988

- 1. Quantitation by 2H2O Standard Curve:
  - 2. Standards are made from deuterium oxide (Aldrich 617385)
  - 3. Pipette 10µl of plasma or standard into Eppendorf
  - 4. <sup>2</sup>H<sub>2</sub>O standards
    - a. Blank (MQ H<sub>2</sub>O)
    - b. 0.1% D<sub>2</sub>O in (MQ H<sub>2</sub>O)
    - c. 0.5% D<sub>2</sub>O in (MQ H<sub>2</sub>O)
    - d. 0.10% D<sub>2</sub>O in (MQ H<sub>2</sub>O)
    - e. 1.5% D<sub>2</sub>O in (MQ H<sub>2</sub>O)
    - f. 2.0% D<sub>2</sub>O in (MQ H<sub>2</sub>O)
    - g. 2.5% D<sub>2</sub>O in (MQ H<sub>2</sub>O)
    - h. 3.0% D<sub>2</sub>O in (MQ H<sub>2</sub>O) i. 3.5% D<sub>2</sub>O in (MQ H<sub>2</sub>O)

    - j. 4.0% D<sub>2</sub>O in (MQ H<sub>2</sub>O)
  - 5. Add 2µl of a 10N NaOH solution to each sample or standard
  - 6. Add 4µl of acetone/acetonitrile solution (10µl of acetone +200µl of acetonitrile) to each sample
  - 7. Be careful when taking samples out of the centrifuge to make sure that all of the drops are at the bottom of the tube
  - 8. Cap and briefly centrifuge samples (~5sec) to ensure NaOH and acetonitrile react with sample
  - 9. Let samples sit overnight (at least 10hrs)
  - 10. Add 500µl of chloroform to samples
  - 11. Add ~ 50mg Na<sub>2</sub>SO<sub>4</sub> salt to each sample
  - 12. Centrifuge sample for 2 minutes
  - 13. Pipette 100µl of chloroform layer into glass insert, place inserts in GC vials and cap, then assay on a GC-MS system, El mode (see below for parameters and references).

- **?** For doubly labelled water studies, such as total energy expenditure; TEE (1,4):
  - 1. H<sub>2</sub><sup>18</sup>O standards:
    - a. Blank (MO H<sub>2</sub>O)
    - b. 0.01% H<sub>2</sub><sup>18</sup>O in (MQ H<sub>2</sub>O)
    - c. 0.05% H<sub>2</sub><sup>18</sup>O in (MQ H<sub>2</sub>O)
    - d.  $0.10\% \ H_2^{18}O$  in (MQ  $H_2O$ )
    - e. 0.15% H<sub>2</sub><sup>18</sup>O in (MQ H<sub>2</sub>O)
    - f. 0.20% H<sub>2</sub>18O in (MO H<sub>2</sub>O)
    - g. 0.25% H<sub>2</sub>18O in (MQ H<sub>2</sub>O)
    - h. 0.30% H<sub>2</sub><sup>18</sup>O in (MQ H<sub>2</sub>O)
    - i. 0.35% H<sub>2</sub><sup>18</sup>O in (MQ H<sub>2</sub>O)
    - j. 0.40% H<sub>2</sub><sup>18</sup>O in (MQ H<sub>2</sub>O)
  - $2. H_2^{18}O$  assay: 5 ul of blood or plasma sample or standard into a  $12 \times 75$ -mm glass tube
  - 3. Then add ~3 mg of PCI5 to samples or standards to generate phosphoric acid; let stand for 20 min
  - 4. To generate TMP, then react samples or standards by adding  $300 \,\mu$ l of freshly prepared etheral-diazomethane (to derivatize samples) and allow to stand at room temperature during reaction, until the ether evaporated; may use an additional  $120 \mu$ l of diethyl ether in hexane solution
  - 5. TMP is extracted by addition of 150 ul of water and 600 µl of chloroform (1:4 ratio) followed by addition of 0.5 g Na<sub>2</sub> SO<sub>4</sub>
  - 6. Samples are then vigorously mixed, and a small aliquot of the chloroform is transferred to a GC-MS vial and assayed on GC-MS system, El mode

Gas Chormatography Mass Spectrometry, GC-MS (EI mode): Acetone and the TMP derivatives are analyzed using an Agilent 5973N-MSD equipped with an Agilent 6890 GC system, and a DB-17MS capillary column (30 m x 0.25 mm x 0.25 mm). The mass spectrometer is operated in the electron impact mode (EI; 70 eV), (1,4).

- 7. Selective ion monitoring of mass-to-charge ratios (m/z)
  - a. For <sup>2</sup>H enrichments monitor acetone (58, 59) and for <sup>18</sup>O enrichments monitor TMP (140,142)
- b. The  $^2$ H enrichments are calculated from the  $^2$ H $_2$ O standard curve and the  $^{18}$ O enrichments are calculated from the signal ratio (142)/(142 + 140).

This is an open access protocol distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited